HCSS User's Reference Manual

Herschel Data Processing

Version 2.0, Document Number: HERSCHEL-HSC-DOC-0935
04 December 2009

HCSS User's Reference Manual: Herschel Data Processing

Table of Contents

I. Categorized view of Commands xii
II. How to use this manual xv
II.1. Related documentation xv
III. Dictionary xvi
1. Numeric 1
1.1. Introduction 1
1.2. Quick Start 1
1.3. Import statements 1
1.4. Constants 2
1.5. Arrays 2
1.6. Toolboxes 13
2. DP Commands 20
2.1. Introduction 20
2.2. ABS 22
2.3. AbstractMappingTask 23
2.4. AddSpectrum 24
2.5. ALL 27
2.6. AllPresent 28
2.7. AmoebaFitter 30
2.8. AnnotationToolbox 31
2.9. AnnularSkyAperturePhotometryExplorer 33
2.10. AnnularSkyAperturePhotometryPanel 36
2.11. AnnularSkyAperturePhotometryProduct 38
2.12. AnnularSkyAperturePhotometryTask 41
2.13. ANY 43
2.14. AnyPresent 45
2.15. AperturePhotometryExplorer 47
2.16. AperturePhotometryPanel 52
2.17. AperturePhotometryProduct 60
2.18. AperturePhotometryTask 68
2.19. ARCCOS 70
2.20. ARCSIN 71
2.21. ARCTAN 72
2.22. ArithmeticSpectrumTask 73
2.23. asciiTableReader 76
2.24. asciiTableWriter 80
2.25. AttribQuery 82
2.26. AutoCorrelationTask 83
2.27. AutomaticContourTask 84
2.28. AutomaticContourTaskSignatureComponent 85
2.29. AverageSpectrum 87
2.30. bg 90
2.31. Bilinear 92
2.32. BinCentres 98
2.33. Bool1d 100
2.34. Bool2d 101
2.35. Bool3d 102
2.36. Bool4d 103
2.37. Bool5d 104
2.38. BoxCarFilter 105
2.39. BoxCarSmoothingTask 107
2.40. Byte1d 108
2.41. Byte2d 109
2.42. Byte3d 110
2.43. Byte4d 111

2.44. Byte5d 112
2.45. CachedPool 113
2.46. CachePool 115
2.47. CEIL 116
2.48. ChannelMapPlotting 117
2.49. CholeskyDecomposition 121
2.50. CircleHistogramExplorer 123
2.51. CircleHistogramPanel 126
2.52. CircleHistogramProduct 128
2.53. CircleHistogramTask 131
2.54. CircularIntegrationTask 133
2.55. clamp 134
2.56. ClampTaskSignatureComponent 136
2.57. clear 139
2.58. clear 141
2.59. Complex1d 143
2.60. Complex2d 144
2.61. Complex3d 145
2.62. Complex4d 146
2.63. Complex5d 147
2.64. CONCATENATE 148
2.65. Condense 149
2.66. ConnectorBox 153
2.67. Contour 154
2.68. ContourLevel 156
2.69. ContourPlotting 157
2.70. ContourTask 161
2.71. Convolution 162
2.72. Correlate 164
2.73. CorrelateMatrix 166
2.74. COS 167
2.75. COSH 169
2.76. CreateRgbImageTask 170
2.77. CreateRgbImageTaskSignatureComponent 172
2.78. crop 174
2.79. CrossCorrelationTask 176
2.80. CubeCompareDisplay 177
2.81. CubeSpectrumAnalysis 180
2.82. CubeSpectrumAnalysisToolbox 182
2.83. CubicSplineInterpolator 200
2.84. CubicSplinesModel 202
2.85. cutLevels 203
2.86. CutLevelsTaskSignatureComponent 205
2.87. DataFlow 207
2.88. DataFlowManager 208
2.89. DbFactory 209
2.90. DbPool 210
2.91. DETERMINANT 213
2.92. DFT2dTask 214
2.93. Display 215
2.94. displaylog 253
2.95. displayQCLog 255
2.96. DivideSpectrum 256
2.97. Double1d 260
2.98. Double2d 261
2.99. Double3d 262
2.100. Double4d 263
2.101. Double5d 264

2.102. EigenvalueDecomposition 265
2.103. EllipseHistogramExplorer 266
2.104. EllipseHistogramPanel 269
2.105. EllipseHistogramProduct 271
2.106. EllipseHistogramTask 274
2.107. Erfc 276
2.108. Erf 277
2.109. EXP10 278
2.110. EXP 279
2.111. ExpN 280
2.112. exportPalToUfDir 281
2.113. ExtractFreqRanges 283
2.114. ExtractMultiplePixelSpectrumPanel 286
2.115. ExtractRegionPixelSpectrumTask 288
2.116. ExtractSinglePixelSpectrumPanel 290
2.117. ExtractSinglePixelSpectrumTask 292
2.118. FFT2dTask 294
2.119. FFT 295
2.120. FitsArchive 297
2.121. fitsReader 304
2.122. FitterFunction 306
2.123. Fitter 308
2.124. FitterTask 309
2.125. FixedMask 313
2.126. FixedSkyAperturePhotometryExplorer 316
2.127. FixedSkyAperturePhotometryPanel 319
2.128. FixedSkyAperturePhotometryProduct 321
2.129. FixedSkyAperturePhotometryTask 324
2.130. FIX 326
2.131. Flag 328
2.132. FlagPixels 335
2.133. FlagSaturatedPixelsCubeTask 338
2.134. FlagSaturatedPixelsTask 339
2.135. Float1d 340
2.136. Float2d 341
2.137. Float3d 342
2.138. Float4d 343
2.139. Float5d 344
2.140. FLOOR 345
2.141. FoldSpectrum 346
2.142. FullQuery 348
2.143. GAMMALN 349
2.144. GammaP 350
2.145. GammaQ 351
2.146. GaussFitTask 352
2.147. GaussianFilter 357
2.148. GaussianSmoothingTask 359
2.149. HAMMING 360
2.150. HANNING 363
2.151. HduHeaders 366
2.152. help 368
2.153. Histogram 370
2.154. Histogram 372
2.155. HistogramPanel 377
2.156. HistogramTask 383
2.157. IaProcessImpl 384
2.158. IFFT 386
2.159. ImageAbsTask 388

2.160. ImageAddTask 389
2.161. ImageAddTaskSignatureComponent 390
2.162. ImageAnalysis 392
2.163. ImageAnalysisToolbox 394
2.164. ImageArithmeticsTask 403
2.165. ImageArithmeticsTaskSignatureComponent 404
2.166. ImageAxis 407
2.167. ImageCeilTask 416
2.168. ImageContour 417
2.169. ImageDivideTask 420
2.170. ImageDivideTaskSignatureComponent 421
2.171. ImageExp10Task 423
2.172. ImageExpNTask 424
2.173. ImageExpTask 425
2.174. ImageFloorTask 426
2.175. ImageHistogramExplorer 427
2.176. ImageHistogramProduct 431
2.177. ImageHistogramTask 434
2.178. ImageHistogramTaskSignatureComponent 435
2.179. ImageLog10Task 438
2.180. ImageLogNTask 439
2.181. ImageLogTask 440
2.182. ImageModuloTask 441
2.183. ImageModuloTaskSignatureComponent 442
2.184. ImageMultiplyTask 444
2.185. ImageMultiplyTaskSignatureComponent 445
2.186. ImagePowerTask 447
2.187. ImageRoundTask 448
2.188. ImageSaverTask 449
2.189. ImageSqrtTask 450
2.190. ImageSquareTask 451
2.191. ImageSubtractTask 452
2.192. ImageSubtractTaskSignatureComponent 453
2.193. importCube 455
2.194. importImage 456
2.195. importRgbImage 457
2.196. importSpectralCube 458
2.197. importUfDirToPal 459
2.198. info 461
2.199. InputImageNSignatureComponent 463
2.200. InputImageSignatureComponent 466
2.201. Int1d 469
2.202. Int2d 470
2.203. Int3d 471
2.204. Int4d 472
2.205. Int5d 473
2.206. IntegratedMapDisplay 474
2.207. IntegrateMapFromCubeTask 476
2.208. Integrator 478
2.209. IntensityCalculator 480
2.210. IntensityMapGui 485
2.211. InverseDFT2dTask 486
2.212. InverseFFT2dTask 487
2.213. INVERSE 488
2.214. IS_FINITE 489
2.215. IS_INFINITE 490
2.216. IS_NAN 491
2.217. KURTOSIS 492

2.218. LayerStruct 494
2.219. LevenbergMarquardtFitter 496
2.220. LinearInterpolator 497
2.221. LineIntensityMapTask 499
2.222. ListContext 502
2.223. localStoreWriter 504
2.224. LOG10 505
2.225. LOG 506
2.226. LogN 507
2.227. Long1d 509
2.228. Long2d 510
2.229. Long3d 511
2.230. Long4d 512
2.231. Long5d 513
2.232. LUDecomposition 514
2.233. ManualContourPanel 516
2.234. ManualContourTask 519
2.235. ManyToOneSpectrumTask 520
2.236. MapContext 522
2.237. MatrixMultiply 524
2.238. MatrixSolve 526
2.239. MAX 527
2.240. MEAN 529
2.241. MeanSmoothingTask 530
2.242. MEDIANDEV 531
2.243. MEDIAN 532
2.244. MedianSmoothingTask 533
2.245. MetaQuery 534
2.246. MIN 535
2.247. MosaicTask 537
2.248. MultiplySpectrum 538
2.249. NearestNeighborInterpolator 542
2.250. NearestNeighbourProjectionTask 544
2.251. Normalize 548
2.252. NotPresent 551
2.253. NumberedDataset 553
2.254. ObservationContext 554
2.255. OpDayGenerator 556
2.256. openFile 557
2.257. openTask 558
2.258. openVariable 559
2.259. OverPlotter 560
2.260. PackedMask 564
2.261. pacs2HipeDouble3d 566
2.262. pause 567
2.263. pointHistoryDisplay 568
2.264. Polygon 570
2.265. PolygonHistogramExplorer 572
2.266. PolygonHistogramPanel 575
2.267. PolygonHistogramProduct 577
2.268. PolygonHistogramTask 580
2.269. Polynomial 582
2.270. poolDataReader 584
2.271. poolDataWriter 587
2.272. PositionList 590
2.273. PowerSpectrum 592
2.274. PowerSpectrum 594
2.275. Pow 595

2.276. PreviousInterpolator 596
2.277. ProcessDistributor 598
2.278. PRODUCT 600
2.279. ProductRef 602
2.280. ProductStorage 603
2.281. ProfileExplorer 610
2.282. Profile 614
2.283. ProfilePanel 617
2.284. ProfilePlotting 622
2.285. ProfileTask 626
2.286. QRDecomposition 628
2.287. Query 630
2.288. RadialVelocityTask 631
2.289. RandomGauss 635
2.290. RandomPoisson 636
2.291. RandomUniform 637
2.292. RangeExtractionGui 639
2.293. RangeExtractionTask 640
2.294. RealFunction 642
2.295. REBIN 643
2.296. RectangleHistogramExplorer 646
2.297. RectangleHistogramPanel 649
2.298. RectangleHistogramProduct 651
2.299. RectangleHistogramTask 654
2.300. RectangularSkyAperturePhotometryExplorer 656
2.301. RectangularSkyAperturePhotometryPanel 659
2.302. RectangularSkyAperturePhotometryProduct 662
2.303. RectangularSkyAperturePhotometryTask 666
2.304. Regrid 669
2.305. REPEAT 677
2.306. ReplaceFreqRanges 678
2.307. ResampleFrequency 680
2.308. RESHAPE 683
2.309. restore 685
2.310. resume 687
2.311. REVERSE 688
2.312. RgbSimpleImage 689
2.313. Rotate 694
2.314. rotate 697
2.315. RotateTaskSignatureComponent 700
2.316. ROUND 702
2.317. RowByRowAverageSpectrum 704
2.318. save 705
2.319. scale 707
2.320. ScaleTaskSignatureComponent 710
2.321. SelectSpectrum 712
2.322. SerialArchive 715
2.323. SerialClientPool 719
2.324. SHIFT 721
2.325. Short1d 723
2.326. Short2d 724
2.327. Short3d 725
2.328. Short4d 726
2.329. Short5d 727
2.330. SIGCLIP 728
2.331. SIGNUM 731
2.332. SimpleAsciiTableReader 732
2.333. SimpleCube 734

2.334. simpleFitsReader 746
2.335. simpleFitsWriter 748
2.336. SimpleImage 750
2.337. SimpleStack 764
2.338. SingularValueDecomposition 774
2.339. SIN 776
2.340. SINH 778
2.341. SkewGaussModel 779
2.342. SKEWNESS 780
2.343. SkyAperturePhotometryExplorer 782
2.344. SkyAperturePhotometryProduct 784
2.345. SkyAperturePhotometryTask 787
2.346. SlicedCube 789
2.347. SlicedImage 803
2.348. SmoothingTask 818
2.349. SmoothSpectrum 819
2.350. SORT 821
2.351. SourceExtractorDaophotTask 822
2.352. SourceExtractorSussextractorTask 827
2.353. SourceExtractorTask 832
2.354. SourceFittingExplorer 837
2.355. SourceFittingPanel 841
2.356. SourceFittingProduct 845
2.357. SourceFittingTask 851
2.358. SpectralProjectionAlgorithm 853
2.359. Spectrum1d 854
2.360. Spectrum2d 856
2.361. SpectrumPlotting 858
2.362. SpectrumStatistics 862
2.363. SpectrumTask 864
2.364. SpireFlags 865
2.365. SQRT 866
2.366. SQUARE 867
2.367. Sso 868
2.368. STDDEV 869
2.369. StitchSpectrum 870
2.370. String1d 873
2.371. SubtractSpectrum 874
2.372. SUM 878
2.373. TablePlotter 880
2.374. TAN 887
2.375. TANH 889
2.376. TaskWrapper 890
2.377. ThreadDynamicProcessImpl 891
2.378. tiledImage 893
2.379. Transform2dTask 894
2.380. translate 895
2.381. TranslateTaskSignatureComponent 897
2.382. TRANSPOSE 899
2.383. transpose 900
2.384. TransposeTaskSignatureComponent 902
2.385. UNIQ_SORTED 904
2.386. UNIQ 906
2.387. VARIANCE 908
2.388. VelocityPosMapComputeTask 909
2.389. VelocityPosMapPlotting 911
2.390. WcsExplorer 914
2.391. Wcs 918

2.392. WeightedMean 942

Categorized view of Commands

This chapter provides a categorized view of all built-in DPfunctions, tasks and objects.

Datasets

- NumberedDataset - NumberedDataset is an alternative for the non-existing VectorDataset.
- Spectrum1d - Spectrum1d is an extension of AbstractSpectrumDataset which in turn
- Spectrum2d - Spectrum2d is an extension of AbstractSpectrumDataset which in turn

Display

- ImageAxis - Axes for image display.

Image

- AnnotationToolbox - A toolbox to draw annotations.
- Display - An Image display for DP. A class to display images.
- Flag - A class to describe Flags for images (SimpleImage, SimpleCube, SimpleStack, SlicedImage, SlicedCube and SlicedStack).
- RgbSimpleImage - A Product describing three color images.
- SimpleCube - A Product describing cubes.
- SimpleImage - A Product describing images.
- SimpleStack - A SimpleStack is a stack of Images.
- SlicedCube - A SlicedCube is a large cube which is stored in slices to make the memory usage lower.
- SlicedImage - A SlicedImage is a large image which is stored in slices to make the memory usage lower.
- Wcs - A class to create a Wcs.

PAL

- DbFactory - An implementation of a ProductPool which saves data to a versant database.
- DbPool - An implementation of a ProductPool which saves data to a versant database (to be exact, any

class

- FitsArchive - A class for reading and writing FITS files.
- HduHeaders - A class for working with FITS HDUs. HDU data is loaded only when requested.
- SerialArchive - A class for writing and reading serialized objects.

developer

- clear - Demonstrate the use of the Ctr-s on top a task

generic task

- FitterTask - generic module: FitterTask
- GaussFitTask - generic module: GaussFitTask

numeric

- REBIN - *

numerics

interp

- Bilinear - Bilinear Algorithm

task

- bg - Execute jython commands in the background
- clear - Clear variables from the jython session.
- displaylog - Open a window displying log messages
- displayQCLog - Open a window displaying QClLogs messages organized in a product
- exportPalToUfDir - Exports observations related to an URN from a pool to a user friendly directory structure
- fitsReader - The FitsReaderTask task.
- help - The help task for interactive help.
- importUfDirToPal - Imports an observation context from an user friendly directory structure into a pool.
- localStoreWriter - Saves a product in a Local Store, either already defined, or a new
- NearestNeighbourProjectionTask - NearestNeighbourProjectionTask
- openFile - opens a variable in a viewer
- openTask - opens a task in its viewer
- openVariable - opens a variable in a viewer
- pause - Pause the execution of jython code
- restore - Restore variables from a file to a jython session
- resume - Pause the execution of jython code
- save - Save variables from the jython session to a file
- SimpleAsciiTableReader - The SimpleAsciiTableReader task.
- simpleFitsReader - The SimpleFitsReaderTask task.
- simpleFitsWriter - Saves a product in a FITS file
- SourceExtractorDaophotTask - This task extracts point sources from an HCSS SimpleImage image.
- SourceExtractorSussextractorTask - This task extracts point sources from an HCSS SimpleImage image.
- SourceExtractorTask - This task extracts point sources from an HCSS SimpleImage image.

cube

- importCube - The ImportCube task for Cubes.
- importSpectralCube - The ImportSpectralCube task for SpectralSimpleCubes.

general

- info - A task for inspecting the content of a variable in the jython session.

image

- clamp - Clamping images and cubes.
- crop - A Task to crop images and cubes.
- cutLevels - A Task to calculate the cut levels of an image.
- ImageSaverTask - A Task to save images.
- importImage - A Task to import images into an Image object.
- importRgbImage - A Task to import color images into an RgbImage object.
- rotate - A Task that rotates images.
- scale - A Task to scale images.
- tiledImage - A Task to convert an image to a TiledImage.
- translate - The Translate task for Images.
- transpose - The Transpose task for Images.

toolbox

- RadialVelocityTask - The RadialVelocity Task.
- Sso - To obtain an Horizons object you need an Ephemeris object and a directory with SSO files

utility task

- asciiTableReader - AsciiTableReaderTask
- asciiTableWriter - Task for writing ASCII files.
- pointHistoryDisplay - Task for displaying graphs of pointing information
- poolDataReader - Task for reading a product from a pool.
- poolDataWriter - Task for writing a product into a pool.

How to use this manual

The *User's Reference Manual* contains information about all the main tasks and classes that you can use within your scripts. There are four version of this manual: the *HCSS* version describes the functions provided by the core Herschel software, and is always shipped with HIPE; the three other versions describe functions provided by HIFI, PACS and SPIRE software. You may or may not have these additional manuals, depending on the software you installed.

This manual includes the following sections:

- Categorized view of Commands. All the functions described in the manual, organised by category.
- Dictionary. A list of definitions of words and acronyms you are likely to encounter in documentation on the Herschel satellite.
- Chapter 1. This section describes the *Numeric* library, one of the cornerstones of the HCSS software. You can find more information about this library in the *Scripting and Data Mining* guide: Chapter 3.
- Section 2.1. This section lists all the available commands in alphabetical order. Each command has a description, usage instructions and examples.

II.1. Related documentation

The aim of this manual is to provide reference information for all the user-relevant aspects of the HCSS system. Despite our efforts, you may find that some routines are missing, or have incomplete or inaccurate descriptions. In this case you are encouraged to consult the *Javadoc* developer's reference documentation. You can access the Javadoc by clicking on *HCSS Developer's Reference Manual (API)* in the table of contents of the HIPE Help System.

Guidance on how to use the Javadoc is provided in the *Scripting and Data Mining* guide: Chapter 5.

Some Javadoc pages may have links to more in-depth developer documentation. Be aware that these are *not* fully fledged help documents and are most useful to system developers or advanced users only.

Inspecting the source code

If you are an advanced user versed in Java and Jython, you might want to have a look at the source code of a task or class. You can include source code in your HIPE installation in the following ways:

- If you are installing a developer build via the Continuous Installation System, the `--src=yes` option will install source code. This is enabled by default if you use the `--developer` option.

  With the `--unpack=yes` option, the source code will be unpacked into a `src` subdirectory in your HIPE installation. With the `--unpack=no` option, source files for each module will be kept as ZIP files in the repository (usually under `$HOME/.hcss.d/repository` in UNIX systems and under `%HOMEPATH%/.hcss.d/repository` in Windows).

- If you are using an installer, select the checkbox next to the question *Would you like to have the source code installed?* This is only available if you choose the *Advanced* installation. The source code will be in the `src` subdirectory of your HIPE installation.

Dictionary

This section contains a list of definitions of words and acronyms you are likely to encounter in documentation on the Herschel satellite.

Dictionary

AAS	[Acronym] Altitude Anomaly Sensors
ABCL	[Acronym] As-Built Configuration List
ACA	[Acronym] Altitude Control Axis
ACC	[Acronym] Attitude Control Computer
ACM	[Acronym] Attitude Control and Measurement
ACMS	[Acronym] Attitude Control and Measurement System
ACS	[Acronym] Auto-Correlation Spectrometer
activateMasks	[Pipeline] PACS task to activate or deactivate specified masks before running a pipeline task
A/D	[Acronym] Analogue to Digital Converter
AD	[Acronym] Applicable Document
ADC	[Acronym] Analogue to Digital Converter
addUTC	[Pipeline] PACS Level 0 task to convert from onboard time to UTC
ADP	[Acronym] Acceptance Data Package
AIT	[Acronym] Assembly, Integration and Test
AIV	[Acronym] Assembly, Integration, and Verification
AM	[Acronym] Avionics Model
AMA	[Acronym] Absolute Measurement Accuracy
AME	[Acronym] Attitude Measurement Error
AO	[Acronym] Announcement of Opportunity
AOCS	[Acronym] Attitude and Orbit Control System
AOR	[Acronym] Astronomical Observation Request
AOS	[Acronym] Acousto Optic Spectrometer
AOT	[Acronym] Astronomical Observing Template
APD	[Acronym] Absolute Pointing Drift
APE	[Acronym] Absolute Pointing Error
API	[Acronym] Applications Programer Interface

API	[Generic HIPE; Acronym] Application Programer Interface. It is an interface that a software program or library implements in order to allow other software to interact with it. In the "API" documentation, the whats and hows of the java tasks and classes in HIPE are provided. These will be a little difficult for those unused to writing programs to understand. The documentation is also known as the javadocs or Developer's Reference Manual.
APID	[Acronym] Application Programer IDentifier. The APID number is how the pipelines identifies spectrometers
AR	[Acronym] Acceptance Review
ARE	[Acronym] Absolute Rate Error
associateSkyPosition	[Pipeline] SPIRE photometry Level 0.5 task to add the pointing product to the timelines. Common to jiggle and scan map pipelines
argument	[I/O; Data types; Other] Or parameter, are the variables you send to a task when you call that task
attribute	[I/O; Data types; Other] Is a name for a specific field in a class. A field that denotes a particular characteristic of the class, much like a property of a class. For example, an important attribute of an observation context is the observation ID
auxiliary	[I/O; Data types; Other] Additional products containing information necessary to process raw Herschel data, but which the general user will never need to look at
BACUS	[Acronym] Bolometer Array Calibration Unit for SPIRE
BBID	[Generic HIPE; Acronym] Building block ID = bbtype*65536 + bbnumbers
bbnumber	[Generic HIPE] Building block number
BE	[Acronym] Back End
BEM	[Acronym] Back End Module (LFI)
BER	[Acronym] Bit Error Rate
block	[Generic HIPE] A limited stream of data, e.g. part of an observation, that are logically related to each other (e.g. see calibration block)
BlockTable	[I/O; Data types; Other] PACS. A table showing the organisation of your observation data (your pipeline-processed or being processed product) into logical blocks, e.g. by raster position, wavelength range, nod position... Is also a class of product
boolean	[Generic HIPE] Can be True/False (1/0)
bps	[Acronym] bits per second
BW	[Acronym] Bandwidth
CA	[Acronym] Calibration Analysis (software)

CachedPool	[I/O; Data types; Other] A type of pool (see pool), containing cached products and meta dagta retrieved from remote pools
calcBsmAngles	[Pipeline] SPIRE photometry Level 0.5 task to convert BSM telemetry in a Y angle and Z angle timeline. Common to jiggle and scan map pipelines
calcBsmFlags	[Pipeline] SPIRE photometry Level 0.5 task to convert BSM telemetry in a Y angle and Z angle timeline. Jiggle pipeline
calibration block	[Generic HIPE] The block, the segment, of your observation when the internal calibration source(s) was observed
calibration product	[Generic HIPE] A product from the calibration store
calibration store	[Generic HIPE] The store of calibration data, necessary to process your data and which comes with HIPE and with your HSA data
calibration tree	[Generic HIPE] The calibration information, held in the calibration store, necessary to reduce Herschel data. It comes with HIPE and with your HSA data and is necessary for pipeline processing
calstore	Generic HIPE. Shorthand for the store of calibration data, which comes with HIPE and with your HSA data
CAP	[Acronym] calibration analysis procedure (a script)
CASSIS	[I/O; Data types; Other] Spectral fitting software (http://cassis.cesr.fr/)
CDD	[Acronym] Configuration Data Document
CEU	[Acronym] Cryo Electronics Unit
CheckDataStructure	[Pipeline] HIFI Level 0.5 task that checks that the datasets included in the HifitimelineProduct have a unique bbnumber
CheckFreqGrid	[Pipeline] HIFI Level 0.5 task that provides information about the frequency ranges observed in the HTP and forms groups of datasets with common LO settings
CheckPhases	[Pipeline] HIFI Level 0.5 task that checks that the Chopper, LO frequency and buffer follow specific patterns prescribed by the observing modes
class	[I/O; Data types; Other] The (java) class of a product defines the type of object it is. In object-oriented programming a class is a construct that is used as a blueprint to create objects, so all objects of a particular class will have the same organisation and definition. Also, CLASS is the name of an (externa) software package for continuum and spectral line analysis
cleanPlateauFrames	[Pipeline] PACS Level 0 task to flag data points at the beginning and end of each chopper movement. Photometry. End of Level 0 pipeline processing
COA	[Acronym] Common Optics Assembly
Co-I	[Acronym] Co-Investigator

COM	[Acronym] Centre of Mass
console	[Generic HIPE] A panel of the HIPE GUI where you can write commands
constructor	[I/O; Data types; Other] In object-oriented programming a constructor in a class is a special block of statements that are called when an object is created declared or constructed)
Context	[I/O: Data types; Other] A Context is a special type of product that contains references to other products stored. Think of it as a bag of other products. This enables a means of building complex data structures. There are two way that these products can be organised in a Context, as a List where they are accessed by index or as a Map where they are accessed as key—value pairs (similar to a python dictionary)
convertChopper2Angle	[Pipeline] PACS Level 0 task to convert chopper instrument positions to sky angle
convertSignal2StandardCap	[Pipeline] PACS Level 0.5 task to convert all data down to the values they would have had if taken at the lowest capacitance setting. Subsequent tasks require this. Spectroscopy
ConvertFrequencyTask	[Pipeline] HIFI Level 1 pipeline task. Converts the IF frequency scale to the sideband frequencies defined by f_usb = f_LO + f_IF and f_lsb = f_LO - f_IF. At the same time, the units are changed from MHz to GHz. Can also be used to transform back to the IF or a velocity scale
COP	[Acronym] Commissioning Operations Plan or Commissioning phase (CoP)
corrBolTimeResponse	[Pipeline] SPIRE photometry Level 0.5 task to do the bolometer time response correction. Common to jiggle and scan map pipelines
CP	[Acronym] Calibration Pointing
CQM	[Acronym] Cryogenic Qualification Model
CRE	[Acronym] Cryogenic Readout Electronics (in some documents: Cold Readout Electronics)
createSpirePointing	[Pipeline] SPIRE photometry Level 0.5 task to run the Pointing Task to get the instrument pointing timeline. Common to jiggle and scan map pipelines
CRS	[Acronym] Coarse Rate Sensors
CS	[Acronym] (internal) calibration source
CSDT	[Acronym] Common Software Development Team
CST	[Acronym] Community Support Tools
Cube	[I/O; Data types; Other] a class of product at Level 1 to 2, of 3 dimensions, usually RA and Dec and time/wavelength or frequency
CUS	[Acronym] Common Uplink System

cutPhotDetTimelines	[Pipeline] SPIRE photometry ccan map Level 0.5 task to cut the timeline back to scan line range. End of Level 0.5 pipeline
CVV	[Acronym] Cryostat Vacuum Vessel
D/A	[Acronym] Digital to Analogue converter
DAC	[Acronym] Digital to Analogue Converter
DACS	[Acronym] Digital Autocorrelator Spectrometer
DAE	[Acronym] Data Acquisition Electronics (LFI)
DAPSAS	[Acronym] Data Processing and Science Analysis Software
DBMS	[Acronym] Database Management System
dBmW/MHz	[Acronym] Noise power level in dB relative to 1 mW in a 1 MHz bandwidth
DbPool	[I/O; Data types; Other] A type of pool (see pool) for accessing products from a remote database (e.g. the Versant database)
DBS	[Acronym] dual beam switch
DBU	[Acronym] Digital Bus Unit, the digital interface provided by the spacecraft
DC	[Acronym] Direct Current. Also, DC/DC: Direct Current voltage converter
DC/DC	[Acronym] Direct Current voltage converter
DDS	[Acronym] Data Distribution System
deactivateMasks	[Pipeline] PACS task to deactivate specified masks before running a pipeline task
DEC	[Acronym] Detector Control
DECMEC	[Acronym] elecronic board, 2 of them: detector and mechanism controller
deglitchTimeline	[Pipeline] SPIRE photometry Level 0.5 task to do the deglitching for scan maps. Common to jiggle and scan map pipelines
demodulate	[Pipeline] SPIRE photometry Level 0.5 task to perform demodulation on jiggle pipeline data
denodding	[Pipeline] SPIRE photometry Level 0.5 task run to remove nodding from jiggle data. Jiggle pipeline
detectCalibrationBlock	[Pipeline] PACS Level 0 task to identify the calibration blocks and fill the CALSOURCE entry in the status table
Developer's Reference Manual	[Generic HIPE] The documentation that details the whats and hows of java tasks and function in HIPE. These will be a little difficult for those unused to writing programs to understand. Also known as the javadocs or API
DHS	[Acronym] Data Handling System

DHSS	[Acronym] Data Handling Subsystem
dictionary	[I/O; Data types; Other] A type of data array (jython)
dither	[I/O; Data types; Other] Moving sky position a small amount and taking another exposure
DMA	[Acronym] Direct Memory Access
dmchead	[Pipeline] PACS. The Dec Mec (detector mechanism) header. It contains the position and status of the instrument sampled at a high frequency. Values therein are in detector units.
DML	[Acronym] Declared Material List
DMS	[Acronym] Document Management System
DoAntennaTemp	[Pipeline] HIFI Level 1 task to translates to the antenna temperature scale
DoChannelWeights	[Pipeline] HIFI Level 0.5 task to compute the (channel-dependent) weights and fills them into the datasets of type 'science'
DoCleanUp	[Pipeline] HIFI Level 1 task to remove data that is no longer needed after running the Level1 pipeline
DOF	[Acronym] Degree of Freedom
DoFluxHotCold	[Pipeline] HIFI Level 0.5 task that applies the bandpass spectra to the science spectra for the intensity calibration. End of Level 1 pipeline
DoFreqGrid	[Pipeline] HIFI Level 1 task to compute a frequency scale which will be used for resampling
DoHkCheck	[Pipeline] HIFI Level 0.5 task that checks the House Keeping contained in a HifiCalibrationDataset
doHrsCorrSP	[Pipeline] HIFI Level 0 HRS task which corrects HRS spectra from IF non-linearity errors
doHrsCutBandEdges	[Pipeline] HIFI Level 0 HRS task which cuts the edges of the HRS sub-bands, according to the bandpass of the filter. End of HRS pipeline
doHrsFFT	[Pipeline] HIFI Level 0 HRS task which applies a FFT processing on the correlation functions of HRS
doHrsFreq	[Pipeline] HIFI Level 0 HRS task which computes the frequency of the sub-bands
doHrsNorm	[Pipeline] HIFI Level 0 HRS task which normalises the raw correlation functions of HRS
doHrsOffsetPow	[Pipeline] HIFI Level 0 HRS task which computes the offset and power of HRS
doHrsPowCorr	[Pipeline] HIFI Level 0 HRS task which corrects the non-Pipeline.linearity error of the power of HRS.
doHrsQDCFast	[Pipeline] HIFI Level 0 HRS task which corrects roughly the quantisation distortion of the correlation functions

doHrsQDCFull	[Pipeline] HIFI Level 0 HRS task which corrects the quantisation distortion of the correlation functions
doHrsSmooth	[Pipeline] HIFI Level 0 HRS task which applies a Hanning smoothing on the spectra
doHrsSubbands	[Pipeline] HIFI Level 0 HRS task which extracts the HRS sub-bands from the HRS readout
doHrsSymm	[Pipeline] HIFI Level 0 HRS task which symmetries the correlation function of HRS to prepare the FFT
doHrsWindow	[Pipeline] HIFI Level 0 HRS task which applies a Hanning or Hamming windowing to the correlation functions of HRS
DoOffSubtract	[Pipeline] HIFI Level 0.5 task to compute the differences between ON and OFF positions
DoPointingTask	[Pipeline] HIFI Level 0.5 task that applies the Pointing Product to the HTP to give position of the spectrum
DoRadialVelocity	[Pipeline] HIFI Level 1 task to correct the local oscillator frequency for the radial velocity of the spacecraft
DoRefSubtract	[Pipeline] HIFI Level 0.5 task that is used for the reference subtraction
DoSidebandGain	[Pipeline] HIFI Level 1 task that applies the sideband gain coefficients to the flux values
DoSpurs	[Pipeline] HIFI Level 1 task that removes spurious signals in the scans
DoSubStitch	[Pipeline] HIFI Level 1 task to adjust the subbands relative to each other, possibly removing the overlap
DoWbsBadPixels	[Pipeline] HIFI Level 0 WBS task that applies the masking pixel list
DoWbsDark	[Pipeline] HIFI Level 0 WBS task to subtract the dark values for all scans in a HifiSpectrumDataset
DoWbsFreq	[Pipeline] HIFI Level 0 WBS task that creates a frequency table for each scan
DoWbsNonLin	[Pipeline] HIFI Level 0 WBS task to perform nonlinearity correction for even and odd WBS pixels
DoWbsScanCount	[Pipeline] HIFI Level 0 WBS task to normalise the integration time of each scan to 10 milliseconds
DoWbsSubbands	[Pipeline] HIFI Level 0 WBS task that separates the output from CCDs into the four subbands for theWBS for all HifiSpectrumDatasets contained in the HifiTimelineProduct
DoWbsZero	[Pipeline] HIFI Level 0 WBS task that subtracts appropriate zero spectra for each time step
DP	[Acronym] Data Processing (usually what we call the HIPE data processing language)
DPL	[Acronym] Declared Process List

DPOP	[Acronym] Daily Prime Operational Phase
DPU	[Acronym] Data Processing Unit
DRCU	[Acronym] Detector Readout and Control Unit
DRM	[Acronym] Developer's Reference Manual
DS	[Acronym] Digital Serial
DSB	[Acronym] Double Side Band
DSP	[Acronym] Digital Signal Processor
DTCP	[Acronym] Daily Telecommunications Period
EDAC	[Acronym] Error Detection And Correction
elecCrossCorrection	[Pipeline] SPIRE photometry Level 0.5 task to do the electrical crosstalk correction. Common to jiggle and scan map pipelines
editor	[Generic HIPE] A panel of HIPE in which you can load, write and run scripts and in which other GUI-based tasks will open
EOM	[Acronym] End of Mission
EOP	[Acronym] Early Orbit Phase
EP	[Acronym] Entrance Pupil
EPLM	[Acronym] Extended Payload Module
ESAC	[Acronym] European Space Astronomy Centre
ESD	[Acronym] Electrostatic Discharge
ESOC	[Acronym] European Space Operations Centre
ESTEC	[Acronym] European Space Technology and Research Centre
ESTRACK	[Acronym] European Space Tracking Station Network
EU	[Acronym] Electrical Unit
FCU	[Acronym] Focal Plane Control Unit (HIFI)
f/D	[Acronym] Ratio of focal length to Diameter
FEM	[Acronym] Front End Module (LFI)
FEU	[Acronym] Front End Unit (LFI)
FFT	[Acronym] Fast Fourier Transform
FH	[Acronym] Feed Horn (LFI)
filterSlew	[Pipeline] PACS Level 1 photometry task to remove the data taken during satellite slews
findBlocks	[Pipeline] PACS Level 0 task to organise your data into "blocks" according to an internal logical. Result is put in the BlockTable of your product

fitRamps	[Pipeline] PACS Level 0 task to fit the slope of the averaged or raw ramps, turning a Ramps product into a Frames product. Spectroscopy
flag	[Generic HIPE] A flag in the context of the pipeline is a layer in a data product where data points, or whole pixels, have been identified as (potentially) bad; aka mask. See also quality flag
flagChopMoveFrames	[Pipeline] PACS Level 0 task to mask individual data points that were taken while the chopper was moving. Spectroscopy
flagGratMove	[Pipeline] PACS Level 0 task to mask individual data point that were taken while the grating was moving. Spectroscopy
FM	[Acronym] Flight Model
FoV	[Acronym] Field of View
FP	[Acronym] Fabry-Perot
FPA	[Acronym] Focal Plane Assembly
FPU	[Acronym] Focal Plane Unit
FRD	[Acronym] Formatted Raw Data
frame	[I/O; Data types; Other] A GUI, or a window in a GUI; see also Frames
Frames	[I/O; Data types; Other] Data Frames (or frames) is a generic word used for the datasets that comes from Herschel. Frames is also PACS class of data product that goes through the pipeline
FS	[Acronym] Flight Spare Model
FSS	[Acronym] Fine Sun Sensor
FTB	[Acronym] Focal Plane JFET and/or RF filter box (SPIRE)
FTP	[Acronym] File Transfer Protocol
FTS	[Acronym] Fourier Transform Spectrometer
FWHM	[Acronym] Full Width Half Maximum
GaAs	[Acronym] Gallium Arsenide Semiconductor
GeGa	[Acronym] Germanium Gallium Detector
getCalTree	[Pipeline] PACS task to get the calibration tree, necessary to do any pipeline processing
getObservation	[I/O; Data types; Other] PACS task to get your ObservationContext from pool or from the HSA
glitch	[Generic HIPE] A hiccup in the signal, due e.g. to a cosmic ray. Unlike for optical data, these glitches may affect the response of the immediately subsequent readouts
GO	[Acronym] Geostationary Orbit or Guest Observer
G/S	[Acronym] Ground Station

G/T	[Acronym] Gain to Temperature Ratio.
GT	[Acronym] Guaranteed Time
GTO	[Acronym] Geostationary Transfer Orbit or Guaranteed Time Observer
GUI	[Acronym] Graphical User Interface
GYR	[Acronym] Gyroscope
HAIO	[Acronym] Herschel Archive Interoperability
HBES	[Acronym] HIFI Back-End Sub-system
HBES-1	[Acronym] HBES IF processor
HBES-2	[Acronym] HBES high resolution spectrometer
HBES-3	[Acronym] HBES wide band spectrometer
HCNE	[Acronym] Herschel Confusion Noise Estimator
HCSS	[Acronym] Herschel Common Science System
HDB	[Acronym] HSA Data Base
HDD	[Acronym] HSA Data Distribution
HDP	[I/O; Data types; Other] Herschel Data Processing (usually what we call our data processing language)
HDU	[Acronym] Header Data Unit (FITS)
HEB	[Acronym] Hot Electron Bolometer
HEMT	[Acronym] High Electron Mobility Transistor
HEO	[Acronym] Highly Eccentric Orbit
HET	[Acronym] Heterodyne instrument of the FIRST model payload
HFCU	[Acronym] HIFI Focal Plane Control Unit
HFPU	[Acronym] HIFI Focal Plane Unit
HGA	[Acronym] High-Gain Antenna
HICU	[Acronym] HIFI Instrument Control Unit
HIFI	[Acronym] Heterodyne Instrument for the Far Infrared
HifiPipelineTask	[Pipeline] Task to run all (or any) of the pipeline algorithms for all (or any) of the HIFI spectrometers
HIPE	[Acronym] Herschel Interactive [Data] Processing Environment
HK	[Acronym] House Keeping (data)
H/K	[Acronym] House Keeping (data)

HLCU	[Acronym] HIFI Local Oscillator Control Unit
HLOU	[Acronym] HIFI Local Oscillator Unit
HLS	[Acronym] High-Level Software (LFI)
HOB	[Acronym] Herschel Optical Bench
HOTAC	[Acronym] Herschel Observing Time Allocation Committee
housekeeping	[Generic HIPE] Data about what satellite was doing, it state, during your observation. The general user will never need to look at the housekeeping data
HPBW	[Acronym] Half-Power Beam Width
HPMCS	[Acronym] Herschel/Planck Mission Control System
HRI	[Acronym] High-Resolution IF processor (HIFI)
HRP	[Acronym] High Resolution IF Processor
HRS	[Acronym] High-Resolution Spectrometer (HIFI)
HSA	[Acronym] Herschel Science Archive
HsaReadPool	[I/O; Data types; Other] A type of pool (see pool), to access the Herschel Bcience Archive
HSC	[Acronym] Herschel Science Centre
HSIA	[Acronym] Hardware/Software Interaction Analysis
HSK	[Acronym] House Keeping
HTP	[Acronym] HifiTimelineProduct, a MapContext containing HifiSpectrumDatasets
HttpClientPool	[I/O; Data types; Other] A type of pool (see pool) but networked (for remote access)
HUI	[Acronym] HSA User Interface
H/W	[Acronym] Hardware
IA	[Acronym] Interactive Analysis
ICC	[Acronym] Instrument Control Centre
ID	[Acronym] Identification
I/F	[Acronym] Interface. Also IF: Intermediate Frequence
IF	[Acronym] Intermediate Frequency
IFP	[Acronym] Intermediate Frequency Processor
IFS	[Acronym] Integral field spectroscopy/spectrograph
IFSS	[Acronym] Intermediate Frequency and Spectrometer System
IFU	[Acronym] integral field unit

ILT	[Acronym] Instrument Level Test
InP	[Acronym] Indium Phosphide semiconductor material
I/O	[Acronym] Input/Output
IPAC	[Acronym] (NASA/JPL) Infrared Processing and Analysis Center
IST	[Acronym] Instrument System Test
javadoc	[Generic HIPE] The documentation that details the whats and hows of java tasks and function in HIPE. These will be a little difficult for those unused to writing programs to understand. Also known as the Developer's Reference Manual or API
JIDE	[Acronym] a previous version of HIPE (jython interactive data-processing environment)
jiggleAverage	[Pipeline] SPIRE photometry Level 0.5 task average on the jiggle position for a number (1-4) of DemodPointingProducts. Jiggle pipeline
Label	[Generic HIPE] A bitword recorded with every PACS frame, indicating where we are in the synchronised mechanism movement sequence (chopper plateau, grating movement, e.t.c.)
LAN	[Acronym] Local Area Network
Level 0	[I/O; Data types; Other] Herschel data can have up to 5 levels, depending on the amount of (mainly pipeline) processing that has been performed. There is a common convention for all Herschel instruments. Level 0 has had no pipeline processing done, and the data are organised in a time sequence (and perhaps other parameters)
Level 0.5	[I/O; Data types; Other] Herschel data can have up to 5 levels, depending on the amount of (mainly pipeline) processing that has been performed. There is a common convention for all Herschel instruments. Level 0.5 has had all basic pipeline processing done so the product can be inspected
Level 1	[I/O; Data types; Other] Herschel data can have up to 5 levels, depending on the amount of (mainly pipeline) processing that has been performed. There is a common convention for all Herschel instruments. Level 1 has had all instrument-correction type pipeline processing done and the data converted to physical units; they may now need to be inspected by the astronomer
Level 2	[I/O; Data types; Other] Herschel data can have up to 5 levels, depending on the amount of (mainly pipeline) processing that has been performed. There is a common convention for all Herschel instruments. Level 2 data should be of science quality
Level 3	[I/O; Data types; Other] Herschel data can have up to 5 levels, depending on the amount of (mainly pipeline) processing that has been performed. There is a common convention for all Herschel instruments. It is hoped that Level 3 data will be astronomical results derived from the data by the user and

	such results maybe input into the Herschel archive (e.g. source catalogues). Suitable for VO (Virtual Observatory) access
LGA	[Acronym] Low-Gain Antenna
list	[I/O; Data types; Other] An array of data (jython)
list context	[I/O; Data types; Other] see ListContext
ListContext	[I/O; Data types; Other] A type of Context which is a list of individual products (some of which can themselves be lists or other Contexts); see also Context
LOBT	[Acronym] Local On-Board Time
LocalPool	[I/O; Data types; Other] PACS. A way to define where you want your pool to be so you can save a product to it
local store	[I/O; Data types; Other] The local store (by default in [your home directory].hcss/lstore) is a database in the form of a directory structure which contains pools of products in the form of FITS files. These pools are themselves subdirectories of the local store. See also storage, pool, PAL
LocalStore	[I/O; Data types; Other] The local store (by default in [your home directory].hcss/lstore) is a database in the form of a directory structure which contains pools of products in the form of FITS files. These pools are themselves subdirectories of the local store. See also storage, pool, PAL
LOS	[Acronym] Line of Sight
LOU	[Acronym] Local Oscillator Unit
lpfResponseCorrection	[Pipeline] SPIRE photometry Level 0.5 task to do the electrical Low Pass Filter response correction. Common to jiggle and scan map pipelines
LSB	[Acronym] Lower Side Band
LSU	[Acronym] Local Oscillator Synthesiser Unit (HIFI)
LTA	[Acronym] Long Term Archive
LWU	[Acronym] Local Oscillator Waveguide Unit (HIFI)
M3	[Acronym] Third Mirror in the optical train starting with the telescope primary
makeTodArray	[Pipeline] PACS Level 1 photometry task to build a time-ordered data stream for input into MadMap and add to the meta header for the output skymap
MapContext	[I/O; Data types; Other] A MapContext is a Context for products grouped into containers with access to each by a key (similar to a python dictionary). See also Context
mask	[Generic HIPE] A layer in a data product where data points, or whole pixels, have been identified as (potentially) bad. Not the same as quality flags
MCC	[Acronym] Mission Control Centre

M-CDR	[Acronym] Mission Level CDR
MCM	[Acronym] Multi Chip Module
MEM	[Acronym] Maximum Entropy Method
Meta data	[I/O; Data types; Other] The data about an observation that are held in the Meta header (which is much like a FITS header)
Meta header	[I/O; Data types; Other] Information about an observation that is contained in a "header", much like a FITS header.
method	[I/O; Data types; Other] In object-oriented programming a method is a group of (software) instructions that is given a unique name and can be called up at any point by simply quoting the name. In other languages a method is called a function, subroutine or procedure. Example: > myTask.getSomething(); the getSomething() is a method for myTask and it returns an answer that depends on what is (or is not) in the ()
MIP	[Acronym] Mission Implementation Plan
MkFluxHotCold	[Pipeline] HIFI Level 0.5 task to compute the bandpass and receiver temperature for the intensity calibration of the spectra
MkFreqGrid	[Pipeline] HIFI Level 1 pipeline task. At the end of the generic pipeline, the flux of all the resulting scans are resampled to a common frequency grid which this tasks computes
MkOffSmooth	[Pipeline] HIFI Level 0.5 task to calibrate a baseline by processing the measurements of an OFF position in sky
MkSidebandGain	[Pipeline] HIFI Level 1 task that prepares a helper object that provides the means to compute the IF- and LO-Pipeline.frequency dependent sideband gains ratios
MkSpur	[Pipeline] HIFI Level 0 WBS task to identify spurs in WBS HifiTimelineProducts. End of WBS pipeline
MkWbsBadPixels	[Pipeline] HIFI Level 0 WBS task that checks for saturated pixels
MkWbsFluxAtten	[Pipeline] HIFI Level 0 WBS task that analyses the attenuator settings
MkWbsFreq	[Pipeline] HIFI Level 0 WBS task that derives frequency scale from comb spectra
MkWbsZero	[Pipeline] HIFI Level 0 WBS task that checks the zeros and compute an interpolation function to represent zeros for each time
MLI	[Acronym] Multi-Layer Insulation
MOC	[Acronym] Mission Operations Centre
MoI	[Acronym] Moment of Inertia
MOIS	[Acronym] Mission Operations Information System
NAIF	[Acronym] Navigation Ancillary Information Facility

naiveApppMapper	[Pipeline] Level 1 SPIRE basic mapper for jiggle maps. End of Level 1 pipeline
naiveScanMapper	[Pipeline] Level 1 SPIRE task for basic map creation for scan maps. Scan map pipeline
namespace	[Generic HIPE] An abstract container providing context for the items it holds; a context for identifiers (unique expressions written in code)
NaN	[Acronym] Not a Number
navigator	[Generic HIPE] A panel of the HIPE GUI where you can navigate through your disc and import some data into HIPE
NDIU	[Acronym] Network Data Interface Unit
NEFD	[Acronym] Noise Equivalent Flux Density
NEP	[Acronym] Noise Equivalent Power
NFS	[Acronym] Network File System
NHSC	[Acronym] NASA Herschel Sciencce Centre
nodAverage	[Pipeline] SPIRE photometry Level 0.5 task averaging denodded jiggle data, producing AveragedPhotPointingProduct. Jiggle pipeline
OBCP	[Acronym] on board control procedure
OBDH	[Acronym] On-board Data Handling (System)
OBS	[Acronym] On-board Software
observation context	[I/O; Data types; Other] The Level 0 Herschel data that you will get from the HSA. It contains at least the Level 0 data, and all levels above that have been pipeline-processed by the HSA. It is a wrapper for everything you need to process and understand your observation. The ObservationContext is also a class, and (not to confuse you or anything) it is also a type of MapContext. The ObservationContext can contain data of Levels 0 to 2 and can contain other Contexts, eg Auxiliary and Calibration
ObservationContext	[I/O; Data types; Other] The Level 0 Herschel data that you will get from the HSA. It contains at least the Level 0 data, and all levels above that have been pipeline-processed by the HSA. It is a wrapper for everything you need to process and understand your observation. The ObservationContext is also a class, and (not to confuse you or anything) it is also a type of MapContext. The ObervationContext can contain data of Levels 0 to 2 and can contain other Contexts, eg Auxiliary and Calibration
obsid	[I/O; Data types; Other] Observation identification (number)
OBSM	[Acronym] On-board Software Monitoring System
OBSW	[Acronym] On-board Software
OBT	[Acronym] On-Board Time
OD	[Acronym] Operational Day

ODB	[Acronym] Operational Database
ODD	[Acronym] On-demand Processed Data
ODP	[Acronym] On-demand Processing
ODR	[Acronym] On-demand Processing Report
OFD	[Acronym] On the Fly processed Data or Operations Facilities Document
OFP	[Acronym] On the Fly Processing
OFR	[Acronym] On the Fly Processing Report
OGSE	[Acronym] Optical Ground Support Equipment
OIRD	[Acronym] Operations Interface Requirements Document
operational day	[I/O; Data types; Other] the Herschel day unit
OTAC	[Acronym] Observing Time Allocation Committee
OTF	[Acronym] On-Target Flag
OTF	[Acronym] On the Fly
OU	[Acronym] Optics Unit
outline	[Generic HIPE] A panel of the HIPE GUI where an outline of a highlighted item in the variables panel is presented
packages	[Generic HIPE] A logical way of organising tasks and functionalities that have been written for you to use in HIPE. Also a panel of the HIPE GUI where all packages that have been imported into HIPE are displayed
packet sequence	[Generic HIPE] A sequence of packets of the rawest of raw Herschel data (telemetry, tm, files are made of up packet sequences)
PACS	[Acronym] Photodetector Array Camera and Spectrometer
PAL	[Acronym] Product Access Layer
PDB	[Acronym] Proposal Data Base
PDE	[Acronym] Pointing Drift Error
PER	[Acronym] Proposal Evaluation Report
perspective	[Generic HIPE] A perspective is a presentation of the HIPE system that is made available to the user though a set of "views", where views are panels providing particular capabilties. Each view is a separate panel in the HIPE GUI and together they make a perspective.The main toolbar lists all perspectives you can have
photAddInstantPointing	[Pipeline] PACS Level 0 task to do the first step of the astrometric calibration, associating raster point counter, nod counter or sky line scan counter to the individual frames within an observation. Photometry

`photAssignRaDec`	[Pipeline] PACS Level 0.5 task to assign RA and Dec to every pixel in the image. Photometry
`photAvgDith`	[Pipeline] PACS Level 0.5 task to mean-combine the chops, after photDiffChop has been run. Photometry
`photAvgNod`	[Pipeline] PACS Level 0.5 photometry task to average nod signals per nod cycle
`photAvgPlateau`	[Pipeline] PACS Level 0.5 task to average all signals on a chopper plateau (chopper not moving time). Photometry
`photCombineNod`	[Pipeline] PACS Level 0.5 task to combine repeated nod cycles. Photometry
`photConvDigit2Volts`	[Pipeline] PACS Level 0 task to convert units to Volts. Photometry
`photCorrectCrosstalk`	[Pipeline] PACS Level 0 task to correct for electronic crosstalk. Photometry
`photDiffCal`	[Pipeline] PACS Level 0 task to subtract the off and on calibration block data and average the results. Various statistics are calculated. Photometry
`photDiffChop`	[Pipeline] PACS Level 0.5 task to subtract the off- from the corresponding on-.chops. Photometry
`photDiffNod`	[Pipeline] PACS Level 0.5 task to subtract the A and B nods, per cycle. Photometry
`photDriftCorrection`	[Pipeline] PACS Level 0.5 task to apply a correction for drift in the flatfield over the observation. Photometry. End of Level 0.5 pipeline processing
`photFlagBadPixels`	[Pipeline] PACS Level 0 task to mask pixels that have been pre-identified by the PACS team as bad. Photometry
`photFlagSaturation`	[Pipeline] PACS Level 0 task to mask individual data points for being saturated. Photometry
`photFluxConversion`	[Pipeline] SPIRE photometry Level 0.5 task to do the flux conversion. Common to jiggle and scan map pipelines
`photGetPointings4PointSource`	[Pipeline] PACS Level 0.5 task to get the pointings for the virtual aperture; part of the astrometric calibration. Photometry
`photHighPassFilter`	[Pipeline] PACS Level 1 photometry task to remove the 1/f noise
`photMakeDithPos`	[Pipeline] PACS Level 0.5 task to check whether a dither pattern exists, and if so to identify the positions. Photometry
`photMakeRasPosCount`	[Pipeline] PACS Level 0.5 task to add raster position to the status table. Photometry
`photMMTDeglitching`	[Pipeline] PACS Level 0 task to detect, mask and remove the effects of cosmic rays (glitches). Photometry
`photOptCrossCorrection`	[Pipeline] SPIRE photometry Level 0.5 task to do the optical crosstalk correction. Common to jiggle and scan map pipelines

photProject	[Pipeline] PACS Level 1 photometry task to create a map out of images, by adding the images. End of Level 1 pipeline
photProjectPointSource	[Pipeline] PACS Level 1 photometry task to create an image covering the total footprint of a point source of an observation. End of Level 1 pipeline processing
photRespFlatFieldCorrection	[Pipeline] Level 0.5 task to apply the flatfield correction and convert signal to a flux density. Photometry
photShiftDith	[Pipeline] PACS Level 1 photometry task to shift the dither offsets of an observation and then add the images
PHS	[Acronym] Proposal Handling Subsystem
PI	[Acronym] Principal Investigator
P/L	[Acronym] Payload
plastic	[Generic HIPE] The technology used for interaction with the VO (virtual observatory)
PLM	[Acronym] Payload Module
POF	[Acronym] Planned Observations File
pointing product	[Pipeline] PACS. The product that contains the instrument pointing over the entire observation
pool	[I/O; Data types; Other] A pool is a Herschel database on your disc, on an external disc, or online. By default pools are subdirectories off of your local store ([your home directory]/.hcss/lstore). Data therein are in FITS format. In a pool you will usually place data that are related in some way. There are several types of pools, the general user will be most used to ProductPools. See also local store, storage, PAL
POS	[Acronym] Planned Observation Sequence
product	[I/O; Data types; Other] Herschel data are carried about in structures called products, which are like software onions: they are made up of layers, each of which has its own description and history of the contents, and on each of which specific actions can be taken. Peel the layers to get at the actual data, be that one number or arrays of numbers. Generally Herschel data products include meta data keywords, tables wth actual data and the history of the generation of the product
product access layer	[I/O; Data types; Other] PAL. This is a manager to allow you to set up, explore and get data from storage areas. The PAL is also a perspective of HIPE
ProductRef	[I/O; Data types; Other] A reference to a product. Not the actual product but a "link" to it. You can have more than one product "stored" in a ProductRef
product reference	[I/O; Data types; Other] A reference to a product. Not the actual product but a "link" to it. You can have more than one product "stored" in a ProductRef
ProductPool	[I/O; Data types; Other] A type of pool (see pool), containing products

product storage	[I/O; Data types; Other] See storage, because product storage is a "storage" of products. ProductStorage is the name of the java class you use to define a storage
ProductStorage	[I/O; Data types; Other] See storage, because product storage is a "storage" of products, and ProductStorage is the name of the task you can use to define the storage
product viewer	[Generic HIPE] Viewers for looking at products. You can access them from the command line or by clicking on a product in the variables panel/editor panel
PSF	[Acronym] Planning Skeleton File or Point Spread Function
PT	[Acronym] Product Tree
PV	[Acronym] Performance Verification
PVOP	[Acronym] Performance Verification Operations Plan
QA	[Acronym] Quality Assurance
QAR	[Acronym] Quality Assessment Report
QCP	[Acronym] Quality Control Pipeline
QLA	[Acronym] Quick Look Assessment (software)
QM	[Acronym] Qualification Model
QPD	[Acronym] Quality Processed Data
QTR	[Acronym] Qualification Test Review
quality flag	[Generic HIPE] An indication of how well a pipeline task ran
Ramps	[I/O; Data types; Other] A PACS class of product used in the pipeline of Level 0 to 0.5. It has 4 dimensions
raster	[I/O; Data types; Other] Moving sky position by small increments over a larger field to observe a larger area in more dense detail
RCS	[Acronym] Reaction Control System
reference	[I/O; Data types; Other] A pointer to something. For example, when you create an array in HIPE "sey = [4,5,6]", then "sey" is a pointer to [4,5,6]. "sey" is not actually [4,5,6], it just references it
RF	[Acronym] Radio Frequency
RFI	[Acronym] Radio Frequency Interference
RFW	[Acronym] Request for Waiver
RMS	[Acronym] root-mean squared
RPE	[Acronym] Relative Pointing Error
rsrfCal	[Pipeline] PACS Level 0.5 task to correct a spectroscopy Frames product for the relative spectral response function. Absolute correct is done with specRespCal.

RSS	[Acronym] root-sum squared
runMadMap	[Pipeline] PACS Level 1 photometry task to run the java MadMap module. This module uses the maximum-likelihood technique to build a map from an input time-ordered data stream. End of Level 1 pipeline processing
RWA	[Acronym] Reaction Wheel Assembly
SA	[Acronym] Solar Array or Scientific Analysis
SAA	[Acronym] Solar Aspect Angle
SAS	[Acronym] Sun Aquisition Sensors
saveObservation	[I/O; Data types; Other] PACS task to save your ObservationContext to a pool
S/C	[Acronym] Spacecraft
secondDeglitching	[Pipeline] SPIRE photometry Level 0.5 task to do a second level degliticing for jiggle pipeline
SED	[Acronym] Spectral Energy Distribution
SerialClientPool	[I/O; Data types; Other] A type of pool (see pool), to read/write or access a remote pool
SIN	[Acronym] Straylight Induced Noise
S/N	[Acronym] Signal to Noise Ratio
SOVT	[Acronym] System Operation Validation Test
spaxel	[Generic HIPE] A spatial pixel, i.e. the spatial unit of a cube
SPC	[Acronym] Science Programme Committee
specAddInstantPointing	[Pipeline] PACS Level 0 task to add the RA and Dec to the central spaxel. Spectroscopy
specAddNod	[Pipeline] PACS Level 0.5 task to add together corresponding nods. Spectroscopy
specAssignRaDec	[Pipeline] PACS Level 0 task to take the RA and Dec that have been assigned to the central spaxel (specAddInstantPointing) and calculate the pointing for all other spaxels. Spectroscopy
specConvDigits2VoltsPerSecFrames	[Pipeline] PACS Level 0 task to convert the units to Volts/s. For a spectroscopy Frames product
specConvDigits2VoltsRamps	[Pipeline] PACS Level 0 task to convert the units to Volts. For a spectroscopy Ramps product
specCorrectHerschelVelocity	[Pipeline] PACS Level 0 task to correct the wavelength grid for the velocity of Herschel during your observation. Spectroscopy
specCorrectSignalNonLinearities	[Pipeline] PACS Level 0.5 task to correct the Frames data points for the fact that the true slope of the raw ramps (that the frames came from) are not linear. Spectroscopy
specDiffChop	[Pipeline] PACS Level 0.5 task to subtract the off chop data from the corresponding on chop data. Spectroscopy

specDiffCs	[Pipeline] PACS Level 0.5 task to calculate the dark and response from the calibration block, for each pixel. Spectroscopy
specExtendStatus	[Pipeline] PACS Level 0 task to add information to the Status table, based on the previous pipeline processing that you have done. Spectroscopy
specFitSignalDrift	[Pipeline] PACS Level 0.5 task to calculate the drift in the response of the pixels during an observation. Spectroscopy
specFlagBadPixelsFrames	[Pipeline] PACS Level 0 task to add a mask to the bad pixels identified by the PACS team. Spectroscopy
specFlagGlitchFramesQTest	[Pipeline] PACS Level 0.5 task to add a mask to individual data points that are glitches. Spectroscopy
specFlagOutliers	[Pipeline] PACS Level 1 task to flag individual data points in a PacsCube for being outliers (most likely glitches). Spectroscopy
specFlagSaturationFrames	[Pipeline] PACS Level 0 task to mask individual data points for saturation. Works on a Frames product. Spectroscopy
specFlagSaturationRamps	[Pipeline] PACS Level 0 task to mask individual data points for saturation. Works on a Ramps product. Spectroscopy
specFrames2PacsCube	[Pipeline] PACS task to convert a spectroscopy Frames product to a PacsCube product. End of Level 0.5 pipeline processing
specProject	[Pipeline] PACS task to take the RebinnedCube and project each spaxel and each data point onto a regular RA/Dec grid on the sky. Spectroscopy and end of Level 2 pipeline processing
specRespCal	[Pipeline] PACS Level 0.5 task to correct the data to an absolute flux scale. Spectroscopy
Spectrum1d	[I/O; Data types; Other] Is a class of product that is for holding 1-dimensional spectral data
Spectrum2d	[I/O; Data types; Other] Is a class of product that is for holding 2-dimensional spectral data
spectrum container	[I/O; Data types; Other] SpectrumContainer is a class of product. A container of spectra
SpectrumContainer	[I/O; Data types; Other] Is a class of product. A container of spectra
specWaveRebin	[Pipeline] PACS Level 1 task to convert the 5x5 PacsCube with several spectra in each spaxel to a 5x5 RebinnedCube with one spectrum in each spaxel. Spectroscopy. End of Level 1 pipeline processing
SPF	[Acronym] Single Point Failure
SPG	[Acronym] Software/Software Product Generation
SPIRE	[Acronym] Spectral and Photometric Imaging Receiver
SpireListContext	[Pipeline] Level 1 SPIRE task to create a SpireListContext to be used as input for map making. Scan map pipeline

SPR	[Acronym] Software Problem Report
SPU	[Acronym] Signal Processing Unit
SREM	[Acronym] Standard Radiation Environment Monitor
SRPE	[Acronym] Spatial Relative Pointing Error
S/S	[Acronym] Subsystem
SSB	[Acronym] Single Side Band
SSO	[Acronym] Solar System Object
SSR	[Acronym] Solid State Recorders
Status	[I/O; Data types; Other] PACS. Information about the instrument status, held in tabular format and added to as you pipeline process your observation
storage	[I/O; Data types; Other] Consider a storage a database storing data in an structure that Herschel observations require. A storage is the variable defined in HIPE pointing to where the data is on disc, rather than the name of the directory on disc that actually contains the data. See also pool, local store, PAL
STR	[Acronym] Star Trackers
SUM	[Acronym] Satellite User Manual
Summary Table	[I/O; Data types; Other] HIFI. a table for each spectrometer at each level in the ObservationContext, detailing the components of the observation
SVM	[Acronym] Service Module
SVT	[Acronym] System Validation Test
S/W	[Acronym] Software
TA	[Acronym] Trend Analysis (software) or Telescope Assembly
TableDataset	[I/O; Data types; Other] A dataset held in a of tabular structure. Is also a class of product
task	[Generic HIPE] A self-contained HIPE script that does something to the input data. Also a panel of HIPE in which tasks are listed
TC	[Acronym] Telecommand
temperatureDriftCorrection	[Pipeline] SPIRE photometry Level 0.5 task to do the temperature drift correction. Common to jiggle and scan map pipelines
TM	[Acronym] Telemetry. A TM file contains telemetry data, and has a tm suffix
ToO	[Acronym] Target of Opportunity
toolbox	[Generic HIPE] A set of routines for use in data processing and which you can use if writing your own scripts in HIPE

tuple	[I/O; Data types; Other] A type of data array (jython)
UM	[Acronym] User Manual
URD	[Acronym] User Requirements Document
URM	[Acronym] User Reference Manual
URN	[Acronym] Uniform Resource Name (a string identifier to uniquely identify any product stored in any pool)
URR	[Acronym] User Requirements Review
USB	[Acronym] Upper Side Band
useRemoveBaseline	[Pipeline] Level 1 SPIRE task to set a boolean Flag to switch on and off the baseline removal. Scan map pipeline
variables	[Generic HIPE] A named location in memory that holds a value/s that can be modified. Also, the HIPE GUI variables panel is where all products, arrays, or otherwise defined or set variables are listed. You can do things to the variables by clicking on them
VC	[Acronym] Virtual Channel
view	[Generic HIPE] The individual panels you see in the HIPE GUI are "views". These each allow you to view and thus search through something, or allow you to type commands into HIPE. The main toolbar lists all views you can have
VO	[Acronym] Virtual Observatory
waveCalc	[Pipeline] PACS Level 0 task to calculate the wavelength grid from the grating positions for an observation. Spectroscopy.
wavelengthGrid	[Pipeline] PACS Level 1 task to calculate the wavelength grid of a PacsCube. Some optimisation possible. Spectroscopy
WBC	[Acronym] Wide-Band Spectrometer Control (HIFI))
WBI	[Acronym] Wide-Band Spectrometer IF processor (HIFI)
WBO	[Acronym] Wide-Band Spectrometer AOS (HIFI)
WBS	[Acronym] Wide-Band Spectrometer
WBSPU	[Acronym] Wide Bandwidth Spectrometer Processing Unit
WCS	[Acronym] world coordinate system
WFE	[Acronym] WaveFront Error
WG	[Acronym] Wave Guide
workbench	[Generic HIPE] The main GUI of HIPE in where you will work. Full workbench has more panels that the workbench, but all panels can also be accessed from the main toolbar
XML	[Acronym] Extensible Markup Language

Chapter 1. Numeric

1.1. Introduction

This guide is written with Jython users in mind and has a strong focus on Jython syntax. Nevertheless the information found here may be quite useful for Java developers as well.

Quick Start	This may help you starting up.
Import statements	Describes various ways to get access to the functionality in this library.
Constants	Describes a couple of useful constants you can import.
Arrays	All you need to know about arrays that are defined within this library.
Toolboxes	All the functions and procedures within this library are grouped in toolboxes.

1.2. Quick Start

The following code serves as a quick introduction that may help using the library.

```
# Get everything from the library:
from herschel.ia.numeric.all import *

# Define an 2d double array, and populate it:
x=Double2d(2,3)
x[0,:]=[1,2,3]
x[1,:]=[4,5,6]
print x

# Compute the result of a simple addition:
y=x+1
print y

# Similarly, but do this by altering x itself:
x+=1
print x

# Using a function:
y=SQUARE(x)
print y
```

1.3. Import statements

This section is not applicable if you access the library components from within a HIPE session, because in these cases all the components are automatically available.

A Jython session does not give automatic access to numeric arrays and/or functions respectively. For that you have to import them into the name-space of your Jython session.

Alternatively you can get finer control over what you import into your session. Because of the layout of the library, you can choose to import arrays definitions only, or even a single array definition.

For those users that are familiar with Java, Jython provides a way to avoid name-space pollution by importing a single name into your session:

```
import herschel
x=herschel.ia.numeric.Double1d([0.,1/3.,0.5,1])
```

```
f=herschel.ia.numeric.toolbox.basic.Basic.SIN
y=f(x)
```

In fact, the import statement above gives you access to the complete herschel code without potential name clashes. Alternatively you could do something like:

```
import herschel.ia.numeric
x=numeric.Double1d([0.,1/3.,0.5,1])
f=numeric.toolbox.basic.Basic.SIN
y=f(x)
```

Importing everything

As a user you may want to import all the arrays and functions of the numeric library in one go. This may be rather convenient as it avoids importing all the bits and pieces yourself.

The easiest way to get access to the library is to import every array and function definition into your name-space using the `all` module:

```
from herschel.ia.numeric.all import *
```

1.4. Constants

The `java.lang.Math` class contains two constants representing #, the ratio of the circumference of a circle to its diameter, and *e*, the base of the natural logarithms. Although these constants do not belong to the Numeric library, they are described here for being a useful tool in many numerical algorithms.

These constants are the best approximations achievable with real numbers, so you are advised to use them instead of defining these quantities yourself. The following code shows how to import the two constants:

```
HIPE> from java.lang.Math import PI
HIPE> print PI
HIPE> 3.141592653589793
HIPE> from java.lang.Math import E
HIPE> print E
HIPE> 2.718281828459045
```

1.5. Arrays

This chapter describes how to create and access arrays.

Definitions	Description of all supported array types and dimensions.
Creation	Creation and initialization of arrays.
Properties	General information about your array.
Conversions	Implicit and explicit conversions..
Operators	Unary and binary operators that can be applied to arrays.
Methods	Additional mechanisms to access or manipulate your array, such as `where`, performing functions in-line.

Definitions

The library defines the following arrays:

	rank of the array				
Type	**1**	**2**	**3**	**4**	**5**
String	String1d	-	-		
Boolean	Bool1d	Bool2d	Bool3d	Bool4d	Bool5d
Byte (8-bit)	Byte1d	Byte2d	Byte3d	Byte4d	Byte5d
Short (16-bit)	Short1d	Short2d	Short3d	Short4d	Short5d
Integer (32-bit)	Int1d	Int2d	Int3d	Int4d	Int5d
Long (64-bit)	Long1d	Long2d	Long3d	Long4d	Long5d
Float (32-bit)	Float1d	Float2d	Float3d	Float4d	Float5d
Double (64-bit)	Double1d	Double2d	Double3d	Double4d	Double5d
Complex (128-bit)	Complex1d	Complex2d	Complex3d	Complex4d	Complex5d

Creation

There are various ways to create an array:

Creating a numeric array of a particular shape

You can create an array by specifying the size of each dimension and optionally a scalar value that is used to initialize all the elements. In general the syntax looks like:

```
x=ArrayPrefix1d(length[,value])
x=ArrayPrefix2d(m,n[,value])
x=ArrayPrefix3d(m,n,p[,value])
```

, where `ArrayPrefix1d` is something like `Int1d`.

Examples:

```
x=Bool1d(1)               # [false]
x=Int1d(3)                # [0,0,0]
x=Int1d(3,4)              # [4,4,4]
x=Double2d(3,4)           # [ [0.0,0.0,0.0], [0.0,0.0,0.0], [0.0,0.0,0.0] -]
x=Complex3d(2,3,4,4-3j)
```

Warning

Caveat for users that come from IDL and FORTRAN: The Jython scripting language (and Java for that matter) is using the *last* dimension as the fastest running index! Therefore, the IDL construct `DBLARR(2,3,4)` is equivalent to the Jython construct `Double3d(4,3,2)`.

Creating a 1d array as a range

Using the following syntax:

```
x=ArrayPrefix1d.range(n)
```

, you can create a one-dimensional array of `n` elements, containing the values `[0,1,...,n-1]`.

Examples:

```
x=Int1d.range(3)          # [0,1,2]
x=Double1d.range(4)       # [0.0,1.0,2.0,3.0]
```

```
x=Complex1d.range(2)      # [0.0+0.0j,1.0+0.0j]
```

Note, this does not work for `Bool1d` *and* `String1d`

Creating a numeric array from a jython array

You can create a numeric array from a jython array. Doing so, the library checks whether the jython array was jagged or not.

```
jx=[1,2,3]                # a jython array
x =Int1d(jx)              # a numeric array of rank 1
x =Int1d([1,2,3])         # idem, but in one go

jx=[ [1,2,3], [4,5,6] -]   # a jython array of arrays
x =Double2d(jx)           # a numeric array of rank 2
x =Double2d([ [1,2,3], [4,5,6] -])
```

Making a copy of a numeric array

The assignment `y=x` will usually mean that the variable names `x` and `y`*refer* to the same values.

For example:

```
x=Int1d.range(3)
y=x
print y    # [0,1,2]

x[0]=-1
print y    # [-1,1,2], as x and y refer to the same contents!!
```

If you would like to create a copy, you have to do that explicitly:

```
x=Int1d.range(3)
y=x.copy()
print y      # [0,1,2]

x[0]=-1
print y      # [0,1,2]
```

Note that this behavior is not specific to this library, but it is part of the jython language!

You may want to consult the following link for more insights about sharing data in numeric arrays.

Converting to another type

You can convert a numeric array to another numeric array of the same shape but of different type:

```
x=Int1d([3,4,5])
y=Double1d(x)
z=Complex1d(x)
x=Int1d(y)
```

Properties

Properties (sometimes called attributes or fields, depending on what computer languages you are familiar with) are named items that tell something about your variable.

An array has several *read-only* properties that can be accessed using the following syntax:

```
variable.property
```

This chapter explains the common properties of an array, using the following example variable:

```
x=Int3d(3,5,4)
```

Class

You can ask the array for its Definitions:

```
print x.__class__# herschel.ia.numeric.Int3d
```

Note the underscores. Actually, this property is not specific to arrays. In fact it can be used on any variable in your jython session, as this property is defined as part of the Jython language!

Size

The size gives you the number of all elements within the array

```
print x.size       # 60
```

Rank

The rank is the number of dimensions of an array

```
print x.rank        # 3
```

Dimensions

The dimensions property tells you something about the number of elements along each dimension.

```
print x.dimensions      # [3,5,4]
print x.dimensions[0]   # 3
```

Conversions

Often you are dealing with an array of a specific type, but your function expects another type. In those cases the array needs to be converted.

Below we discuss the conversion behaviors:

Implicit Conversion

An implicit conversion is something the *system* is doing for you. A function may need a Double1d as input, but it can also handle an Int1d. It just silently converts it to what is needed.

Examples:

```
x=Double1d.range(3) # [0.0,1.0,2.0]
x[0]=1              # implicitly convert -'1' to -'1.0'
y=Byte1d.range(3)   # [0,1,2]
x+=y                # implicitly convert y to the type of x
```

Explicit Conversion

An explicit conversion is something *you* force upon the system. This may be because a particular function is expecting an Float1d array, but your data is stored in an Int1d array.

With an explicit conversions you can also truncate a floating point array into an integer array; this is called narrowing. The opposite is called widening.

Examples:

```
f=Float1d.range(3)+0.5  # [0.5,1.5,2.5]
d=Double1d(f)           # widening!
i=Int1d(d)              # narrowing! [0,1,2]
```

```
z=Complex1d(d)          # [0.5+0j,1.5+0j,2.5+0j]
```

Operators

The numeric library provides an extensive set of operators that allow you to manipulate the arrays in various ways.

Access

You can access elements in an array by using the square brackets (`[access-part]`) notation. The *access-part* is a comma-separated list of access items, where each item can be an index or a range/slice:

index — The indices run from `0` to `n-1`, where n is the length of a particular dimension.

selection — An arbitrary number of indices for a particular dimension, e.g.:

`Selection([1,3,7,200])`

slice — A slice is specified as: `begin:end[:step]`, where:

- begin — starting index. If not specified, it assumes the first element; if negative, it counts backwards from the **length** of the dimension in question.
- end — ending index. The specified index is *excluded*. If not specified, it takes the length of the dimension in question; if negative, it counts backwards from the **length** of the dimension in question.
- step — step size. Must be a positive number. If not specified, it assumes a default step size of one.

Note, that [:],[::],[:end:],[start:], [::step] are all valid statements, as each field is optional.

To illustrate the above we will use the following variables:

```
vector # array data of rank 1
array  # array data of rank 2
cube   # array data of rank 3
```

Rank 1 Arrays

Syntax:

```
# elemental access
vector[i]=value
value=vector[i]

# slices
vector[i:j]=value     # value is {scalar|data1d|jython-1d-sequence}
value=vector[i:j]     # returns a data1d of the same type as vector
```

Example:

```
x=Int1d([1,2,3,4,5,6])
#        -| -| -| -| -| -|
# index: 0 1 2 3 4 5
x[1]                                # 2 as indexing always starts at 0
x[:]                                # [1,2,3,4,5,6]
x[1:]                               # [2,3,4,5,6]
x[:-1]                              # [1,2,3,4,5]
x[2:5]                              # [3,4,5]
x[::2]                              # [2,4,6]
```

Rank 2 Arrays

Syntax:

```
# elemental access
array[i,j]=value          # value is a scalar
value=array[i,j]

# slices
array[i0:i1,j0:j1]=value  # value is {scalar|data2d|jython-2d-sequence}
value=array[i0:i1,j0:j1]  # returns a data2d of the same type as array

# section
array[i,j0:j1]=value      # value is {scalar|data1d|jython-1d-sequence}
array[i0:i1,j]=value
value=array[i0:i1,j]      # returns a data1d of the same type as array
value=array[i,j0:j1]
```

Example:

```
x=Int2d([[1,2,3,4],[5,6,7,8],[9,10,11,12]])
x[1,1]              # 6
x[1,:]              # [5,6,7,8]
x[:,1]              # [2,6,10]
x[:,1:-1]           # [ [2,3],[6,7],[10,11] -]
```

Rank 3 Arrays

Syntax:

```

# elemental access
cube[i,j,k]=value             # value is a scalar
value=cube[i,j,k]

# slices
cube[i0:i1,j0:j1,k0:k1]=value # value is {scalar|data3d|jython-3d-sequence}
value=cube[i0:i1,j0:j1,k0:k1] # returns a data3d of the same type as cube

# section
cube[i,j0:j1,k0:k1]=value     # value is {scalar|data2d|jython-2d-sequence}
cube[i0:i1,j,k0:k1]=value
cube[i0:i1,j0:j1,k]=value
cube[i,j0:j1,k0:k1]=value     # returns a data2d of the same type as cube
cube[i0:i1,j,k0:k1]=value
cube[i0:i1,j0:j1,k]=value

cube[i,j,k0:k1]=value         # value is {scalar|data1d|jython-1d-sequence}
cube[i,j0:j1,k]=value
cube[i0:i1,j,k]=value
value=cube[i,j,k0:k1]         # returns a data1d of the same type as cube
value=cube[i,j0:j1,k]
value=cube[i0:i1,j,k]
```

Arithmetic Operators

You can use the following list of operators on arrays that are of numeric type (Byte arrays ... Complex arrays):

OP	Operation	Example	Before	After
*	multiplication	x*2	4	8
/	division	x/2	4	2
+	addition	x+2	4	6
-	subtraction	x-2	4	2

****	exponentiation	`x**2`	4	16
%	modulus	`x%2`	5	1

, where **OP** denotes the operator symbol. All arithmetic operators can be used with the following syntax:

```
# classic
arrayNd = arrayNd OP scalar
arrayNd = arrayNd OP arrayNd

# in-line
arrayNd OP= scalar
arrayNd OP= arrayNd
```

, where `arrayNd` is the name of an array variable of `N` dimensions. The first two lines create a new array. The new array has the same type as the widest type of the two variables in the right-hand-side expression:

```
a=Int1d([1,2,3])
b=Float1d([4,5,6])
c=a*1.          # c is a Double1d
c=a+b        # c is a Float1d
```

The form `OP=`, we sometimes refer to as an *in-line operator*, as they do not produce a new result, but apply the operation on the left-hand-side. Though this form is functionally equivalent to its counterpart (`z=x OP y`), there are some subtleties.

The in-line form of the operator does not create an array, but tries to change the left-hand-side. This saves memory and increases speed of the operation.

Note, that the type of the right-hand-side can not be wider than the left-hand-side:

```
x=Int1d([1,2,3])
y=Float1d([4,5,6])
x+=1.       # error: the right-hand-side is a floating point scalar!
x+=y     # error: the right-hand-side is a floating point array!
x*=2     # OK: [2,4,6]
y+=x     # OK: [6.0,9.0,12.0]
```

Logical Operators

Logical operators combine logical expressions, and they are defined for all boolean arrays.

If one defines two variables:

```
x=Bool1d([1,0,1,0])
y=Bool1d([1,0,0,1])
```

then the following logical operators are applicable:

OP	Operator	Example	Result
&	and	`x & y`	[true,false,false,false]
|	inclusive or	`x | y`	[true,false,true,true]
^	exclusive or	`x ^ y`	[false,false,true,true]

Relational Operators

Relational operators compare two arrays on an element-by-element basis, and they are defined for all numeric ordered arrays (thus not for complex arrays).

If one defines two variables:

```
x=Int1d([1,2,3])
y=Double1d([3,2,1])
```

then the following relational operators are applicable:

OP	Operator	Example	Result
<	less than	`x < y`	[true,true,false]
<=	less than or equals	`x <= y`	[true,true,false]
==	equals	`x == y`	[false,true,false]
!=	not equals	`x != y`	[true,false,true]
>=	greater than or equals	`x >= y`	[false,true,true]
>	greater than	`x > y`	[false,false,true]

Methods

This section is under construction.

This section describes various special methods of all defined arrays.

Apply and Perform Methods	Methods that allow you to execute a function onto an array either by creating a new result or modifying the input array itself.
Where	Where methods act like query mechanisms that may help you to filter your data.
Operator Methods	Alternative approach for using operators such as `+, -, . . .` and potential benefits.
Methods	Expanding arrays along a specified dimension

Apply and Perform Methods

In general a Jython User will use the following Jython syntax to apply functions to an array:

```
x=Double1d(...)
y=SIN(SQUARE(x))
```

Method: apply()

Using the Java syntax in Jython provides exactly the same results:

```
x=Double1d(...)
y=x.apply(SQUARE).apply(SIN)
```

Method: perform()

Note that in the examples above two array copies are made. An alternative that mutates the array itself:

```
x=Double1d(...)
x.perform(SQUARE).perform(SIN)
```

Combining

If you want to keep the original data intact, a combination of apply and perform might do the trick:

```
x=Double1d(...)
y=x.apply(SQUARE).perform(SIN)
```

When to use what

In the last example, the SQUARE function is applied to x in order to create a new array; then the SIN function is performed onto the newly created array.

The combination of apply and perform methods allow you to avoid unnecessary creation and initialization of temporary arrays. That is, it allows for optimization of your code

In general, we recommend to prototype your code with the normal syntax. Once satisfied with your algorithm, you may want to tune it using the methods described above.

Where

The `where` method allows you to to query and filter your array data. The mechanisms and how to use it are described in this chapter.

Functionality

`Where` methods return a Selection object that contains an indexing mechanism into an array. The basic syntax is:

```
q=x.where( predicate -)
y=x[q]                  # getting selected elements
x[q]=v                  # setting selected elements
```

where:

- **x** is the array this function is operating on,
- **predicate** - the applied logical function,
- **q** is a Selection object containing the subscripts of those elements matching specified predicate;
- **y** - a one dimensional array holding only those elements in `x` that are defined at subsscripts defined in `q`;
- **v** - is a value or an array of values of the same type as `x`. These values are assigned to those elements in `x` that are defined at subsscripts defined in `q`.

Selection object

All `where` methods return a selection. A selection object is a container of *long index* subscripts, where a multi-dimensional array is treated as if it would be a one-dimensional array.

Taking a two-dimensional array as an example, the mapping is as follows:

Table 1.1. Mapping of long indices to normal indices in a m x n array.

	j=0	**1**	**...**	**n-1**
i=0	0	1	...	n-1
1	1*n	1*n+1	...	1*n+n-1
:	:	:	:	:
m-1	(m-1)*n	(m-1)*n+1	...	(m-1)*n+n-1

For example the subscripts `(i=2,j=2)` in a `(m x n)=(3x4)` array correspond to the `long index=2*4+2=10`.

Basic Usage

The `where` function works on arrays of any rank, except for an input argument that is a Jython *lambda* expression: this kind of functionality is limited to arrays of rank one.

Below follows the various ways of using `where` functionality:

Using a mask as your predicate

As described above the predicate specifies the condition(s) that are evaluated for the array the `where` method is operating on.

One way of using this method is by providing a mask as a predicate. You can create this mask manually or as a result of a logical expression. The mask must have the same shape as the array it is operating on:

```
x=Double1d(  [1,2,3,4,5,6,7,8,9,10] -)

# Applying a manually created mask
q=x.where(Bool1d( [1,0,1,0,1,0,1,0,1,0] -))
print q              # [0,2,4,6,8]
print x[q]           # [1,3,5,7,9]

# Applying a mask resulting from a logical expression:
q=x.where( (x>2).and(x<8) -)            # alternative syntax: (x>2)&(<8)
print q                                 # [2,3,4,5,6]
print x[q]                              # [3,4,5,6,7]

# Same, but now on a 2x5 array:
x=Double2d( [ [1,2,3,4,5],[6,7,8,9,10] -] -)
q=x.where( (x>2).and(x<8) -)      # alternative syntax: (x>2)&(<8)
print q                                 # [2,3,4,5,6]
print x[q]                              # [3,4,5,6,7]

# Assignment
x[q]=44
print x
# [[1,2,44,44,44],[44,44,8,9,10]]
x[q]=Double1d([33,22,11,22,33])
print x                                 # [[1,2,33,22,11],[22,33,8,9,10]]
```

Using Predicate Functions

The `where` method also works in conjunction with array predicate objects, such as the function IS_FINITE (is finite number).

```
x=Double1d(  [1,2,Double.NaN,3,4] -)
q=x.where(IS_FINITE)
print x[q]                              # [1,2,3,4]
```

Lambda Predicate Expressions

Lambda expressions are Jython constructs to apply a certain logic to a list of elements:

```
x=Double1d(  [1,2,3,4,5,6,7,8,9,10] -)
q=x.where(lambda i: i>2 and i<8)
print x[q]                              # [3,4,5,6,7]
```

When to use what

Predicate function and boolean arrays have a better performance than lambda expressions.

Advanced Usage

A selection created on one object can be applied to another object as well. This is demonstrated in the sections below.

Applying a selection along a dimension

Suppose a set of numeric arrays are somehow related, for example -using the objects defined below- the value a1d[i] is related to a2d[i,:] and a3d[:,i,:].

Then we create a selection by e.g. applying the `where` function on a1d, and apply that selection to a2d and a3d as well as follows:

```
# ---- array definition ----
# 4 elements
a1d=Double1d([1,5,Double.NaN,2])
# 4x3 elements
a2d=Int2d([ [1,2,3],[4,5,6],[7,8,9],[10,11,12] -])

# 2x4x2 elements
a3d=Byte3d([ [[1,2],[2,3],[3,4],[4,5]], [[5,4],[4,3],[3,2],[2,1]] -])

# ---- creating a selection manually ----
mask=Bool1d([1,0,0,1])
q=a1d.where(mask)
print -"Selected indices:",q # [0,3]

# ---- filtering your data ----
print a1d[q]                # [1.0,2.0]
print a2d[q,:]              # [ [1,2,3],[10,11,12] -]
print a3d[:,q,:]            # [ [[1,2],[4,5]], [[5,4],[2,1]] -]

# ---- creating a selection using predicate function ----
q=a1d.where(IS_FINITE)
print -"Selected indices:",q # [0,1,3]

# ---- filtering your data ----
print a1d[q]                # [1.0,5.0,2.0]
print a2d[q,:]              # [ [1,2,3],[4,5,6],[10,11,12] -]
print a3d[:,q,:]            # [ [[1,2],[2,3],[4,5]], [[5,4],[4,3],[2,1]] -]
```

Applying a selection on an array of different shape

The example above showed how to apply a selection along a particular dimension. This section is making use of the *long indexing* features of arrays as described in section Jython Usage->Arrays->Operators->Access.

In short the idea is that a Selection *can* be considered as a set of long indices. For example the indices `[i,j]=[1,2]` in a 4x3 array corresponds to the long index `li=1*3+2=5`. Thus:

```
# ---- definitions ----
a1d=Int1d( [4,1,3,9,2,7,4,5] -)
a2d=Double2d([ [1,2,3,4], [4,3,2,1] -])

# ---- query ----
q=a1d.where( (a1d > 2).and(a1d < 8).and(a1d -!= 4) -)
print q
# [2,5,7]

# ---- query used as long index ----
print a1d[q] # [3,7,5]
print a2d[q] # [3.0,3.0,1.0]
```

Manipulating and creating Selections

The `where` method creates a Selection for you as specified by the predicate argument of this method. It is possible however to create and/or manipulate the indices yourself by converting a selection to and from an Int1d array as follows:

```
# create a selection from an integer array
q=Selection([1,2,6]) # holding indices 1,2 and 6

# extracting the indices from a selection as an Int1d array
x=q.toInt1d()
x[2]=7

# recreate the modified selectionfrom a Int1d array
q=Selection(x)
```

One possible usage is these conversions may be a function that manipulates indices, and the best way to manipulate them is as if they were elements in an integer array (including all the access possibilities and applicable functions). For example if one would like to change the order of of the selection:

```
x=Int1d([1,2,3,4,5])
q=x.where(x > 2) # indices: [2,3,4]
print x[q]          # values:  [3,4,5]

q=Selection(REVERSE(q.toInt1d()))
print x[q]          # values: [5,4,3]
```

Operator Methods

The numeric library provides syntax constructs that allow for the section called “Operators” of writing binary and unary operators, which is not possible in Java. As the library is written for Jython and Java users, these operators are available in the form of methods as well.

There are subtle differences:

- All operators that could be written as inline operators are implemented as methods that mutate the array it operates on.
- All operator methods are explicit, that is no conversions apply. For example adding an array to say an Int1d array only works if the array that is added is an Int1d array as well.

Operator Methods

Arithmetic Operators

All inline operators such as "+=", "-=", "*=" have equivalent methods named "add", "subtract", "divide", etc...

Relational Operators

All operators such as "==", "!=", "&lt", etc... have equivalent methods named "eq", "ne", "lt", etc...

Logical Operators

All logical operators such as "&", "!", "|" and "^" have equivalent methods named "and", "not", "or" and "xor" respectively. The latter methods mutate the logical array it is operating on:

```
a.and(b).or(c)          # contents of -'a' is altered!
r=a.copy().and(b).or(c)          # contents of -'a' is altered!
```

When to use what

Operator methods that work inline are as fast as their abbreviated syntax (e.g. "+="). The real benefit comes from a style of writing:

```
y=SQRT( SQUARE(SIN(x)/n) + 1 -)
y=x.apply(SIN).divide(n).perform(SQUARE).add(1).perform(SQRT)
```

The code snippet above has reduced the creation of temporary arrays from four down to zero!

1.6. Toolboxes

Introduction

Toolboxes are add-ons that extend the functionality of numeric arrays. All the functions and procedures within this library are grouped in toolboxes.

Each toolbox has it own set of specialized functions, documentation and example code. If you click on one of the toolboxes on the left, you will get more information about the functionality it provides.

Currently available toolboxes are:

The Basic Toolbox	Basic functions like SIN, SQUARE, MIN, ...
The Fit Toolbox	Provides functionality for fitting.
The Filter Toolbox	Provides filter functions and utilities useful for processing time-series and images.
The Integration Toolbox	Provides numeric integration methods, for both continuous functions and discrete data.
The Interpolator Toolbox	Provides functions and utilities for interpolation and extrapolation.
The Mask Handling Toolbox	Provides facilities for handling masks that are stored in numeric library arrays.
The Matrix Toolbox	Set of functions and utilities to manipulate matrices.
The Random Functions Toolbox	Set of functions for populating arrays with random elements.
The XFORM Toolbox	Provides Transformational functions such as FFT.

The Basic Toolbox

This toolbox provides basic functions in the following categories:

- General Functions
- Trigonometric Functions
- Nearest Integer Functions
- Reduction Functions
- Statistical Functions

```
name-space: herschel.ia.numeric.toolbox.basic
```

General Functions

- Rotate
- Pow
- Polynomial
- CONCATENATE
- NotPresent
- AnyPresent
- LOG
- MEDIANDEV

- ExpN
- SHIFT
- SIGCLIP
- SIGNUM
- IS_FINITE
- UNIQ
- IS_NAN
- SQUARE
- EXP10
- SQRT
- RESHAPE
- EXP
- IS_INFINITE
- UNIQ_SORTED
- SORT
- ABS
- LOG10
- REVERSE
- LogN

Trigonometric Functions

- ARCSIN
- ARCTAN
- TAN
- COS
- SIN
- COSH
- TANH
- SINH
- ARCCOS

Nearest Integer Functions

- FIX
- ROUND

- FLOOR
- CEIL

Reduction Functions

This family of functions reduces a sequence of values a single value by combining elements via a supplied function. Additionally, this mechanism can be used to reduce an array of rank N to an N-1 array.

The general syntax of reduction functions is as follows:

```
y=f(x [,dim])
```

where: *x* is the input array of any rank, *dim* an optional dimension and *y* is the result of the computation. If the optional dimension is not specified, the array is reduced to a single scalar value.

If the dimension is specified the function computes the result by reducing the array elements along that dimension into a single value; the resulting array has a rank which is equivalent to x.rank-1.

For example, consider an arbitrary reduction function *f* and the following two-dimensional array

```
  -| 1 2 -|
x=| 3 4 -|
```

Then:

```
f(x)   = f([1,2,3,4])
f(x,0) = [ f(1,3), f(2,4) -]
f(x,1) = [ f(1,2), f(3,4) -]
```

- MIN
- AllPresent
- PRODUCT
- ALL
- MAX
- ANY
- SUM

Statistical Functions

The following statistical functions accept integral as well floating-point arrays; the former implicitly transformed to a double array.

You have to filter out non-finite elements (such as NaN elements) as these functions produce sensible results only if all elements have finite values:

```
x=Double1d([Double.NaN,1,Double.NaN,3,2,3,4,Double.NaN,4])
print MEDIAN(x)                       # ERROR: the median is not NaN
print MEDIAN(x[x.where(IS_FINITE)])   # 3.0
```

- KURTOSIS
- MEDIAN
- GammaP

- Erfc
- CorrelateMatrix
- Correlate
- MEAN
- Erf
- SKEWNESS
- STDDEV
- VARIANCE
- GAMMALN
- GammaQ

The Filter Toolbox

This toolbox provides filter functions.

```
name-space: herschel.ia.numeric.toolbox.filter
```

- GaussianFilter
- BoxCarFilter
- Convolution

The Fit Toolbox

The fitter toolbox provides a generalized way to fit models to data and to estimate the best values of the model parameters. An introduction to the use of fit package can be found here.

Before proceeding it is wise to familiarize yourself with the background information about the Fitter classes.

To get started we present worked examples on almost all aspects of of the package.

```
name-space: herschel.ia.numeric.toolbox.fit
```

The Integration Toolbox

The integration toolbox provides a generalized way to compute integrals, through different numeric methods.

```
name-space: herschel.ia.numeric.toolbox.integr
```

- FitterFunction
- Integrator

The Interpolator Toolbox

This toolbox provides interpolation functions.

```
name-space: herschel.ia.numeric.toolbox.interp
```

- LinearInterpolator
- NearestNeighborInterpolator
- Regrid
- CubicSplineInterpolator
- PreviousInterpolator

The Mask Handling Toolbox

This toolbox provides facilities for mask handling.

```
name-space: herschel.ia.numeric.toolbox.mask
```

- PackedMask
- FixedMask

The Matrix Toolbox

This toolbox provides matrix functions.

```
name-space: herschel.ia.numeric.toolbox.matrix
```

- EigenvalueDecomposition
- LUDecomposition
- TRANSPOSE
- CholeskyDecomposition
- MatrixMultiply
- DETERMINANT
- MatrixSolve
- INVERSE
- QRDecomposition
- SingularValueDecomposition

The Random Functions Toolbox

This toolbox provides random functions.

```
name-space: herschel.ia.numeric.toolbox.random
```

- RandomUniform
- RandomPoisson
- RandomGauss

The XFORM Toolbox

This toolbox provides transformation functions and utilities.

```
name-space: herschel.ia.numeric.toolbox.xform
```

- HANNING
- PowerSpectrum
- FFT
- HAMMING
- IFFT

Chapter 2. DP Commands

2.1. Introduction

This chapter is a complete listing of all built-in DP functions, task and objects, collectively referred to as commands.

How to use this chapter

All of Dp's commands are documented alphabetically in this chapter. A first section gives a general overview what a command is used for and how to use it. This includes a general description and some examples. The "API summary" section provides a quick overview of the available constructors, methods and properties of a command. It is intended as quick reference for users that just need to remember a certain functionality. The "API details" section provides more detailed information about the constructors, methods and properties. Furthermore it provides links to other references and information about the command's history.

Overview

A table gives the full name of the command, indicates if it is written in Java or Jython and if it is just an ordinary command or if it follows the HCSS Task specifications. The import statement in this table can be copied to a Jython console.

Description

General description of the command.

Examples

Most commands include one or more examples that demonstrates how the command is used. Most of the examples are just one or two lines of DP code that can be entered at the Jython prompt. Others are code fragments or routines designed to serve as an examples for your own programs.

Limitations and Miscellaneous

The "Limitations" and "Miscellaneous" sections describes the boundaries of applicability and other specialties of the command.

API Summary

The API Summary provides a quick summary of the commands constructor, method, and properties. Note that most of the arguments are positional parameters that must be supplied in the order indicated by the command's syntax. However arguments can be often supplied by specifying their names. If its the case then they can provided in any order.

Constructor

Constructors are used to create a command.

Method

Methods are functions of a command that can be executed.

Properties

Properties are fields of a command that can be read or written by a command. INPUT properties contain values that are required by a command, OUTPUT properties contain the result of a command, INOUT provide both functionalities at the same time.

See also

The "See also" section provides links to related commands, to other manuals, or to external resources in the Internet.

History

The "History" section describes the changes occurred to the command.

2.2. ABS

Full Name:	herschel.ia.numeric.toolbox.basic.Abs
Alias:	ABS
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Abs

Description

Gives the absolute value of a number or a numeric array. For complex numbers, ABS(x) gives the modulus.

Example

Example 1: Apply ABS on a Int1d

```
x=Int1d( [-1,0,1] -)
print ABS(-123), ABS(x) # 123 [1,0,1]
```

API Summary

Jython Syntax
<y>=ABS(<x>)

Properties
any number and numeric type **x** [INPUT, MANDATORY, default=no default value]
any number and numeric type **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any number and numeric type x [INPUT, MANDATORY, default=no default value]

Accepts any number and numeric type.

any number and numeric type y [OUTPUT, MANDATORY, default=no default value]

For complex numbers, ABS(z) gives the modulus.

2.3. AbstractMappingTask

Full Name:	herschel.ia.toolbox.image.AbstractMappingTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import AbstractMappingTask

Description

An abstract Task for mapping.

An abstract Task where the overlap of an input pixel with (smaller) output pixels must be determined.

API Summary

Property
boolean **oversample** [INPUT, OPTIONAL, default=Default value : true]

API details

Property

boolean oversample [INPUT, OPTIONAL, default=Default value : true]

Indication whether oversampling should be done.

2.4. AddSpectrum

Full Name:	herschel.ia.toolbox.spectrum.AddSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import AddSpectrum

Description

Task for adding a scalar to the flux data included in a spectrum container or for adding two spectrum containers on a spectrum-by-spectrum basis (computed as an average).

For the scalar mode, 'ds' and 'param' need to specified - for the pair-wise mode, 'ds1' and 'ds2' need to be set. In the pairwise mode, the task iterates through the two containers and computes the pair-operation. In case the size of the two containers is different, the iteration stops at the minimum size. Hence, the remaining spectra in the larger container are ignored. In case one of the datasets only contains a single spectrum, the task always refers to this single spectrum while iterating over all the spectra in the other dataset.

Different selection schemes are available for selecting the point spectra or the segments to be processed. The most simple scheme is to specify lists of point spectrum indices (`selection=[1,3,4,2]`). In this case, the operation (scalar- or pair-operation) is just taken over the point spectra with corresponding indices. Instead of specifying a list of indices (which requires the knowledge of these) other recipes to specify a selection are available. Typical recipes test attribute values to match certain values or to be included in a given interval. These recipes we refer to as selection models. The different options to specify selections can be combined. Here, an AND logic is adopted.

Similarly, you can specify what segments to consider. In the most simple case, you can just specify the indices of segments to be considered (for the scalar operation `segments=[1,3,4]` and for the pair operation `segments1=[1,3,4], segments1=[3,6,5]`). In more advanced situations you can use a `SegmentSelection` object. Note that the pairs of segments to be processed need to be consistent - otherwise the processing will fail.

You can specify whether the orginal datasets should be overwritten with the 'overwrite' flag. By default no data is overwritten. In the pair-wise mode, it is not always possible to overwrite the data - in particular if non-trivial segment selections are specified.

For the pair-wise mode, there are further options that can be selected by the 'variant' (e.g. whether to use flags and weights).

Example

Example 1: from Jide:

```
from herschel.ia.toolbox.spectrum import AddSpectrum
add = AddSpectrum()
spectraOut = add(ds1=spectra1, ds2=spectra2)
spectraOut = add(ds=spectra, param=2.1)
spectraOut = add(ds=spectra, selection={"bbtype":[6031]}, param=2.1)
spectraOut = add(ds=spectra, selection=[0,1,2,3], param=2.1)
spectraOut = add(ds=spectra, selection={"Chopper":([-4.4,5.9],0.2), -"bbtype":
[6031]}, param=2.1)
spectraOut = add(ds=spectra, selection={"LoFrequency":(4000.0,5000.0)},
param=2.1)
spectraOut = add(ds=spectra, selection={"bbtype":[6031]}, segments=[2,3],
param=2.1)
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, OPTIONAL, default=no default value.]
Double **param** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection_lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection_index** [INPUT, OPTIONAL, default=No default value.]
Boolean **overwrite** [INPUT, OPTIONAL, default=False.]
SpectrumContainer **ds1** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **ds2** [INPUT, OPTIONAL, default=no default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Object **segments1** [INPUT, OPTIONAL, default=no default value.]
Object **segments2** [INPUT, OPTIONAL, default=no default value.]
String **variant** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

SpectrumContainer ds [INPUT, OPTIONAL, default=no default value.]

Input container to be processed by the task in case the task is used as a scalar operation.

Double param [INPUT, OPTIONAL, default=no default value.]

The scalar parameter to be considered when the task is used as scalar operation.

Object selection [INPUT, OPTIONAL, default=None.]

Specify what point spectra the operation should be applied to. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra for which the add should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

Boolean overwrite [INPUT, OPTIONAL, default=False.]

Specify whether the input data container can be reused - the values found therein is overwritten.

SpectrumContainer ds1 [INPUT, OPTIONAL, default=no default value.]

First input container for pair-wise operations.

SpectrumContainer ds2 [INPUT, OPTIONAL, default=no default value.]

Second input container for pair-wise operations.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments the operation should be applied to. There are two options available:

- Either pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.
- Specify a PyList of segment indices.

Object segments1 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds1'.

Object segments2 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds2'.

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-wave" / "flux-wave-weight" / "flux-flag-wave" / "flux-weight-flag-wave"

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

See also

- ArithmeticSpectrumTask

History

- `2007-08-17 - meli`: Initial.
- `2008-03-16 - meli`: major refactoring of the toolbox.
- `2008-10-03 - meli`: segments, javadoc

2.5. ALL

Full Name:	herschel.ia.numeric.toolbox.basic.All
Alias:	ALL
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import All

Description

Determines whether all elements in the array evaluate to true.

The input array must be of integral type (e.g. bytes,integers) and the result is a boolean array.

Example

Example 1: Apply ALL on a Int1d: check if all the array items, in the specified dimension, are lower than '3'

```
x=Int2d( [ [1,2], [1,4], [1,6] -])
print ALL(x<3)    #all items => 0 (false)
print ALL(x<3, 0) #dim 0 => [ ALL(Int1d([1,1,1]) < 3) -, ALL(Int1d([2,4,6]) <
3) -] = [true, false]
print ALL(x<3, 1) #dim 1 => [ ALL(Int1d([1,2]) < 3) -, ALL(Int1d([1,4]) < 3),
ALL(Int1d([1,6]) < 3) = [true, false, false]
```

API Summary

Jython Syntax

```
<y>=ALL(<array_expression>[,<dimension>])
```

Properties

any expression with an integral type **x** [INPUT, MANDATORY, default=no default value]

integer **dimesion** [INPUT, OPTIONAL, default=all the array items]

a boolean array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any expression with an integral type x [INPUT, MANDATORY, default=no default value]

The input array must be of integral type (e.g. bytes,integers) See example.

integer dimesion [INPUT, OPTIONAL, default=all the array items]

The dimension where to apply the expression.

a boolean array y [OUTPUT, MANDATORY, default=no default value]

The result is a boolean array

2.6. AllPresent

Full Name:	herschel.ia.numeric.toolbox.basic.AllPresent
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import AllPresent

Description

Tests whether all of the bits in specified mask are present in the elements of the input array.

The input array must be of integral type (e.g. bytes,integers) and the result is a boolean array.

Example

Example 1: Apply AllPresent on a Int1d: test if a binary 'and' comparison, item by item, with '3' (as mask) is equals to '3'

```
x=Int1d([0,1,2,3])
print AllPresent(3)(x)
#=> [  (0 & 3) == 3,   (1 & 3) == 3,   (2 & 3) == 3,   (3 & 3) == 3  -] =
[false,false,false,true]
print x.apply(AllPresent(3)) #Another way for using AllPresent
```

API Summary

Jython Syntax
<y>=AllPresent(<bitmask>)(<x>)

Properties
any integral type **x** [INPUT, MANDATORY, default=no default value]
any number **bitmask** [INPUT, MANDATORY, default=no default value]
a boolean array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any integral type x [INPUT, MANDATORY, default=no default value]

The input array must be of integral type (e.g. bytes,integers)

any number bitmask [INPUT, MANDATORY, default=no default value]

Accepts any number.

a boolean array y [OUTPUT, MANDATORY, default=no default value]

The result is a boolean array

See also

- AnyPresent
- NotPresent

2.7. AmoebaFitter

Full Name:	herschel.ia.numeric.toolbox.fit.AmoebaFitter
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.fit import AmoebaFitter

Description

Simulated annealing simplex finding minimum.

AmoebaFitter can be used in two modes: with simulated annealing on or off. The simulated annealing mode is invoked by setting the temperature to some value. By default it is off: temperature at zero.

When the temperature is set to (or left at) zero, AmoebaFitter acts as a simple Nelder-Mead downhill simplex method. With two advantages and one disadvantage. The pro's are that it is reasonably fast and that it does not need partial derivatives. The con is that it will fall into the first local minimum it encounters. No guarantee that this minimum has anything to do with the absolute minimum. This T=0 modus can only be used in mono-modal problems.

In the other modus, when the temperature is set at some value the simplex sometimes takes a uphill step, depending on the temperature at that moment. Steps downhill are always taken. In that way it is possible to climb out of local minima to find better ones. Meanwhile the temperature is steadily lowered, concentrating the search on the by now hopefully found absolute minimum. Of course this takes much more iterations and still there is **no guarantee** that the best value is found. But a better chance. The initial temperature which suggests itself is of the order of the difference between $\#^2$ at a random point and $\#^2$ at the minimum. AmoebaFitter can be used with limits set to one or more of the parameters.

An introduction to the use of fit package can be found here.

At least once have a look at the background on the organization and structure of the package.

Example

Example 1: The fit/demo directory contains worked

```
<a href="demo/jython.html">examples</a>
on almost all aspects of of the package.
```

Limitations

1. AmoebaFitter is **not** guarateed to find the global minimum.

2. The calculation of the evidence is an Gaussian approximation which is only exact for linear models with a fixed scale.

2.8. AnnotationToolbox

Full Name:	herschel.ia.gui.image.gui.AnnotationToolbox
Type:	Java Class -
Import:	from herschel.ia.gui.image.gui import AnnotationToolbox
Category:	Image

Description

A toolbox to draw annotations.

AnnotationToolbox construct a toolbox where the use can select which annotation to display. Using the mouse, the annotation can be put on the image. The jython command to reconstruct the annotation is also shown.

API Summary

Constructors
AnnotationToolbox(Display d) Constructor for the annotation toolbox.
AnnotationToolbox(Display d, boolean useAsComponent) Constructs the annotation toolbox.

Methods
getComponent() Returns the component that contains the annotation toolbox.
close() Closes the annotation toolbox.
saveJythonCode() Saves the jython code to a python script.

API details

Constructors

AnnotationToolbox(Display d)

Constructor for the annotation toolbox.

Constructs the annotation toolbox.

Argument

Display **d** [INPUT, MANDATORY]

AnnotationToolbox(Display d, boolean useAsComponent)

Constructs the annotation toolbox.

Constructs the annotation toolbox. If useAsComponent is true, the annotation toolbox is component based.

AnnotationToolbox(Display d, boolean useAsComponent)

Arguments

Display **d** [INPUT, MANDATORY]

boolean **useAsComponent** [INPUT, MANDATORY]

Methods

getComponent()

Returns the component that contains the annotation toolbox.

Returns the component that contains the annotation toolbox.

close()

Closes the annotation toolbox.

Closes the annotation toolbox.

saveJythonCode()

Saves the jython code to a python script.

Saves the jython code to reconstruct the annotations to a python script.

2.9. AnnularSkyAperturePhotometryExplorer

Full Name:	herschel.ia.gui.image.AnnularSkyAperturePhotometryExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import AnnularSkyAperturePhotometryExplorer

Description

An explorer for AnnularSkyAperturePhotometryProducts.

An explorer for AnnularSkyAperturePhotometryProducts.

API Summary

Constructors
AnnularSkyAperturePhotometryExplorer() The construction of a new AnnularSkyAperturePhotometryExplorer.
AnnularSkyAperturePhotometryExplorer(Object object) The construction of a new AnnularSkyAperturePhotometryExplorer associated with the given object.

Methods
boolean **canHandle**(Class className) Checks whether this AnnularSkyAperturePhotometryExplorer can handle objects of the given class.
AnnularSkyAperturePhotometryProduct **getObject**() Returns the object.
Class **getVariableType**() Returns the expected variable type.
JScrollPane **getParameterTable**() Returns the parameter table.
JPanel **getPlotPanel**() Returns the plot panel.
JPanel **getSkyIntensityPlotPanel**() Returns the plot panel.
JComponent **getSkyIntensityPlot**() Returns the sky intensity plot.

API details

Constructors

AnnularSkyAperturePhotometryExplorer()
The construction of a new AnnularSkyAperturePhotometryExplorer. The construction of a new AnnularSkyAperturePhotometryExplorer.

AnnularSkyAperturePhotometryExplorer(Object object)

The construction of a new AnnularSkyAperturePhotometryExplorer associated with the given object.

The construction of a new AnnularSkyAperturePhotometryExplorer associated with the given object.

Argument

Object **object** [INPUT, MANDATORY]

Methods

boolean canHandle(Class className)

Checks whether this AnnularSkyAperturePhotometryExplorer can handle objects of the given class.

Returns true if this AnnularSkyAperturePhotometryExplorer can handle object of the given calss; false otherwise.

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true if this AnnularSkyAperturePhotometry can handle objects of the given class; false otherwise.

AnnularSkyAperturePhotometryProduct getObject()

Returns the object.

Returns the object for this AnnularSkyAperturePhotometyrExplorer.

Return

AnnularSkyAperturePhotometryProduct

Returns the object for this AnnularSkyAperturePhotometryExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this AnnularSkyAperturePhotometryExplorer.

Return

Class

Returns the expected variable type for this AnnularSkyAperturePhotometryExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

Constructs and returns the parameter table for this AnnularSkyAperturePhotometryExplorer.

Return

JScrollPane getParameterTable()

JScrollPane

Returns the parameter table for this AnnularSkyAperturePhotometryExplorer.

JPanel getPlotPanel()

Returns the plot panel.

Constructs and returns the plot panel for this AnnularSkyAperturePhotometryExplorer.

Return

JPanel

Returns the plot panel for this AnnularSkyAperturePhotometryExplorer.

JPanel getSkyIntensityPlotPanel()

Returns the plot panel.

Constructs and returns the plot panel for this AnnularSkyAperturePhotometryExplorer.

Return

JPanel

Returns the plot panel for this AnnularSkyAperturePhotometryExplorer.

JComponent getSkyIntensityPlot()

Returns the sky intensity plot.

Constructs and returns the sky intensity plot for this AnnularSkyAperturePhotometryExplorer.

Return

JComponent

Returns the sky intensity plot for this AnnularSkyAperturePhotometryExplorer.

2.10. AnnularSkyAperturePhotometryPanel

Full Name:	herschel.ia.toolbox.image.gui.AnnularSkyAperturePhotometryPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import AnnularSkyAperturePhotometryPanel

Description

A panel for the AnnularSkyAperturePhotometryTask.

A panel to serve as GUI for the AnnularSkyAperturePhotometryTask.

API Summary

Constructor
AnnularSkyAperturePhotometryPanel() The construction of a new AnnularSkyAperturePhotometryPanel.

Methods
JPanel **getAperturesPanel()** Returns the panel where to specify the parameters for the apertures.
JComponent **getSkyApertureComponent()** Retturns the component where to specify the inner and outer radius of the annular sky aperture.
drawFigures() Draws the circles bounding the apertures on the image.
moveConfirmedFigures() Allows the user to move the circles bounding the apertures.
clearSkyAperture() Clears the annular sky aperture.

API details

Constructor

AnnularSkyAperturePhotometryPanel()
The construction of a new AnnularSkyAperturePhotometryPanel. The construction of a new AnnularSkyAperturePhotometryPanel.

Methods

JPanel getAperturesPanel()
Returns the panel where to specify the parameters for the apertures. Returns the panel where to specify the parameters for the apertures for this AnnularSkyAperturePhotometryPanel. **Return**

JPanel getAperturesPanel()

JPanel

Returns the panel where to specify the parameters for the apertures for this AnnularSkyAoerturePhotometryPanel.

JComponent getSkyApertureComponent()

Retturns the component where to specify the inner and outer radius of the annular sky aperture.

Returns the component where to specify the inner and outer radius of the annular sky aperture for this AnnularSkyAperturePhotometryPanel.

Return

JComponent

Returns the component where to specify the inner and outer radius of the annular sky aperture for this AnnularSkyAperturePhotometryPanel.

drawFigures()

Draws the circles bounding the apertures on the image.

Draws the circles on the image for this AnnularSkyAperturePhotometryPanel.

moveConfirmedFigures()

Allows the user to move the circles bounding the apertures.

Allows the user to move the circles bounding the apertures for this AnnularSkyAperturePhotometryPanel.

clearSkyAperture()

Clears the annular sky aperture.

Clears the annular sky aperture for this AnnularSkyAperturePhotometryPanel.

2.11. AnnularSkyAperturePhotometryProduct

Full Name:	herschel.ia.dataset.image.AnnularSkyAperturePhotometryProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import AnnularSkyAperturePhotometryProduct

Description

A class to deal with the results of aperture photometry with a circular

target aperture and an annular sky aperture.

API Summary

Constructor
AnnularSkyAperturePhotometryProduct() The constructor of a new AnnularSkyAperturePhotometryProduct.

Methods
setRadii(double innerPixels, double outerPixels) Sets the inner and outer radius in pixels for this
setRadii(double innerPixels, double innerArcsec, double outerPixels, double outerArcsec) Sets the inner and outer radius for this
double **getInnerRadiusPixels**() Returns the inner radius for this AnnularSkyAperturePhotometryProduct in pixels.
double **getInnerRadiusArcsec**() Returns the inner radius for this AnnularSkyAperturePhotometryProduct
double **getOuterRadiusPixels**() Returns the outer radius for this AnnularSkyAperturePhotometryProduct in pixels.
double **getOuterRadiusArcsec**() Returns the outer radius for this AnnularSkyAperturePhotometryProduct in arcsec.
TableDataset **getSkyIntensityPlot**() Returns the sky intensity plot for this
Double1d **getSkyRadius**() Returns the sky radius in pixels for the sky intensity
Double1d **getSkyIntensity**() Returns the sky intensity for the sky intensity plot for this

Miscellaneous

Aperture specific information is stored in meta data, all other data (results of calculations) are stored in TableDatasets.

API details

Constructor

AnnularSkyAperturePhotometryProduct()

The constructor of a new AnnularSkyAperturePhotometryProduct.

Methods

setRadii(double innerPixels, double outerPixels)

Sets the inner and outer radius in pixels for this

AnnularSkyAperturePhotometryProduct to the given numbers of pixels.

Arguments

double **innerPixels** [INPUT, MANDATORY]

double **outerPixels** [INPUT, MANDATORY]

setRadii(double innerPixels, double innerArcsec, double outerPixels, double outerArcsec)

Sets the inner and outer radius for this

AnnularSkyAperturePhotometryProduct to the given numbers of pixels and arcsec.

Arguments

double **innerPixels** [INPUT, MANDATORY]

double **innerArcsec** [INPUT, MANDATORY]

double **outerPixels** [INPUT, MANDATORY]

double **outerArcsec** [INPUT, MANDATORY]

double getInnerRadiusPixels()

Returns the inner radius for this AnnularSkyAperturePhotometryProduct in pixels.

Return

double

Returns the inner radius for this AnnularSkyAperturePhotometryProduct in pixels.

double getInnerRadiusArcsec()

Returns the inner radius for this AnnularSkyAperturePhotometryProduct

in arcsec.

Return

double

Returns the inner radius for this AnnularSkyAperturePhotometryProduct in arcsec.

double getOuterRadiusPixels()

Returns the outer radius for this AnnularSkyAperturePhotometryProduct in pixels.

Return

`double getOuterRadiusPixels()`

double

Returns the outer radius for this AnnularSkyAperturePhotometryProduct in pixels.

`double getOuterRadiusArcsec()`

Returns the outer radius for this AnnularSkyAperturePhotometryProduct in arcsec.

Return

double

Returns the outer radius for this AnnularSkyAperturePhotometryProduct in arcsec.

`TableDataset getSkyIntensityPlot()`

Returns the sky intensity plot for this

AnnularSkyAperturePhotometryProduct.

Return

TableDataset

Returns the sky intensity plot for this AnnularSkyAperturePhotometryProduct.

`Double1d getSkyRadius()`

Returns the sky radius in pixels for the sky intensity

plot for this AnnularSkyAperturePhotometryProduct.

Return

Double1d

Returns the sky radius in pixels for the sky intensity plot for this AnnularSkyAperturePhotometryProduct.

`Double1d getSkyIntensity()`

Returns the sky intensity for the sky intensity plot for this

AnnularSkyAperturePhotometryProduct.

Return

Double1d

Returns the sky intensity for the sky intensity plot for this AnnularSkyAperturePhotometryProduct.

2.12. AnnularSkyAperturePhotometryTask

Full Name:	herschel.ia.toolbox.image.AnnularSkyAperturePhotometryTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import AnnularSkyAperturePhotometryTask

Description

A Task for aperture photometry.

A Task for aperture photometry, using a circular target aperture and an annular sky aperture.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **centerX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **centerY** [INPUT, OPTIONAL, default=Default value : NaN]
String **centerRA** [INPUT, OPTIONAL, default=Default value : "centerRA"]
String **centerDEC** [INPUT, OPTIONAL, default=Default value : "centerDec"]
Double **radiusPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **radiusArcsec** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **algorithm** [INPUT, MANDATORY, default=Default value : 4]
AnnularSkyAperturePhotometryProduct **result** [OUTPUT, MANDATORY, default=No default value]
Double **innerPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **innerArcsec** [INPUT, OPTIONAL, default=Default value : NaN]
Double **outerPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **outerArcsec** [INPUT, OPTIONAL, default=Default value : NaN]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double centerX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the target center.

Double centerY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the target center.

String centerRA [INPUT, OPTIONAL, default=Default value : "centerRA"]

The right ascension of the target center.

String centerDEC [INPUT, OPTIONAL, default=Default value : "centerDec"]

The declination of the target center.

Double radiusPixels [INPUT, OPTIONAL, default=Default value : NaN]

The target radius (i.e. the radius of the circular target aperture) in pixels.

Double radiusArcsec [INPUT, OPTIONAL, default=Default value : NaN]

Integer algorithm [INPUT, MANDATORY, default=Default value : 4]

The sky estimation algorithm.

AnnularSkyAperturePhotometryProduct result [OUTPUT, MANDATORY, default=No default value]

The result.

Double innerPixels [INPUT, OPTIONAL, default=Default value : NaN]

The inner radius of the annular sky aperture in pixels.

Double innerArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The inner radius of the annular sky aperture in arcsec.

Double outerPixels [INPUT, OPTIONAL, default=Default value : NaN]

The outer radius of the annular sky aperture in pixels.

Double outerArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The outer radius of the annular sky aperture in arcsec.

2.13. ANY

Full Name:	herschel.ia.numeric.toolbox.basic.Any
Alias:	ANY
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Any

Description

Determines whether any element in the array evaluates to true.

The input array must be of integral type (e.g. bytes,integers) and the result is a boolean array.

Example

Example 1: Apply ANY on a Int2d: check if any array item, in the specified dimension, is lower than '3'

```
x=Int2d( [ [1,2], [3,4], [5,6] -])
print ANY(x<3)    #any item => 1 (true)
print ANY(x<3, 0) #dim 0 => [ ANY(Int1d([1,3,5]) < 3) -, ANY(Int1d([2,4,6]) <
3) -] = [true, true]
print ANY(x<3, 1) #dim 1 => [ ANY(Int1d([1,2]) < 3) -, ANY(Int1d([3,4]) < 3),
ANY(Int1d([5,6]) < 3) = [true, false, false]
```

API Summary

Jython Syntax

```
<y>=ALL(<array_expression>[,<dimension>])
```

Properties

any expression with an integral type **x** [INPUT, MANDATORY, default=no default value]
integer **dimesion** [INPUT, OPTIONAL, default=all the array items]
a boolean array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any expression with an integral type x [INPUT, MANDATORY, default=no default value]

The input array must be of integral type (e.g. bytes,integers) See example.

integer dimesion [INPUT, OPTIONAL, default=all the array items]

The dimension where to apply the expression.

a boolean array y [OUTPUT, MANDATORY, default=no default value]

The result is a boolean array

See also

- ALL

2.14. AnyPresent

Full Name:	herschel.ia.numeric.toolbox.basic.AnyPresent
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import AnyPresent

Description

Tests whether any of the bits in specified mask are present in the elements of the input array.

The input array must be of integral type (e.g. bytes,integers) and the result is a boolean array.

Example

Example 1: Apply AnyPresent on a Int1d: test if a binary 'and' comparison, item by item, with '3' (as mask) is not equals to '0'

```
x=Int1d([0,1,2,3])
print AnyPresent(3)(x)
#=> [  (0 & 3) -!= 0,   (1 & 3) -!= 0,   (2 & 3) -!= 0,   (3 & 3) -!= 0  -]
=  [false,true,true,true]
print x.apply(AnyPresent(3)) #Another way for using AnyPresent
```

API Summary

Jython Syntax
<y>=AnyPresent(<bitmask>)(<x>)

Properties
any integral type **x** [INPUT, MANDATORY, default=no default value]
any number **bitmask** [INPUT, MANDATORY, default=no default value]
a boolean array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any integral type x [INPUT, MANDATORY, default=no default value]

The input array must be of integral type (e.g. bytes,integers)

any number bitmask [INPUT, MANDATORY, default=no default value]

Accepts any number.

a boolean array y [OUTPUT, MANDATORY, default=no default value]

The result is a boolean array

See also

- AllPresent
- NotPresent

2.15. ApperturePhotometryExplorer

Full Name:	herschel.ia.gui.image.ApperturePhotometryExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import ApperturePhotometryExplorer

Description

An explorer for ApperturePhotometryProducts.

An explorer for ApperturePhotometryProducts.

API Summary

Constructors
ApperturePhotometryExplorer() The construction of a new ApperturePhotometryExplorer.
ApperturePhotometryExplorer(Object object) The construction of a new ApperturePhotometryExplorer associated with the given object.

Methods
String **getName()** Returns the name.
String **getDescription()** Returns the description.
boolean **canHandle**(Class className) Checks whether this ApperturePhotometryExplorer can handle objects of the given class.
setObject(Object object) Sets the object.
ApperturePhotometryProduct **getObject()** Returns the object.
Class **getVariableType()** Returns the expected variable type.
JComponent **getComponent()** Returns the component that is responsible for displaying the object.
JPanel **getDataPanel()** Returns the data panel.
JScrollPane **getParameterTable()** Returns the parameter table.
JScrollPane **getResultsTable()** Returns the results table.
JPanel **getPlotPanel()** Returns the plot panel.
JPanel **getCurveOfGrowthPanel()** Returns the curve of growth panel.

Methods
`JComponent` **`getCurveOfGrowth()`** Returns the curve of growth.
`addDataObjectListener``(DataObjectListener listener)` Adds the given listener.
`removeDataObjectListener``(DataObjectListener listener)` Removes the given listener.

API details

Constructors

`AperturePhotometryExplorer()`
The construction of a new AperturePhotometryExplorer. The construction of a new AperturePhotometryExplorer.

`AperturePhotometryExplorer(Object object)`
The construction of a new AperturePhotometryExplorer associated with the given object. The construction of a new AperturePhotometryExplorer associated with the given object. **Argument** `Object` **`object`** `[INPUT, MANDATORY]`

Methods

`String getName()`
Returns the name. Returns the name for this AperturePhotometryExplorer. **Return** **String** Returns the name for this AperturePhotometryExplorer.

`String getDescription()`
Returns the description. Returns the description for this AperturePhotometryExplorer. **Return** **String** Returns the description for this AperturePhotometryExplorer.

`boolean canHandle(Class className)`
Checks whether this AperturePhotometryExplorer can handle objects of the given class. Returns true if this AperturePhotometryExplorer can handle objects of the given class; false otherwise.

boolean canHandle(Class className)

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true of this ApperturePhotometryExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this ApperturePhotometryExplorer to the given object.

Argument

Object **object** [INPUT, MANDATORY]

ApperturePhotometryProduct getObject()

Returns the object.

Returns the object for this ApperturePhotometryExplorer.

Return

ApperturePhotometryProduct

Returns the object for this ApperturePhotometryExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this ApperturePhotometryExplorer.

Return

Class

Returns the expected variable type for this ApperturePhotometryExplorer.

JComponent getComponent()

Returns the component that is responsible for displaying the object.

Returns the component that is responsible for displaying the data object for this ApperturePhotometryExplorer.

Return

JComponent

Returns the component that is responsible for displaying the data object for this ApperturePhotometryExplorer.

JPanel getDataPanel()

Returns the data panel.

JPanel getDataPanel()

Returns the data panel for this AperturePhotometryExplorer.

Return

JPanel

Returns the data panel for this AperturePhotometryExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

Constructs and returns the parameter table for this AperturePhotometryExplorer.

Return

JScrollPane

Returns the parameter table for this AperturePhotometryExplorer.

JScrollPane getResultsTable()

Returns the results table.

Constructs and returns the results table for this AperturePhotometryExplorer.

Return

JScrollPane

Returns the results table for this AperturePhotometryExplorer.

JPanel getPlotPanel()

Returns the plot panel.

Constructs and returns the plot panel for this AperturePhotometryExplorer.

Return

JPanel

Returns the plot panel for this AperturePhotometryExplorer.

JPanel getCurveOfGrowthPanel()

Returns the curve of growth panel.

Constructs and returns the curve of growth panel for this AperturePhotometryExplorer.

Return

JPanel

Returns the curve of growthpanel for this AperturePhotometryExplorer.

JComponent getCurveOfGrowth()

Returns the curve of growth.

Constructs and returns the curve of growth for this AperturePhotometryExplorer.

JComponent getCurveOfGrowth()

Return

JComponent

Returns the curve of growth for this AperturePhotometryExplorer.

addDataObjectListener(DataObjectListener listener)

Adds the given listener.

Adds the given listener to this AperturePhotometryExplorer to receive data object events from it.

Argument

DataObjectListener **listener** [INPUT, MANDATORY]

removeDataObjectListener(DataObjectListener listener)

Removes the given listener.

Removes the given listener for this AperturePhotometryExplorer, so that it no longer receives data object events by this explorer.

Argument

DataObjectListener **listener** [INPUT, MANDATORY]

2.16. ApperturePhotometryPanel

Full Name:	herschel.ia.toolbox.image.gui.ApperturePhotometryPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ApperturePhotometryPanel

Description

A panel for aperture photometry.

A panel to serve as GUI for the ApperturePhotometryTask.

API Summary

Constructor
ApperturePhotometryPanel() The construction of a new ApperturePhotometryPanel.

Methods
JPanel **getImagePanel()** Returns a display for the image.
JPanel **getTargetCenterPanel()** Returns the panel where to specify the targe center.
adjustTargetCenter() Allows the user to drage the circle indicating the target center.
boolean **isInImage**(MouseEvent me) Checks whether the given mouse event occurred inside the image.
boolean **isInImage**(double pixX, double pixY) Checks whether the given pixel coordinates lie inside the image.
JPanel **getAperturesPanel()** Returns the panel where to specify the parameters for the apertures for this ApperturePhotometryPanel.
JPanel **getTargetAperturePanel()** Returns the panel where to specify the target radius.
JComponent **getSkyApertureComponent()** Returns the panel where to specify the parameters for the annular/rectangular sky aperture.
JPanel **getAlgorithmPanel()** Returns the panel where to specify the kind of pixels to use and the sky estimation algorithm.
JPanel **getButtonPanel()** Returns the button panel.
Modifier **addDefaultModifier**(String name) Returns the default modifier for the parameter with the given name.
JLabel **newLabel**(String title, String tooltip) Returns a label with the given title and tooltip.
Border **newBorder**(String title) Returns a border with the given title.

Methods
setVariableSelection(VariableSelection selection) Setting the variable selection.
setSiteEventHandler(SiteEventHandler handler) Setting the site event handler.
setTask(TaskApi task) Associating the task.
Display **getDisplay**() Returns the display.
Image **getImage**() Returns the associated image.
TaskApi **getTask**() Returns the associated task.
Map **getSelectionMap**() Returns the associated selection map.
Map **getModifierMap**() Returns the associated modifier map.
SiteEventHandler **getHandler**() Returns the associated site event handler.
double **getTargetRadius**() Returns the target radius in pixels.
trigger() Triggers the execution of the associated task.
transferFromModifierToSelectionMap() Transfers the information from the modifier to the selection map.
drawFigures() Draws the figures bounding the apertures on the image.
moveConfirmedFigures() Allows to move/resize the figures bounding the apertures.
clearSkyAperture() Clears the sky aperture.

API details

Constructor

ApperturePhotometryPanel()
The construction of a new ApperturePhotometryPanel. The construction of a new ApperturePhotometryPanel.

Methods

JPanel getImagePanel()
Returns a display for the image.

JPanel getImagePanel()

Returns a panel that displays the image for this PhotometryPanel.

Return

JPanel

Returns a panel that displays the image for this AperturePhotometryPanel.

JPanel getTargetCenterPanel()

Returns the panel where to specify the targe center.

Returns the panel where to specify the target center for this AperturePhotometryPanel.

Return

JPanel

Returns the panel where to specify the target center for this AperturePhotometryPanel.

adjustTargetCenter()

Allows the user to drage the circle indicating the target center.

Allows the user to drag the circle indicating the target center for this AperturePhotometryPanel.

boolean isInImage(MouseEvent me)

Checks whether the given mouse event occurred inside the image.

Returns true if the given mouse event occurred inside the image for this AperturePhotometryPanel; false otherwise.

Argument

MouseEvent **me** [INPUT, MANDATORY]

Return

boolean

Returns true if the given mouse event occurred inside the image for this AperturePhotometryPanel; false otherwise.

boolean isInImage(double pixX, double pixY)

Checks whether the given pixel coordinates lie inside the image.

Returns true if the given pixel coordinates lie inside the image for this AperturePhotometryPanel; false otherwise.

Arguments

double **pixX** [INPUT, MANDATORY]

double **pixY** [INPUT, MANDATORY]

Return

boolean

Returns true if the given pixel coordinates lie inside the image for this AperturePhotometryPanel; false otherwise.

JPanel getAperturesPanel()

Returns the panel where to specify the parameters for the apertures for this ApperturePhotometryPanel.

Returns the panel where to specify the parameters for the apertures for this ApperturePhotometryPanel.

Return

JPanel

Returns the panel where to specify the parameters for the apertures for this ApperturePhotometryPanel.

JPanel getTargetAperturePanel()

Returns the panel where to specify the target radius.

Returns the panel where to specify the target radius for this ApperturePhotometryPanel.

Return

JPanel

Returns the panel where to specify the target radius for this ApperturePhotometryPanel.

JComponent getSkyApertureComponent()

Returns the panel where to specify the parameters for the annular/rectangular sky aperture.

Returns the panel where to specify the parameters for the annular/rectangular sky aperture for this ApperturePhotometryPanel.

Return

JComponent

Returns the panel where to specify the parameter for the annular/rectangular sky aperture for this ApperturePhotometryPanel.

JPanel getAlgorithmPanel()

Returns the panel where to specify the kind of pixels to use and the sky estimation algorithm.

Returns the panel where to specify the kind of pixels to use and the sky estimation algorithm for this ApperturePhotometryPanel.

Return

JPanel

Returns the panel where to specify the kind of pixels to use and the sky estimation algorithm for this ApperturePhotometryPanel.

JPanel getButtonPanel()

Returns the button panel.

Returns the button panel for this ApperturePhotometryPanel

Return

JPanel

JPanel getButtonPanel()

Returns the button panel for this ApperturePhotometryPanel.

Modifier addDefaultModifier(String name)

Returns the default modifier for the parameter with the given name.

Returns the default modifier for the parameter with the given name for this ApperturePhotometryPanel.

Argument

String **name** [INPUT, MANDATORY]

Return

Modifier

Returns the default modifier for the parameter with the given name.

JLabel newLabel(String title, String tooltip)

Returns a label with the given title and tooltip.

Returns a label with the given title and tooltip.

Arguments

String **title** [INPUT, MANDATORY]

String **tooltip** [INPUT, MANDATORY]

Return

JLabel

Returns a label with the given title and tooltip.

Border newBorder(String title)

Returns a border with the given title.

Returns a label with the given title and tooltip.

Argument

String **title** [INPUT, MANDATORY]

Return

Border

Returns a border with the given title.

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the variable selection for this ApperturePhotometryPanel to the given variable selection.

Argument

VariableSelection **selection** [INPUT, MANDATORY]

setSiteEventHandler(SiteEventHandler handler)

Setting the site event handler.

setSiteEventHandler(SiteEventHandler handler)

Sets the site event handler for this AperturePhotometryPanel to the given site event handler.

Argument

`SiteEventHandler` **`handler`** `[INPUT, MANDATORY]`

setTask(TaskApi task)

Associating the task.

Associates the given task with this AperturePhotometryPanel.

Argument

`TaskApi` **`task`** `[INPUT, MANDATORY]`

Display getDisplay()

Returns the display.

Returns the display for this AperturePhotometryPanel.

Return

Display

Returns the display for this AperturePhotometryPanel.

Image getImage()

Returns the associated image.

Returns the image associated with this AperturePhotometryPanel.

Return

Image

Returns the image associated with this AperturePhotometryPanel.

TaskApi getTask()

Returns the associated task.

Returns the task associated with this AperturePhotometryPanel.

Return

TaskApi

Returns the task associated with this AperturePhotometryPanel.

Map getSelectionMap()

Returns the associated selection map.

Returns the selection map associated with this AperturePhotometryPanel.

Return

Map

Returns the selection map associated with this AperturePhotometryPanel.

Map getModifierMap()

Returns the associated modifier map.

Returns the modifier map associated with this ApperturePhotometryPanel.

Return

Map

Returns the modifier map associated with this ApperturePhotometryPanel.

SiteEventHandler getHandler()

Returns the associated site event handler.

Returns the site event handler associated with this ApperturePhotometryPanel.

Return

SiteEventHandler

Returns the site event handler associated with this ApperturePhotometryPanel.

double getTargetRadius()

Returns the target radius in pixels.

Returns the target radius for this ApperturePhotometryPanel in pixels.

Return

double

Returns the target radius for this ApperturePhotometryPanel in pixels.

trigger()

Triggers the execution of the associated task.

Triggers the execution of the task associated with this ApperturePhotometryPanel.

transferFromModifierToSelectionMap()

Transfers the information from the modifier to the selection map.

Transfers the information for this ApperturePhotometryPanel from the modifier to the selection map.

drawFigures()

Draws the figures bounding the apertures on the image.

Draws the figures bounding the apertures for this ApperturePhotometryPanel on the image.

moveConfirmedFigures()

Allows to move/resize the figures bounding the apertures.

Allows to move/resize the figures bounding the apertures for this ApperturePhotometryPanel.

clearSkyAperture()
Clears the sky aperture. Clears the sky aperture for this AperturePhotometryPanel.

2.17. ApperturePhotometryProduct

Full Name:	herschel.ia.dataset.image.ApperturePhotometryProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import ApperturePhotometryProduct

Description

A class to deal with the results of aperture photometry.

API Summary

Constructor
ApperturePhotometryProduct() The constructor of a new ApperturePhotometryProduct.

Methods
setTargetCenter(double centerX, double centerY) Sets the target center for this ApperturePhotometryProduct to
setTargetCenter(double centerX, double centerY, String centerRA, String centerDec) Sets the target center for this ApperturePhotometryproduct
setTargetRadius(double pixels) Sets the target radius for this ApperturePhotometryProduct
setTargetRadius(double pixels, double arcsec) Sets the target radius for this ApperturePhotometryProduct
setPixels(boolean fractional) Sets the type of pixels (entire / fractional) used for this
setUnit(Unit unit) Sets the unit for this ApperturePhotometryProduct to the given unit.
setResultsTable(Double2d resultsTable) Sets the results table for this ApperturePhotometryProduct to the
setCurveOfGrowth(Double1d growthRadius, Double1d growthFlux) Sets the curve of growth for this ApperturePhotometryProduct for the given
Double1d **getTargetCenterPixelCoordinates**() Returns the target center for this ApperturePhotometryProduct in
String1d **getTargetCenterSkyCoordinates**() Returns the target center for this ApperturePhotometryProduct in
double **getTargetRadiusPixels**() Returns the target radius for this ApperturePhotometryProduct in pixels.
double **getTargetRadiusArcsec**() Returns the target radius for this ApperturePhotometryProduct in arcsec.
String **getPixels**() Returns the String representation of the type of pixels (fractional / entire) used

Methods
`String` **`getUnit()`** Returns the unit for this AperturePhotometryProduct.
`TableDataset` **`getTable()`** Returns the results table for this AperturePhotometryProduct.
`Double2d` **`getDouble2dTable()`** Returns the results table for this AperturePhotometryProduct as a Double2d.
`Double1d` **`getTotal()`** Returns the total flux for the target, the sky and the target from
`Double1d` **`getNbOfPixels()`** Returns the number of pixels for the target, the sky and the target from
`Double1d` **`getIntensityPerPixel()`** Returns the intensity per pixel for the target, the sky and the
`Double1d` **`getError()`** Returns the error for the target, the sky and the target from which the
`double` **`getTargetPlusSkyTotal()`** Returns the total flux for the target (sky included) for this
`double` **`getNbOfTargetPlusSkyPixels()`** Returns the number of pixels for the target (sky included) for this
`double` **`getIntensityPerTargetPlusSkyPixel()`** Returns the intensity per pixel for the target (sky included) for this
`double` **`getTargetPlusSkyError()`** Returns the error for the target (sky included) for this AperturePhotometryProduct.
`double` **`getIntensityPerSkyPixel()`** Returns the intensity per pixel for the sky for this AperturePhotometryProduct.
`double` **`getTargetTotal()`** Returns the total flux for the target (sky subtracted) for this
`double` **`getNbOfTargetPixels()`** Returns the number of pixels for the target (sky subtracted) for this
`double` **`getIntensityPerTargetPixel()`** Returns the intensity per pixel for the target (sky subtracted) for this
`double` **`getTargetError()`** Returns the error for the target (sky subtracted) for this
`TableDataset` **`getCurveOfGrowth()`** Returns the curve of growth for this AperturePhotometryProduct.
`Double1d` **`getGrowthRadius()`** Returns the growth radius for this AperturePhotometryProduct.
`Double1d` **`getGrowthFlux()`** Returns the growth flux for this AperturePhotometryProduct,

Miscellaneous

Aperture specific information is stored in meta data, all other data (results of calculations) are stored in TableDatasets.

API details

Constructor

ApturePhotometryProduct()

The constructor of a new AperturePhotometryProduct.

Methods

setTargetCenter(double centerX, double centerY)

Sets the target center for this AperturePhotometryProduct to

the given pixel coordinates.

Arguments

double **centerX** [INPUT, MANDATORY]

double **centerY** [INPUT, MANDATORY]

setTargetCenter(double centerX, double centerY, String centerRA, String centerDec)

Sets the target center for this AperturePhotometryproduct

to the given pixel and sky coordinates.

Arguments

double **centerX** [INPUT, MANDATORY]

double **centerY** [INPUT, MANDATORY]

String **centerRA** [INPUT, MANDATORY]

String **centerDec** [INPUT, MANDATORY]

setTargetRadius(double pixels)

Sets the target radius for this AperturePhotometryProduct

to the given number of pixels.

Argument

double **pixels** [INPUT, MANDATORY]

setTargetRadius(double pixels, double arcsec)

Sets the target radius for this AperturePhotometryProduct

to the given number of pixels and arcsec.

Arguments

double **pixels** [INPUT, MANDATORY]

double **arcsec** [INPUT, MANDATORY]

setPixels(boolean fractional)

Sets the type of pixels (entire / fractional) used for this

AperturePhotometryProduct.

setPixels(boolean fractional)

Argument

`boolean` **`fractional`** `[INPUT, MANDATORY]`

setUnit(Unit unit)

Sets the unit for this AperturePhotometryProduct to the given unit.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

setResultsTable(Double2d resultsTable)

Sets the results table for this AperturePhotometryProduct to the

given table.

Argument

`Double2d` **`resultsTable`** `[INPUT, MANDATORY]`

setCurveOfGrowth(Double1d growthRadius, Double1d growthFlux)

Sets the curve of growth for this AperturePhotometryProduct for the given

growth radius and growth flux.

Arguments

`Double1d` **`growthRadius`** `[INPUT, MANDATORY]`

`Double1d` **`growthFlux`** `[INPUT, MANDATORY]`

Double1d getTargetCenterPixelCoordinates()

Returns the target center for this AperturePhotometryProduct in

pixel coordinates.

Return

Double1d

Returns the target center for this AperturePhotometryProduct in pixel coordinates.

String1d getTargetCenterSkyCoordinates()

Returns the target center for this AperturePhotometryProduct in

sky coordinates.

Return

String1d

Returns the target center for this AperturePhotometryProduct in sky coordinates.

double getTargetRadiusPixels()

Returns the target radius for this AperturePhotometryProduct in pixels.

Return

double

double getTargetRadiusPixels()

Returns the target radius for this AperturePhotometryProduct in pixels.

double getTargetRadiusArcsec()

Returns the target radius for this AperturePhotometryProduct in arcsec.

Return

double

Returns the target radius for this AperturePhotometryProduct in arcsec.

String getPixels()

Returns the String representation of the type of pixels (fractional / entire) used

for this AperturePhotometryProduct.

Return

String

Returns the String representation of the type of pixels (fractional / entire) used for this AperturePhotometryProduct.

String getUnit()

Returns the unit for this AperturePhotometryProduct.

Return

String

Returns the unit for this AperturePhotometryProduct.

TableDataset getTable()

Returns the results table for this AperturePhotometryProduct.

Return

TableDataset

Returns the results table for this AperturePhotometryProduct.

Double2d getDouble2dTable()

Returns the results table for this AperturePhotometryProduct as a Double2d.

Return

Double2d

Returns the results table for this AperturePhotometryProduct as a Double2d.

Double1d getTotal()

Returns the total flux for the target, the sky and the target from

which the sky has been subtracted for this AperturePhotometryProduct.

Return

Double1d getTotal()

Double1d

Returns the total flux for the target, the sky and the target from which the sky has been subtracted for this AperturePhotometryProduct.

Double1d getNbOfPixels()

Returns the number of pixels for the target, the sky and the target from

which the sky has been subtracted.

Return

Double1d

Returns the number of pixels for the target, the sky and the target from which the sky has been subtracted.

Double1d getIntensityPerPixel()

Returns the intensity per pixel for the target, the sky and the

target from which the sky has been subtracted for this AperturePhotometryProduct.

Return

Double1d

Returns the intensity per pixel for the target, the sky and the target from which the sky has been subtracted for this AperturePhotometryProduct.

Double1d getError()

Returns the error for the target, the sky and the target from which the

sky has been subtracted for this AperturePhotometryProduct.

Return

Double1d

Returns the error for the target, the sky and the target from which the sky has been subtracted for this AperturePhotometryProduct.

double getTargetPlusSkyTotal()

Returns the total flux for the target (sky included) for this

AperturePhotometryProduct.

Return

double

Returns the total flux for the target (sky included) for this AperturePhotometryProduct.

double getNbOfTargetPlusSkyPixels()

Returns the number of pixels for the target (sky included) for this

AperturePhotometryProduct.

`double getNbOfTargetPlusSkyPixels()`

Return

double

Returns the number of pixels for the target (sky included) for this ApperturePhotometryProduct.

`double getIntensityPerTargetPlusSkyPixel()`

Returns the intensity per pixel for the target (sky included) for this

ApperturePhotometryProduct.

Return

double

Returns the intensity per pixel for the target (sky included) for this ApperturePhotometryProduct.

`double getTargetPlusSkyError()`

Returns the error for the target (sky included) for this ApperturePhotometryProduct.

Return

double

Returns the error for the target (sky included) for this ApperturePhotometryProduct.

`double getIntensityPerSkyPixel()`

Returns the intensity per pixel for the sky for this ApperturePhotometryProduct.

Return

double

Returns the intensity per pixel for the sky for this ApperturePhotometryProduct.

`double getTargetTotal()`

Returns the total flux for the target (sky subtracted) for this

ApperturePhotometryProduct.

Return

double

Returns the total flux for the target (sky subtracted) for this ApperturePhotometryProduct.

`double getNbOfTargetPixels()`

Returns the number of pixels for the target (sky subtracted) for this

ApperturePhotometryProduct.

Return

double

Returns the number of pixels for the target (sky subtracted) for this ApperturePhotometryProduct.

`double getIntensityPerTargetPixel()`

Returns the intensity per pixel for the target (sky subtracted) for this

ApperturePhotometryProduct.

Return

double

Returns the intensity per pixel for the target (sky subtracted) for this ApperturePhotometryProduct.

`double getTargetError()`

Returns the error for the target (sky subtracted) for this

ApperturePhotometryProduct.

Return

double

Returns the error for the target (sky subtracted) for this ApperturePhotometryProduct.

`TableDataset getCurveOfGrowth()`

Returns the curve of growth for this ApperturePhotometryProduct.

Return

TableDataset

Returns the curve of growth for this ApperturePhotometryProduct.

`Double1d getGrowthRadius()`

Returns the growth radius for this ApperturePhotometryProduct.

Return

Double1d

Returns the growth radius for this ApperturePhotometryProduct.

`Double1d getGrowthFlux()`

Returns the growth flux for this ApperturePhotometryProduct,

Return

Double1d

Returns the growth flux for this ApperturePhotometryProduct.

2.18. AperturePhotometryTask

Full Name:	herschel.ia.toolbox.image.AperturePhotometryTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import AperturePhotometryTask

Description

An abstract Task for aperture photometry.

Three Tasks implement this interface. They all use a circular target aperture. Two use a sky aperture (annular/rectangular) to estimate the sky with one of the five sky estimation algorithms. The third one uses a fixed value for the sky.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **centerX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **centerY** [INPUT, OPTIONAL, default=Default value : NaN]
String **centerRA** [INPUT, OPTIONAL, default=Default value : "centerRA"]
String **centerDec** [INPUT, OPTIONAL, default=Default value : "centerDec"]
Double **radiusPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **radiusArcsec** [INPUT, OPTIONAL, default=Default value : 4]
boolean **fractional** [INPUT, OPTIONAL, default=Default value : true]
boolean **centroid** [INPUT, OPTIONAL, default=Default value : false]
AperturePhotometryProduct **result** [OUTPUT, MANDATORY, default=No default value]

Miscellaneous

In the current version two subclasses extend this class : - an abstract class for aperture photometry for which the sky is estimated through a sky aperture (annular/rectangular) and a sky estimation algorithm - a class for aperture photometry for which to sky has a fixed value, given by the user In both cases, a circular target aperture is used.

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]
The image.

Double centerX [INPUT, OPTIONAL, default=Default value : NaN]
The x-pixel-coordinate of the target center.

Double centerY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the target center.

String centerRA [INPUT, OPTIONAL, default=Default value : "centerRA"]

The right ascension of the target center.

String centerDec [INPUT, OPTIONAL, default=Default value : "centerDec"]

The declination of the target center.

Double radiusPixels [INPUT, OPTIONAL, default=Default value : NaN]

The radius of the circular target aperture in pixels.

Integer radiusArcsec [INPUT, OPTIONAL, default=Default value : 4]

The radius of the circular target aperture in arcsec.

boolean fractional [INPUT, OPTIONAL, default=Default value : true]

The type of pixels.

boolean centroid [INPUT, OPTIONAL, default=Default value : false]

Indicates whether to centroid on the target center.

AperturePhotometryProduct result [OUTPUT, MANDATORY, default=No default value]

The result.

2.19. ARCCOS

Full Name:	herschel.ia.numeric.toolbox.basic.ArcCos
Alias:	ARCCOS
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import ArcCos

Description

Computes the inverse cosine of a number or array, and may be of any type.

Gives the inverse cosine of a number or array. The input must be in the range [-1,1], and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type. The result is in radians.

Example

Example 1: Apply ARCCOS on a Float1d

```
x=Float1d([0,0.5])
print  ARCCOS(x) # [1.5707964,1.0471976]
```

API Summary

Jython Syntax
<y>=ARCCOS(<x>)

Properties
any type **x** [INPUT, MANDATORY, default=no default value]
radians **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any type x [INPUT, MANDATORY, default=no default value]

must be in the range [-1,1], and may be of any type.

radians y [OUTPUT, MANDATORY, default=no default value]

Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type. The result is in radians.

See also

- COS
- COSH

2.20. ARCSIN

Full Name:	herschel.ia.numeric.toolbox.basic.ArcSin
Alias:	ARCSIN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import ArcSin

Description

Computes the inverse sine of a number or array, and may be of any type.

Gives the inverse sine of a number or array. The input must be in the range [-1,1], and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type. The result is in radians.

Example

Example 1: Apply ARCSIN on a Float1d

```
x=Float1d([0,0.5])
print  ARCSIN(x) # [0.0,0.5235988]
```

API Summary

Jython Syntax
<y>=ARCSIN(<x>)

Properties
any type **x** [INPUT, MANDATORY, default=no default value]
radians **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any type x [INPUT, MANDATORY, default=no default value]
must be in the range [-1,1], and may be of any type.

radians y [OUTPUT, MANDATORY, default=no default value]
Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type. The result is in radians.

See also

- SIN
- SINH

2.21. ARCTAN

Full Name:	herschel.ia.numeric.toolbox.basic.ArcTan
Alias:	ARCTAN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import ArcTan

Description

Computes the inverse tangent of a number or array, and may be of any type.

Gives the inverse tangent of a number or array. The input must be in the range [-1,1], and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type. The result is in radians.

Example

Example 1: Apply ARCTAN on a Float1d

```
x=Float1d([0,0.5])
print  ARCTAN(x) # [0.0,0.4636476]
```

API Summary

Jython Syntax
<y>=ARCTAN(<x>)

Properties
any type **x** [INPUT, MANDATORY, default=no default value]
radians **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any type x [INPUT, MANDATORY, default=no default value]

must be in the range [-1,1], and may be of any type.

radians y [OUTPUT, MANDATORY, default=no default value]

Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type. The result is in radians.

See also

- TAN
- TANH

2.22. ArithmeticSpectrumTask

Full Name:	herschel.ia.toolbox.spectrum.ArithmeticSpectrumTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import ArithmeticSpectrumTask

Description

Base task for applying a scalar operation to the flux data in a spectrum container or processing two spectrum containers on a spectrum-by-spectrum basis.

For the scalar mode, 'ds' and 'param' need to specified - for the pair-wise mode, 'ds1' and 'ds2' need to be set. In the pairwise mode, the task iterates through the two containers and computes the pair-operation. In case the size of the two containers is different, the iteration stops at the minimum size. Hence, the remaining spectra in the larger container are ignored. In case one of the datasets only contains a single spectrum, the task always refers to this single spectrum while iterating over all the spectra in the other dataset.

Different selection schemes are available for selecting the point spectra or the segments to be processed. The most simple scheme is to specify lists of point spectrum indices (`selection=[1,3,4,2]`). In this case, the operation (scalar- or pair-operation) is just taken over the point spectra with corresponding indices. Instead of specifying a list of indices (which requires the knowledge of these) other recipes to specify a selection are available. Typical recipes test attribute values to match certain values or to be included in a given interval. These recipes we refer to as selection models. The different options to specify selections can be combined. Here, an AND logic is adopted.

Similarly, you can specify what segments to consider. In the most simple case, you can just specify the indices of segments to be considered (for the scalar operation `segments=[1,3,4]` and for the pair operation `segments1=[1,3,4], segments1=[3,6,5]`). In more advanced situations you can use a `SegmentSelection` object. Note that the pairs of segments to be processed need to be consistent - otherwise the processing will fail.

You can specify whether the orginal datasets should be overwritten with the 'overwrite' flag. By default no data is overwritten. In the pair-wise mode, it is not always possible to overwrite the data - in particular if non-trivial segment selections are specified.

For the pair-wise mode, there are further options that can be selected by the 'variant' (e.g. whether to use flags and weights).

API Summary

Properties
SpectrumContainer **ds** [INPUT, OPTIONAL, default=no default value.]
Double **param** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection_lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection_index** [INPUT, OPTIONAL, default=No default value.]
Boolean **overwrite** [INPUT, OPTIONAL, default=False.]
SpectrumContainer **ds1** [INPUT, OPTIONAL, default=no default value.]

Properties
SpectrumContainer **ds2** [INPUT, OPTIONAL, default=no default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Object **segments1** [INPUT, OPTIONAL, default=no default value.]
Object **segments2** [INPUT, OPTIONAL, default=no default value.]
String **variant** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

SpectrumContainer ds [INPUT, OPTIONAL, default=no default value.]

Input container to be processed by the task in case the task is used as a scalar operation.

Double param [INPUT, OPTIONAL, default=no default value.]

The scalar parameter to be considered when the task is used as scalar operation.

Object selection [INPUT, OPTIONAL, default=None.]

Specify what point spectra the operation should be applied to. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra for which the add should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

Boolean overwrite [INPUT, OPTIONAL, default=False.]

Specify whether the input data container can be reused - the values found therein is overwritten.

SpectrumContainer ds1 [INPUT, OPTIONAL, default=no default value.]

First input container for pair-wise operations.

SpectrumContainer ds2 [INPUT, OPTIONAL, default=no default value.]

Second input container for pair-wise operations.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments the operation should be applied to. There are two options available:

- Either pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.
- Specify a PyList of segment indices.

Object segments1 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds1'.

Object segments2 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds2'.

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-wave" / "flux-wave-weight" / "flux-flag-wave" / "flux-weight-flag-wave"

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

History

- `2009-05-20 - meli`: Initial.

2.23. asciiTableReader

Full Name:	herschel.ia.toolbox.util.AsciiTableReaderTask
Alias:	asciiTableReader
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import AsciiTableReaderTask
Category:	utility task

Description

AsciiTableReaderTask

Task for reading ascii files.

Examples

Example 1: Read a raw space-separated ascii table

```
# test_space.dat contents
# start
1 2 3
2 3 4
5 6 7
# end
from herschel.ia.io.ascii import AsciiParser
atrt = AsciiTableReaderTask()
tds = atrt(file="test_space.dat", \
    parserDelim=" -", \
    #template=TableTemplate(3,names=["a","b","c"]), \
    parserIgnore= -'^\s*$|^\s*#', \
    parserIgnoreWarn= 1, \
    parserGuess=AsciiParser.GUESS_TRY)
# tds will hold a TableDataset with the data, blank lines will be ignored,
and warnings will be issued for ignored lines
```

Example 2: Read a file

```
atrt = AsciiTableReaderTask()
tableDataset = atrt(file="file.ascii")
print tableDataset
```

Example 3: Read a file without HCSS header (first row does not contain names), delimiter is tab

```
atrt = AsciiTableReaderTask()
tableDataset = atrt(file=&quot;file.ascii&quot;, parserDelim='\t',
parserGuess=AsciiParser.GUESS_TRY)
```

Example 4: Read a file without HCSS header (first row contains names), delimiter is tab.

```
tableDataset = atrt(file=&quot;file.ascii&quot;, parserDelim='\t',
parserGuess=AsciiParser.GUESS_TRY, parseNames=1)
```

API Summary

Jython Syntax

```
tableDataset=AsciiTableReaderTask()(file=&quot;file.ascii&quot;)
```

Jython Syntax
`see examples`

Properties
`String` **`file`** `[INPUT, MANDATORY, default=null]`
`String` **`table`** `[OUTPUT, MANDATORY, default=null]`
`String` **`configFile`** `[INPUT, OPTIONAL, default=null]`
`String` **`configFileOutput`** `[INPUT, OPTIONAL, default=null]`
`AsciiParser` **`parser`** `[INPUT, OPTIONAL, default=default AsciiTableTool parser]`
`String` **`parserIgnore`** `[INPUT, OPTIONAL, default=default AsciiParser ignore value.]`
`Boolean` **`parserIgnoreWarn`** `[INPUT, OPTIONAL, default=default AsciiTableTool warnWhenIgnore value (false).]`
`Integer` **`parserSkip`** `[INPUT, OPTIONAL, default=default AsciiParser skipping rows value.]`
`Boolean` **`parserTrim`** `[INPUT, OPTIONAL, default=default AsciiParser trim rows value.]`
`Integer` **`parserGuess`** `[INPUT, OPTIONAL, default=GUESS_NONE Guess behavior.]`
`String` **`parserDelim`** `[INPUT, OPTIONAL, default=comma separator.]`
`Boolean` **`parseNames`** `[INPUT, OPTIONAL, default=default AsciiParser parseNames value.]`
`TableTemplate` **`template`** `[INPUT, OPTIONAL, default=extracted from the first file rows.]`

API details

Properties

`String file [INPUT, MANDATORY, default=null]`

Input file.

`String table [OUTPUT, MANDATORY, default=null]`

TableDataset object loaded.

`String configFile [INPUT, OPTIONAL, default=null]`

Configuration file where the formatter (AsciiFormatter), parser (AsciiParser) and table template (TableTemplate) must be specified. When configFile parameter is specified, any parameter related to parser or to table template are not allowed.

`String configFileOutput [INPUT, OPTIONAL, default=null]`

If a file is specified, an output configuration file will be created.

`AsciiParser parser [INPUT, OPTIONAL, default=default AsciiTableTool parser]`

AsciiParser object

String parserIgnore [INPUT, OPTIONAL, default=default AsciiParser ignore value.]

String expression to ignore when parsing a file. AsciiParser.setIgnore(expression) is called.

Boolean parserIgnoreWarn [INPUT, OPTIONAL, default=default AsciiTableTool warnWhenIgnore value (false).]

Specifies if the parser must issue a warning if a line is ignored (emit only if true). AsciiTableTool.setWarnWhenIgnore(expression) is called.

Integer parserSkip [INPUT, OPTIONAL, default=default AsciiParser skipping rows value.]

Number of rows to skip when reading a file. AsciiParser.setSkip(number of lines) is called.

Boolean parserTrim [INPUT, OPTIONAL, default=default AsciiParser trim rows value.]

Specifies if the parser must trim each row when reading a file. AsciiParser.setTrim(strip lines) is called.

Integer parserGuess [INPUT, OPTIONAL, default=GUESS_NONE Guess behavior.]

Specifies if the parser should guess column types. Files should not contain HCSS header (use skip=AsciiReader.HCSS_HEADER for skipping HCSS header or comment these lines) AsciiParser.setGuess(guessType) is called. Valid options: -AsciiParser.GUESS_NONE: (default) file must contains template or template must be provided (no guess) -AsciiParser.GUESS_TRY: guess types based on the first 100 records -AsciiParser.GUESS_ALL: guess types based on all records -AsciiParser.ALL_STRING: each record is a string (no guess required) -AsciiParser.ALL_BOOLEAN: each record is a boolean (no guess required) -AsciiParser.ALL_BYTE: each record is a byte (no guess required) -AsciiParser.ALL_INTEGER: each record is an integer (no guess required) -AsciiParser.ALL_LONG: each record is a long (no guess required) -AsciiParser.ALL_FLOAT: each record is a float (no guess required) -AsciiParser.ALL_DOUBLE: each record is a double (no guess required) -AsciiParser.ALL_COMPLEX: each record is a complex (no guess required)

String parserDelim [INPUT, OPTIONAL, default=comma separator.]

Specifies the field separator. If it is one character, a csvParser is selected. If it is an expression, a RegExpParser is selected.

Boolean parseNames [INPUT, OPTIONAL, default=default AsciiParser parseNames value.]

Specifies if the parser must read column names when reading a file. AsciiParser.firstRowAreColumnNames(expression) is called.

TableTemplate template [INPUT, OPTIONAL, default=extracted from the first file rows.]

Specifies the data structure.

History

- `2007-11-22 - JCS`: initial version
- `2008-08-22 - JDS`: added optional parameter parserIgnoreWarn (SCR HCSS-3674), serialVersionUID, parameter descriptions, better jython doc

- `2009-09-30 - JSS`: modifiers are created through getCustomModifiers (SCR HCSS-8253)

2.24. asciiTableWriter

Full Name:	herschel.ia.toolbox.util.AsciiTableWriterTask
Alias:	asciiTableWriter
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import AsciiTableWriterTask
Category:	utility task

Description

Task for writing ASCII files.

Example

Example 1: write a table in an text file

```
...
atwt = AsciiTableWriterTask()
atwt(file="file.ascii", table=TableDataset())
...
```

API Summary

Jython Syntax

```
asciiTableWriter(<file>, <table> [, <configFile>,
<configFileOutput>, <formatter>, \
<formatterHeader>, <formatterCommented>, <formatterCommentPrefix>,
<template>])
```

Properties

- String **file** [INPUT, true, default=null]
- TableDataset **table** [INPUT, true, default=null]
- String **configFile** [INPUT, false, default=null]
- String **configFileOutput** [INPUT, false, default=null]
- AsciiFormatter **formatter** [INPUT, false, default=default AsciiTableTool formatter.]
- Boolean **formatterHeader** [INPUT, false, default=default AsciiFormatter header allowance value.]
- Boolean **formatterCommented** [INPUT, false, default=default AsciiFormatter comments allowance value.]
- String **formatterCommentPrefix** [INPUT, false, default=default AsciiFormatter comments prefix value.]
- TableTemplate **template** [INPUT, false, default=extracted from the first file rows.]

API details

Properties

String file [INPUT, true, default=null]

Output file.

TableDataset table [INPUT, true, default=null]

TableDataset object to be saved.

String configFile [INPUT, false, default=null]

Configuration file where the formatter (AsciiFormatter), parser (AsciiParser) and table template (TableTemplate) must be specified. When configFile parameter is specified, any parameter related to parser or to table template are not allowed.

String configFileOutput [INPUT, false, default=null]

If a file is specified, an output configuration file will be created.

AsciiFormatter formatter [INPUT, false, default=default AsciiTableTool formatter.]

AsciiFormatter object

Boolean formatterHeader [INPUT, false, default=default AsciiFormatter header allowance value.]

Specifies allowance of header information AsciiFormatter.setHeader(true/false) is called.

Boolean formatterCommented [INPUT, false, default=default AsciiFormatter comments allowance value.]

Specifies allowance of comments when writing a file. AsciiFormatter.setCommented(true/false) is called.

String formatterCommentPrefix [INPUT, false, default=default AsciiFormatter comments prefix value.]

Specifies the prefix of all comments. AsciiFormatter.setCommentPrefix(expression) is called.

TableTemplate template [INPUT, false, default=extracted from the first file rows.]

Specifies the data structure.

History

- `2007-11-22 - JCS`: initial version
- `2009-09-30 - JSS`: modifiers are created through getCustomModifiers (SCR HCSS-8253)

2.25. AttribQuery

Full Name:	herschel.ia.pal.query.AttribQuery
Type:	Java Class -
Import:	from herschel.ia.pal.query import AttribQuery

Description

Attribute Query formulates a query on the attributes of a Product.

In principle this can be the fastest query on the Product Access Layer. Known attributes are:

- type : String
- creator : String
- creationDate: FineTime
- startDate : FineTime
- endDate : FineTime
- modelName : String
- instrument : String
- description : String

Example

Example 1: Example of a query on attributes

```
date = SimpleTimeFormat().parse("2008-10-31T12:00:00
TAI").microsecondsSince1958()
q = AttribQuery(Product, -"p", -"p.creationDate < -" + str(date) + -"L and
p.creator = -'Me'")
```

See also

- ???

2.26. AutoCorrelationTask

Full Name:	herschel.ia.toolbox.image.AutoCorrelationTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import AutoCorrelationTask

Description

A Task to calculate the linear Pearson correlation coefficient of an image.

A Task to calculate the linear Pearson correlation coefficient of an image. We start from a M x N image (M = number of rows, N = number of columns) and calculate the N x N linear Pearson coeffient matrix . The i'th row and j'th column element corresponds to the correlation of the i'th and j'th columns of the M x N matrix.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double2d correlation [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image.

`Double2d correlation [OUTPUT, MANDATORY, default=No default value]`

The correlation.

2.27. AutomaticContourTask

Full Name:	herschel.ia.toolbox.image.AutomaticContourTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import AutomaticContourTask

Description

A Task for making contours.

A Task for making contours for a given number of contour levels aith a given distribution between the given extreme contour values.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Integer **levels** [INPUT, MANDATORY, default=No default value]
Double **min** [INPUT, MANDATORY, default=No default value]
Double **max** [INPUT, MANDATORY, default=No default value]
String **distribution** [INPUT, MANDATORY, default=No default value]
ImageContour **contours** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Integer levels [INPUT, MANDATORY, default=No default value]

The number of contour levels.

Double min [INPUT, MANDATORY, default=No default value]

The minimum contour value.

Double max [INPUT, MANDATORY, default=No default value]

The maximum contour value.

String distribution [INPUT, MANDATORY, default=No default value]

The distribution of the contour values.

ImageContour contours [OUTPUT, MANDATORY, default=No default value]

The ImageContour.

2.28. AutomaticContourTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.AutomaticContourTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import AutomaticContourTaskSignatureComponent

Description

The task dialog for the AutomaticContourTask.

A task dialog to serve as GUI for the AutomaticContourTask.

API Summary

Constructor
AutomaticContourTaskSignatureComponent() The construction of a new AutomaticContourTaskSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
Map **getParameters()** Returns a map of parameters and modifiers.
setSignature(SignatureApi signature) Setting the signature.
setVariableSelection(VariableSelection selection) Setting the variable selection.
JComponent **getComponent()** Returns the component.

API details

Constructor

AutomaticContourTaskSignatureComponent()
The construction of a new AutomaticContourTaskSignatureComponent. The construction of a new AutomaticContourTaskSignatureComponent.

Methods

check()
Validates the current modifications.

check()

Validates the current modifications for this AutomaticContourTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this AutomaticContourTaskSignatureComponent.

Map getParameters()

Returns a map of parameters and modifiers.

Returns a map of parameters and modifiers storing the value selected by the user for this AutomaticContourTaskSignatureComponent.

Return

Map

Returns a map of parameters and modifiers storing the value selected by the user for this AutomaticContourTaskSignatureComponent.

setSignature(SignatureApi signature)

Setting the signature.

Sets the given signature as the signature for this AutomaticContourTaskSignatureComponent.

Argument

`SignatureApi` **`signature`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this AutomaticContourTaskSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

JComponent getComponent()

Returns the component.

Returns the component for this AutomaticContourTaskSignatureComponent.

Return

JComponent

Returns the component for this AutomaticContourTaskSignatureComponent.

2.29. AverageSpectrum

Full Name:	herschel.ia.toolbox.spectrum.AverageSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import AverageSpectrum

Description

Task for averaging the individual spectra included in one or several `SpectrumContainer` (see in `herschel.ia.dataset.spectrum`).

The averaging operation is applied to the spectral segments included in the different spectra. For other attributes characterizing the spectrum information and included in the same spectrum container, suitable defaults can be defined (depending on the runtime types or the 'instrument' metadata element; typically, these defaults are defined by the ICC's). A further option is that the user can register such operations from the command line:

```
avg.register("integrations", "ADD")
```

The input data with the spectra to be averaged can be provided in different forms: Either any data object that implements `SpectrumContainer` or any array of such. However, for a successful processing of the task, the data included in the containers should all be consistent. This means that the number of segments found in all the spectra in the containers should be the same and the lengths of these segments should be consistent. Otherwise an exception should be thrown.

Different selection schemes are available for selecting the point spectra or the segments to be averaged. The most simple scheme is to specify lists of point spectrum indices (`selection=[1,3,4,2]`). In this case, the average is just taken over the point spectra with corresponding indices. Instead of specifying a list of indices (which requires the knowledge of these) other recipes to specify a selection are available. Typical recipes test attribute values to match certain values or to be included in a given interval. These recipes we refer to as selection models. The different options to specify selections can be combined. Here, an AND logic is adopted.

Similarly, you can specify what segments to consider in the averaging. In the most simple case, you can just specify the indices of segments to be considered `segments=[1,3,4]`. In more advanced situations you can use a `SegmentSelection` object.

Sometimes, the selection model also provides a natural segmentation of the data into groups. If you want to calculate the average on a per group basis then you can set the per_group flag to true.

Using the keyword grouping the user may specify a grouping model which allows to partition the spectra included in the container into suitable sub-groups. Here, when a grouping model is specified, the average is calculated for each sub-group separately. Grouping and selections can be combined such that the selection model(s) impose(s) constraints on the spectra to be included in the groups.

Example

Example 1: from Jide:

```
from herschel.ia.toolbox.spectrum import AverageSpectrum
avg = AverageSpectrum()
avg.register("integrations","ADD")
averagedSpectra = avg(ds=spectra)
spectraOut = avg(ds=spectra, segments=[1,3])
spectraOut = avg(ds=spectra, selection={"bbtype":[6031, 6032]})
spectraOut = avg(ds=spectra, selection=[0,1,2,3])
spectraOut = avg(ds=spectra, selection={"LoFrequency":(4000.0,5000.0)})
spectraOut = avg(ds=spectra, selection={"Chopper":([-4.4,5.9],0.1))
```

Example 1: from Jide:

```
spectraOut = avg(ds=spectra, selection={"Chopper":([-4.4,5.9],0.1),
segments=[1,2])
from herschel.ia.toolbox.spectrum.selections.models import RangesSelectionModel
spectraOut = avg(ds=spectra, selection=RangesSelectionModel("Chopper",
[-4.4,5.9], 0.1)) # the same as above
# or all combined:
spectraOut = avg(ds=spectra, selection={"bbtype":[6031, 6032], -"Chopper":
([-4.4,5.9],0.1), -"LoFrequency":(4000.0,5000.0))
from herschel.ia.toolbox.spectrum.selections.models import RangesGroupingModel
averagedSpectraPerGroup = avg(ds=spectra,
grouping=RangesGroupingModel("Chopper", 0.1})
```

API Summary

Properties
Object **ds** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection index** [INPUT, OPTIONAL, default=No default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
String **variant** [INPUT, OPTIONAL, default=no default value.]
Boolean **per group** [INPUT, OPTIONAL, default=no default value.]
GroupingModel **grouping** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

Object ds [INPUT, OPTIONAL, default=no default value.]

Input data to be processed by the task. Several types are possible:

- SpectrumContainer
- Array of SpectrumContainer, i.e. SpectrumContainer[]
- List of SpectrumContainer, i.e. List
- Any product with implementations of `SpectrumContainer` inside.

Object selection [INPUT, OPTIONAL, default=None.]

Specification of what point spectra the average should be restricted to. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra for which the average should be taken.

Object selection [INPUT, OPTIONAL, default=None.]

- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments the operation should be applied to. There are two options available:

- Either pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.
- Specify a PyList of segment indices.

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-wave" / "flux-wave-weight" / "flux-flag-wave" / "flux-weight-flag-wave"

Boolean per_group [INPUT, OPTIONAL, default=no default value.]

Specify that the average should be calculated on a per group basis - once a selection model is specified that provides a natural grouping of the data.

GroupingModel grouping [INPUT, OPTIONAL, default=no default value.]

Grouping model that can be used to partition the point spectra into groups and calculate the average on a per group basis. When a grouping model is specified, the 'per_group'-flag is obsolete.

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

See also

- ManyToOneSpectrumTask

2.30. bg

Full Name:	herschel.ia.toolbox.util.BackgroundTask
Alias:	bg
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import BackgroundTask
Category:	task

Description

Execute jython commands in the background

The bg task is used to execute jython commands in a background Thread. The Thread is returned to allow Thread operations.

Example

Example 1: save specified variable names and values

```
bg("myfunc()")
```

API Summary

Jython Syntax
bg(<command>)

Properties
String **command** [INPUT, YES, default=No default value]
String **command** [OUPUT, YES, default=The created Tread]

Limitations

Only applicable from a jide session

Miscellaneous

No miscellaneous

API details

Properties

String command [INPUT, YES, default=No default value]

The name of command to be executed

String command [OUPUT, YES, default=The created Tread]

Return the Thread created internally to allow Thread operations

See also

- ???

History

- `2004-07-13 - NdC`: first release.

2.31. Bilinear

Full Name:	herschel.ia.numeric.toolbox.interp.Bilinear
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.interp import Bilinear
Category:	numerics/interp

Description

Bilinear Algorithm

The Bilinear class uses bilinear interpolation algorithm to compute the value at the point (x,y) on a regular grid where the images[i, j] i=0, m-1 and j=0, n-1 are known. The nearest neighbor extrapolation is used when the point (x,y) falls outside the boundary of the regular grid if the extrapolation is requested.

The Bilinear has the following arguments:

images: Input, a double2d data array

x: Input, a location array

y: Input, a location array

grid:The grid keyword controls how the location arrays specify where interpolates are desired.

If grid is not set, the location arrays, x, y must have the same number of elements. The result has the same structure and number of elements as x. Let n be the number of elements in x and y and the data array is images[n, n], and the result is also an one dimension array of size n.

If grid is set, let m be the number of elements in x, let n be the number of elements in y. The result has dimensions [m, n]. The element [i,j] of the result contains the value of images interpolated at position (xi, yj).

missing: The value to return for elements outside the bounds of images.

If this value is not specified, interpolated positions that fall outside the bounds of the array images - that is, elements of the x or y arguments that are either less than zero or greater than the largest subscript in the corresponding dimension of images - are set equal to the value of the nearest element of the images.

Examples

Example 1: All data points are inside the boundary

```
from herschel.ia.numeric.toolbox.interp import  Bilinear
from herschel.ia.numeric import *
from herschel.ia.numeric.toolbox.basic  import *
images=RESHAPE(Double1d.range(16), [4,4])
x=[0.0, 1.5]
y=[0.5, 2.5]
bi_imag =Bilinear(Bilinear.GRID, x,y)(images)
print bi_imag
  [
    [0.5,2.5],
    [6.5,8.5]
   -]
```

Example 2: Some data points are on the boundary without GRID is set (the default)

```
from herschel.ia.numeric.toolbox.interp import  Bilinear
```

Example 2: Some data points are on the boundary without GRID is set (the default)

```
from herschel.ia.numeric import *
from herschel.ia.numeric.toolbox.basic  import *
images=RESHAPE(Double1d.range(16), [4,4])
x=[0.0, 1.5, 3]
y=[0.5, 1.0, 2.5]
bi_imag =Bilinear(x,y)(images)
print bi_imag
[0.5,7.0,14.0]
```

Example 3: Some data points are on the boundary with GRID is set

```
from herschel.ia.numeric.toolbox.interp import  Bilinear
from herschel.ia.numeric import *
from herschel.ia.numeric.toolbox.basic  import *
images=RESHAPE(Double1d.range(16), [4,4])
x=[0.0, 1.5, 3]
y=[0.5, 1.0, 2.5]
bi_imag =Bilinear(Bilinear.GRID,x,y)(images)
print bi_imag
  [
  [0.5,1.0,2.5],
  [6.5,7.0,8.5],
  [12.5,13.0,14.5]
  -]
```

Example 4: Input x and y coordinate have different array size when GRID is set.

```
images=RESHAPE(Double1d.range(16), [4,4])
x=[0.0, 1.0]
y=[0.5, 1.0, 2.5, 3.5]
bi_imag=Bilinear(Bilinear.GRID,x,y)(images)
print bi_imag
[
    [0.5,1.0,2.5,3.0],
    [4.5,5.0,6.5,7.0]
]
```

Example 5: Some data points are outside boundary with missing=-1 and GRID is set.

```
from herschel.ia.numeric.toolbox.interp import  Bilinear
from herschel.ia.numeric import *
from herschel.ia.numeric.toolbox.basic  import *
images=RESHAPE(Double1d.range(16), [4,4])
x=[-0.5,2]
y=[0.5,1.5]
bi_imag1=Bilinear(Bilinear.GRID, x,y, --1.0)(images)
print bi_imag1
[
    [-1.0,-1.0],
    [8.5,9.5]
]
```

Example 6: Some data points are outside boundary with missing=-2 and without GRID is set

```
from herschel.ia.numeric.toolbox.interp import  Bilinear
from herschel.ia.numeric import *
from herschel.ia.numeric.toolbox.basic import *
images=RESHAPE(Double1d.range(16), [4,4])
x=Double1d.range(3).add(1.5)
y=Double1d.range(3).add(1.5)
img1=Bilinear(Bilinear.GRID, x,y, --2.0)(images)
print img1
[7.5,12.5,-2.0]
```

Example 7: Java example

```
import herschel.ia.numeric.Double1d;
import herschel.ia.numeric.Double2d;
import herschel.ia.numeric.toolbox.basic.Reshape;
import herschel.ia.numeric.toolbox.interp.Bilinear;
public class Test {
   public static void main(String[] args) {
     Double2d images=(Double2d) Double1d.range(16).apply(new Reshape(4,4));
     Double1d x=Double1d.range(3).add(0.5);
     Double1d y=Double1d.range(3).add(0.5);
     Double2d newImages1=(Double2d) images.apply(new
Bilinear(Bilinear.GRID,x, y));
     Double1d newImages2=(Double1d) images.apply(new Bilinear(x, y));
     Double2d newImages3=(Double2d) new Bilinear(Bilinear.GRID,x,
y -).of(images);
     Double1d newImages4=(Double1d) new Bilinear(x, y).of(images);
    System.out.println("newImages1="+newImages1);
    System.out.println("newImages2="+newImages2);
    System.out.println("newImages3="+newImages3);
    System.out.println("newImages4="+newImages4);
   -}
}
  newImages1=[
[2.5,3.5,4.5],
[6.5,7.5,8.5],
[10.5,11.5,12.5]
]
newImages2=[2.5,7.5,12.5]
newImages3=[
[2.5,3.5,4.5],
[6.5,7.5,8.5],
[10.5,11.5,12.5]
]
newImages4=[2.5,7.5,12.5]
```

API Summary

Constructors
Bilinear(Double1d x, Double1d y)
Bilinear(double[] x, double[] y)
Bilinear(Boolean grid, Double1d x, Double1d y)
Bilinear(Boolean grid, double[] x, double[] y)
Bilinear(Double1d x, Double1d y, double missing)
Bilinear(double[] x, double[] y, double missing)
Bilinear(Boolean grid, Double1d x, Double1d y, double missing)
Bilinear(Boolean grid, double[] x, double[] y, double missing)

Method
ArrayData **of**(Double2d images)

API details

Constructors

Bilinear(Double1d x, Double1d y)

Arguments

Double1d **x** [INPUT, MANDATORY, default=no default value]

Bilinear(Double1d x, Double1d y)

The array containing the x "virtual subscripts" of the images for which to interpolate values.

Double1d **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

Errors

Array

size error The length of array x and y has to be equal. The exception will be thrown if the lengths of the array x and y are not equal.

Bilinear(double[] x, double[] y)

Arguments

double[] **x** [INPUT, MANDATORY, default=no default value]

The array containing the x "virtual subscripts" of the images for which to interpolate values.

double[] **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

Errors

Array

size error The length of array x and y has to be equal. The exception will be thrown if the lengths of the array x and y are not equal.

Bilinear(Boolean grid, Double1d x, Double1d y)

Arguments

Boolean **grid** [INPUT, MANDATORY, default=no default value]

If grid is true and if the x contains m elements and y contains n elements, the result has dimensions [m, n], where the element [i,j] of the result contains the value of Images interpolated at position (xi, yj). If the grid is false, the result is the same as calling Bilinear without the grid argument.

Double1d **x** [INPUT, MANDATORY, default=no default value]

The array containing the x "virtual subscripts" of the images for which to interpolate values.

Double1d **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

Bilinear(Boolean grid, double[] x, double[] y)

Arguments

Boolean **grid** [INPUT, MANDATORY, default=no default value]

If grid is true and if the x contains m elements and y contains n elements, the result has dimensions [m, n], where the element [i,j] of the result contains the value of Images interpolated at position (xi, yj). If the grid is false, the result is the same as calling Bilinear without the grid argument.

double[] **x** [INPUT, MANDATORY, default=no default value]

The array containing the x "virtual subscripts" of the images for which to interpolate values.

double[] **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

Bilinear(Double1d x, Double1d y, double missing)

Arguments

Bilinear(Double1d x, Double1d y, double missing)

Double1d **x** [INPUT, MANDATORY, default=no default value]

The array containing the x "virtual subscripts" of the images for which to interpolate values.

Double1d **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

double **missing** [INPUT, MANDATORY, default=no default value]

When missing is given, the value outside the boundary is set to missing.

Bilinear(double[] x, double[] y, double missing)

Arguments

double[] **x** [INPUT, MANDATORY, default=no default value]

The array containing the x "virtual subscripts" of the images for which to interpolate values.

double[] **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

double **missing** [INPUT, MANDATORY, default=no default value]

When missing is given, the value outside the boundary is set to missing.

Bilinear(Boolean grid, Double1d x, Double1d y, double missing)

Arguments

Boolean **grid** [INPUT, MANDATORY, default=no default value]

If grid is true and if the x contains m elements and y contains n elements, the result has dimensions [m, n], where the element [i,j] of the result contains the value of Images interpolated at position (xi, yj). If the grid is false, the result is the same as calling Bilinear without the grid argument.

Double1d **x** [INPUT, MANDATORY, default=no default value]

The array containing the x "virtual subscripts" of the images for which to interpolate values.

Double1d **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

double **missing** [INPUT, MANDATORY, default=no default value]

When missing is given, the value outside the boundary is set to missing.

Bilinear(Boolean grid, double[] x, double[] y, double missing)

Arguments

Boolean **grid** [INPUT, MANDATORY, default=no default value]

If grid is true and if the x contains m elements and y contains n elements, the result has dimensions [m, n], where the element [i,j] of the result contains the value of Images interpolated at position (xi, yj). If the grid is false, the result is the same as calling Bilinear without the grid argument.

double[] **x** [INPUT, MANDATORY, default=no default value]

The array containing the x "virtual subscripts" of the images for which to interpolate values.

double[] **y** [INPUT, MANDATORY, default=no default value]

The array containing the y "virtual subscripts" of the images for which to interpolate values

double **missing** [INPUT, MANDATORY, default=no default value]

When missing is given, the value outside the boundary is set to missing.

Method

`ArrayData of(Double2d images)`

Argument

`Double2d` **`images`** `[INPUT, MANDATORY, default=no default value]`

A two dimension data array.

Return

ArrayData

the interpolated image values at the (xi, yj).

See also

- CubicSplineInterpolator
- NearestNeighborInterpolator
- http://en.wikipedia.org/wiki/Bilinear

History

- `2007-03-05 - first`: version
- `2007-03-24 - revised`: version
- `2008-03-27 - implemented`: SPR4608
- `2009-02-25 - add`: URM SPR-6124
- March 5, 2007 - first version
- March 24, 2008 - revised version
- Include missing argument to set the value where the point is outside the boundary
- images: A two dimensional array, Double2d data
- Missing:
- The value to return for elements outside the bounds of iamges. If this keyword is not
- specified, interpolated positions that fall outside the bounds of the array images -
- that is, elements of the x or y arguments that are either less than zero or
- greater than the largest subscript in the corresponding dimension of images - are set
- equal to the value of the nearest element ofimages.
- Feb. 24, 2009
- Updated documentation

2.32. BinCentres

Full Name:	herschel.ia.numeric.toolbox.basic.BinCentres
Alias:	BinCentres
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import BinCentres

Description

Return the bin centers for a Numeric data histogram base on a

use-supplied bin size.

Examples

Example 1: Plot Histogram over BinCentres for a Double1d

```
from herschel.ia.numeric import *
from herschel.ia.numeric.toolbox.random import RandomGauss
from herschel.ia.numeric.toolbox.basic import Histogram
from herschel.ia.numeric.toolbox.basic import BinCentres
d = Double1d(200000,10.0)
d[90000:115000] = 20.0
d[99000:110000] = 22.0
d[99900:100100] = 23.0
d[99990:100010] = 24.0
d[100000] = 24,5
rnd = RandomGauss()
for ix in range(200000):
  d[ix] += rnd.calc(0.1)
p = PlotXY (d)
binsize = STDDEV (d) * 2.35
print binsize
hist=Histogram(binsize)
bins=BinCentres(binsize)
p2=PlotXY(bins(d),hist(d))
style=p2.getStyle()
style.setChartType(Style.HISTOGRAM)
p.close ()
p2.close ()
```

Example 2: Plot Histogram over BinCentres for a Byte1d

```
vals = [0, 27, 25, 60, 62, 70, 71, 73, 74, 100, 120, 92, 85, 116]
d = Byte1d (vals)
p = PlotXY (d)
binsize = 5
print binsize
hist=Histogram(binsize)
bins=BinCentres(binsize)
p2=PlotXY(bins(d),hist(d))
style=p2.getStyle()
style.setChartType(Style.HISTOGRAM)
p.close ()
p2.close ()
```

Example 3: Plot Histogram over BinCentres for a Double5d

```
d = Double5d (5,4,3,2,1, 2.0)
d.set (4,3,2,1,0, 10.0)
d.set (3,3,2,1,0, 9.0)
d.set (2,3,2,1,0, 8.0)
```

Example 3: Plot Histogram over BinCentres for a Double5d

```
d.set (1,3,2,1,0, 7.0)
binsize = 1.0
hist = Histogram (binsize)
bins = BinCentres (binsize)
p=PlotXY(bins(d),hist(d))
style=p.getStyle()
style.setChartType(Style.HISTOGRAM)
p.close ()
```

API Summary

Jython Syntax
bin=BinCentres(1) <c>=bin(<x>)

Property
MANDATORY. **x INPUT** [any scalar array, MANDATORY, default=no default value]

API details

Property

MANDATORY. x INPUT [any scalar array, MANDATORY, default=no default value]

See also

- Histogram

2.33. Bool1d

Full Name:	herschel.ia.numeric.Bool1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Bool1d

Description

A rectangular numeric boolean array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.34. Bool2d

Full Name:	herschel.ia.numeric.Bool2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Bool2d

Description

A rectangular numeric boolean array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.35. Bool3d

Full Name:	herschel.ia.numeric.Bool3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Bool3d

Description

A rectangular numeric boolean array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.36. Bool4d

Full Name:	herschel.ia.numeric.Bool4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Bool4d

Description

A rectangular numeric boolean array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.37. Bool5d

Full Name:	herschel.ia.numeric.Bool5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Bool5d

Description

A rectangular numeric boolean array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.38. BoxCarFilter

Full Name:	herschel.ia.numeric.toolbox.filter.BoxCarFilter
Alias:	BoxCarFilter
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.filter import BoxCarFilter

Description

Creates a box car filter, that can be applied to numeric arrays of rank 1.

Example

Example 1: Apply BoxCarFilter on a Int1d

```
x=Int1d([1,3,2,4,6,5])
f=BoxCarFilter(2)
print f(x) # [0.5,2.0,2.5,3.0,5.0,5.5]
```

API Summary

Jython Syntax

```
<f>=BoxCarFilter(<width> [,<center>=true|false]
[,<edge>=Convolution.ZEROES|CIRCULAR|REPEAT])
<x>=<f>(<x>)
```

Properties

integer **width** [INPUT, MANDATORY, default=no default value]

boolean **center** [INPUT, NOT_MANDATORY, default=false]

Convolution.ZEROES|CIRCULAR|REPEAT **edge** [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]

API details

Properties

integer width [INPUT, MANDATORY, default=no default value]

It must be an integer value

boolean center [INPUT, NOT_MANDATORY, default=false]

Set center to true or false

Convolution.ZEROES|CIRCULAR|REPEAT edge [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]

Set edge to the following:

- edge=Convolution.ZEROES: Set result to zero at edges.
- edge=Convolution.CIRCULAR: Wrap around at edges (circular convolution).

Convolution.ZEROES|CIRCULAR|REPEAT edge [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]
• edge=Convolution.REPEAT: Repeat the edge values of input array.

See also

- Convolution
- GaussianFilter

2.39. BoxCarSmoothingTask

Full Name:	herschel.ia.toolbox.image.BoxCarSmoothingTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import BoxCarSmoothingTask

Description

A Task to smooth an image using a convolution with a box car.

A Task to smooth an image by convolving it with a box car function.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double width [INPUT, MANDATORY, default=Default value : Integer(3)]`
`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image before smoothing.

`Double width [INPUT, MANDATORY, default=Default value : Integer(3)]`

The width of the box car function.

`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

The image after smoothing.

2.40. Byte1d

Full Name:	herschel.ia.numeric.Byte1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Byte1d

Description

A rectangular numeric byte array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.41. Byte2d

Full Name:	herschel.ia.numeric.Byte2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Byte2d

Description

A rectangular numeric byte array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.42. Byte3d

Full Name:	herschel.ia.numeric.Byte3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Byte3d

Description

A rectangular numeric byte array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.43. Byte4d

Full Name:	herschel.ia.numeric.Byte4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Byte4d

Description

A rectangular numeric byte array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.44. Byte5d

Full Name:	herschel.ia.numeric.Byte5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Byte5d

Description

A rectangular numeric byte array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.45. CachedPool

Full Name:	herschel.ia.pal.pool.cache.CachedPool
Type:	Java Class -
Import:	from herschel.ia.pal.pool.cache import CachedPool

Description

Implementation of a PAL ProductPool that adds caching functionality to

a remote ProductPool.

Example

Example 1: # combining a cached remote pool with local pool

```
hsa=CachedPool( HsaReadPool() -)
local=LocalStoreFactory.getStore("local")
store=ProductStorage([local,hsa])
# load an observation by tag name
tag="OBS:S:00500019C0"
obs=store.load(tag).product
# modify and save new version into local pool
obs.creator="My funny Valentine"
ref=store.saveAs(obs,tag)
```

API Summary

Constructors
CachedPool(String remote) Creates an instance of a CachedPool that is wrapped around another
CachedPool(String remote, ProductPool delegated) Creates an instance of a CachedPool that is wrapped around another

API details

Constructors

CachedPool(String remote)

Creates an instance of a CachedPool that is wrapped around another

supplied ProductPool.

Argument

String **remote** [INPUT, MANDATORY, default=The name of the ProductPool]

this CachedPool should cache.

Return

CachedPool

An instance of the CachedPool.

CachedPool(String remote, ProductPool delegated)

Creates an instance of a CachedPool that is wrapped around another

supplied ProductPool.

Arguments

`String` **remote** `[INPUT, MANDATORY, default=The name of the ProductPool]`

this CachedPool should cache.

`ProductPool` **delegated** `[INPUT, MANDATORY]`

Return

CachedPool

An instance of the CachedPool.

2.46. CachePool

Full Name:	herschel.ia.pal.pool.cache.CachePool
Type:	Java Class -
Import:	from herschel.ia.pal.pool.cache import CachePool

Description

A ProductPool implementation that caches a remote pool. This pool is

useful in situations where performance is important, or that network bandwidth needs to be optimized. The cached data is stored in your local file system under the directory defined by: `${hcss.ia.pal.pool.cache.dir}/pal_cache`. By default: `${HOME}/.hcss/pal_cache` (UNIX), or `C:\Documents and Settings\<user>\.hcss\pal_cache` (Windows).

The identifier for the CachedPool (which you may need eg if you want to access that pool remotely) is the same ID as the pool which is being cached.

Example

Example 1: Create a CachedPool around a DbPool storage=ProductStorage()

```
storage.register(CachedPool(DbPool.getInstance()))
```

2.47. CEIL

Full Name:	herschel.ia.numeric.toolbox.basic.Ceiling
Alias:	CEIL
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Ceiling

Description

Gives the smallest integer greater than or equal to x.

Returns a float array for float input array and double array for any other numeric array type.

Example

Example 1: Apply CEIL on a Float1d

```
x=Float1d([0.1,0.5,0.9])
print CEIL(x) # [1.0,1.0,1.0] *
```

API Summary

Jython Syntax
<y>=CEIL(<x>)

Properties
any array of rank 1 **x** [INPUT, MANDATORY, default=no default value]
float or double array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of rank 1 x [INPUT, MANDATORY, default=no default value]

The input array can be an array of rank 1

float or double array y [OUTPUT, MANDATORY, default=no default value]

Returns a float array for float input array and double array for any other numeric array type.

See also

- FLOOR
- ROUND

2.48. ChannelMapPlotting

Full Name:	herschel.ia.gui.cube.ChannelMapPlotting
Type:	Java Class -
Import:	from herschel.ia.gui.cube import ChannelMapPlotting

Description

ChannelMapPlotting

A class to deal with ChannelMapPlotting.

API Summary

Constructor
ChannelMapPlotting(boolean useAsComponent, CubeSpectrumAnalysisToolbox toolbox) Constructor for ChannelMapPlotting. When the new ChannelMapPlotting is

Methods
int **getUsedContourValues**() Returns the used type of contour values for this ChannelMapPlotting
int **getUsedContourLevelRange**() Returns the used type of contour level range for this
String **getErrorMessage**() Returns a convenient error message for the given input. If no
ArrayList **getContourValues**() Returns a list with all contour values for this ChannelMapPlotting.
ArrayList **getContourColors**() Returns the colors that should be used for the contours of the
int **getNumberOfContourLevels**() Returns the number of contour levels for this ChannelMapPlotting if
double[] **getContourLevels**() Returns the used lower and upper contour value for this
double **getMinimumContourLength**() Returns the minimum length for contours to be drawn on the image.
String **getUsedDistribution**() Returns the type of distribution of the contour levels, that is
ArrayList **getImageFigures**() Returns all ImageFigures used for this ChannelMapPlotting.

API details

Constructor

ChannelMapPlotting(boolean useAsComponent, CubeSpectrumAnalysisToolbox toolbox)

Constructor for ChannelMapPlotting. When the new ChannelMapPlotting is

component-based, a window for contour plotting is opened; otherwise nothinng will be shown.

Arguments

`boolean` **`useAsComponent`** `[INPUT, MANDATORY]`

`CubeSpectrumAnalysisToolbox` **`toolbox`** `[INPUT, MANDATORY]`

Methods

int getUsedContourValues()

Returns the used type of contour values for this ChannelMapPlotting

(manual or automatic).

Return

int

Returns the used type of contour values for this ChannelMapPlotting (manual or automatic).

int getUsedContourLevelRange()

Returns the used type of contour level range for this

ChannelMapPlotting (manual or image cut levels).

Return

int

Returns the used type of contour level range for this ChannelMapPlotting (manual or image cut levels).

String getErrorMessage()

Returns a convenient error message for the given input. If no

errors occur in the input, null is returned.

Return

String

Returns a convenient error message for the given input. If no errors occur in the input, null is returned.

ArrayList getContourValues()

Returns a list with all contour values for this ChannelMapPlotting.

Return

ArrayList

ArrayList getContourValues()

Returs a list with all contour values for this ChannelMapPlotting.

ArrayList getContourColors()

Returns the colors that should be used for the contours of the

different contour values.

Return

ArrayList

Returns the colors that should be used for the contours of the different contour values.

int getNumberOfContourLevels()

Returns the number of contour levels for this ChannelMapPlotting if

the contour values are to be calculated automatically; otherwise -1 is returned.

Return

int

Returns the number of contour levels for this ChannelMapPlotting if the contour values are to be calculated automatically; otherwise -1 is returned.

double[] getContourLevels()

Returns the used lower and upper contour value for this

ChannelMapPlotting (manual or image cut levels).

Return

double[]

The used lower and upper contour value for this ChannelMapPlotting (manual or image cut levels).

double getMinimumContourLength()

Returns the minimum length for contours to be drawn on the image.

Return

double

Returns the minimum length for contours to be drawn on the image.

String getUsedDistribution()

Returns the type of distribution of the contour levels, that is

used for this ChannelMapPlotting (linear, log or ln).

Return

String

Returns the type of distribution of the contour levels, that is used for this ChannelMapPlotting (linear, log or ln).

ArrayList getImageFigures()

Returns all ImageFigures used for this ChannelMapPlotting.

Return

ArrayList

Returns all ImageFigures used for this ChannelMapPlotting.

2.49. CholeskyDecomposition

Full Name:	herschel.ia.numeric.toolbox.matrix.CholeskyDecomposition
Alias:	CholeskyDecomposition
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import CholeskyDecomposition

Example

Example 1: ##

```
#####   CholeskyDecomposition    #####
########################################
#
### HIPE ###
A=Double2d (\
    [\
       [3944.2141901709658, --39.83013886638742,
24.856149542676924, --49.90362121047403],\
       [-39.83013886638742, 3958.7850982903415, 39.244285251565444,
37.29778768650653],\
       [24.856149542676924, 39.244285251565444,
3952.2910884701473, --1.216735893731549],\
       [-49.90362121047403, 37.29778768650653, --1.216735893731549,
3950.7089115298527],\
    -])
B = Double2d (\
[\
   [1184.8157857233916],\
   [-360.85066234104187],\
   [-426.7929837904702],\
   [-179.95015720518913],\
])
CholeskyD = CholeskyDecomposition(A)
solution = B.apply(CholeskyD)
print solution
[
[0.29968672246274],
[-0.08666981085100102],
[-0.10902299389485229],
[-0.04097866183941969]
]
isSpd = CholeskyD.isSpd
print isSpd
1
triangularFactor = CholeskyD.l
print triangularFactor
[
[62.8029791504429,0.0,0.0,0.0],
[-0.6342077940438997,62.91568070651636,0.0,0.0],
[0.39577978431778954,0.6277495758130477,62.86286962351098,0.0],
[-0.7946059547737568,0.5848119575853922,-0.020192561781548726,62.84691798442629]
]
```

API Summary

Jython Syntax
`A=Double2d()`
`B=Double2d()`
`res=B.apply(CholeskyDecomposition(A))`

Jython Syntax

`CholeskyD = CholeskyDecomposition(A)`
`solution = B.apply(CholeskyD)`
`isSpd = CholeskyD.isSpd`
`triangularFactor = CholeskyD.l`

Property
`Double2d A [INPUT, MANDATORY, default=no default value]`

API details

Property

`Double2d A [INPUT, MANDATORY, default=no default value]`
Input must be a Double2d or Float2d array.

2.50. CircleHistogramExplorer

Full Name:	herschel.ia.gui.image.CircleHistogramExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import CircleHistogramExplorer

Description

An explorer for CircleHistogramProducts.

An explorer for CircleHistogramProducts.

API Summary

Constructors
`CircleHistogramExplorer()`
The construction of a new CircleHistogramExplorer.
`CircleHistogramExplorer(Object object)`
The construction of a new CircleHistogramExplorer associated with the given object.

Methods
`String` **`getName()`**
Returns the name.
`String` **`getDescription()`**
Returns the description.
`boolean` **`canHandle(Class className)`**
Checks whether this CircleHistogramExplorer can handle objects of the given class.
`setObject(Object object)`
Sets the object.
`CircleHistogramProduct` **`getObject()`**
Returns the object.
`Class` **`getVariableType()`**
Returns the expected variable type.
`JScrollPane` **`getParameterTable()`**
Returns the parameter table.

API details

Constructors

`CircleHistogramExplorer()`
The construction of a new CircleHistogramExplorer. The construction of a new CircleHistogramExplorer.

`CircleHistogramExplorer(Object object)`
The construction of a new CircleHistogramExplorer associated with the given object.

CircleHistogramExplorer(Object object)

The construction of a new CircleHistogramExplorer associated with the given object.

Argument

Object **object** [INPUT, MANDATORY]

Methods

String getName()

Returns the name.

Returns the name for this CircleHistogramExplorer.

Return

String

Returns the name for this CircleHistogramExplorer.

String getDescription()

Returns the description.

Returns the description for this CircleHistogramExplorer.

Return

String

Returns the description for this CircleHistogramExplorer.

boolean canHandle(Class className)

Checks whether this CircleHistogramExplorer can handle objects of the given class.

Returns true if this CircleHistogramExplorer can handle objects of the given class; false otherwise.

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true if this CircleHistogramExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this CircleHistogramExplorer to the given object.

Argument

Object **object** [INPUT, MANDATORY]

CircleHistogramProduct getObject()

Returns the object.

Returns the object for this CircleHistogramExplorer.

`CircleHistogramProduct getObject()`

Return

CircleHistogramProduct

Returns the object for this CircleHistogramExplorer.

`Class getVariableType()`

Returns the expected variable type.

Returns the expected variable type for this CircleHistogramExplorer.

Return

Class

Returns the expected variable type for this CircleHistogramExplorer.

`JScrollPane getParameterTable()`

Returns the parameter table.

Returns the parameter table for this CircleHistogramExplorer.

Return

JScrollPane

Returns the parameter table for this CircleHistogramExplorer

2.51. CircleHistogramPanel

Full Name:	herschel.ia.toolbox.image.gui.CircleHistogramPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import CircleHistogramPanel

Description

A panel for the CircleHistogramPanel.

A panel to serve as GUI for the CircleHistogramTask.

API Summary

Constructor
`CircleHistogramPanel()`
The construction of a new CircleHistogramPanel.

Methods
`drawFigure()`
Draws the circle on the image.
`updateFigure()`
Updates the circle.
`trigger()`
Triggers the execution of the associated task.
`updateHistogram()`
Updates the histogram.

API details

Constructor

`CircleHistogramPanel()`
The construction of a new CircleHistogramPanel. The construction of a new CircleHistogramPanel.

Methods

`drawFigure()`
Draws the circle on the image. Draws the circle on the image associated with this CircleHistogramPanel.

`updateFigure()`
Updates the circle. Updates the circle associated with this CircleHistogramPanel.

trigger()
Triggers the execution of the associated task. Triggers the execution of the task associated with this CircleHistogramPanel.

updateHistogram()
Updates the histogram. Updates the histogram associated with this CircleHistogramPanel.

2.52. CircleHistogramProduct

Full Name:	herschel.ia.dataset.image.CircleHistogramProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import CircleHistogramProduct

Description

A class to deal with the results of a circle histogram.

API Summary

Constructor
`CircleHistogramProduct()` The constructor of a new CircleHistogramProduct.

Methods
`setCenter``(double centerX, double centerY)` Sets the center for this CircleHistogramProduct
`setCenter``(double centerX, double centerY, String centerRA, String centerDec)` Sets the center for this CircleHistogramProduct
`setRadius``(double pixels)` Sets the radius for this CircleHistogramProduct
`setRadius``(double pixels, double arcsec)` Sets the radius for this ImageHistogramProduct
`Double1d` **`getCenterPixelCoordinates`**`()` Returns the center for this CircleHistogramProduct in
`String1d` **`getCenterSkyCoordinates`**`()` Returns the center for this CircleHistogramProduct in
`double` **`getRadiusPixels`**`()` Returns the radius for this CircleHistogramProduct in pixels.
`double` **`getRadiusArcsec`**`()` Returns the radius for this CircleHistogramProduct in arcsec.

API details

Constructor

`CircleHistogramProduct()`
The constructor of a new CircleHistogramProduct.

Methods

`setCenter(double centerX, double centerY)`
Sets the center for this CircleHistogramProduct

setCenter(double centerX, double centerY)

to the given pixel coordinates.

Arguments

double **centerX** [INPUT, MANDATORY]

double **centerY** [INPUT, MANDATORY]

setCenter(double centerX, double centerY, String centerRA, String centerDec)

Sets the center for this CircleHistogramProduct

to the given pixel and sky coordinates.

Arguments

double **centerX** [INPUT, MANDATORY]

double **centerY** [INPUT, MANDATORY]

String **centerRA** [INPUT, MANDATORY]

String **centerDec** [INPUT, MANDATORY]

setRadius(double pixels)

Sets the radius for this CircleHistogramProduct

to the given number of pixels.

Argument

double **pixels** [INPUT, MANDATORY]

setRadius(double pixels, double arcsec)

Sets the radius for this ImageHistogramProduct

to the given number of pixels and arcsec.

Arguments

double **pixels** [INPUT, MANDATORY]

double **arcsec** [INPUT, MANDATORY]

Double1d getCenterPixelCoordinates()

Returns the center for this CircleHistogramProduct in

pixel coordinates.

Return

Double1d

Returns the center for this CircleHistogramProduct in pixel coordinates.

String1d getCenterSkyCoordinates()

Returns the center for this CircleHistogramProduct in

sky coordinates.

Return

`String1d getCenterSkyCoordinates()`

String1d

Returns the center for this CircleHistogramProduct in sky coordinates.

`double getRadiusPixels()`

Returns the radius for this CircleHistogramProduct in pixels.

Return

double

Returns the radius for this CircleHistogramProduct in pixels.

`double getRadiusArcsec()`

Returns the radius for this CircleHistogramProduct in arcsec.

Return

double

Returns the radius for this CircleHistogramProduct in arcsec.

2.53. CircleHistogramTask

Full Name:	herschel.ia.toolbox.image.CircleHistogramTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import CircleHistogramTask

Description

A Task to make a histogram within a circle.

A Task to make a histogram of a region of interest, which is bounded by a circle.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **lowCut** [INPUT, OPTIONAL, default=Default value : NaN]
Double **highCut** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **bins** [INPUT, MANDATORY, default=Default value : new Integer(2000)]
Double **centerX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **centerY** [INPUT, OPTIONAL, default=Default value : NaN]
String **centerRA** [INPUT, OPTIONAL, default=Default value : "centerRA"]
String **centerDec** [INPUT, OPTIONAL, default=Default value : "centerDec"]
Double **radiusPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **radiusArcsec** [INPUT, OPTIONAL, default=Default value : NaN]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double lowCut [INPUT, OPTIONAL, default=Default value : NaN]

The lower cut level.

Double highCut [INPUT, OPTIONAL, default=Default value : NaN]

The upper cut level.

Integer bins [INPUT, MANDATORY, default=Default value : new Integer(2000)]

The number of bins.

Double centerX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the center of the circle.

Double centerY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the center of the circle.

String centerRA [INPUT, OPTIONAL, default=Default value : "centerRA"]

The right ascension of the center of the circle.

String centerDec [INPUT, OPTIONAL, default=Default value : "centerDec"]

The declination of the center of the circle.

Double radiusPixels [INPUT, OPTIONAL, default=Default value : NaN]

The radius of the circle in pixels.

Double radiusArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The radius of the circle in arcsec.

2.54. CircularIntegrationTask

Full Name:	herschel.ia.toolbox.image.CircularIntegrationTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import CircularIntegrationTask

Description

An abstract Task that deals with the integration of a circular region.

To do the integration of a circular region, this region is divided into : * the central pixel (in which the center of the circular region lies) * the rows and columns between two quadrants

2.55. clamp

Full Name:	herschel.ia.toolbox.image.ClampTask
Alias:	clamp
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ClampTask
Category:	task/image

Description

Clamping images and cubes.

The Clamp task for Images and Cubes. ClampTask is a task which restricts the range of pixel values for a source image by constraining the range of pixels to defined "low" and "high" values. The clamp algorithm sets all the pixels whose value is below "low" to "low" and sets all the pixels whose value is above "high" to "high". The "low" value must be less than or equal to the "high" value.

Example

Example 1: Clamping an image to lower value 11 and higher value 240

```
clamp(image = image, low = 11, high = 240)
```

API Summary

Jython Syntax

```
clamp(image, 11, 240)
```

Properties

`Image image [INPUT, MANDATORY, default=No default value]`
`double low [INPUT, OPTIONAL, default=No default value]`
`double high [INPUT, OPTIONAL, default=No default value]`
`Image clampedImage [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The Image to be clamped.

`double low [INPUT, OPTIONAL, default=No default value]`

The low clamp value.

`double high [INPUT, OPTIONAL, default=No default value]`

The high clamp value.

`Image clampedImage [OUTPUT, MANDATORY, default=No default value]`

The clamped image.

2.56. ClampTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ClampTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ClampTaskSignatureComponent

Description

The task dialog for the ClampTask.

A task dialog to serve as GUI for the ClampTask.

API Summary

Constructor
ClampTaskSignatureComponent() The construction of a new ClampTaskSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
getParameters() Returns a map of parameters and modifiers storing the value selected by the user.
setSignature(SignatureApi signature) Setting the signature.
setVariableSelection(VariableSelection selection) Setting the variable selection.
JLabel **newLabel**(String title, String tooltip) Returns a lable with the given title and tooltip.
JComponent **getComponent**() Returns the component.

API details

Constructor

ClampTaskSignatureComponent()
The construction of a new ClampTaskSignatureComponent. The construction of a new ClampTaskSignatureComponent.

Methods

check()
Validates the current modifications.

check()

Validates the current modifications for this ClampTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this ClampTaskSignatureComponent.

getParameters()

Returns a map of parameters and modifiers storing the value selected by the user.

Returns a map of parameters and modifiers storing the value selected by the user for this ClampTaskSignatureComponent.

setSignature(SignatureApi signature)

Setting the signature.

Sets the given signature as the signature for this ClampTaskSignatureComponent.

Argument

`SignatureApi` **`signature`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this ClampTaskSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

`JLabel` newLabel(`String` title, `String` tooltip)

Returns a lable with the given title and tooltip.

Returns a lable with the given title and tooltip.

Arguments

`String` **`title`** `[INPUT, MANDATORY]`

`String` **`tooltip`** `[INPUT, MANDATORY]`

Return

JLabel

Returns a lable with the given title and tooltip.

`JComponent` getComponent()

Returns the component.

Returns the component for this ClampTaskSignatureComponent.

Return

JComponent

Returns the component for this ClampTaskSignatureComponent.

2.57. clear

Full Name:	herschel.ia.task.example.InterruptableTask
Alias:	clear
Type:	Java Task -
Import:	from herschel.ia.task.example import InterruptableTask
Category:	developer

Description

Demonstrate the use of the Ctr-s on top a task

Capture Ctrl-s events and provides a recovery action

Examples

Example 1: run the task

```
interruptable()
```

Example 2: run the task with 1000 iteration

```
interruptable(1000)
```

API Summary

Jython Syntax

```
clear("variableName") <br>
clear("variableA,variableB") <br>
clear(all=True)
```

Property

```
Integer iterations [INPUT, NO, default=10000]
```

Limitations

The current implementation allows deleting of packages and class, no pre-filter is performed

Miscellaneous

No miscellaneous

API details

Property

`Integer iterations [INPUT, NO, default=10000]`

The number of iterations to be performed

See also

- references

History

- `2004-07-13 - NdC`: first release.

2.58. clear

Full Name:	herschel.ia.toolbox.util.ClearTask
Alias:	clear
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import ClearTask
Category:	task

Description

Clear variables from the jython session.

The clear task is used to clear a variable from the jython session and reclaim the allocated memory. The task allows also for clearing every variable with the execption of reserved names. When used as in the following "Clear(all=True)" deletes all parameters made by the user - including those from user set up files

Examples

Example 1: clear a single variable

```
clear("variableName")
```

Example 2: clear a list of variables

```
clear("variableA, variableB, -...")
```

Example 3: clear all variables created by the user - including those from user set up files

```
clear(all=True)
```

API Summary

Jython Syntax
`clear("variableName")`
`clear("variableA,variableB")`
`clear(all=True)`

Properties
`String variable [INPUT, No, default=NO default value]`
`Boolean all [INPUT, NO, default=False]`

Limitations

The current implementation allows deleting of packages and class, no pre-filter is performed

Miscellaneous

No miscellaneous

API details

Properties

String variable [INPUT, No, default=NO default value]
The name of the variable to erase or a list (comma separated) of variables

Boolean all [INPUT, NO, default=False]
The all option for erasing every variable

History

- 2004-07-13 - NdC: first release

2.59. Complex1d

Full Name:	herschel.ia.numeric.Complex1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Complex1d

Description

A rectangular numeric Complex array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.60. Complex2d

Full Name:	herschel.ia.numeric.Complex2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Complex2d

Description

A rectangular numeric Complex array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.61. Complex3d

Full Name:	herschel.ia.numeric.Complex3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Complex3d

Description

A rectangular numeric Complex array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.62. Complex4d

Full Name:	herschel.ia.numeric.Complex4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Complex4d

Description

A rectangular numeric Complex array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.63. Complex5d

Full Name:	herschel.ia.numeric.Complex5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Complex5d

Description

A rectangular numeric Complex array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.64. CONCATENATE

Full Name:	herschel.ia.numeric.toolbox.basic.Concatenate
Alias:	CONCATENATE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Concatenate

Description

Concatenates an array of rank > 1 into an array rank 1 of the same type.

The elements are concatenated starting from the highest dimension.

Example

Example 1: Apply ABS on a Int1d

```
x=Double2d([ [1,2,3,4],[5,6,7,8] -])
print CONCATENATE(x) # [1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0]
x=Int3d([ [ [1,2],[3,4] -], [ [5,6],[7,8] -], [ [9,10],[11,12] -] -])
print CONCATENATE(x) # [1,2,3,4,5,6,7,8,9,10,11,12]
```

API Summary

Jython Syntax

```
<y>=CONCATENATE(<x>)
```

Properties

any array type **x** [INPUT, MANDATORY, default=no default value]

an array of any type **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array type x [INPUT, MANDATORY, default=no default value]

The input must be an array of rank > 1

an array of any type y [OUTPUT, MANDATORY, default=no default value]

The result is an array of rank 1 .

See also

- RESHAPE

2.65. Condense

Full Name:	herschel.ia.numeric.toolbox.basic.Condense
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Condense

Description

Condense array x along dimension d applying function f using a truncation size.

This function obtains an array where each item is the result of applying a function (ie: SUM, COS, etc.) to the original array to the specified dimension. The 'chunkSize' argument specifies how many items are used for each item of the returned array.

Condense modes (see 'mode' parameter):

-Default mode : Condense array x along dimension d applying function f using a truncation size

-Boxcar mode : Run a boxcar window of a certain size over the data array

Condense works like any ArrayToNumber or ArrayReductor over a dimension (ie: SUM(array,along_dim_d)) but you can split the original array into chunks. You will obtain an array with the number of chunks that you have specified (the number of items of the returned array is truncated if it is required, see example). Nevertheless, if you use 'boxcar' mode, chunks are created based on the current position for each item of the returned array (see 'mode' parameter and the example).

Example

Example 1: Untitled

```
IA>>x=RESHAPE(Int1d.range(4*2),[4,2])
IA>>print x
  [
   [0,1],
   [2,3],
   [4,5],
   [6,7]
  -]
IA>>print Condense(0,1,SUM)(x) #mode = Default
  java.lang.IllegalArgumentException: Chunk need to be bigger then 1 -!
IA>>print Condense(0,2,SUM)(x) #mode = Default
  [
   [2,4],
   [10,12]
  -]
  #Get chunks of two items along dimension 0:
  #First chunk: SUM(Int2d([[0,1],[2,3]]),0) = [2,4]
  #Second chunk: SUM(Int2d([[4,5],[6,7]]),0) = [10,12]
IA>>print Condense(0,3,SUM)(x) #mode = Default
  [
   [6,9]
  -]
  #Get chunks of three items along dimension 0:
  #First chunk: SUM(Int2d([[0,1],[2,3],[4,5]]),0) = [6,9]
  #Second chunk: [6,7] skipped
IA>>print Condense(0,4,SUM)(x) #mode = Default
  [
   [12,16]
  -]
  #Get chunks of four items along dimension 0:
  #First chunk: SUM(Int2d([[0,1],[2,3],[4,5],[6,7]]),0) = [12,16]
```

Example 1: Untitled

```
IA>>print Condense(0,2,SUM,"boxcar")(x)
  [
   [2,4],
   [6,8],
   [10,12],
   [6,7]
  -]
  #Get chunks of two items along dimension 0 => one item after current
position:
  #First   chunk: SUM(Int2d([[0,1],[2,3]]),0) = [2,4]
  #Second  chunk: SUM(Int2d([[2,3],[4,5]]),0) = [6,8]
  #Third   chunk: SUM(Int2d([[4,5],[6,7]]),0) = [10,12]
  #Fourth  chunk: SUM(Int2d([[6,7]]),0) = [10,12]
IA>>print Condense(0,3,SUM,'boxcar')(Int2d([[0,1],[2,3],[4,5],[6,7],[8,9],
[10,11],[12,13]]))
  [
   [2,4],
   [6,9],
   [12,15],
   [18,21],
   [24,27],
   [30,33],
   [22,24]
  -]
  #Get chunks of three items along dimension 0 => one item before current
position, one item
  #after current position:
  #First   chunk: SUM (Int2d([[0,1],[2,3]]),0)            = [2,4]
  #Second  chunk: SUM (Int2d([[0,1],[2,3],[4,5]]),0)      = [6,9]
  #Third   chunk: SUM (Int2d([[2,3],[4,5],[6,7]]),0)      = [12,15]
  #Fourth  chunk: SUM (Int2d([[4,5],[6,7],[8,9]]),0)      = [18,21]
  #Fifth   chunk: SUM (Int2d([[6,7],[8,9],[10,11]]),0)    = [24,27]
  #Sixth   chunk: SUM (Int2d([[8,9],[10,11],[12,13]]),0)  = [30,33]
  #Seventh chunk: SUM (Int2d([[10,11],[12,13]]),0)        = [22,24]
IA>>print Condense(0,4,SUM,'boxcar')(Int2d([[0,1],[2,3],[4,5],[6,7],[8,9],
[10,11],[12,13]]))
  [
   [6,9],
   [12,16],
   [20,24],
   [28,32],
   [36,40],
   [18,20],
   [22,24]
  -]
  #Get chunks of four items along dimension 0 => one item before current
position, two items
  #after current position:
  #First   chunk: SUM (Int2d([[0,1],[2,3],[4,5]]),0)           = [6,9]
  #Second  chunk: SUM (Int2d([[0,1],[2,3],[4,5],[6,7]]),0)     = [12,16]
  #Third   chunk: SUM (Int2d([[2,3],[4,5],[6,7],[8,9]]),0)     = [20,24]
  #Fourth  chunk: SUM (Int2d([[4,5],[6,7],[8,9],[10,11]]),0)   = [28,32]
  #Fifth   chunk: SUM (Int2d([[6,7],[8,9],[10,11],[12,13]]),0) = [36,40]
  #Sixth   chunk: SUM (Int2d([[8,9],[10,11]]),0)               = [18,20]
  #Seventh chunk: SUM (Int2d([[10,11],[12,13]]),0)             = [22,24]
</pre>
```

API Summary

Jython Syntax

```
outArray = Condense ( alongDimension, chunkSize, function [,mode])
(inArray)
```

Properties

float or double array **inArray** [INPUT, MANDATORY, default=p]

Properties
integer **alongDimension** [INPUT, MANDATORY, default=p]
int **chunkSize** [INPUT, MANDATORY, default=p]
ArrayReductor|ArrayToNumber **function** [INPUT, MANDATORY, default=p]
OPTIONAL **mode** [INPUT, default = false, default=no default value]
float or double array **outArray** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

float or double array inArray [INPUT, MANDATORY, default=p]

Input array of n dimensions

integer alongDimension [INPUT, MANDATORY, default=p]

Dimension in which the function will be applied (starting on zero)

int chunkSize [INPUT, MANDATORY, default=p]

Size of chunks to process. See boxcar parameter.

ArrayReductor|ArrayToNumber function [INPUT, MANDATORY, default=p]

Function to apply

OPTIONAL mode [INPUT, default = false, default=no default value]

Selection of special mode. Currently "default" or "boxcar"

If this argument is specified, the mode is set to "boxcar" (it does not matter the string you write). If this argument is not specified, the mode is set to "default".

- "default": the array is splitted into arrays of the size specified by 'chunkSize' (along the specified dimension). The remaining items (that cannot fit in a chunk) are ignored. 'chunkSize' 1 is not allowed.
- "boxcar" : chunks are created using a "box" centered in the current item. The process goes item by item along the specified dimension:
  - 'chunkSize' = 1: not allowed.
  - 'chunkSize' < 1:
    - Odd 'chunkSize': chunk is compound of the item in the current position, (chunkSize/2) item(s) before the current position and (chunkSize/2) item(s) after the current position. (Division is integer division)
    - Even 'chunkSize': chunk is compound of the item in the current position, ((chunkSize/2)-1) item(s) before the current position and (chunkSize/2) item(s) after the current position. (Division is integer division)

  Example: 'chunkSize' = 3: (along the specified dimension) one item before current position, the current item and another item before current position. 'chunkSize' = 4: one item before current position, the current item and two items after current position.

OPTIONAL mode [INPUT, default = false, default=no default value]

(See examples.)

float or double array outArray [OUTPUT, MANDATORY, default=no default value]

Return an array where the function 'function' was applied on data chunks 'chunkSize' in dimension 'alongDimension'

The center of the box is always the actual index. in case of an "even" box the value before the theorhetical center (see boxcar parameter)

2.66. ConnectorBox

Full Name:	herschel.ia.dataflow.ConnectorBox
Type:	Java Class -
Import:	from herschel.ia.dataflow import ConnectorBox

Description

Non-process components as processes.

This class allows non-process components to be managed by dataflow as they were processes. The non-process component will have a ConnectorBox as member variable and the developer can call create* methods. The non-process component must implement Connectable interface and in its getProcess() method will return the connector box.

Example

Example 1: how to create a ConnectorBox

```
<pre>
public class MyComponent extends JFrame implement Connectable,
ProcessInputListener {
  private ConnectorBox _conn_box;
  -// implementation of Connectable getProcess method
  public IaProcess getProcess() { return _conn_box; -}
  public MyComponent( String name_as_component, String name_as_process -) {
      super(name_as_component);
      _conn_box = new ConnectorBox( name_as_process -);
      ProcessInput input = _conn_box.createInput( -"input", Product.class -);
      input.addProcessInputListener( this -);
  -}
  -// implementation of ProcessInputListener handle method
  public void handle( ProcessInputEvent ev -) {
    -// do stuff with the product that comes inside ev.
  -}
}
</pre>
```

Limitations

no limitation

See also

- reference

History

- 26-5-2005 jcg: change javadoc format for help support.

2.67. Contour

Full Name:	herschel.ia.dataset.image.Contour
Type:	Java Class -
Import:	from herschel.ia.dataset.image import Contour

Description

A class to deal with Contours.

API Summary

Constructor
Contour(Double2d contourPoints) This constructor for Contour creates a new Contour and sets the

Methods
int **getNbOfContourPoints**() Returns the number of contour points for this Contour.
convert(Wcs wcsOld, Wcs wcsNew) Converts the pixel coordinates of the contour points of this

API details

Constructor

Contour(Double2d contourPoints)

This constructor for Contour creates a new Contour and sets the

data (contour points) for the new Contour to the given data (contour points).

Argument

Double2d **contourPoints** [INPUT, MANDATORY]

Methods

int getNbOfContourPoints()

Returns the number of contour points for this Contour.

Return

int

Returns the number of contour points for this Contour.

convert(Wcs wcsOld, Wcs wcsNew)

Converts the pixel coordinates of the contour points of this

Contour from one Wcs to pixel coordinates to pixel coordinates in another Wcs.

Arguments

convert(Wcs wcsOld, Wcs wcsNew)

Wcs **wcsOld** [INPUT, MANDATORY]

Wcs **wcsNew** [INPUT, MANDATORY]

2.68. ContourLevel

Full Name:	herschel.ia.dataset.image.ContourLevel
Type:	Java Class -
Import:	from herschel.ia.dataset.image import ContourLevel

Description

A class to deal with ContourLevels.

API Summary

Constructor
`ContourLevel(double contourValue)`
This constructor creates a new ContourLevel for the given contour

Method
`addContour(Contour contour)`
Adds the given Contour to this ContourLevel.

API details

Constructor

`ContourLevel(double contourValue)`

This constructor creates a new ContourLevel for the given contour

value.

Argument

`double` **`contourValue`** `[INPUT, MANDATORY]`

Method

`addContour(Contour contour)`

Adds the given Contour to this ContourLevel.

Argument

`Contour` **`contour`** `[INPUT, MANDATORY]`

2.69. ContourPlotting

Full Name:	herschel.ia.toolbox.image.gui.ContourPlotting
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ContourPlotting

Description

An implementation of contour plotting.

API Summary

Constructors
ContourPlotting(ImageAnalysisToolbox toolbox) The standard constructor for ContourPlotting. This constructor creates a window
ContourPlotting(boolean useAsComponent, ImageAnalysisToolbox toolbox) Constructor for ContourPlotting. When the new ContourPlotting is

Methods
int **getUsedContourValues**() Returns the used type of contour values for this ContourPlotting
int **getUsedContourLevelRange**() Returns the used type of contour level range for this
String **getErrorMessage**() Returns an appropriate error message for the given input. If no
ArrayList **getContourValues**() Returns a list with all contour values for this ContourPlotting.
ArrayList **getContourColors**() Returns the colors that should be used for the contours of the
int **getNumberOfContourLevels**() Returns the number of contour levels for this ContourPlotting if
double[] **getContourLevels**() Returns the used lower and upper contour value for this
double **getMinimumContourLength**() Returns the minimum length for contours to be drawn on the image.
String **getUsedDistribution**() Returns the type of distribution of the contour levels, that is
ArrayList **getImageFigures**() Returns all ImageFigures used for this ContourPlotting.

API details

Constructors

ContourPlotting(ImageAnalysisToolbox toolbox)

The standard constructor for ContourPlotting. This constructor creates a window

in which you must give the input parameters, needed to perform contour plotting on the image, analyzed with the given ImageAnalysisToolbox.

Argument

ImageAnalysisToolbox **toolbox** [INPUT, MANDATORY]

ContourPlotting(boolean useAsComponent, ImageAnalysisToolbox toolbox)

Constructor for ContourPlotting. When the new ContourPlotting is

component-based, a window for contour plotting is opened; otherwise nothing will be shown.

Arguments

boolean **useAsComponent** [INPUT, MANDATORY]

ImageAnalysisToolbox **toolbox** [INPUT, MANDATORY]

Methods

int getUsedContourValues()

Returns the used type of contour values for this ContourPlotting

(manual or automatic).

Return

int

Returns the used type of contour values for this ContourPlotting (manual or automatic).

int getUsedContourLevelRange()

Returns the used type of contour level range for this

ContourPlotting (manual or image cut levels).

Return

int

Returns the used type of contour level range for this ContourPlotting (manual or image cut levels).

String getErrorMessage()

Returns an appropriate error message for the given input. If no

errors occur in the input, null is returned.

Return

String

String getErrorMessage()

Returns an appropriate error message for the given input. If no errors occur in the input, null is returned.

ArrayList getContourValues()

Returns a list with all contour values for this ContourPlotting.

Return

ArrayList

Returs a list with all contour values for this ContourPlotting.

ArrayList getContourColors()

Returns the colors that should be used for the contours of the

different contour values.

Return

ArrayList

Returns the colors that should be used for the contours of the different contour values.

int getNumberOfContourLevels()

Returns the number of contour levels for this ContourPlotting if

the contour values are to be calculated automatically; otherwise -1 is returned.

Return

int

Returns the number of contour levels for this ContourPlotting if the contour values are to be calculated automatically; otherwise -1 is returned.

double[] getContourLevels()

Returns the used lower and upper contour value for this

ContourPlotting (manual or image cut levels).

Return

double[]

The used lower and upper contour value for this ContourPlotting (manual or image cut levels).

double getMinimumContourLength()

Returns the minimum length for contours to be drawn on the image.

Return

double

Returns the minimum length for contours to be drawn on the image.

String getUsedDistribution()

Returns the type of distribution of the contour levels, that is

String getUsedDistribution()

used for this ContourPlotting (linear, log or ln).

Return

String

Returns the type of distribution of the contour levels, that is used for this ContourPlotting (linear, log or ln).

ArrayList getImageFigures()

Returns all ImageFigures used for this ContourPlotting.

Return

ArrayList

Returns all ImageFigures used for this ContourPlotting.

2.70. ContourTask

Full Name:	herschel.ia.toolbox.image.ContourTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ContourTask

Description

A Task for making contours for a given contour value.

A Task for making contours for a given contour value and that is called withing AutomaticContourTask and ManualContourTask.

API Summary

Properties
`Image` **`image`** `[INPUT, MANDATORY, default=No default value]`
`Double` **`value`** `[INPUT, MANDATORY, default=No default value]`
`ImageContour` **`contours`** `[OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image.

`Double value [INPUT, MANDATORY, default=No default value]`

The contour value.

`ImageContour contours [OUTPUT, MANDATORY, default=No default value]`

The image contour.

2.71. Convolution

Full Name:	herschel.ia.numeric.toolbox.filter.Convolution
Alias:	Convolution
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.filter import Convolution

Description

Creates a Convolution filter, that can be applied to numeric arrays of rank 1.

Example

Example 1: Apply Convolution on a Int1d

```
x=Int1d([1,3,2,4,6,5])
f=Convolution( Double1d([1,3,2]) -)
print f(x) # [1.0,6.0,13.0,16.0,22.0,31.0]
```

API Summary

Jython Syntax

```
<f>=Convolution(<kernel> [,<center>=true|false]
[,<edge>=Convolution.ZEROES|CIRCULAR|REPEAT])
<x>=<f>(<x>)
```

Properties

Double1d **kernel** [INPUT, MANDATORY, default=no default value]

boolean **center** [INPUT, NOT_MANDATORY, default=false]

Convolution.ZEROES|CIRCULAR|REPEAT **center** [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]

API details

Properties

Double1d kernel [INPUT, MANDATORY, default=no default value]

It must be a Double1d array, when =true, the kernel should have an odd number of elements.

boolean center [INPUT, NOT_MANDATORY, default=false]

Set center to true or false.

Convolution.ZEROES|CIRCULAR|REPEAT center [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]

Set edge to true or false

- edge=Convolution.ZEROES: Set result to zero at edges.
- edge=Convolution.CIRCULAR: Wrap around at edges (circular convolution).

Convolution.ZEROES|CIRCULAR|REPEAT center [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]
• edge=Convolution.REPEAT: Repeat the edge values of input array.

See also

- BoxCarFilter
- GaussianFilter

History

- 23 Apr 2008 AS Modify default for center parameter; default is center=True.

2.72. Correlate

Full Name:	herschel.ia.numeric.toolbox.basic.Correlate
Alias:	Correlate
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Correlate

Description

Yields the linear Pearson correlation coefficient of the input arrays.

If one vector is longer than the other, only the values up to the length of the shortest vector will be taken into account.

Example

Example 1: Correlation of two vectors of long

```
x = Long1d([65, 63, 67, 64, 68, 62, 70, 66, 68, 67, 69, 71])
y = Long1d([68, 66, 68, 65, 69, 66, 68, 65, 71, 67, 68, 70])
print Correlate(x)(y) # 0.7026516450800809
```

API Summary

Jython Syntax

```
<r>=Correlate(<x>)(<y>)
```

Properties

any ordered 1d array **x** [INPUT, MANDATORY, default=no default value]

any ordered 1d array **y** [INPUT, MANDATORY, default=no default value]

double **r** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any ordered 1d array x [INPUT, MANDATORY, default=no default value]

May be an integral or floating-point array; the former implicitly transformed to a double array.

any ordered 1d array y [INPUT, MANDATORY, default=no default value]

May be an integral or floating-point array; the former implicitly transformed to a double array.

double r [OUTPUT, MANDATORY, default=no default value]

Returns the linear Pearson correlation coefficient of the input arrays.

See also

- CorrelateMatrix

2.73. CorrelateMatrix

Full Name:	herschel.ia.numeric.toolbox.basic.CorrelateMatrix
Alias:	CorrelateMatrix
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import CorrelateMatrix

Description

Yields the linear Pearson correlation coefficients of the input M x N matrix.

The result is a N x N matrix with each i, j value equal to the correlation coefficient of the i and j columns of the original matrix.

Example

Example 1: Apply Correlation of a matrix of integers

```
m = Int2d([ [65, 67], [64, 68], [67, 71] -])
print CorrelateMatrix()(m)
# [ [1.0, 0.8386278693775344], [0.8386278693775344, 1.0] -]
```

API Summary

Jython Syntax
`<r>=CorrelateMatrix()(<m>)`

Properties
`any ordered 2d array (M rows x N columns) m [INPUT, MANDATORY, default=no default value]`
`Double2d r [OUTPUT, MANDATORY, default=no default value]`

API details

Properties

`any ordered 2d array (M rows x N columns) m [INPUT, MANDATORY, default=no default value]`

May be an integral or floating-point array; the former implicitly transformed to a double array.

`Double2d r [OUTPUT, MANDATORY, default=no default value]`

Returns the N x N matrix with the linear Pearson correlation coefficients of the input matrix.

See also

- Correlate

2.74. COS

Full Name:	herschel.ia.numeric.toolbox.basic.Cos
Alias:	COS
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Cos

Description

Computes the trigonometric cosine of an number or array

Gives the cosine of a number or array. The input is in radians, and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

Example

Example 1: Apply COS on a Float1d

```
x=Float1d([0,0.5])
print  COS(x) # [1.0,0.87758255]
```

API Summary

Jython Syntax
`<y>=COS(<x>)`

Properties
`any type x [INPUT, MANDATORY, default=no default value]`
`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`

API details

Properties

`any type x [INPUT, MANDATORY, default=no default value]`

The input is in radians, and may be of any type.

`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`

Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

See also

- ARCCOS
- COSH
- SIN
- TAN

2.75. COSH

Full Name:	herschel.ia.numeric.toolbox.basic.CosH
Alias:	COSH
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import CosH

Description

Computes the trigonometric hyperbolic cosine of an number or array

Gives the hyperbolic cosine of a number or array. The input is in radians, and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

API Summary

Jython Syntax
`<y>=COSH(<x>)`

Properties
`any type x [INPUT, MANDATORY, default=no default value]`
`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`

Miscellaneous

Does not work for complex values.

API details

Properties

`any type x [INPUT, MANDATORY, default=no default value]`
The input is in radians, and may be of any type.

`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`
Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

See also

- COS
- ARCCOS

2.76. CreateRgbImageTask

Full Name:	herschel.ia.toolbox.image.CreateRgbImageTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import CreateRgbImageTask

Description

A Task to combine three images to an RGB image.

A Task to combine three images of the same region on the sky, but in different filters, to an RGB image.

API Summary

Properties
Image **red** [INPUT, MANDATORY, default=No default value]
Image **green** [INPUT, MANDATORY, default=No default value]
Image **blue** [INPUT, MANDATORY, default=No default value]
Double **percent** [INPUT, MANDATORY, default=Default value : 98.0]
Double **lowRed** [INPUT, OPTIONAL, default=No default value]
Double **highRed** [INPUT, OPTIONAL, default=No default value]
Double **lowGreen** [INPUT, OPTIONAL, default=No default value]
Double **highGreen** [INPUT, OPTIONAL, default=No default value]
Double **lowBlue** [INPUT, OPTIONAL, default=No default value]
Double **highBlue** [INPUT, OPTIONAL, default=No default value]
RgbSimpleImage **rgb** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image red [INPUT, MANDATORY, default=No default value]

The red input image.

Image green [INPUT, MANDATORY, default=No default value]

The green input image.

Image blue [INPUT, MANDATORY, default=No default value]

The blue input image.

Double percent [INPUT, MANDATORY, default=Default value : 98.0]

The percentage of values to include.

Double lowRed [INPUT, OPTIONAL, default=No default value]

The low cut level for the red image.

Double highRed [INPUT, OPTIONAL, default=No default value]

The high cut level for the red image.

Double lowGreen [INPUT, OPTIONAL, default=No default value]

The low cut level for the green image.

Double highGreen [INPUT, OPTIONAL, default=No default value]

The high cut level for the green image.

Double lowBlue [INPUT, OPTIONAL, default=No default value]

The low cut level for the blue image.

Double highBlue [INPUT, OPTIONAL, default=No default value]

The high cut level for the blue image.

RgbSimpleImage rgb [OUTPUT, MANDATORY, default=No default value]

The output RGB image.

2.77. CreateRgbImageTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.CreateRgbImageTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import CreateRgbImageTaskSignatureComponent

Description

The task dialog for the CreateRgbImageTask.

A task dialog to serve as GUI for the CreateRgbImageTask.

API Summary

Constructor
`CreateRgbImageTaskSignatureComponent()` The construction of a new CreateRgbImageTaskSignatureComponent.

Methods
`check()` Validates the current modifications.
`clear()` Clears the current modifications.
`Map` **`getParameters()`** Returns a map of parameters and modifiers storing the value selected by the user.
`setSignature``(SignatureApi signature)` Setting the signature.
`setVariableSelection``(VariableSelection selection)` Setting the variable selection.
`getComponent()` Returns the component.

API details

Constructor

`CreateRgbImageTaskSignatureComponent()`
The construction of a new CreateRgbImageTaskSignatureComponent. The construction of a new CreateRgbImageTaskSignatureComponent.

Methods

`check()`
Validates the current modifications.

check()

Validates the current modifications for this CreateRgbImageTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the curent modifications for this CreateRgbImageTaskSignatureComponent.

Map getParameters()

Returns a map of parameters and modifiers storing the value selected by the user.

Returns a map of parameters and modifiers storing the value selected by the user for this CreateRgbImageTaskSignatureComponent.

Return

Map

Returns a map of parameters and modifiers storing the value selected by the user for this CreateRgbImageTaskSignatureComponent.

setSignature(SignatureApi signature)

Setting the signature.

Sets the given signature as the signature for this CreateRgbImageTaskSignatureComponent.

Argument

`SignatureApi` **`signature`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this CreateRgbImageTaskSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

getComponent()

Returns the component.

Returns the component for this CreateRgbImageTaskSignatureComponent.

2.78. crop

Full Name:	herschel.ia.toolbox.image.CropTask
Alias:	crop
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import CropTask
Category:	task/image

Description

A Task to crop images and cubes.

A Task to crop images and cubes to a specified rectangular area. The upper left pixel and the lower right pixel should be given.

Example

Example 1: Cropping an image between x-coordinate 11 and 240, and between y-coordinates 240 and 300

```
crop(image = image, x1 = 11, x2 = 55, y1 = 240, y2 = 300)
```

API Summary

Jython Syntax

```
crop(image, 11, 240, 55, 300)
```

Properties

```
Image image [INPUT, MANDATORY, default=No default value]
int row1 [INPUT, MANDATORY, default=No default value]
int column1 [INPUT, MANDATORY, default=No default value]
int row2 [INPUT, OPTIONAL, default=No default value]
int column2 [INPUT, MANDATORY, default=No default value]
```

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The Image to be cropped

int row1 [INPUT, MANDATORY, default=No default value]

The x coordinate of the left upper pixel of the rectangle to crop

int column1 [INPUT, MANDATORY, default=No default value]

The y coordinate of the left upper pixel of the rectangle to crop

int row2 [INPUT, OPTIONAL, default=No default value]

The x coordinate of the lower right pixel of the rectangle to crop

int column2 [INPUT, MANDATORY, default=No default value]
The y coordinate of the lower right pixel of the rectangle to crop

2.79. CrossCorrelationTask

Full Name:	herschel.ia.toolbox.image.CrossCorrelationTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import CrossCorrelationTask

Description

A Task to calculate the linear Pearson correlation coefficient of two images.

A Task to calculate the linear Pearson correlation coefficient of two images. We start from a M x N image (M = number of rows, N = number of columns) and calculate the N x N linear Pearson coeffient matrix . The i'th row and j'th column element corresponds to the correlation of the i'th and j'th columns of the M x N matrix.

API Summary

Properties
`Image image1 [INPUT, MANDATORY, default=No default value]`
`Image image2 [INPUT, MANDATORY, default=No default value]`
`paramType correlation [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image1 [INPUT, MANDATORY, default=No default value]`

The first image.

`Image image2 [INPUT, MANDATORY, default=No default value]`

The second image.

`paramType correlation [OUTPUT, MANDATORY, default=No default value]`

The correlation.

2.80. CubeCompareDisplay

Full Name:	herschel.ia.gui.cube.CubeCompareDisplay
Type:	Java Class -
Import:	from herschel.ia.gui.cube import CubeCompareDisplay

Description

A class to compare visually 2 spectralcubes when they shere a same sky location

API Summary

Methods
setBegin(Double begin) Sets the begin of the straight line, associated with this
setEnd(Double end) Sets the end of the straight line, associated with this
ImageFigure **getLine**() Returns the straight line (ImageFigure), of which we wish to plot
Double **getBegin**() Returns the begin of the drawn line in PixelCoordinates.
Double **getEnd**() Returns the end of the drawn line in PixelCoordinates.
String **getSkyCoordinates**() Returns the String version of the sky coordinates
boolean **isInImage**(MouseEvent e) Checks whether the given MouseEvent has occured within the image
boolean **isInImage**(double pixX, double pixY) Checks whether the point with given PixelCoordinates (pixX, pixY)

API details

Methods

setBegin(Double begin)

Sets the begin of the straight line, associated with this

Velocity position map to the given point (in UserCoordinates).

Argument

Double **begin** [INPUT, MANDATORY]

setEnd(Double end)

Sets the end of the straight line, associated with this

Velocity position map to the given point (in UserCoordinates).

Argument

setEnd(Double end)

Double **end** [INPUT, MANDATORY]

ImageFigure getLine()

Returns the straight line (ImageFigure), of which we wish to plot

the intensity in this CubeCompareDisplay.

Return

ImageFigure

The straight line (ImageFigure), of which we wish to plot the intensity in this CubeCompareDisplay.

Double getBegin()

Returns the begin of the drawn line in PixelCoordinates.

Return

Double

Returns the begin of the drawn line in PixelCoordinates.

Double getEnd()

Returns the end of the drawn line in PixelCoordinates.

Return

Double

Returns the end of the drawn line in PixelCoordinates.

String getSkyCoordinates()

Returns the String version of the sky coordinates

(WorldCoordinates) of the begin and end of the drawn straight line.

Return

String

Returns the String version of the sky coordinates (WorldCoordinates) of the begin and end of the drawn straight line.

boolean isInImage(MouseEvent e)

Checks whether the given MouseEvent has occured within the image

we are analysing with this CubeSpectrumAnalysisToolbox.

Argument

MouseEvent **e** [INPUT, MANDATORY]

Return

boolean

Returns true if the given MouseEvent has occured within the image that is being analysed with this CubeSpectrumAnalysisToolbox; false otherwise.

boolean isInImage(double pixX, double pixY)

Checks whether the point with given PixelCoordinates (pixX, pixY)

lies in the image we are analysing with this CubeSpectrumAnalysisToolbox.

Arguments

double **pixX** [INPUT, MANDATORY]

double **pixY** [INPUT, MANDATORY]

Return

boolean

Returns true if the point with given PixelCoordinates (pixX, pixY) lies in the image we are analysing with this CubeSpectrumAnalysisToolbox; false otherwise.

2.81. CubeSpectrumAnalysis

Full Name:	herschel.ia.gui.cube.CubeSpectrumAnalysis
Type:	Java Class -
Import:	from herschel.ia.gui.cube import CubeSpectrumAnalysis

Description

CubeSpectrumAnalysis

A class for dealing with CubeSpectrumAnalysis (in the current version : SpectrumPlotting, Averaged Spectrum Plotting, Velocitiy map Channel Map).

API Summary

Constructor
CubeSpectrumAnalysis(CubeSpectrumAnalysisToolbox toolbox, String title) Standard constructor for CubeSpectrumAnalysis. A new window with the

Methods
JFrame **getFrame**() Method that returns the JFrame of this CubeSpectrumAnalysis.
CubeSpectrumAnalysisToolbox **getToolbox**() Returns the CubeSpectrumAnalysisToolbox, associated with this
Container **getComponent**() Returns the content pane (Container) of the JFrame of this
ArrayList **getImageFigures**() Returns all ImageFigures used for this CubeSpectrumAnalysis.

API details

Constructor

CubeSpectrumAnalysis(CubeSpectrumAnalysisToolbox toolbox, String title)

Standard constructor for CubeSpectrumAnalysis. A new window with the

given title and associated with the given CubeSpectrumAnalysisToolbox is crested.

Arguments

CubeSpectrumAnalysisToolbox **toolbox** [INPUT, MANDATORY]

String **title** [INPUT, MANDATORY]

Methods

JFrame getFrame()

Method that returns the JFrame of this CubeSpectrumAnalysis.

JFrame getFrame()

Return

JFrame

The JFrame of this CubeSpectrumAnalysis.

CubeSpectrumAnalysisToolbox getToolbox()

Returns the CubeSpectrumAnalysisToolbox, associated with this

CubeSpectrumAnalysis.

Return

CubeSpectrumAnalysisToolbox

Returns the CubeSpectrumAnalysisToolbox, associated with this CubeSpectrumAnalysis.

Container getComponent()

Returns the content pane (Container) of the JFrame of this

CubeSpectrumAnalysis.

Return

Container

Returns the content pane (Container) of the JFrame of this CubeSpectrumAnalysis.

ArrayList getImageFigures()

Returns all ImageFigures used for this CubeSpectrumAnalysis.

Return

ArrayList

Returns all ImageFigures used for this CubeSpectrumAnalysis.

2.82. CubeSpectrumAnalysisToolbox

Full Name:	herschel.ia.gui.cube.CubeSpectrumAnalysisToolbox
Type:	Java Class -
Import:	from herschel.ia.gui.cube import CubeSpectrumAnalysisToolbox

Description

An implementation of a toolbox for spectrum analysis.

In the current version do the following :

1) You can extract a raw single pixel spectrum from a position selected when clicking on the mouse in the image. <br 2) You can extract an averaged spectrum on a region defined the image by drawing a shape with the mouse. - The circle selection use a linear approximation to compute the weight of the border pixels - The circle selection is "free floating"

5) You can construct a velocity position map, by drawing a line on the image. the velocities are computed from the different layers along the Z axis

6) From 15-09-08 this cube Spectrum Analysis toolbox is registered as a Viewer for the SimpleCube. this mean that in HIPE a simpleCube Variable can be automatically visualized with it . This toolbox is registered in HIPE on the SimpleCube and therefore can be launch via the right button menu In all cases the spectrum analysis is performed on the cube with the shown layer considered as the reference frame. The result is shown in a multi-tab section on the righthand side. All the features are using Task which can be launched from e JIDE environment.

A basic example on how to open a toolbox for spectrum analysis on an SimpleCube Cds or a couple of arrays (Double3d cube,Double1d wavelength)

or

A basic example on how to open a toolbox for spectrum analysis on an SimpleCube Cds or a couple of arrays (Double3d cube,Double1d wavelength)

cat = CubeSpectrumAnalysisToolbox(Cds)

or

cat = CubeSpectrumAnalysisToolbox(Cube,Wavearray)

cat = CubeSpectrumAnalysisToolbox()

cat.setCube(simpleCube)

or

cat = CubeSpectrumAnalysisToolbox()

cat.setCube(SpectralSimpleCube)

or

cat = CubeSpectrumAnalysisToolbox()

cat.setCube(Cube,VaweArray)

or

cat = CubeSpectrumAnalysisToolbox()

cat.setCube(SimpleCube)

to create a simplecube and launch the CubeAnalysistoolbox do this:

```
from herschel.ia.dataset import *
from herschel.ia.numeric import *
from herschel.ia.dataset.image import *
from herschel.ia.dataset.image.wcs import *
import herschel.ia.gui.plot.PlotXY
from herschel.share.unit.Length import *
Waves =Double1d.range(900)/900.*4.E-6
print Waves
a= Double1d(900)
b= RandomUniform()
cube = Double3d(900,5,6)
for raw in range(5):
for column in range(6):
shift1=int( 100.*b.calc(1.))
for wave in range(900):
if raw==2:
cube[wave,raw,column]=3 + EXP((-1.)*(wave -(350.+shift1))*(wave - (350.+shift1))/((50.*50.)))*100.+b.calc(1.)
elif raw==3:
cube[wave,raw,column]=3 + EXP((-1.)*(wave - (350.+shift1))*(wave - (350.+shift1))/((50.*50.)))*100.+b.calc(1.)
else :
cube[wave,raw,column]=0
myWcs = Wcs()
simplecube2 = SimpleCube()
simplecube2.setCube(cube)
myWcs.setNAxis(3)
myWcs.setCrval1(0.0)
myWcs.setCrval2(0.0)
myWcs.setCrpix1(0)
myWcs.setCrpix2(0)
myWcs.setCdelt1(0.1)
myWcs.setCdelt2(0.1)
myWcs.setCtype1("RA---TAN")
myWcs.setCtype2("DEC--TAN")
```

myWcs.setCtype3("Wavelength")

myWcs.setCunit1("[4.84813681109536E-6 rad]")

myWcs.setCunit2("[4.84813681109536E-6 rad]")

myWcs.setCunit3("[MICROMETERS]")

myWcs.setEpoch(2000)

myWcs.setImageIndex(Waves,MICROMETERS)

simplecube2.setWcs(myWcs)

import herschel.ia.gui.cube.CubeSpectrumAnalysisToolbox

initialization of the CubeSpectrumAnalysisToolbox

cat = CubeSpectrumAnalysisToolbox()

cat.setCube(simplecube2)

Example

Example 1: A basic example on how to open a toolbox for spectrum analysis on an

```
SimpleCube Cds or a couple of arrays (Double3d cube,Double1d wavelength)
cat = CubeSpectrumAnalysisToolbox(Double3d)<br>
or<br>
cat = CubeSpectrumAnalysisToolbox(SimpleCube)<br>
or<br>
cat = CubeSpectrumAnalysisToolbox(Cube,Wavearray)<br>
cat = CubeSpectrumAnalysisToolbox()<br>
cat.setCube(Cds)<br>
or <br>
cat = CubeSpectrumAnalysisToolbox() <br>
cat.setCube(Cube,VaweArray)<br>
or <br>
<br>
cat = CubeSpectrumAnalysisToolbox() <br>
cat.setCube(SimpleCube)<br>
to create a simplecube and launch the CubeAnalysistoolbox do this:
from herschel.ia.dataset import *
from herschel.ia.numeric import *
from herschel.ia.dataset.image import *
from herschel.ia.dataset.image.wcs import *
import herschel.ia.gui.plot.PlotXY
from herschel.share.unit.Length import *
Waves =Double1d.range(900)/900.*4.E-6
print Waves
a= Double1d(900)
b= RandomUniform()
cube = Double3d(900,5,6)
for raw in range(5):
for column in range(6):
shift1=int( 100.*b.calc(1.))
for wave in range(900):
if raw==2:
  cube[wave,raw,column]=3 + EXP((-1.)*(wave --(350.+shift1))*(wave -- (350.
+shift1))/((50.*50.)))*100.+b.calc(1.)
elif raw==3:
  cube[wave,raw,column]=3 + EXP((-1.)*(wave -- (350.+shift1))*(wave -- (350.
+shift1))/((50.*50.)))*100.+b.calc(1.)
else -:
  cube[wave,raw,column]=0
myWcs = Wcs()
simplecube2 = SimpleCube()
simplecube2.setCube(cube)
myWcs.setNAxis(3)
myWcs.setCrval1(0.0)
```

Example 1: A basic example on how to open a toolbox for spectrum analysis on an

```
myWcs.setCrval2(0.0)
myWcs.setCrpix1(0)
myWcs.setCrpix2(0)
myWcs.setCdelt1(0.1)
myWcs.setCdelt2(0.1)
myWcs.setCtype1("RA---TAN")
myWcs.setCtype2("DEC--TAN")
myWcs.setCtype3("Wavelength")
myWcs.setCunit1("[4.84813681109536E-6 rad]")
myWcs.setCunit2("[4.84813681109536E-6 rad]")
myWcs.setCunit3("[MICROMETERS]")
myWcs.setEpoch(2000)
myWcs.setImageIndex(Waves,MICROMETERS)
simplecube2.setWcs(myWcs)
import herschel.ia.gui.cube.CubeSpectrumAnalysisToolbox
# initialization of the CubeSpectrumAnalysisToolbox
cat =  CubeSpectrumAnalysisToolbox()
cat.setCube(simplecube2)
```

API Summary

Constructors
CubeSpectrumAnalysisToolbox() The standard constructor for CubeSpectrumAnalysisToolbox. This
CubeSpectrumAnalysisToolbox(Array3dData array3d) Constructor for CubeSpectrumAnalysisToolbox. This constructor shows an
CubeSpectrumAnalysisToolbox(Array3dData array3d, Double1d wave1d) Constructor for CubeSpectrumAnalysisToolbox. This constructor shows an
CubeSpectrumAnalysisToolbox(Array3dData array3d, Double1d wave1d, String specDim, String specUnit) Constructor for CubeSpectrumAnalysisToolbox. This constructor shows an
CubeSpectrumAnalysisToolbox(type simpleCube) Constructor for CubeSpectrumAnalysisToolbox. This constructor shows a

Methods
SaveCurrentImage() Makes a menubar (Image, Help) for the Jpanel version this CubeSpectrumAnalysisToolbox.
setCube(Array3dData array3d) Sets the image you wish to analyse with this CubeSpectrumAnalysisToolbox,
setCube(SimpleCube simplecube) Sets the Cube you wish to analyse with this CubeSpectrumAnalysisToolbox,
setCube(SpectralSimpleCube spectralsimplecube) Sets the Cube you wish to analyse with this CubeSpectrumAnalysisToolbox,
setCube(Array3dData array3d, Double1d wavearray) Sets the image you wish to analyse with this CubeSpectrumAnalysisToolbox,
addCube(Array3dData array3d) Adds the given image (Array3dData) to the images, analysed with
exit() Exits this CubeSpectrumAnalysisToolbox (closes (the window of) this
closeActiveTab()

Methods
Closes the active tab, if there is one.
closeAllTabs() Closes all tabs, if there are any.
setEnabled(boolean enabled) Disables/enables all tabs on the JTabbedPane ans the menus for
boolean **isEnabled**() Returns whether the JTabbedPane and menus for closing tabs and
Double1d **getWaves**() Method that returns the Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.
boolean **isInHipe**() Method that returns the way the CubeSpectrumAnalysisToolbox was openned.
SimpleCube **getSimpleCube**() Method that returns the Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.
SpectralSimpleCube **getSpectralSimpleCube**() Method that returns the Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.
String **getSpecDim**() Method that return The string indicating the physical dimension of the spectrum
String **getSpecUnit**() Method that return The string indicating the unit of the spectrum
JFrame **getFrame**() Method that returns the JFrame of this CubeSpectrumAnalysisToolbox.
JPanel **getPanel**() Method that returns the JPanel of this CubeSpectrumAnalysisToolbox.
JTabbedPane **getTabbedPane**() Method that returns the JTabbedPane of this CubeSpectrumAnalysisToolbox.
SimpleImage **getSimpleImage**() Returns the displayed image (SimpleImage).
PlotXY **getRtSpectrum**() Returns the displayed image (ImageDataset).
Display **getDisplay**() Returns the Display of the Cube you are analysing with
int **getSelectedLayer**() Returns the index of the shown layer, or the index of the selected
Double **getMaxValue**() Returns the maximal value of the "image" of the cube
Double **getMinValue**() Returns the maximal value of the "image" of the cube
int **getSelectedTab**() Returns the index of the tab, selected for the shown layer.

Methods
`JTabbedPane getTabOnPane()` Returns the tab (JTabbedPane) on the JTabbedPane, that is
`VelocityPosMapPlotting getVelocityPosMap()` Returns the tab (JTabbedPane) on the JTabbedPane, that is
`SpectrumPlotting getSpecPlot()` Returns the SpectrumPlotting to acces to all the values of
`SpectrumAvgPlotting getAvgSpecPlot()` Returns the SpectrumAvgPlotting jframe to acces to all the values of
`ChannelMapPlotting getChannelMapPlot()` Returns the ChannelMapPlotting jframe to acces to all the values of
`IntegratedMapDisplay getIntegratedmpaPlot()` Returns the IntegratedMapDisplay jframe to acces to all the values of
`IntensityMapGui getLineIntensityMap()` Returns the IntegratedMapDisplay jframe to acces to all the values of
`SimpleCube getExtractedCube()` Returns the range extraction gui jframe to acces to all the values of
`CubeCompareDisplay getcubecompare()` Returns cube comparison GUI jframe to acces to all the values of
`Spectrum1d getSinglePixelSpectrum()` Returns the single pixel spectrum as Spectrum1d
`Spectrum1d getAvgspectrum()` that returns the Averaged spectrum from the region spectrum extarction task
`SpectralSimpleCube getRangeExtractedCube()` returns the sub-range cube from the range extraction range feature
`SimpleImage getVelocityAxisImage()` returns the velocity position map for the "map mode" of the velocityposition map feature
`String getCubeName()` returns the name of the cube
`SimpleCube getVelocityMapCube()` returns the velocity position map for the "map mode" of the velocityposition map feature
`ArrayList getIntegratedMapImages()` Returns the single pixel spectrum as Spectrum1d
`setWaves(Array3dData cube3d)` Method that initialize the Double1d array of the wavelength of
`setWaves(Double1d waves1d)` Method that initialize the Double1d array of the wavelength of this CubeSpectrumAnalysisToolbox.
`setCubeName(String name)` set the name of the cube
`boolean isInImage(MouseEvent e)` Checks whether the given MouseEvent has occured within the image
`boolean isInImage(double pixX, double pixY)`

Methods
Checks whether the point with given PixelCoordinates (pixX, pixY)
`boolean hasWCS()` Returns true if SkyCoordinates are available for the image,
`showlineIntensityMap()` unknown
`showSpectrum()` click on a spaxel in the image to stop the real tim espectrum display
`showSpectrumAvg()` Drawn a region on the image, depending of the option selected
`showVelocityPosMap()` Draws a staight line on the image, starting at the point in the
`showChannelMap()` Draws a staight line on the image, starting at the point in the
`showIntegratedMap()` Draws a staight line on the image, starting at the point in the
`guiRangeExtract()` Draws a staight line on the image, starting at the point in the
`ArrayList getAllFigures()` Returns all ImageFigures used for this CubeSpectrumAnalysisToolbox.
`addFigures(ArrayList figures)` Adds the ImageFigures belonging to the selected tab up front to
`removeLastFigure(type figures The ImageFigures to add to the list of ImageFigures)` Adds the ImageFigures belonging to the selected tab up front to
`updateImage()` Updates the image, when another tab is made active.
`removeAllAnnotations()` Makes all annotations invisible.
`createSpaceOnTabbedPane()` Creates a free space at the end of the Arraylist of ArrayLists of
`createSpaceInTab()` Creates a free space at index 0 in the ArrayList of CanvasFigures,
`RangeExtractionGui getRangeextraction()`

API details

Constructors

`CubeSpectrumAnalysisToolbox()`
The standard constructor for CubeSpectrumAnalysisToolbox. This constructor shows an empty CubeSpectrumAnalysisToolbox window in 2 parts, with only a title, buttons for maximizing, minimizing and closing the window, a menubar (File, Image, Help) and a colorbar and a statusbar at the bottom.

CubeSpectrumAnalysisToolbox(Array3dData array3d)

Constructor for CubeSpectrumAnalysisToolbox. This constructor shows an

empty CubeSpectrumAnalysisToolbox window in 2 parts, with a title, buttons for maximising, minimising and closing the window, and a menubar (file, Spectrum, Help). Also the image you wish to analyse, is displayed.

Argument

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

CubeSpectrumAnalysisToolbox(Array3dData array3d, Double1d wave1d)

Constructor for CubeSpectrumAnalysisToolbox. This constructor shows an

empty CubeSpectrumAnalysisToolbox window in 2 parts, with a title, buttons for maximizing, minimizing and closing the window, and a menubar (file, Spectrum, Help). Also the image you wish to analyse, is displayed. THE DEFAULT UNIT is MICROMETER

Arguments

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

`Double1d` **`wave1d`** `[INPUT, MANDATORY]`

CubeSpectrumAnalysisToolbox(Array3dData array3d, Double1d wave1d, String specDim, String specUnit)

Constructor for CubeSpectrumAnalysisToolbox. This constructor shows an

empty CubeSpectrumAnalysisToolbox window in 2 parts, with a title, buttons for maximising, minimising and closing the window, and a menubar (file, Spectrum, Help). Also the image you wish to analyse, is displayed.

Arguments

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

`Double1d` **`wave1d`** `[INPUT, MANDATORY]`

`String` **`specDim`** `[INPUT, MANDATORY]`

`String` **`specUnit`** `[INPUT, MANDATORY]`

CubeSpectrumAnalysisToolbox(type simpleCube)

Constructor for CubeSpectrumAnalysisToolbox. This constructor shows a

CubeSpectrumAnalysisToolbox window in 2 parts, with a title, buttons for maximising, minimising and closing the window, and a menubar (file, Spectrum, Help). Also the "cube" of the Simplecube you wish to analyse, is displayed.

Argument

`type` **`simpleCube`** `[INPUT, MANDATORY, default=no default value]`

The SimpleCube containing all the information of an observation you wish to analyse and display with this CubeSpectrumAnalysisToolbox.

Methods

SaveCurrentImage()

Makes a menubar (Image, Help) for the Jpanel version this CubeSpectrumAnalysisToolbox.

setCube(Array3dData array3d)

Sets the image you wish to analyse with this CubeSpectrumAnalysisToolbox,

setCube(Array3dData array3d)

to the given ImageDataset.

Argument

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

setCube(SimpleCube simplecube)

Sets the Cube you wish to analyse with this CubeSpectrumAnalysisToolbox,

to the given SimpleCube.

Argument

`SimpleCube` **`simplecube`** `[INPUT, MANDATORY]`

setCube(SpectralSimpleCube spectralsimplecube)

Sets the Cube you wish to analyse with this CubeSpectrumAnalysisToolbox,

to the given spectralSimpleCube.

Argument

`SpectralSimpleCube` **`spectralsimplecube`** `[INPUT, MANDATORY]`

setCube(Array3dData array3d, Double1d wavearray)

Sets the image you wish to analyse with this CubeSpectrumAnalysisToolbox,

to the given ImageDataset.

Arguments

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

`Double1d` **`wavearray`** `[INPUT, MANDATORY]`

addCube(Array3dData array3d)

Adds the given image (Array3dData) to the images, analysed with

this CubeSpectrumAnalysisToolbox.

Argument

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

exit()

Exits this CubeSpectrumAnalysisToolbox (closes (the window of) this

CubeSpectrumAnalysisToolbox).

closeActiveTab()

Closes the active tab, if there is one.

closeAllTabs()

Closes all tabs, if there are any.

setEnabled(boolean enabled)

Disables/enables all tabs on the JTabbedPane ans the menus for

setEnabled(boolean enabled)

closing tabs and performing image analysis, of this CubeSpectrumAnalysisToolbox.

Argument

`boolean` **`enabled`** `[INPUT, MANDATORY]`

boolean isEnabled()

Returns whether the JTabbedPane and menus for closing tabs and

performing image analysis, of this CubeSpectrumAnalysisToolbox are enabled/disabled.

Return

boolean

Returns true is the JTabbedPane and menus for closing tabs and performing image analysis, of this CubeSpectrumAnalysisToolbox are enabled; false otherwise.

Double1d getWaves()

Method that returns the Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.

Return

Double1d

The Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.

boolean isInHipe()

Method that returns the way the CubeSpectrumAnalysisToolbox was openned.

true if it's open with the right menu in the variable list of hipe false when openned with the classical command line call

Return

boolean

the way the CubeSpectrumAnalysisToolbox was openned. true if it's open with the right menu in the variable list of hipe false when openned with the classical command line call

SimpleCube getSimpleCube()

Method that returns the Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.

Return

SimpleCube

The Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.

SpectralSimpleCube getSpectralSimpleCube()

Method that returns the Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.

Return

SpectralSimpleCube

The Float1d array of the wavelength of this CubeSpectrumAnalysisToolbox.

String getSpecDim()

Method that return The string indicating the physical dimension of the spectrum

Return

String

The string indicating the physical dimension of the spectrum

String getSpecUnit()

Method that return The string indicating the unit of the spectrum

Return

String

The string indicating the unit of the spectrum

JFrame getFrame()

Method that returns the JFrame of this CubeSpectrumAnalysisToolbox.

Return

JFrame

The JFrame of this CubeSpectrumAnalysisToolbox.

JPanel getPanel()

Method that returns the JPanel of this CubeSpectrumAnalysisToolbox.

Return

JPanel

The JPanel of this CubeSpectrumAnalysisToolbox.

JTabbedPane getTabbedPane()

Method that returns the JTabbedPane of this CubeSpectrumAnalysisToolbox.

Return

JTabbedPane

The JTabbedPane of this CubeSpectrumAnalysisToolbox.

SimpleImage getSimpleImage()

Returns the displayed image (SimpleImage).

Return

SimpleImage

Returns the displayed image (SimpleImage).

PlotXY getRtSpectrum()

Returns the displayed image (ImageDataset).

Return

PlotXY

PlotXY getRtSpectrum()

Returns the displayed image (ImageDataset).

Display getDisplay()

Returns the Display of the Cube you are analysing with

this CubeSpectrumAnalysisToolbox.

Return

Display

Returns the display of the Cube you are analysing with this CubeSpectrumAnalysisToolbox.

int getSelectedLayer()

Returns the index of the shown layer, or the index of the selected

tab on the JTabbedPane.

Return

int

Returns the index of the shown layer,or the index of the selected tab on the JTabbedPane.

Double getMaxValue()

Returns the maximal value of the "image" of the cube

Return

Double

Returns the maximal value of the "image" of the cube

Double getMinValue()

Returns the maximal value of the "image" of the cube

Return

Double

Returns the maximal value of the "image" of the cube

int getSelectedTab()

Returns the index of the tab, selected for the shown layer.

Return

int

The index of the tab, selected for the shown layer.

JTabbedPane getTabOnPane()

Returns the tab (JTabbedPane) on the JTabbedPane, that is

selected.

Return

JTabbedPane getTabOnPane()

JTabbedPane

Returns the tab (JTabbedPane) on the JTabbedPane, that is selected.

VelocityPosMapPlotting getVelocityPosMap()

Returns the tab (JTabbedPane) on the JTabbedPane, that is

selected.

Return

VelocityPosMapPlotting

Returns the tab (JTabbedPane) on the JTabbedPane, that is selected.

SpectrumPlotting getSpecPlot()

Returns the SpectrumPlotting to acces to all the values of

single pixel spectrum extraction.

Return

SpectrumPlotting

Returns the SpectrumPlotting to acces to all the values of single pixel spectrum extraction.

SpectrumAvgPlotting getAvgSpecPlot()

Returns the SpectrumAvgPlotting jframe to acces to all the values of

single pixel spectrum extraction.

Return

SpectrumAvgPlotting

Returns the SpectrumAvgPlotting to acces to all the values of single pixel spectrum extraction.

ChannelMapPlotting getChannelMapPlot()

Returns the ChannelMapPlotting jframe to acces to all the values of

channel map exraction

Return

ChannelMapPlotting

Returns the ChannelMapPlotting jframe to acces to all the values of channel map exraction

IntegratedMapDisplay getIntegratedmpaPlot()

Returns the IntegratedMapDisplay jframe to acces to all the values of

channel map exraction

Return

IntegratedMapDisplay

IntegratedMapDisplay getIntegratedmpaPlot()

Returns the IntegratedMapDisplay jframe to acces to all the values of channel map exraction

IntensityMapGui getLineIntensityMap()

Returns the IntegratedMapDisplay jframe to acces to all the values of

channel map exraction

Return

IntensityMapGui

Returns the IntegratedMapDisplay jframe to acces to all the values of channel map exraction

SimpleCube getExtractedCube()

Returns the range extraction gui jframe to acces to all the values of

channel map exraction

Return

SimpleCube

Returns the range extraction gui jframe to acces to all the values of channel map exraction

CubeCompareDisplay getcubecompare()

Returns cube comparison GUI jframe to acces to all the values of

the feature

Return

CubeCompareDisplay

Returns cube comparison GUI jframe to acces to all the values of the feature

Spectrum1d getSinglePixelSpectrum()

Returns the single pixel spectrum as Spectrum1d

Return

Spectrum1d

Returns the single pixel spectrum as Spectrum1D

Spectrum1d getAvgspectrum()

that returns the Averaged spectrum from the region spectrum extarction task

Return

Spectrum1d

that returns the Averaged spectrum from the region spectrum extarction task

SpectralSimpleCube getRangeExtractedCube()

returns the sub-range cube from the range extraction range feature

Return

SpectralSimpleCube

SpectralSimpleCube getRangeExtractedCube()

returns the sub-range cube from the range extraction range feature

SimpleImage getVelocityAxisImage()

returns the velocity position map for the "map mode" of the velocityposition map feature

Return

SimpleImage

returns the velocity position map for the "map mode" of the velocityposition map feature

String getCubeName()

returns the name of the cube

Return

String

returns the name of the cube

SimpleCube getVelocityMapCube()

returns the velocity position map for the "map mode" of the velocityposition map feature

Return

SimpleCube

returns the velocity position map for the "map mode" of the velocityposition map feature

ArrayList getIntegratedMapImages()

Returns the single pixel spectrum as Spectrum1d

Return

ArrayList

Returns the single pixel spectrum as Spectrum1D

setWaves(Array3dData cube3d)

Method that initialize the Double1d array of the wavelength of

this CubeSpectrumAnalysisToolbox.

Argument

`Array3dData` **`cube3d`** `[INPUT, MANDATORY]`

setWaves(Double1d waves1d)

Method that initialize the Double1d array of the wavelength of this CubeSpectrumAnalysisToolbox.

Argument

`Double1d` **`waves1d`** `[INPUT, MANDATORY]`

setCubeName(String name)

set the name of the cube

Argument

setCubeName(String name)

`String` **name** [INPUT, MANDATORY]

boolean isInImage(MouseEvent e)

Checks whether the given MouseEvent has occured within the image

we are analysing with this CubeSpectrumAnalysisToolbox.

Argument

`MouseEvent` **e** [INPUT, MANDATORY]

Return

boolean

Returns true if the given MouseEvent has occured within the image that is being analysed with this CubeSpectrumAnalysisToolbox; false otherwise.

boolean isInImage(double pixX, double pixY)

Checks whether the point with given PixelCoordinates (pixX, pixY)

lies in the image we are analysing with this CubeSpectrumAnalysisToolbox.

Arguments

double **pixX** [INPUT, MANDATORY]

double **pixY** [INPUT, MANDATORY]

Return

boolean

Returns true if the point with given PixelCoordinates (pixX, pixY) lies in the image we are analysing with this CubeSpectrumAnalysisToolbox; false otherwise.

boolean hasWCS()

Returns true if SkyCoordinates are available for the image,

analysed with this CubeSpectrumAnalysisToolbox; false otherwise.

Return

boolean

Returns true if SkyCoordinates are available for the image, analysed with this CubeSpectrumAnalysisToolbox; false otherwise.

showlineIntensityMap()

unknown

showSpectrum()

click on a spaxel in the image to stop the real tim espectrum display

and keep the last one, whe you are out of the image the spectrum is the last one which was read

showSpectrumAvg()

Drawn a region on the image, depending of the option selected

showSpectrumAvg()

on the right side of the window and of the point clicked in the image with the mouse. and plots the averaged spectrum along that "cylinder" .When you click or move outside of the image, no shape is defined.

showVelocityPosMap()

Draws a staight line on the image, starting at the point in the

you clicked on with the mouse the 1st time, and ending at the current mouse position (in the image), or at the 2nd point (in the image) you clicked on, and plots the intensity along that straight lin. When you click or move outside of the image, no straight line is drawn and no plot is shown.

showChannelMap()

Draws a staight line on the image, starting at the point in the

you clicked on with the mouse the 1st time, and ending at the current mouse position (in the image), or at the 2nd point (in the image) you clicked on, and plots the intensity along that straight lin. When you click or move outside of the image, no straight line is drawn and no plot is shown.

showIntegratedMap()

Draws a staight line on the image, starting at the point in the

you clicked on with the mouse the 1st time, and ending at the current mouse position (in the image), or at the 2nd point (in the image) you clicked on, and plots the intensity along that straight lin. When you click or move outside of the image, no straight line is drawn and no plot is shown.

guiRangeExtract()

Draws a staight line on the image, starting at the point in the

you clicked on with the mouse the 1st time, and ending at the current mouse position (in the image), or at the 2nd point (in the image) you clicked on, and plots the intensity along that straight lin. When you click or move outside of the image, no straight line is drawn and no plot is shown.

ArrayList getAllFigures()

Returns all ImageFigures used for this CubeSpectrumAnalysisToolbox.

Return

ArrayList

Returns all ImageFigures used for this CubeSpectrumAnalysisToolbox.

addFigures(ArrayList figures)

Adds the ImageFigures belonging to the selected tab up front to

the list of ImageFigures, used for this CubeSpectrumAnalysisToolbox.

Argument

ArrayList **figures** [INPUT, MANDATORY]

removeLastFigure(type figures The ImageFigures to add to the list of ImageFigures)

Adds the ImageFigures belonging to the selected tab up front to

removeLastFigure(type figures The ImageFigures to add to the list of ImageFigures)

the list of ImageFigures, used for this CubeSpectrumAnalysisToolbox.

Argument

`type` **figures The ImageFigures to add to the list of ImageFigures** `[INPUT, MANDATORY, default=no default value]`

used for this CubeSpectrumAnalysisToolbox.

updateImage()

Updates the image, when another tab is made active.

removeAllAnnotations()

Makes all annotations invisible.

createSpaceOnTabbedPane()

Creates a free space at the end of the Arraylist of ArrayLists of

ArrayLists of ImageFigures, that belong to the image analysis on the shown layer.

createSpaceInTab()

Creates a free space at index 0 in the ArrayList of CanvasFigures,

belonging to a new image analysis on the shown layer.

RangeExtractionGui getRangeextraction()

Return

RangeExtractionGui

the RangeExtractionGui

See also

- Display, PlotXY

2.83. CubicSplineInterpolator

Full Name:	herschel.ia.numeric.toolbox.interp.CubicSplineInterpolator
Alias:	CubicSplineInterpolator
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.interp import CubicSplineInterpolator

Description

Creates a cubic spline interpolation function from a set of knots (x,y),

that can be applied to numeric arrays of rank 1.

The second derivative is assumed to be zero at the end points (i.e. a natural spline).

Example

Example 1: Create and apply a CubicSplineInterpolator on a Double1d

```
# create some knots
x=Double1d.range(10) # [0.0,1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0]
f=CubicSplineInterpolator(x,SQUARE(x))
u=Float1d([1,1.1,2,2.6,3,3.9])
print f(u) # [1.0,1.1970944,4.0,6.7656145,9.0,15.209593]
```

API Summary

Jython Syntax

```
<f>=CubicSplineInterpolator(<x>,<y>[,allowExtrapolation])
```

Properties

Double1d **x** [INPUT, MANDATORY, default=no default value]

Double1d **y** [INPUT, NOT_MANDATORY, default=false]

boolean **allowExtrapolation** [INPUT, NOT_MANDATORY, default=false]

API details

Properties

Double1d x [INPUT, MANDATORY, default=no default value]

The knots are Double1d

Double1d y [INPUT, NOT_MANDATORY, default=false]

The knots are Double1d

boolean allowExtrapolation [INPUT, NOT_MANDATORY, default=false]

Extrapolation is not allowed by default. Boolean.TRUE allows extrapolation.

See also

- LinearInterpolator

- NearestNeighborInterpolator

2.84. CubicSplinesModel

Full Name:	herschel.ia.numeric.toolbox.fit.CubicSplinesModel
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.fit import CubicSplinesModel

Description

General cubic splines model with arbitrary knot settings.

A number (<< datapoints) of knots are layed out on the x-axis at arbitrary position, generally more knots where the curvature is higher. The knots need to be monotonuously increasing in x. Through these knots a cubic splines function is obtained which best fits the datapoints. One needs at least 2 knots, one smaller and one larger than all x-values in the dataset.

If the end knots are put in between the x-values in the dataset, a kind of extrapoling spline is obtained. It still works more or less.

Example

Example 1: example

```
<p>
<b>This model is NOT for cubic spline interpolation</b>.
```

2.85. cutLevels

Full Name:	herschel.ia.toolbox.image.CutLevelsTask
Alias:	cutLevels
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import CutLevelsTask
Category:	task/image

Description

A Task to calculate the cut levels of an image.

CutLevelsTask is a task which returns the cut levels of an Image. The cut levels can be calculated using 2 methods :

- PERCENT : A certain percentage of the pixels is calculated.
- MEDIAN_FILTER : A window of 7 pixels is taken. From this window, the median is taken. This median is then compared with the minimum and maximum value of the image. 21 pixels are skipped in the column dimension and 3 rows are skipped.

Examples

Example 1: Calculate the cut levels where 95% of the values are included.

```
cutLevelsTask(image = im, method=CutLevels.PERCENT, percent = 95.0)
```

Example 2: Calculate the cut levels using the median filter

```
cutLevelsTask(image = im, method=CutLevels.MEDIAN_FILTER)
```

API Summary

Jython Syntax

```
cutLevels(image, CutLevels.PERCENT, 95.0)
```

Properties

```
Image image [INPUT, MANDATORY, default=No default value]
int method [INPUT, MANDATORY, default=CutLevels.MEDIAN_FILTER]
double percent [INPUT, OPTIONAL, default=99.5]
double[] cutLevels [OUTPUT, MANDATORY, default=No default value]
```

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image to use for calculating the cut levels.

int method [INPUT, MANDATORY, default=CutLevels.MEDIAN_FILTER]

The method to use for calculating the cut levels (CutLevels.PERCENT or CutLevels.MEDIAN_FILTER).

double percent [INPUT, OPTIONAL, default=99.5]

The percentage of pixels to use in the calculation of the cut levels.

double[] cutLevels [OUTPUT, MANDATORY, default=No default value]

The minimum and maximum cut level.

2.86. CutLevelsTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.CutLevelsTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import CutLevelsTaskSignatureComponent

Description

A task dialog for the CutLevelsTask.

A task dialog to serve as GUI for the SourceFittingTask.

API Summary

Constructor
CutLevelsTaskSignatureComponent() The constructor of a new CutLevelsTaskSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
Map **getParameters()** Returns a map of parameters and modifiers.
setSignature(SignatureApi sig) Setting the signature.
setVariableSelection(VariableSelection selection) Setting the variable selection.
JComponent **getComponent()** Returns the component.

API details

Constructor

CutLevelsTaskSignatureComponent()
The constructor of a new CutLevelsTaskSignatureComponent. The constructor of a new CutLevelsTaskSignatureComponent.

Methods

check()
Validates the current modifications. Validates the current modifications for this CutLevelsTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this CutLevelTaskSignatureComponent.

Map getParameters()

Returns a map of parameters and modifiers.

Returns a map of parameters and modifiers storing the value selected by the user for this CutLevelsTaskSignatureComponent.

Return

Map

Returns a map of parameters and modifiers storing the value selected by the user for this CutLevelsTaskSignatureComponent.

setSignature(SignatureApi sig)

Setting the signature.

Sets the given signature as the signature for this CutLevelsTaskSignatureComponent.

Argument

`SignatureApi` **`sig`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this CutLevelsTaskSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

JComponent getComponent()

Returns the component.

Returns the component for this CutLevelsTaskSignatureComponent.

Return

JComponent

Returns the component for this CutLevelsTaskSignatureComponent.

2.87. DataFlow

Full Name:	herschel.ia.dataflow.DataFlow
Type:	Java Class -
Import:	from herschel.ia.dataflow import DataFlow

Description

Groups several processes as one big process.

It is a process that may manage processes. Processes are created within the dataflow, and may be connected among them. DataFlow allows created processes outside to be added to it. A developer may inherit from this class in order to create a specific dataflow.

Example

Example 1: how to use a dataflow with given processes.

```
<pre>
from herschel.ia.dataflow import *
#creating dataflow and processes.
df = DataFlow("MyDataFlow")
df.createProcess("generator", -"myprocesses.ProcessGenerator")
df.createProcess("fft", -"myprocesses.ProcessFFT")
# adding a created process
p = myprocess.ProcessFFT("viewer")
df.addProcess(p)
#connecting processes
df.connect("generator.output", -"fft.input")
df.connect("fft.output", -"viewer.input")
# putting the viewer in a JFrame.
from javax.swing import *
frame = JFrame("MyFrame")
viewer = df.getProcess("viewer")
frame.getContentPane().add(viewer.getJComponent())
frame.setSize(600,600)
frame.setVisible(1)
# starting the dataflow.
df.start()
</pre>
```

Limitations

no limitation

See also

- reference

History

- 26-5-2005 jcg: change javadoc format for help support.

2.88. DataFlowManager

Full Name:	herschel.ia.dataflow.DataFlowManager
Type:	Java Class -
Import:	from herschel.ia.dataflow import DataFlowManager

Description

Shows dataflows.

Allows to the user to see the dataflow in a graphical environment.

Example

Example 1: how to show a dataflow

```
<pre>
from herschel.ia.dataflow import *
df = DataFlow("mydf")
df.createProcess(...)
df.createProcess(...)
df.createProcess(...)
DataFlowManager(df)
</pre>
```

Limitations

no limitation

See also

- reference

History

- 26-5-2005 jcg: change javadoc format for help support.

2.89. DbFactory

Full Name:	herschel.ia.pal.pool.db.DbFactory
Type:	Java Class -
Import:	from herschel.ia.pal.pool.db import DbFactory
Category:	PAL

Description

An implementation of a ProductPool which saves data to a versant database.

You need to define a property which will store the name of the database you wish the DbPool to use. Please check that the property of the same name points to a valid physical database.

Depending on your network performance and proximity to the database pool you may want to wrap a CachedPool around the DbPool. See the last example below.

Examples

Example 1: Create a DbPool passing it a map

```
Configuration.setProperty("dbProperty", -"&lt;dbname&gt;@&lt;hostname&gt;")
params = java.util.HashMap()<br>
params.put("id", -"dbpool")<br>
params.put("database", -"dbProperty")<br>
storage=ProductStorage();<br>
storage.register(DbFactory.createPool("db", params)
```

Example 2: Create a DbPool that points to the database property "hcss.ia.pal.pool.db.database"

```
storage=ProductStorage();<br>
storage.register(DbFactory.getStore())
```

Example 3: Create a DbPool that points to the database <dbname>@<hostname>

```
storage=ProductStorage() <br>
storage.register(DbFactory.getStore(&lt;dbname&gt;@&lt;hostname&gt;, poolName))
```

Example 4: Saving and Loading to/from a DbPool

```
ref=storage.save(myproduct) <br>
ref=storage.load(ref)
```

Example 5: Wrapping a CachedPool around a DbPool

```
storage.register(CachedPool(DbFactory.getStore()))
```

2.90. DbPool

Full Name:	herschel.ia.pal.pool.db.DbPool
Type:	Java Class -
Import:	from herschel.ia.pal.pool.db import DbPool
Category:	PAL

Description

An implementation of a ProductPool which saves data to a versant database (to be exact, any

object database that uses the HCSS ObjectStore interface).

New: The DbPool continues to support the direct creation of its pools, however it is now recommended that DbPool(s) be created using the DbFactory methods.

You need to define a property which will store the name of the database you wish the DbPool to use. By default this is "hcss.test.database". Please check that the property of the same name points to a valid physical database.

Depending on your network performance and proximity to the database pool you may want to wrap the a CachedPool around the DbPool. See the last example below.

Examples

Example 1: Create a DbPool that points to the default database property "hcss.test.database"

```
storage=ProductStorage() <br>
storage.register(DbPool.getInstance())
```

Example 2: Create a DbPool that points to the database property "my.database"

```
storage=ProductStorage() <br>
storage.register(DbPool.getInstance("my.database", poolName))
```

Example 3: Saving and Loading to/from a DbPool

```
ref=storage.save(myproduct)<br>
ref=storage.load(ref)
```

Example 4: Wrapping a CachedPool around a DbPool

```
storage.register(CachedPool(DbPool.getInstance()))
```

API Summary

Methods
`DbPool getInstance(String databaseProperty, String poolName)` DbPool
`DbPool getInstance(String databaseProperty)`

Methods
DbPool
`DbPool getInstance()`
Creates an instance of a DbPool connected to the logical database of default property named
`DbPool createInstance(String databaseProperty)`
DbPool

API details

Methods

`DbPool getInstance(String databaseProperty, String poolName)`

DbPool

Creates an instance of a DbPool connected to a logical database

Arguments

`String` **`databaseProperty`** `[INPUT, MANDATORY, default=no default value]`

The logical name of the database, for example "hcss.test.database"

`String` **`poolName`** `[INPUT, MANDATORY, default=no default value]`

The actual name of the database pool

Return

DbPool

An instance of the DbPool.

`DbPool getInstance(String databaseProperty)`

DbPool

Creates an instance of a DbPool connected to a logical database

Argument

`String` **`databaseProperty`** `[INPUT, MANDATORY, default=no default value]`

The logical name of the database, for example "hcss.test.database"

Return

DbPool

An instance of the DbPool.

`DbPool getInstance()`

Creates an instance of a DbPool connected to the logical database of default property named

"hcss.test.database"

Return

DbPool

An instance of the DbPool.

DbPool createInstance(String databaseProperty)

DbPool

Creates an instance of a DbPool connected to a logical database

Argument

String **databaseProperty** [INPUT, MANDATORY]

Return

DbPool

An instance of the DbPool.

2.91. DETERMINANT

Full Name:	herschel.ia.numeric.toolbox.matrix.MatrixDeterminant
Alias:	DETERMINANT
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import MatrixDeterminant

Description

Yields the determinant of a square matrix.

Example

Example 1: Apply a DETERMINANT to a Double2d matrix

```
A=Double2d([ [1,2],[3,4] -])
print DETERMINANT(A) # --2
```

API Summary

Jython Syntax

```
<y>=DETERMINANT(<x>)
```

Properties

`any square matrix x [INPUT, MANDATORY, default=no default value]`

`double y [INPUT, NOT_MANDATORY, default=false]`

Miscellaneous

Does not work for complex matrices.

API details

Properties

`any square matrix x [INPUT, MANDATORY, default=no default value]`

Any square matrix

`double y [INPUT, NOT_MANDATORY, default=false]`

Returns a double

See also

- CubicSplineInterpolator
- LinearInterpolator

2.92. DFT2dTask

Full Name:	herschel.ia.toolbox.image.DFT2dTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import DFT2dTask

Description

A Task for two dimensional Discrete Fourier Transforms.

A Task that calculates the 2D Discrete Fourier Transform and the power spectrum.

API Summary

Properties
`Numeric2dData image [INPUT, MANDATORY, default=No default value]`
`Complex2d transform [OUTPUT, MANDATORY, default=No default value]`
`Double2d spectrum [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Numeric2dData image [INPUT, MANDATORY, default=No default value]`

The input image.

`Complex2d transform [OUTPUT, MANDATORY, default=No default value]`

The transform.

`Double2d spectrum [OUTPUT, MANDATORY, default=No default value]`

The spectrum.

2.93. Display

Full Name:	herschel.ia.gui.image.Display
Alias:	Display
Type:	Java Class -
Import:	from herschel.ia.gui.image import Display
Category:	Image

Description

An Image display for DP. A class to display images.

This class can display a SimpleImage, SimpleCube or any numeric2d or numeric3d object. A status bar, color bar, a zoomed section of the image and an overview of the image are also available.

Examples

Example 1: Display a SimpleImage

```
d = Display(mySimpleImage)
```

Example 2: A basic example on how to Display a Double2d

```
im = Double2d(600, 400)
for i in range(600):
 for j in range(400):
  im.set(i, j, i + j)
d = Display(im)
```

API Summary

Constructors
Display() The standard constructor
Display(boolean useAsComponent, boolean imageVisible) A Display constructor
Display(boolean useAsComponent) A constructor to use Display as a component.
Display(Image imds) A constructor which displays an Image.
Display(Cube cube) A constructor which displays a Cube.
Display(Stack stack) A constructor which displays a Stack.
Display(RgbImage imds) A constructor which displays an RgbImage.
Display(Image imds, boolean imageVisible) A Display constructor
Display(Cube imds, boolean imageVisible) A Display constructor

Constructors
Display(Stack stack, boolean imageVisible) A Display constructor
Display(Array2dData data) A constructor to display a Numeric2d.
Display(Array2dData data, boolean imageVisible) A Display constructor
Display(Array3dData data) A constructor to display a numeric3d
Display(Array3dData data, boolean imageVisible) A display constructor

Methods
int **getLayerShown**() Returns the number of the shown layer
setVisible(boolean imageVisible) Toggles the display visible or invisible.
JPanel **getComposedComponent**() Returns a panel with all components of this Display on it.
ImageColorbar **getColorBarComponent**() Returns the color bar component.
DivaMainImageDisplay **getComponent**() Returns the component where the image is displayed.
ImagePanner **getPannerComponent**() Returns the panner component with the overview of the image.
StatusPanel **getStatusPanelComponent**() Returns the component with the status panel.
setStatusPanelComponent(StatusPanel imageDisplayStatusPanel) Set a new status panel for the display.
ImageZoom **getZoomComponent**() Returns the component with the zoomed view.
setImage(Array2dData imageData) Set a new numeric2d image.
setImage(Array3dData imageData) Sets a new numeric3d image.
setImage(Image imds) Sets a new Image to Display.
setImage(Cube cube) Sets a new cube to display.
setImage(Stack stack) Sets a new stack to display.
setImage(RgbImage imds) Sets a new RgbImage to Display.

Methods
addLayer(Layer layer) Adds a new layer to the display.
addLayer(Array2dData imageData) Adds a new layer with numeric2d data
addLayer(Array3dData imageData) Adds a new layer with numeric3d data
addLayer(Image imds) Adds a new layer with an Image to the display.
addLayer(RgbImage imds) Adds a new layer with an RgbImage to the display.
addLayer(Cube cube) Adds a new layer with a Cube to the display.
addLayer(Stack stack) Adds a new layer with a Stack to the display.
Layer **getLayer**() Returns the shown layer.
Layer **getLayer**(int i) Returns the Layer object
showLayer(int i) Shows a chosen layer.
removeLayer() Removes the current layer.
removeLayer(int i) Removes a layer.
updateImage(Array2dData imageData) Updates the layer with numeric2d data.
updateImage(Image imds) Updates the layer with an Image.
updateImage(RgbImage imds) Updates the layer with an Image.
updateImage(Array3dData imageData) Updates the layer with numeric3d data.
updateImage(Cube imds) Updates the layer with a cube.
updateImage(Stack stack) Updates the layer with a stack.
setBackground(Color bgColor) Sets the background color.
annotationToolbox() Fires up the annotation toolbox.
CanvasFigure **addAnnotation**(String text, double row, double column)

Methods
Adds a text annotation.
`CanvasFigure addAnnotationWorldCoordinates(String text, double ra, double decl)` Adds a text annotation
`CanvasFigure addGreekAnnotation(String text, double row, double column)` Adds a Greek annotation
`CanvasFigure addGreekAnnotationWorldCoordinates(String text, double ra, double decl)` Adds a Greek annotation
`Font getAnnotationFont()` Returns the default font for annotations.
`Font getAnnotationFont(double row, double column)` Returns the font for the specified annotation.
`Font getAnnotationFontWorldCoordinates(double ra, double dec)` Returns the font for the specified annotation.
`Color getAnnotationFontColor()` Returns the default color for annotations.
`Color getAnnotationFontColor(double row, double column)` Returns the color of the specified annotation.
`Color getAnnotationFontColorWorldCoordinates(double ra, double dec)` Returns the color of the specified annotation.
`removeAnnotation(double row, double column)` Removes the specified annotation
`removeAnnotationWorldCoordinates(double ra, double dec)` Remove the specified annotation.
`removeAnnotation(CanvasFigure fig)` Removes the specified annotation.
`removeAnnotations()` Removes all annotations.
`setAnnotationFont(Font f)` Changes the font of all Annotations.
`setAnnotationFont(double row, double column, Font f)` Changes the font of the specified annotations.
`setAnnotationFontWorldCoordinates(double ra, double dec, Font f)` Changes the font of the specified annotations.
`setAnnotationFont(int size)` Changes the font size of all annotations.
`setAnnotationFont(double row, double column, int size)` Changes the font size of the specified annotations.
`setAnnotationFontWorldCoordinates(double ra, double dec, int size)`

Methods
Changes the font size of the specified annotations.
setAnnotationFontColor(Color color) Sets the default color for annotations.
setAnnotationFontColor(double row, double column, Color color) Sets the font color for the specified annotation.
setAnnotationFontColorWorldCoordinates(double ra, double dec, Color color) Sets the font color for the specified annotation.
CanvasFigure **addEllipse**(double row, double column, double w, double h, float lineWidth, Color color) Adds an ellipse.
addFigure(CanvasFigure fig) Adds a CanvasFigure
CanvasFigure **addEllipse**(double row, double column, double w, double h, float lineWidth, Color color, double positionAngle) Adds an ellipse
CanvasFigure **addCircle**(double row, double column, double radius, float lineWidth, Color color) Adds a circle
CanvasFigure **addLine**(double row1, double column1, double row2, double column2, float lineWidth, Color color) Adds a line.
CanvasFigure **addPolygon**(double[] coords, float lineWidth, Color color) Adds a polygon
CanvasFigure **addPolyline**(double[] coords, float lineWidth, Color color) Adds a polyline.
CanvasFigure **addRectangle**(double minRow, double minColumn, double w, double h, float lineWidth, Color color) Adds a rectangle.
ArrayList **addImageContour**(ImageContour imageContour, ArrayList colors, int minLength) Adds an ImageContour.
ArrayList **addImageContour**(ImageContour imageContour, ArrayList colors) Adds an ImageContour.
ArrayList **addWcsImageContour**(ImageContour imageContour, ArrayList colors, int minLength) Add an ImageContour.
ArrayList **addWcsImageContour**(ImageContour imageContour, ArrayList contourColors) Adds an ImageContour.
ArrayList **addContourLevel**(ContourLevel contourLevel, Color contourColor, int minimumContourLength)

Methods
Adds a ContourLevel.
ArrayList **addContourLevel**(ContourLevel level, Color color) Adds a ContourLevel.
ArrayList **addContourLevel**(ContourLevel level, Wcs wcs, Color color, int minLength) Adds a ContourLevel.
ArrayList **addContourLevel**(ContourLevel level, Wcs wcs, Color color) addContourLevel(ContourLevel level, Wcs wcs, Color color)
ImageFigure **addContour**(Contour contour, Color color, int minLength) Adds a Contour.
ImageFigure **addContour**(Contour contour, Color color) Adds a Contour
ImageFigure **addContour**(Contour contour, Wcs wcs, Color color, int minLength) Adds a Contour.
ImageFigure **addContour**(Contour contour, Wcs wcs, Color color) Adds a Contour.
ArrayList **addPositionList**(PositionList positionList, Color color) Overlays the given source list on this Display,
ArrayList **addPositionList**(PositionList positionList) Overlays the given source list on this Display,
ArrayList **showAxes**(boolean showAxis) Enables or disables the axes for the displayed image.
ImageAxis **getLeftaxis**() Returns the left axis.
ImageAxis **getRightaxis**() Returns the right axis.
ImageAxis **getBottomaxis**() Returns the bottom axis.
ImageAxis **getTopaxis**() Returns the top axis.
ArrayList **getAxes**() Returns an array with the axes.
addAxis(String label, Position orientation) Adds new axis.
deleteAxis(ImageAxis axis) Deletes the given axis.
close() Closes the display.
editColors()

Methods
Edit the colors using a popup.
editCutLevels() Edit the cut levels using a popup.
String **getColortable**() Returns the name of the color table.
double[] **getCutLevels**() Returns the cut levels.
Image **getImage**() Returns the displayed image.
RgbImage **getRgbImage**() Returns the displayed image.
double[] **getPixelCoordinates**(double c1, double c2) Returns the image coordinates
Number **getIntensity**(int row, int column) Returns the intensity of the pixel
Number **getIntensityFromWorldCoordinates**(double c1, double c2) Returns the intensity of the pixel.
Unit **getUnit**() Returns the unit.
float **getZoomFactor**() Returns the used zoom factor.
printDialog() Opens a printer dialog.
getPrintControl() Returns the printControl.
createPrintJob() Creates a print job.
PrinterJob **getPrintJob**() Returns the printer job.
setPrintJob(PrinterJob job) Sets a printer job.
print(String path) Print the displayed image to a ps file.
print(HashPrintRequestAttributeSet attributes) Print the displayed image to a ps file.
print(String path, String orientation) Prints the displayed image to a ps file.
save() Pops up a dialog to save your image.
saveAsJPG(String filename) Saves the display as a jpg file.

Methods
saveAsPS(String filename) Saves the display as a ps file.
saveScreenshot(String filename) Save the file as a screenshot.
saveCurrentView(String filename) Saves the current view of the image.
setColortable(String colortableName) Sets the color table.
setColortable(String colortableName, String intensityName) Sets the color table.
setColortable(String colortableName, String intensityName, String scaleName) Sets the color table.
setCutLevels(double percent) Sets the cut levels.
setCutLevels(double min, double max) Sets the cut levels.
setCutLevels() Sets the cut levels.
setCutLevels(double[] minmax) Sets the cut levels
setUnit(Unit u) Sets the unit.
setZoomFactor(float zoomFactor) Sets the zoom factor.
zoom(double row, double column, float zoomFactor) Zooms the image.
zoomWorldCoordinates(double ra, double decl, float zoomFactor) Zooms the image.
zoomIn() Zooms the image in.
zoomOut() Zoom the image out.
zoomFit() Zoom the image.
flipYAxis() Flips the y axis of the displayed image.
setFlipYAxis(boolean flipAxis) Sets whether the current image should be flipped.
getFlipYAxis() Returns whether the Y axis is flipped.
isFlipped()

Methods
Returns whether the current layer is flipped.
setDepthAxis(int depthAxis) Sets the depth axis for cubes.
getDepthAxis() Returns the depth axis for cubes.

API details

Constructors

Display()

The standard constructor

The standard constructor for Display. This constructor shows an empty display window.

Display(boolean useAsComponent, boolean imageVisible)

A Display constructor

A constructor where you have the possibility to display the image in the background (which means the image will not be shown) or to use the display as a component to include in a gui in jide.

Arguments

boolean **useAsComponent** [INPUT, MANDATORY]

boolean **imageVisible** [INPUT, MANDATORY]

Display(boolean useAsComponent)

A constructor to use Display as a component.

A constructor where you have the possibility to use the display as a component to include in a gui in jide.

Argument

boolean **useAsComponent** [INPUT, MANDATORY]

Example

Example how to use Display as a component

```
from javax.swing import * from java.awt import BorderLayout
dc = Display(True)
frame = JFrame()
frame.setTitle("Image display using Components")
frame.setSize(800, 600) # The main component, with the image
component = dc.getComponent()
# The zoom, panner, status and colorbar components
zoomComponent = dc.getZoomComponent()
pannerComponent = dc.getPannerComponent()
statusComponent = dc.getStatusPanelComponent()
colorbarComponent = dc.getColorBarComponent()
# Adding the components to the frame
frame.getContentPane().add(component, BorderLayout.CENTER)
frame.getContentPane().add(statusComponent, BorderLayout.NORTH)
frame.getContentPane().add(colorbarComponent, BorderLayout.SOUTH)
frame.show()
dc.setImage(image)
```

Display(Image imds)

A constructor which displays an Image.

A constructor which immediately displays the given Image.

Argument

`Image` **`imds`** `[INPUT, MANDATORY]`

Display(Cube cube)

A constructor which displays a Cube.

A constructor which immediately displays the given Cube.

Argument

`Cube` **`cube`** `[INPUT, MANDATORY]`

Display(Stack stack)

A constructor which displays a Stack.

A constructor which immediately displays the given Stack.

Argument

`Stack` **`stack`** `[INPUT, MANDATORY]`

Display(RgbImage imds)

A constructor which displays an RgbImage.

A constructor which immediately displays the given RgbImage.

Argument

`RgbImage` **`imds`** `[INPUT, MANDATORY]`

Display(Image imds, boolean imageVisible)

A Display constructor

A constructor which immediately displays the given Image. It is possible to not yet display the Image.

Arguments

`Image` **`imds`** `[INPUT, MANDATORY]`

`boolean` **`imageVisible`** `[INPUT, MANDATORY]`

Display(Cube imds, boolean imageVisible)

A Display constructor

A constructor which immediately displays the given Cube. It is possible to not yet display the Cube.

Arguments

`Cube` **`imds`** `[INPUT, MANDATORY]`

`boolean` **`imageVisible`** `[INPUT, MANDATORY]`

Display(Stack stack, boolean imageVisible)

A Display constructor

Display(Stack stack, boolean imageVisible)

A constructor which immediately displays the given Stack. It is possible to not yet display the Stack.

Arguments

```
Stack stack [INPUT, MANDATORY]
boolean imageVisible [INPUT, MANDATORY]
```

Display(Array2dData data)

A constructor to display a Numeric2d.

A constructor which immediately displays the given numeric2d

Argument

```
Array2dData data [INPUT, MANDATORY]
```

Display(Array2dData data, boolean imageVisible)

A Display constructor

A constructor which immediately displays the given numeric2d. It is possible to not yet display the image.

Arguments

```
Array2dData data [INPUT, MANDATORY]
boolean imageVisible [INPUT, MANDATORY]
```

Display(Array3dData data)

A constructor to display a numeric3d

A constructor which immediately displays the given numeric3d

Argument

```
Array3dData data [INPUT, MANDATORY]
```

Display(Array3dData data, boolean imageVisible)

A display constructor

A constructor which immediately displays the given numeric3d

Arguments

```
Array3dData data [INPUT, MANDATORY]
boolean imageVisible [INPUT, MANDATORY]
```

Methods

int getLayerShown()

Returns the number of the shown layer

Returns the number of the layer which is shown.

Return

int

int getLayerShown()

The number of the layer which is shown.

setVisible(boolean imageVisible)

Toggles the display visible or invisible.

Toggles the imageDisplay visible or invisible. True to make the image visible, False to hide the image.

Argument

`boolean` **`imageVisible`** `[INPUT, MANDATORY]`

JPanel getComposedComponent()

Returns a panel with all components of this Display on it.

Returns a panel with all components of this Display on it.

Return

JPanel

Returns a panel with all component of this Display on it.

ImageColorbar getColorBarComponent()

Returns the color bar component.

Returns a JComponent that contains the color bar. The color bar can be used to create your own component based Display.

Return

ImageColorbar

The ImageColorbar to use in you own components.

DivaMainImageDisplay getComponent()

Returns the component where the image is displayed.

Returns the component where the image is shown. This can be used to make your own GUI's with an image.

Return

DivaMainImageDisplay

The component to use in your own GUI's

Example

Example on how to integrate Display in your own GUI.

```
from javax.swing import * from java.awt import BorderLayout
dc = Display(True)
frame = JFrame() frame.setTitle("Image display using Components")
frame.setSize(800, 600)
# The main component, with the image
component = dc.getComponent()
# The zoom, panner, status and colorbar components
zoomComponent = dc.getZoomComponent()
pannerComponent = dc.getPannerComponent()
```

DivaMainImageDisplay getComponent()

```
statusComponent = dc.getStatusPanelComponent()
colorbarComponent = dc.getColorBarComponent()
# Adding the components to the frame
frame.getContentPane().add(component, BorderLayout.CENTER)
frame.getContentPane().add(statusComponent, BorderLayout.NORTH)
frame.getContentPane().add(colorbarComponent, BorderLayout.SOUTH)
frame.show()
dc.setImage(image)
```

ImagePanner getPannerComponent()

Returns the panner component with the overview of the image.

Returns the component which contains the overview of the image (100x100). This can be used to make your own GUI's with an image.

Return

ImagePanner

The component with the overview to use in your own GUI's

StatusPanel getStatusPanelComponent()

Returns the component with the status panel.

Returns the component which contains the status bar of the image. The status exists of zoom buttons, magnification, pixel coordinates, pixel intensity and sky coordinates. This can be used to make your own GUI's with an image.

Return

StatusPanel

The component with the status panel to use in your own GUI's

setStatusPanelComponent(StatusPanel imageDisplayStatusPanel)

Set a new status panel for the display.

Attaches a new status panel to the display.

Argument

StatusPanel **imageDisplayStatusPanel** [INPUT, MANDATORY]

ImageZoom getZoomComponent()

Returns the component with the zoomed view.

Returns the component which contains the a zoomed view of the image. The zoomed view has a zoom factor of 4. This component can be used to make your own GUI's with an image.

Return

ImageZoom

The component with the zoomed view to use in your own GUI's

setImage(Array2dData imageData)

Set a new numeric2d image.

setImage(Array2dData imageData)

Sets a new image on the display. A Bool2d, Int2d, Double2d, ... can be used.

Argument

`Array2dData` **`imageData`** `[INPUT, MANDATORY]`

setImage(Array3dData imageData)

Sets a new numeric3d image.

Shows a new image on the display. A Bool3d, Int3d, Double3d, ... can be used. The first image is show, the other images are used as extra layers.

Argument

`Array3dData` **`imageData`** `[INPUT, MANDATORY]`

setImage(Image imds)

Sets a new Image to Display.

Shows a new image on the display. The world-coordinate system of the Image is used.

Argument

`Image` **`imds`** `[INPUT, MANDATORY]`

setImage(Cube cube)

Sets a new cube to display.

A Cube is shown on the display. The world-coordinate system of the Cube is used.

Argument

`Cube` **`cube`** `[INPUT, MANDATORY]`

setImage(Stack stack)

Sets a new stack to display.

A Stack is shown on the display. The world-coordinate system of the Cube is used.

Argument

`Stack` **`stack`** `[INPUT, MANDATORY]`

setImage(RgbImage imds)

Sets a new RgbImage to Display.

Shows a new image on the display.

Argument

`RgbImage` **`imds`** `[INPUT, MANDATORY]`

addLayer(Layer layer)

Adds a new layer to the display.

Adds a new layer to the display. A Layer must be constructed before.

Argument

`Layer` **`layer`** `[INPUT, MANDATORY]`

addLayer(Array2dData imageData)

Adds a new layer with numeric2d data

Adds a new layer to the display. A Bool2d, Int2d, Double2d, ... can be used.

Argument

`Array2dData` **`imageData`** `[INPUT, MANDATORY]`

addLayer(Array3dData imageData)

Adds a new layer with numeric3d data

Adds new layers to the display. A Bool3d, Int3d, Double3d, ... can be used.

Argument

`Array3dData` **`imageData`** `[INPUT, MANDATORY]`

addLayer(Image imds)

Adds a new layer with an Image to the display.

Adds a new layer to the display. An Image is added as extra layer of the display.

Argument

`Image` **`imds`** `[INPUT, MANDATORY]`

addLayer(RgbImage imds)

Adds a new layer with an RgbImage to the display.

Adds a new layer to the display. An RgbImage is added as extra layer of the display.

Argument

`RgbImage` **`imds`** `[INPUT, MANDATORY]`

addLayer(Cube cube)

Adds a new layer with a Cube to the display.

Adds a new layer to the display. A Cube is added as extra layer of the display.

Argument

`Cube` **`cube`** `[INPUT, MANDATORY]`

addLayer(Stack stack)

Adds a new layer with a Stack to the display.

Adds a new layer to the display. A Stack is added as extra layer of the display.

Argument

`Stack` **`stack`** `[INPUT, MANDATORY]`

Layer getLayer()

Returns the shown layer.

Returns the Layer that is shown.

Return

Layer

Layer getLayer()

The layer that is shown at the moment.

Layer getLayer(int i)

Returns the Layer object

The Layer with the given index is returned.

Argument

`int` **`i`** `[INPUT, MANDATORY]`

Return

Layer

The layer with the given index.

showLayer(int i)

Shows a chosen layer.

Shows the Layer with the given index. The Layer with the given index is shown.

Argument

`int` **`i`** `[INPUT, MANDATORY]`

removeLayer()

Removes the current layer.

Removes the Layer that is shown.

removeLayer(int i)

Removes a layer.

Removes the given Layer.

Argument

`int` **`i`** `[INPUT, MANDATORY]`

updateImage(Array2dData imageData)

Updates the layer with numeric2d data.

Updates the layer of the image that is displayed. A numeric2d will be used as input for the new layer. The annotations, cut levels and zoom factor are kept.

Argument

`Array2dData` **`imageData`** `[INPUT, MANDATORY]`

updateImage(Image imds)

Updates the layer with an Image.

Updates the layer of the image that is displayed. An Image will be used as input for the new layer. The annotations, cut levels and zoom factor are kept.

Argument

`Image` **`imds`** `[INPUT, MANDATORY]`

updateImage(RgbImage imds)

Updates the layer with an Image.

Updates the layer of the image that is displayed. An RgbImage will be used as input for the new layer. The annotations, cut levels and zoom factor are kept.

Argument

`RgbImage` **`imds`** `[INPUT, MANDATORY]`

updateImage(Array3dData imageData)

Updates the layer with numeric3d data.

Updates the layer of the image that is displayed. A numeric3d will be used as input for the new layer. The annotations, cut levels and zoom factor are kept.

Argument

`Array3dData` **`imageData`** `[INPUT, MANDATORY]`

updateImage(Cube imds)

Updates the layer with a cube.

Updates the layer of the image that is displayed. A cube will be used as input for the new layer. The annotations, cut levels and zoom factor are kept.

Argument

`Cube` **`imds`** `[INPUT, MANDATORY]`

updateImage(Stack stack)

Updates the layer with a stack.

Updates the layer of the image that is displayed. A Stack will be used as input for the new layer. The annotations, cut levels and zoom factor are kept.

Argument

`Stack` **`stack`** `[INPUT, MANDATORY]`

setBackground(Color bgColor)

Sets the background color.

Changes the background of the image. The background can be black or white.

Argument

`Color` **`bgColor`** `[INPUT, MANDATORY]`

annotationToolbox()

Fires up the annotation toolbox.

Returns the AnnotationToolbox for the display. The AnnotationToolbox lets the user put annotation on the image, like ellipses, rectangles, text, ...

CanvasFigure addAnnotation(String text, double row, double column)

Adds a text annotation.

CanvasFigure addAnnotation(String text, double row, double column)

Adds a text annotation A text annotation will be placed, starting at the given pixel coordinates.

Arguments

String **text** [INPUT, MANDATORY]

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as a CanvasFigure

CanvasFigure addAnnotationWorldCoordinates(String text, double ra, double decl)

Adds a text annotation

A text annotation will be placed, starting at the given sky coordinates.

Arguments

String **text** [INPUT, MANDATORY]

double **ra** [INPUT, MANDATORY]

double **decl** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as a CanvasFigure

CanvasFigure addGreekAnnotation(String text, double row, double column)

Adds a Greek annotation

A greek text annotation will be placed, starting at the given pixel coordinates. All ascii text will be converted to greek characters : a becomes alpha, b becomes beta, ...

Arguments

String **text** [INPUT, MANDATORY]

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as a CanvasFigure

CanvasFigure addGreekAnnotationWorldCoordinates(String text, double ra, double decl)

Adds a Greek annotation

A greek text annotation will be placed, starting at the given world coordinates. All ascii text will be converted to greek characters : a becomes alpha, b becomes beta, ...

CanvasFigure addGreekAnnotationWorldCoordinates(String text, double ra, double decl)

Arguments

String **text** [INPUT, MANDATORY]

double **ra** [INPUT, MANDATORY]

double **decl** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as a CanvasFigure

Font getAnnotationFont()

Returns the default font for annotations.

Returns the font used for the annotations.

Return

Font

The font used for the annotations.

Font getAnnotationFont(double row, double column)

Returns the font for the specified annotation.

Returns the font used for the annotation that begins at the given pixel coordinates.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

Return

Font

The font used for the specified annotation.

Font getAnnotationFontWorldCoordinates(double ra, double dec)

Returns the font for the specified annotation.

Returns the font used for the annotation that begins at the given world coordinates.

Arguments

double **ra** [INPUT, MANDATORY]

double **dec** [INPUT, MANDATORY]

Return

Font

The font used for the specified annotation.

Color getAnnotationFontColor()

Returns the default color for annotations.

Color getAnnotationFontColor()

Returns the default color used for the text annotations.

Return

Color

The default color used for the text annotations.

Color getAnnotationFontColor(double row, double column)

Returns the color of the specified annotation.

Returns the font color used for the annotation that begins at the given pixel coordinates.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

Return

Color

The color used for the specified text annotation.

Color getAnnotationFontColorWorldCoordinates(double ra, double dec)

Returns the color of the specified annotation.

Returns the color used for the annotation that begins at the given world coordinates.

Arguments

double **ra** [INPUT, MANDATORY]

double **dec** [INPUT, MANDATORY]

Return

Color

The color used for the specified text annotation.

removeAnnotation(double row, double column)

Removes the specified annotation

Removes the annotation at the given pixel coordinates.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

removeAnnotationWorldCoordinates(double ra, double dec)

Remove the specified annotation.

Removes the annotation at the given world coordinates.

Arguments

double **ra** [INPUT, MANDATORY]

double **dec** [INPUT, MANDATORY]

removeAnnotation(CanvasFigure fig)

Removes the specified annotation.

Removes the given annotation.

Argument

CanvasFigure **fig** [INPUT, MANDATORY]

removeAnnotations()

Removes all annotations.

Removes all the annotations from the display.

setAnnotationFont(Font f)

Changes the font of all Annotations.

Changes the font of all annotations that are visible on the Display.

Argument

Font **f** [INPUT, MANDATORY]

setAnnotationFont(double row, double column, Font f)

Changes the font of the specified annotations.

Changes the font of the annotations which are located at the given pixel coordinates.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

Font **f** [INPUT, MANDATORY]

setAnnotationFontWorldCoordinates(double ra, double dec, Font f)

Changes the font of the specified annotations.

Changes the font of the annotations which are located at the given world coordinates.

Arguments

double **ra** [INPUT, MANDATORY]

double **dec** [INPUT, MANDATORY]

Font **f** [INPUT, MANDATORY]

setAnnotationFont(int size)

Changes the font size of all annotations.

Changes the font size of all annotations.

Argument

int **size** [INPUT, MANDATORY]

setAnnotationFont(double row, double column, int size)

Changes the font size of the specified annotations.

Changes the font size of the annotations which are located at the given pixel coordinates.

setAnnotationFont(double row, double column, int size)

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

int **size** [INPUT, MANDATORY]

setAnnotationFontWorldCoordinates(double ra, double dec, int size)

Changes the font size of the specified annotations.

Changes the font size of the annotations which are located at the given world coordinates.

Arguments

double **ra** [INPUT, MANDATORY]

double **dec** [INPUT, MANDATORY]

int **size** [INPUT, MANDATORY]

setAnnotationFontColor(Color color)

Sets the default color for annotations.

Changes the font color of all annotations.

Argument

Color **color** [INPUT, MANDATORY]

setAnnotationFontColor(double row, double column, Color color)

Sets the font color for the specified annotation.

Changes the font color of the annotations which are located at the given pixel coordinates.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

setAnnotationFontColorWorldCoordinates(double ra, double dec, Color color)

Sets the font color for the specified annotation.

Changes the font color of the annotations which are located at the given world coordinates.

Arguments

double **ra** [INPUT, MANDATORY]

double **dec** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

CanvasFigure addEllipse(double row, double column, double w, double h, float lineWidth, Color color)

Adds an ellipse.

Adds an ellipse to the image at a given place, with a given dimension, line width and color.

Arguments

CanvasFigure addEllipse(double row, double column, double w, double h, float lineWidth, Color color)

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

double **w** [INPUT, MANDATORY]

double **h** [INPUT, MANDATORY]

float **lineWidth** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as CanvasFigure

addFigure(CanvasFigure fig)

Adds a CanvasFigure

Adds the given CanvasFigure to the image.

Argument

CanvasFigure **fig** [INPUT, MANDATORY]

CanvasFigure addEllipse(double row, double column, double w, double h, float lineWidth, Color color, double positionAngle)

Adds an ellipse

Adds an ellipse to the image at a given place, with a given dimension, line width, color and position angle.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

double **w** [INPUT, MANDATORY]

double **h** [INPUT, MANDATORY]

float **lineWidth** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

double **positionAngle** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as CanvasFigure

CanvasFigure addCircle(double row, double column, double radius, float lineWidth, Color color)

Adds a circle

Adds a circle to the image at a given place, with a given dimension, line width and color.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

CanvasFigure addCircle(double row, double column, double radius, float lineWidth, Color color)

double **radius** [INPUT, MANDATORY]

float **lineWidth** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as CanvasFigure

CanvasFigure addLine(double row1, double column1, double row2, double column2, float lineWidth, Color color)

Adds a line.

Adds an line to the image at a given place, with a given line width and color.

Arguments

double **row1** [INPUT, MANDATORY]

double **column1** [INPUT, MANDATORY]

double **row2** [INPUT, MANDATORY]

double **column2** [INPUT, MANDATORY]

float **lineWidth** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as CanvasFigure

CanvasFigure addPolygon(double[] coords, float lineWidth, Color color)

Adds a polygon

Adds a polygon to the image at a given place, with a given line width and color. The coordinates should be given as [row1, column1, row2, column2, ...]

Arguments

double[] **coords** [INPUT, MANDATORY]

float **lineWidth** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as CanvasFigure

CanvasFigure addPolyline(double[] coords, float lineWidth, Color color)

Adds a polyline.

Adds a polyline to the image at a given place, with a given line width and color. The coordinates should be given as [row1, column1, row2, column2, ...]

CanvasFigure addPolyline(double[] coords, float lineWidth, Color color)

Arguments

double[] **coords** [INPUT, MANDATORY]

float **lineWidth** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as CanvasFigure

CanvasFigure addRectangle(double minRow, double minColumn, double w, double h, float lineWidth, Color color)

Adds a rectangle.

Adds an rectangle to the image at a given place, with a given dimension, line width and color.

Arguments

double **minRow** [INPUT, MANDATORY]

double **minColumn** [INPUT, MANDATORY]

double **w** [INPUT, MANDATORY]

double **h** [INPUT, MANDATORY]

float **lineWidth** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

CanvasFigure

The annotation as CanvasFigure

ArrayList addImageContour(ImageContour imageContour, ArrayList colors, int minLength)

Adds an ImageContour.

Draws the Contours of the given ImageContour in the given Color on the image (if their length is at least the given minimum length) and returns the drawn Contours as an ArrayList of ImageFigures.

Arguments

ImageContour **imageContour** [INPUT, MANDATORY]

ArrayList **colors** [INPUT, MANDATORY]

int **minLength** [INPUT, MANDATORY]

Return

ArrayList

The drawn Contours as an ArrayList of ImageFigures.

ArrayList addImageContour(ImageContour imageContour, ArrayList colors)

Adds an ImageContour.

ArrayList addImageContour(ImageContour imageContour, ArrayList colors)

Draws the Contours of the given ImageContour in the given Colors on the image and returns the drawn Contours as an ArrayList of ImageFigures.

Arguments

ImageContour **imageContour** [INPUT, MANDATORY]

ArrayList **colors** [INPUT, MANDATORY]

Return

ArrayList

Returns the drawn Contours as an ArrayList of ImageFigures.

ArrayList addWcsImageContour(ImageContour imageContour, ArrayList colors, int minLength)

Add an ImageContour.

Draws the Contours of the given ImageContour in the given Color on the image based on the Wcs (if their length is at least the given minimum length) and returns the drawn Contours as an ArrayList of ImageFigures.

Arguments

ImageContour **imageContour** [INPUT, MANDATORY]

ArrayList **colors** [INPUT, MANDATORY]

int **minLength** [INPUT, MANDATORY]

Return

ArrayList

The drawn Contours as an ArrayList of ImageFigures.

ArrayList addWcsImageContour(ImageContour imageContour, ArrayList contourColors)

Adds an ImageContour.

Draws the Contours of the given ImageContour in the given Color on the image based on the Wcs and returns the drawn Contours as an ArrayList of ImageFigures.

Arguments

ImageContour **imageContour** [INPUT, MANDATORY]

ArrayList **contourColors** [INPUT, MANDATORY]

Return

ArrayList

The drawn Contours as an ArrayList of ImageFigures.

ArrayList addContourLevel(ContourLevel contourLevel, Color contourColor, int minimumContourLength)

Adds a ContourLevel.

Draws the Contours of the given ContourLevel in the given Color on the image (if their length is at least the given minimum length) and returns the drawn Contours as an ArrayList of ImageFigures.

ArrayList addContourLevel(ContourLevel contourLevel, Color contourColor, int minimumContourLength)

Arguments

ContourLevel **contourLevel** [INPUT, MANDATORY]

Color **contourColor** [INPUT, MANDATORY]

int **minimumContourLength** [INPUT, MANDATORY]

Return

ArrayList

Returns the drawn Contours as an ArrayList of ImageFigures.

ArrayList addContourLevel(ContourLevel level, Color color)

Adds a ContourLevel.

Draws the Contours of the given ContourLevel in the given Color on the image and returns the drawn Contours as an ArrayList of ImageFigures.

Arguments

ContourLevel **level** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

ArrayList

The drawn Contours as an ArrayList of ImageFigures.

ArrayList addContourLevel(ContourLevel level, Wcs wcs, Color color, int minLength)

Adds a ContourLevel.

Draws the Contours of the given ContourLevel in the given Color on the image (if their length is at least the given minimum length) and returns the drawn Contours as an ArrayList of ImageFigures.

Arguments

ContourLevel **level** [INPUT, MANDATORY]

Wcs **wcs** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

int **minLength** [INPUT, MANDATORY]

Return

ArrayList

Returns the drawn Contours as an ArrayList of ImageFigures.

ArrayList addContourLevel(ContourLevel level, Wcs wcs, Color color)

addContourLevel(ContourLevel level, Wcs wcs, Color color)

Draws the Contours of the given ContourLevel in the given Color on the image and returns the drawn Contours as an ArrayList of ImageFigures.

Arguments

ArrayList addContourLevel(ContourLevel level, Wcs wcs, Color color)

ContourLevel **level** [INPUT, MANDATORY]

Wcs **wcs** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

ArrayList

Returns the drawn Contours as an ArrayList of ImageFigures.

ImageFigure addContour(Contour contour, Color color, int minLength)

Adds a Contour.

Draws the given Contour on the image (if its length is at least the given minimum length) and returns the drawn Contour as an ImageFigure.

Arguments

Contour **contour** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

int **minLength** [INPUT, MANDATORY]

Return

ImageFigure

Returns the drawn Contour as an ImageFigure.

ImageFigure addContour(Contour contour, Color color)

Adds a Contour

Draws the given Contour in the given Color on the image and returns the drawn Contour as an ImageFigure.

Arguments

Contour **contour** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

ImageFigure

Returns the drawn Contour as an ImageFigure.

ImageFigure addContour(Contour contour, Wcs wcs, Color color, int minLength)

Adds a Contour.

Draws the given Contour in the given Color on the image (if its length is at least the given minimum length) based on the Wcs and returns the drawn Contour as an ImageFigure.

Arguments

Contour **contour** [INPUT, MANDATORY]

Wcs **wcs** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

ImageFigure addContour(Contour contour, Wcs wcs, Color color, int minLength)

int **minLength** [INPUT, MANDATORY]

Return

ImageFigure

Returns the drawn Contour as an ImageFigure.

ImageFigure addContour(Contour contour, Wcs wcs, Color color)

Adds a Contour.

Draws the given Contour in the given Color on the image based on the Wcs and returns the drawn Contour as an ImageFigure.

Arguments

Contour **contour** [INPUT, MANDATORY]

Wcs **wcs** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

ImageFigure

Returns the drawn Contour as an ImageFigure.

ArrayList addPositionList(PositionList positionList, Color color)

Overlays the given source list on this Display,

in the given color.

Arguments

PositionList **positionList** [INPUT, MANDATORY]

Color **color** [INPUT, MANDATORY]

Return

ArrayList

Returns a list of sources.

ArrayList addPositionList(PositionList positionList)

Overlays the given source list on this Display,

in the given color.

Argument

PositionList **positionList** [INPUT, MANDATORY]

Return

ArrayList

Returns a list of sources.

ArrayList showAxes(boolean showAxis)

Enables or disables the axes for the displayed image.

ArrayList showAxes(boolean showAxis)

Enables or disables the axes for the displayed image. If the parameter is true, two axes are drawn, one on the left side and one at the bottom. An array with the axes is returned.

Argument

`boolean` **showAxis** `[INPUT, MANDATORY]`

Return

ArrayList

An ArrayList with the axes.

ImageAxis getLeftaxis()

Returns the left axis.

Returns the left axis of the Display. If there is no left axis, the standard left axis is made, shown and returned.

Return

ImageAxis

The left axis

ImageAxis getRightaxis()

Returns the right axis.

Returns the right axis of the Display. If there is no right axis, the standard right axis is made, shown and returned.

Return

ImageAxis

The right axis

ImageAxis getBottomaxis()

Returns the bottom axis.

Returns the bottom axis of the Display. If there is no bottom axis, the standard bottom axis is made, shown and returned.

Return

ImageAxis

The bottom axis

ImageAxis getTopaxis()

Returns the top axis.

Returns the top axis of the Display. If there is no top axis, the standard top axis is made, shown and returned.

Return

ImageAxis

ImageAxis getTopaxis()

The top axis

ArrayList getAxes()

Returns an array with the axes.

Returns an array with the axes. Using methods on the Axes, the appearance can be changed.

Return

ArrayList

An ArrayList with the Axes.

addAxis(String label, Position orientation)

Adds new axis.

Adds a new axis.

Arguments

String **label** [INPUT, MANDATORY]

Position **orientation** [INPUT, MANDATORY]

deleteAxis(ImageAxis axis)

Deletes the given axis.

Deletes the given axis.

Argument

ImageAxis **axis** [INPUT, MANDATORY]

close()

Closes the display.

Closes the display and frees the memory.

editColors()

Edit the colors using a popup.

A windows opens where you can change the color table, intensity and scale.

editCutLevels()

Edit the cut levels using a popup.

A windows opens where you can set the cut levels of the image.

String getColortable()

Returns the name of the color table.

Returns the name of the color table

Return

String

String getColortable()

The name of the color table

double[] getCutLevels()

Returns the cut levels.

Returns an array with the cut levels of the displayed image.

Return

double[]

The cut levels of the displayed image.

Image getImage()

Returns the displayed image.

Returns the displayed Image.

Return

Image

The displayed Image

RgbImage getRgbImage()

Returns the displayed image.

Returns the displayed Image.

Return

RgbImage

The displayed Image

double[] getPixelCoordinates(double c1, double c2)

Returns the image coordinates

Returns the image coordinates of the given world coordinates

Arguments

`double` **`c1`** `[INPUT, MANDATORY]`

`double` **`c2`** `[INPUT, MANDATORY]`

Return

double[]

The corresponding image coordinates as a 2 dimensional array of doubles, the first one describing the row and the second the column.

Number getIntensity(int row, int column)

Returns the intensity of the pixel

Returns the intensity of the pixel with given pixel coordinates

Number getIntensity(int row, int column)

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

The intensity of the given pixel

Number getIntensityFromWorldCoordinates(double c1, double c2)

Returns the intensity of the pixel.

Returns the intensity of the pixel with given world coordinates.

Arguments

`double` **`c1`** `[INPUT, MANDATORY]`

`double` **`c2`** `[INPUT, MANDATORY]`

Return

Number

double The intensity of the given pixel.

Unit getUnit()

Returns the unit.

Returns the unit of the image

Return

Unit

The unit of the image.

float getZoomFactor()

Returns the used zoom factor.

Returns the used zoom factor. The returned zoomfactor is bigger than 1 if the image is zoomed in, otherwise, the zoomfactor is between 0 and 1

Return

float

The zoomfactor of the displayed image.

printDialog()

Opens a printer dialog.

A dialog is opened where you can choice the printer, number of copies, page setup and appearance.

getPrintControl()

Returns the printControl.

getPrintControl()

Returns the printControl to make it possible to print using the command line.

Example

How to print from the command line

```
job = d.getPrintJob()
job.setCopies(2) # Set the number of copies
pservices = job.lookupPrintServices()
job.setPrintService(pservices[3]) #Use the printer of choice
d.setPrintJob(job)
job.print()
```

createPrintJob()

Creates a print job.

Creates a print job.

PrinterJob getPrintJob()

Returns the printer job.

Returns the printer job.

Return

PrinterJob

The printerJob.

setPrintJob(PrinterJob job)

Sets a printer job.

Set a given printer job.

Argument

PrinterJob **job** [INPUT, MANDATORY]

print(String path)

Print the displayed image to a ps file.

Prints the displayed image to a ps file. The settings can be changed with the method setPrintJob(job) or with the GUI obtained from the method createPrintJob()

Argument

String **path** [INPUT, MANDATORY]

print(HashPrintRequestAttributeSet attributes)

Print the displayed image to a ps file.

Prints the displayed image to a ps file.

Argument

HashPrintRequestAttributeSet **attributes** [INPUT, MANDATORY]

print(String path, String orientation)

Prints the displayed image to a ps file.

print(String path, String orientation)

Prints the displayed image to a ps file. The settings can be changed with the method setPrintJob(job) or with the GUI obtained from the method createPrintJob() The orientation of the page can be "landscape" (or "l"), "portrait" (or "p"), "reverse_landscape" (or "rl"), "reverse_portrait" (or "rp")

Arguments

`String` **path** [INPUT, MANDATORY]

`String` **orientation** [INPUT, MANDATORY]

save()

Pops up a dialog to save your image.

Pops up a file chooser and saves the image as fits, jpeg, tiff, png or bmp file.

saveAsJPG(String filename)

Saves the display as a jpg file.

Saves the display as a jpg file.

Argument

`String` **filename** [INPUT, MANDATORY]

saveAsPS(String filename)

Saves the display as a ps file.

Saves the display as a ps file.

Argument

`String` **filename** [INPUT, MANDATORY]

saveScreenshot(String filename)

Save the file as a screenshot.

Saves the file as screenshot. Saves the display as jpg, png, tiff, bmp or FITS.

Argument

`String` **filename** [INPUT, MANDATORY]

saveCurrentView(String filename)

Saves the current view of the image.

Saves the view as screenshot. The annotations are also saved!

Argument

`String` **filename** [INPUT, MANDATORY]

setColortable(String colortableName)

Sets the color table.

Sets the color table of the displayed image.

Argument

setColortable(String colortableName)

String **colortableName** [INPUT, MANDATORY]

setColortable(String colortableName, String intensityName)

Sets the color table.

Sets the colortable of the displayed image.

Arguments

String **colortableName** [INPUT, MANDATORY]

String **intensityName** [INPUT, MANDATORY]

setColortable(String colortableName, String intensityName, String scaleName)

Sets the color table.

Sets the colortable Sets the colortable of the displayed image

Arguments

String **colortableName** [INPUT, MANDATORY]

String **intensityName** [INPUT, MANDATORY]

String **scaleName** [INPUT, MANDATORY]

setCutLevels(double percent)

Sets the cut levels.

Sets the cut level of the displayed image.

Argument

double **percent** [INPUT, MANDATORY]

setCutLevels(double min, double max)

Sets the cut levels.

Sets the cut level of the displayed image.

Arguments

double **min** [INPUT, MANDATORY]

double **max** [INPUT, MANDATORY]

setCutLevels()

Sets the cut levels.

Sets the cut level of the displayed image.

setCutLevels(double[] minmax)

Sets the cut levels

Sets the cut level of the displayed image.

Argument

double[] **minmax** [INPUT, MANDATORY]

setUnit(Unit u)

Sets the unit.

Sets the unit of the displayed image.

Argument

`Unit` **`u`** `[INPUT, MANDATORY]`

setZoomFactor(float zoomFactor)

Sets the zoom factor.

Sets the zoomfactor of the displayed image.

Argument

`float` **`zoomFactor`** `[INPUT, MANDATORY]`

zoom(double row, double column, float zoomFactor)

Zooms the image.

Sets the zoomfactor of the displayed image and the coordinates which should appear in the center of the image.

Arguments

`double` **`row`** `[INPUT, MANDATORY]`

`double` **`column`** `[INPUT, MANDATORY]`

`float` **`zoomFactor`** `[INPUT, MANDATORY]`

zoomWorldCoordinates(double ra, double decl, float zoomFactor)

Zooms the image.

Sets the zoomfactor of the displayed image and the coordinates which should appear in the center of the image.

Arguments

`double` **`ra`** `[INPUT, MANDATORY]`

`double` **`decl`** `[INPUT, MANDATORY]`

`float` **`zoomFactor`** `[INPUT, MANDATORY]`

zoomIn()

Zooms the image in.

Zooms the displayed image. The zoom factor changes the following way : ...1/8, 1/4, 1/2, 1, 2, 4, 8, ...

zoomOut()

Zoom the image out.

Zooms the displayed image out. The zoom factor changes the following way : ..., 8, 4, 2, 1, 1/2, 1/4, 1/8, ...

zoomFit()

Zoom the image.

zoomFit()

Zooms the image to a zoomfactor so that the image is shown in total on the screen. Axes are taken into account

flipYAxis()

Flips the y axis of the displayed image.

If this method is called, the current axis is flipped. If the displayed image has the WCS keyword flipy, this method will have no effect.

setFlipYAxis(boolean flipAxis)

Sets whether the current image should be flipped.

The current image will be flipped.

Argument

`boolean` **`flipAxis`** `[INPUT, MANDATORY]`

getFlipYAxis()

Returns whether the Y axis is flipped.

Returns true if the current image is flipped.

isFlipped()

Returns whether the current layer is flipped.

Returns true if the current layer is flipped.

setDepthAxis(int depthAxis)

Sets the depth axis for cubes.

Set the depth axis for the current and newly added cubes. The first axis (0) is the standard depth axis.

Argument

`int` **`depthAxis`** `[INPUT, MANDATORY]`

getDepthAxis()

Returns the depth axis for cubes.

Returns which axis is the depth axis.

See also

- SimpleImage
- SimpleCube

2.94. displaylog

Full Name:	herschel.ia.toolbox.util.DisplayLogTask
Alias:	displaylog
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import DisplayLogTask
Category:	task

Description

Open a window displying log messages

The display task is used to open a log window handler and assign it to a log

Examples

Example 1: attach the window to a logger

```
# create a logger
log=java.util.logging.Logger.getLogger("")
# display the logger in the window
displaylog(log)
# sending logs
log.info("ahh, an info message")
log.warning("ehm, a warning message")
log.severe("oops! a severe message")
```

Example 2: remove the window attached to a logger

```
# create a logger
log=java.util.logging.Logger.getLogger("")
# display the logger in the window
displaylog(log)
# sending logs
log.info("ahh, an info message")
# stop displaing messages from log by removing it from the window
displaylog(log, option="remove")
# no displaied any longer
log.info("ahh, an new info message")
```

Example 3: change the size (number of lines to be displaied) in the window

```
displaylog(option="change", size=8000)
```

API Summary

Jython Syntax

```
displaylog(logger)
```

Properties

`Logger logger [INPUT, No, default=java.util.logging.Logger.getLogger("")]`
`String option [INPUT, No, default="add"]`
`Integer size [INPUT, No, default=4096]`

Limitations

No time buffering, logs could clutter the java window system

Miscellaneous

No miscellaneous

API details

Properties

`Logger logger [INPUT, No, default=java.util.logging.Logger.getLogger("")]`

The log to display the messages into the window

`String option [INPUT, No, default="add"]`

Specify the action to be taken, default value is "add" which enables the display for the specified logger, the "remove" option stops displaying messages for an attached logger, the "change" option works in pair with parameter size.

`Integer size [INPUT, No, default=4096]`

Specify the number of lines to be displaied in the window, the parameter is effectively set up *only* if the "change" value for the parameter "option" is specified

History

- `2007-01-26 - NdC`: first release

2.95. displayQCLog

Full Name:	herschel.ia.qcp.DisplayQCLogTask
Alias:	displayQCLog
Type:	Java Task -
Import:	from herschel.ia.qcp import DisplayQCLogTask
Category:	task

Description

Open a window displaying QClLogs messages organized in a product

The show task is used to open a log window handler and assign it to a log

Example

Example 1: display the QCLog

```
displayQCLog()
```

Limitations

No time buffering, logs could clutter the java window system

Miscellaneous

No miscellaneous

History

- `2007-03-22 - NdC`: first release

2.96. DivideSpectrum

Full Name:	herschel.ia.toolbox.spectrum.DivideSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import DivideSpectrum

Description

Task for dividing the flux data included in a spectrum container by a scalar or for dividing two spectrum containers on a spectrum-by-spectrum basis by each other.

For the scalar mode, 'ds' and 'param' need to specified - for the pair-wise mode, 'ds1' and 'ds2' need to be set. In the pairwise mode, the task iterates through the two containers and computes the pair-operation. In case the size of the two containers is different, the iteration stops at the minimum size. Hence, the remaining spectra in the larger container are ignored. In case one of the datasets only contains a single spectrum, the task always refers to this single spectrum while iterating over all the spectra in the other dataset.

Different selection schemes are available for selecting the point spectra or the segments to be processed. The most simple scheme is to specify lists of point spectrum indices (`selection=[1,3,4,2]`). In this case, the operation (scalar- or pair-operation) is just taken over the point spectra with corresponding indices. Instead of specifying a list of indices (which requires the knowledge of these) other recipes to specify a selection are available. Typical recipes test attribute values to match certain values or to be included in a given interval. These recipes we refer to as selection models. The different options to specify selections can be combined. Here, an AND logic is adopted.

Similarly, you can specify what segments to consider. In the most simple case, you can just specify the indices of segments to be considered (for the scalar operation `segments=[1,3,4]` and for the pair operation `segments1=[1,3,4], segments1=[3,6,5]`). In more advanced situations you can use a `SegmentSelection` object. Note that the pairs of segments to be processed need to be consistent - otherwise the processing will fail.

You can specify whether the orginal datasets should be overwritten with the 'overwrite' flag. By default no data is overwritten. In the pair-wise mode, it is not always possible to overwrite the data - in particular if non-trivial segment selections are specified.

For the pair-wise mode, there are further options that can be selected by the 'variant' (e.g. whether to use flags and weights).

Example

Example 1: from Jide:

```
from herschel.ia.toolbox.spectrum import DivideSpectrum
divide = DivideSpectrum()
dividedByFactor = divide(ds=spectra, param=2.1)
dividedByFactor = divide(ds=spectra, selection={"bbtype":[6031]}, param=2.1)
dividedByFactor = divide(ds=spectra, selection=[0,1,2,3], param=2.1)
dividedByFactor = divide(ds=spectra, selection={"Chopper":
([-4.4,5.9],0.2), -"bbtype":[6031]}, param=2.1)
dividedByFactor = divide(ds=spectra, selection={"LoFrequency":
(4000.0,5000.0)}, param=2.1)
dividedPairWise = divide(ds1=spectra1, ds2=spectra2)
dividedPairWise = divide(ds1=spectra1, ds2=spectra2, selection={"bbtype":
[6031]})
dividedPairWise = divide(ds1=spectra1, ds2=spectra2, selection=[0,1,2,3])
dividedPairWise = divide(ds1=spectra1, ds2=spectra2, selection={"Chopper":
([-4.4,5.9],0.2), -"bbtype":[6031]})
```

Example 1: from Jide:

```
dividedPairWise = divide(ds1=spectra1, ds2=spectra2, selection={"LoFrequency":
(4000.0,5000.0)})
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, OPTIONAL, default=no default value.]
Double **param** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection_lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection_index** [INPUT, OPTIONAL, default=No default value.]
Boolean **overwrite** [INPUT, OPTIONAL, default=False.]
SpectrumContainer **ds1** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **ds2** [INPUT, OPTIONAL, default=no default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Object **segments1** [INPUT, OPTIONAL, default=no default value.]
Object **segments2** [INPUT, OPTIONAL, default=no default value.]
String **variant** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

SpectrumContainer ds [INPUT, OPTIONAL, default=no default value.]

Input container to be processed by the task in case the task is used as a scalar operation.

Double param [INPUT, OPTIONAL, default=no default value.]

The scalar parameter to be considered when the task is used as scalar operation.

Object selection [INPUT, OPTIONAL, default=None.]

Specify what point spectra the operation should be applied to. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra for which the add should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

Boolean overwrite [INPUT, OPTIONAL, default=False.]

Specify whether the input data container can be reused - the values found therein is overwritten.

SpectrumContainer ds1 [INPUT, OPTIONAL, default=no default value.]

First input container for pair-wise operations.

SpectrumContainer ds2 [INPUT, OPTIONAL, default=no default value.]

Second input container for pair-wise operations.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments the operation should be applied to. There are two options available:

- Either pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.
- Specify a PyList of segment indices.

Object segments1 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds1'.

Object segments2 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds2'.

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-wave" / "flux-wave-weight" / "flux-flag-wave" / "flux-weight-flag-wave"

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

See also

- SpectrumTask

History

- `2007-08-17 - meli`: initial.

- `2008-03-16 - meli`: major refactoring of the toolbox.
- `2008-10-03 - meli`: segments, javadoc

2.97. Double1d

Full Name:	herschel.ia.numeric.Double1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Double1d

Description

A rectangular numeric double array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.98. Double2d

Full Name:	herschel.ia.numeric.Double2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Double2d

Description

A rectangular numeric double array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.99. Double3d

Full Name:	herschel.ia.numeric.Double3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Double3d

Description

A rectangular numeric double array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.100. Double4d

Full Name:	herschel.ia.numeric.Double4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Double4d

Description

A rectangular numeric double array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.101. Double5d

Full Name:	herschel.ia.numeric.Double5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Double5d

Description

A rectangular numeric double array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.102. EigenvalueDecomposition

Full Name:	herschel.ia.numeric.toolbox.matrix.EigenvalueDecomposition
Alias:	EigenvalueDecomposition
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import EigenvalueDecomposition

Example

Example 1: A=Double2d([[1.,1.,1.],[1.,2.,3.],[1.,3.,6.]])

```
evd=A.apply(EigenvalueDecomposition())
print evd.d
print evd.v
```

API Summary

Jython Syntax

```
A=Double2d()
evd=A.apply(EigenvalueDecomposition())
# get the eigenvalue matrix D
D = evd.d
# get the eigenvector matrix V
V = evd.v
# Get the imaginary eigenvalues
imagEigenvalues = evd.imagEigenvalues
# Get the real eigenvalues
realEigenvalues = evd.realEigenvalues
```

Property
Double2d **A** [INPUT, MANDATORY, default=no default value]

API details

Property

Double2d A [INPUT, MANDATORY, default=no default value]

Input must be a Double2d or Float2d array.

2.103. EllipseHistogramExplorer

Full Name:	herschel.ia.gui.image.EllipseHistogramExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import EllipseHistogramExplorer

Description

An explorer for EllipseHistogramProducts.

An explorer for EllipseHistogramProducts.

API Summary

Constructors
`EllipseHistogramExplorer()` The construction of a new EllipseHistogramExplorer.
`EllipseHistogramExplorer(Object object)` The construction of a new EllipseHistogramExplorer associated with the given object.

Methods
`String` **`getName()`** Returns the name.
`String` **`getDescription()`** Returns the description.
`boolean` **`canHandle(Class className)`** Checks whether this EllipseHistogramExplorer can handle objects of the given class.
`setObject(Object object)` Sets the object.
`EllipseHistogramProduct` **`getObject()`** Returns the object.
`Class` **`getVariableType()`** Returns the expected variable type.
`JScrollPane` **`getParameterTable()`** Returns the parameter table.

API details

Constructors

`EllipseHistogramExplorer()`
The construction of a new EllipseHistogramExplorer. The construction of a new EllipseHistogramExplorer.

`EllipseHistogramExplorer(Object object)`
The construction of a new EllipseHistogramExplorer associated with the given object.

EllipseHistogramExplorer(Object object)

The construciton of a new EllipseHistogramExplorer associated with the given object.

Argument

Object **object** [INPUT, MANDATORY]

Methods

String getName()

Returns the name.

Returns the name for this EllipseHistogramExplorer.

Return

String

Returns the name for this EllipseHistogramExplorer.

String getDescription()

Returns the description.

Returns the description for this EllipseHistogramExplorer.

Return

String

Returns the description for this EllipseHistogramExplorer.

boolean canHandle(Class className)

Checks whether this EllipseHistogramExplorer can handle objects of the given class.

Returns true if this EllipseHistogramExplorer can handle objects of the given class; false otherwise.

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true if this EllipseHistogramExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this EllipseHistogramExplorer to the given object.

Argument

Object **object** [INPUT, MANDATORY]

EllipseHistogramProduct getObject()

Returns the object.

`EllipseHistogramProduct getObject()`

Returns the object for this EllipseHistogramExplorer.

Return

EllipseHistogramProduct

Returns the object for this EllipseHistogramExplorer.

`Class getVariableType()`

Returns the expected variable type.

Returns the expected variable type for this EllipseHistogramExplorer.

Return

Class

Returns the expected variable type for this EllipseHistogramExplorer.

`JScrollPane getParameterTable()`

Returns the parameter table.

Returns the parameter table for this EllipseHistogramExplorer.

Return

JScrollPane

Returns the parameter table for this EllipseHistogramExplorer.

2.104. EllipseHistogramPanel

Full Name:	herschel.ia.toolbox.image.gui.EllipseHistogramPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import EllipseHistogramPanel

Description

A panel for the EllipseHistogramTask.

A panel to serve as GUI for the EllipseHistogramTask.

API Summary

Constructor
`EllipseHistogramPanel()`
The construction of a new EllipseHistogramPanel.

Methods
`drawFigure()`
Draws the ellipse on the image.
`updateFigure()`
Updates the associated ellipse.
`trigger()`
Triggers the execution of the associated task.
`updateHistogram()`
Updates the associated histogram.

API details

Constructor

`EllipseHistogramPanel()`
The construction of a new EllipseHistogramPanel. The construction of a new EllipseHistogramPanel

Methods

`drawFigure()`
Draws the ellipse on the image. Draws the ellipse on the image associated with this EllipseHistogramPanel.

`updateFigure()`
Updates the associated ellipse. Updates the ellipse associated with this EllipseHistogramPanel.

trigger()
Triggers the execution of the associated task. Triggers the execution of the task associated with this EllipseHistogramPanel.

updateHistogram()
Updates the associated histogram. Updates the histogram associated with this EllipseHistogramPanel.

2.105. EllipseHistogramProduct

Full Name:	herschel.ia.dataset.image.EllipseHistogramProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import EllipseHistogramProduct

Description

A class to deal with the results of an ellipse histogram.

API Summary

Constructor
`EllipseHistogramProduct()` The constructor of a new EllipseHistogramProduct.

Methods
`setCenter``(double centerX, double centerY)` Sets the center for this EllipseHistogramProduct
`setCenter``(double centerX, double centerY, String centerRA, String centerDec)` Sets the center for this EllipseHistogramProduct
`setDimensions``(double widthPixels, double heightPixels)` Sets the dimensions for this EllipseHistogramProduct to the
`setDimensions``(double widthPixels, double heightPixels, double widthArcsec, double heightArcsec)` Sets the dimensions for this EllipseHistogramProduct to the
`Double1d` **`getCenterPixelCoordinates`**`()` Returns the center for this EllipseHistogramProduct in
`String1d` **`getCenterSkyCoordinates`**`()` Returns the center for this EllipseHistogramProduct in
`double` **`getWidthPixels`**`()` Returns the width for this EllipseHistogramProduct in pixels.
`double` **`getWidthArcsec`**`()` Returns the width for this EllipseHistogramProduct in arcsec.
`double` **`getHeightPixels`**`()` Returns the height for this EllipseHistogramProduct in pixels.
`double` **`getHeightArcsec`**`()` Returns the height for this EllipseHistogramProduct in arcsec.

API details

Constructor

`EllipseHistogramProduct()`
The constructor of a new EllipseHistogramProduct.

Methods

setCenter(double centerX, double centerY)

Sets the center for this EllipseHistogramProduct

to the given pixel coordinates.

Arguments

double **centerX** [INPUT, MANDATORY]

double **centerY** [INPUT, MANDATORY]

setCenter(double centerX, double centerY, String centerRA, String centerDec)

Sets the center for this EllipseHistogramProduct

to the given pixel and sky coordinates.

Arguments

double **centerX** [INPUT, MANDATORY]

double **centerY** [INPUT, MANDATORY]

String **centerRA** [INPUT, MANDATORY]

String **centerDec** [INPUT, MANDATORY]

setDimensions(double widthPixels, double heightPixels)

Sets the dimensions for this EllipseHistogramProduct to the

given dimensions in pixels.

Arguments

double **widthPixels** [INPUT, MANDATORY]

double **heightPixels** [INPUT, MANDATORY]

setDimensions(double widthPixels, double heightPixels, double widthArcsec, double heightArcsec)

Sets the dimensions for this EllipseHistogramProduct to the

given dimensions in pixels and arcsec.

Arguments

double **widthPixels** [INPUT, MANDATORY]

double **heightPixels** [INPUT, MANDATORY]

double **widthArcsec** [INPUT, MANDATORY]

double **heightArcsec** [INPUT, MANDATORY]

Double1d getCenterPixelCoordinates()

Returns the center for this EllipseHistogramProduct in

pixel coordinates.

Return

Double1d

Double1d getCenterPixelCoordinates()

Returns the center for this EllipseHistogramProduct in pixel coordinates.

String1d getCenterSkyCoordinates()

Returns the center for this EllipseHistogramProduct in

sky coordinates.

Return

String1d

Returns the center for this EllipseHistogramProduct in sky coordinates.

double getWidthPixels()

Returns the width for this EllipseHistogramProduct in pixels.

Return

double

Returns the width for this EllipseHistogramProduct in pixels.

double getWidthArcsec()

Returns the width for this EllipseHistogramProduct in arcsec.

Return

double

Returns the width for this EllipseHistogramProduct in arcsec.

double getHeightPixels()

Returns the height for this EllipseHistogramProduct in pixels.

Return

double

Returns the height for this EllipseHistogramProduct in pixels.

double getHeightArcsec()

Returns the height for this EllipseHistogramProduct in arcsec.

Return

double

Returns the height for this EllipseHistogramProduct in arcsec.

2.106. EllipseHistogramTask

Full Name:	herschel.ia.toolbox.image.EllipseHistogramTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import EllipseHistogramTask

Description

A Task to make a histogram within an ellipse.

A Task to make a histogram of a region of interest, which is bounded by an ellipse.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **lowCut** [INPUT, OPTIONAL, default=Default value : NaN]
Double **highCut** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **bins** [INPUT, MANDATORY, default=Default value : new Integer(2000)]
Double **centerX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **centerY** [INPUT, OPTIONAL, default=Default value : NaN]
String **centerRA** [INPUT, OPTIONAL, default=Default value : "centerRA"]
String **centerDec** [INPUT, OPTIONAL, default=Default value : "centerDec"]
Double **widthPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **heightPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **widthArcsec** [INPUT, OPTIONAL, default=Default value : NaN]
Double **heightArcsec** [INPUT, OPTIONAL, default=Default value : NaN]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double lowCut [INPUT, OPTIONAL, default=Default value : NaN]

The lower cut level.

Double highCut [INPUT, OPTIONAL, default=Default value : NaN]

The upper cut level.

Integer bins [INPUT, MANDATORY, default=Default value : new Integer(2000)]

The number of bins.

Double centerX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the center of the ellipse.

Double centerY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the center of the ellipse.

String centerRA [INPUT, OPTIONAL, default=Default value : "centerRA"]

The right ascension of the center of the ellipse.

String centerDec [INPUT, OPTIONAL, default=Default value : "centerDec"]

The declination of the center of the ellipse.

Double widthPixels [INPUT, OPTIONAL, default=Default value : NaN]

The width of the ellipse in pixels.

Double heightPixels [INPUT, OPTIONAL, default=Default value : NaN]

The height of the ellipse in pixels.

Double widthArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The width of the ellipse in arcsec.

Double heightArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The height of the ellipse in arcsec.

2.107. Erfc

Full Name:	herschel.ia.numeric.toolbox.basic.Erfc
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Erfc

Description

Computes the Complementary Error function.

Example

Example 1: Apply ERFC on a Double1d

```
x = Double1d([-5.0,-1.0,-0.5,0.0,0.5,1.0,5.0])
erc = ERFC(x)
print erc  # [1.9999999999984626,1.8427007900291827,1.520499876068384,

1.0,0.4795001239316159,0.15729920997081737,1.5374597939680894E-12]
```

API Summary

Jython Syntax

```
<y>=ERFC(<x>)
```

Properties

an doulble array or number **x** [INPUT, MANDATORY, default=.]

returns an array (or a number if the input is a number) **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

an doulble array or number x [INPUT, MANDATORY, default=.]

returns an array (or a number if the input is a number) y [OUTPUT, MANDATORY, default=no default value]

where each element is the Complementary Error function of the corresponding element of the input array.

See also

- Erf

2.108. Erf

Full Name:	herschel.ia.numeric.toolbox.basic.Erf
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Erf

Description

Computes the Error function.

Example

Example 1: Apply ERF on a Double1d

```
x = Double1d([-5.0,-1.0,-0.5,0.0,0.5,1.0,5.0])
er = ERF(x)
print er  # [-0.9999999999984626,-0.8427007900291826,-0.5204998760683841,
            0.0,0.5204998760683841,0.8427007900291826,0.9999999999984626]
```

API Summary

Jython Syntax

```
<y>=ERF(<x>)
```

Properties

an double array or number **x** [INPUT, MANDATORY, default=.]

returns an array (or a number if the input is a number) **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

an double array or number x [INPUT, MANDATORY, default=.]

returns an array (or a number if the input is a number) y [OUTPUT, MANDATORY, default=no default value]

where each element is the Error function of the corresponding element of the input array.

See also

- Erfc

2.109. EXP10

Full Name:	herschel.ia.numeric.toolbox.basic.Exp10
Alias:	EXP10
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Exp10

Description

Gives 10 raised to the power of array x

Example

Example 1: Apply EXP10 on a Int1d

```
x=Double1d([1,2,3,4])
print EXP10(x) #  [10.0, 100.0, 1000.0, 10000.0]
```

API Summary

Jython Syntax
<y>=EXP10(<x>)

Properties
any number or array **x** [INPUT, MANDATORY, default=no default value]
a number or an array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any number or array x [INPUT, MANDATORY, default=no default value]

a number or an array y [OUTPUT, MANDATORY, default=no default value]

The result is a number or an array depending on the input

See also

- EXP10

2.110. EXP

Full Name:	herschel.ia.numeric.toolbox.basic.Exp
Alias:	EXP
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Exp

Description

Gives the exponential function applied to a number or array.

Example

Example 1: Apply EXP on a Int1d

```
x=Double1d([0,1])
print LOG(EXP(x)) #  [0.0,1.0]
```

API Summary

Jython Syntax
<y>=EXP(<x>)

Properties
any number or array **x** [INPUT, MANDATORY, default=no default value]
a number or an array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any number or array x [INPUT, MANDATORY, default=no default value]

a number or an array y [OUTPUT, MANDATORY, default=no default value]

The result is a number or an array depending on the input

See also

- LOG

2.111. ExpN

Full Name:	herschel.ia.numeric.toolbox.basic.ExpN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import ExpN

Description

Gives the specified base raised to each item array: y=ExpN base$^{(x)}$.

Example

Example 1: Apply ExpN on a Int1d

```
x=Double1d([1,2,3,4])
print ExpN(2)(x) # [2.0,4.0,8.0,16.0]
print x.apply(ExpN(2)) # [2.0,4.0,8.0,16.0]
```

API Summary

Jython Syntax

```
<y>=ExpN(<base>)(<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]
a number **base** [INPUT, MANDATORY, default=no default value]
a number or an array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

a number base [INPUT, MANDATORY, default=no default value]

The base n

a number or an array y [OUTPUT, MANDATORY, default=no default value]

The result is a number or an array depending on the input

See also

- ExpN

2.112. exportPalToUfDir

Full Name:	herschel.ia.toolbox.util.ExportPalToUfDirTask
Alias:	exportPalToUfDir
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import ExportPalToUfDirTask
Category:	task

Description

Exports observations related to an URN from a pool to a user friendly directory structure

The exportPalToUfDir task is used to export observations to a user friendly directory structure, so that they can be easily inspected, used and shared outside of HIPE.

Please note that only LocalStores and HsaReadPools can export their observations.

Example

Example 1: Simple example exportPalToUfDir(pool=poolSrc ,

```
urn="urn:poolid:herschel.ia.obs.ObservationContext:0", dirout="/exportdir1")
```

API Summary

Jython Syntax

```
exportPalToUfDir(<pool> , <urn>, <dirout> [, <warn>])
```

Properties

ProductPool **pool** [INPUT, MANDATORY, default=No default value The pool to export products from.]

String **urn** [INPUT, MANDATORY, default=No default value The urn that defines what to export]

Boolean **warn** [INPUT, OPTIONAL, default=true If true]

String **dirout** [INPUT, MANDATORY, default=No default value The directory where the observations]

Limitations

The dirout must not exist (cannot repeatedly export to the same dir).

Miscellaneous

No miscellaneous

API details

Properties

ProductPool pool [INPUT, MANDATORY, default=No default value The pool to export products from.]

String urn [INPUT, MANDATORY, default=No default value The urn that defines what to export]

Boolean warn [INPUT, OPTIONAL, default=true If true]

exists and it is not empty.

String dirout [INPUT, MANDATORY, default=No default value The directory where the observations]

will be exported with a user friendly structure

See also

- ???

History

- 2009-01-16 - JDS: initial version
- 2009-09-30 - JSS: modifiers are created through getCustomModifiers (SCR HCSS-8253)

2.113. ExtractFreqRanges

Full Name:	herschel.ia.toolbox.spectrum.ExtractFreqRanges
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import ExtractFreqRanges

Description

Task for extracting a range or ranges from the segments of one or several `SpectrumContainer`.

Different possibilities are available for specifying the ranges (see the `ranges`-parameter below. Specifying frequency intervals means that all the spectra are tested for the suitable ranges. In presence of frequency drift these ranges may be different from spectrum to spectrum. For the spectrum container the enveloping range is taken so that the all the PointSpectra included in the result container have again the same width of the segments. Here, the number of frequency intervals and the number of segments does not need to coincide. For each of the segments with a non-trivial overlap with one of the frequency intervals will lead to a segment in the result container.

Example

Example 1: from Jide

```
slices = extract(ds=spectra, segments=[1,3])
slices = extract(ds=spectra, ranges=[(4100,4400),(4600,4900),(5100,5900),
(6100,6900),(7100,7900)])
slices = extract(ds=spectra, ranges=[(4100,4400),(4600,4900),(5100,5900),
(6100,6900),(7100,7900)], selection={"bbtype":[6031]})
slices = extract(ds=spectra, ranges=[(4100,4400),(4600,4900),(5100,5900),
(6100,6900),(7100,7900)], selection={"Chopper":([-4.4,5.9],0.2)})
slices = extract(ds=spectra, ranges=[(4100,4400),(4600,4900),(5100,5900),
(6100,6900),(7100,7900)], selection=[0,1,2,3])
slices = extract(ds=spectra, ranges=[(4100,4400),(4600,4900),(5100,5900),
(6100,6900),(7100,7900)], selection={"LoFrequency":(4000.0,5000.0)})
slices = extract(ds=spectra, ranges=([4100,4600,5100,6100,7100],
[4400,4900,5900,6900,7900]))
# or in -"the old way":
min = Double1d([4100,4600,5100,6100,7100])
max = Double1d([4400,4900,5900,6900,7900])
slices = extract(ds=spectra, min=min, max=max)
```

API Summary

Properties
Object **ds** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value.]
Object **ranges** [INPUT, OPTIONAL, default=no default value.]
Double1d **minFreq** [INPUT, OPTIONAL, default=no default value.]
Double1d **maxFreq** [INPUT, OPTIONAL, default=no default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]

API details

Properties

Object ds [INPUT, OPTIONAL, default=no default value.]

Input data to be processed by the task. Several types are possible:

- SpectrumContainer
- Array of SpectrumContainer, i.e. SpectrumContainer[]
- List of SpectrumContainer, i.e. List
- Any product with implementations of `SpectrumContainer` inside.

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value.]

The resulting container created by this task.

Object ranges [INPUT, OPTIONAL, default=no default value.]

Specify the range to be extracted - either by specifying ranges of channel numbers or frequency ranges:

- Type Range[]: Range of channel numbers for each sub-segment to be extracted.
- Type Range: Range of channel numbers to be extracted (if only one segment in the data).
- Type PyList or PyTuples: Each PyTuple defines an interval on the frequency scale.
- Type PyTuple of two PyLists: The first list with the minima and the second with the maxima of the intervals on the frequency scale.

Double1d minFreq [INPUT, OPTIONAL, default=no default value.]

For each of the ranges to be extracted the minimum frequency.

Double1d maxFreq [INPUT, OPTIONAL, default=no default value.]

For each of the ranges to be extracted the maximum frequency.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments to restrict on. There are two options available:

- Specify a PyList of segment indices or
- pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.

Object selection [INPUT, OPTIONAL, default=None.]

Specify what point spectra to restricted to. Different ways to specify these selections are possible:

Object selection [INPUT, OPTIONAL, default=None.]

- Specify a list of indices (in jython) of the point spectra for which the processing should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

See also

- ManyToOneSpectrumTask

History

- `2008-01-29 - meli`: initial.
- `2008-03-16 - meli`: major refactoring of the toolbox.
- `2009-05-18 - meli`: more ways to specify selections and frequency ranges.

2.114. ExtractMultiplePixelSpectrumPanel

Full Name:	herschel.ia.gui.cube.ExtractMultiplePixelSpectrumPanel
Type:	Java Class -
Import:	from herschel.ia.gui.cube import ExtractMultiplePixelSpectrumPanel

Description

A panel for the SinglePixelSpectrum extraction task

API Summary

Constructor
ExtractMultiplePixelSpectrumPanel() The constructor of a new ExtractSinglePixelSpectrumPanel.

Methods
JPanel **getPixelsPanel()** Returns the panel where to specify the radii for the
drawFigures() Draws the circles on the image for this
clearSpectrumExtraction() Clears the annular sky aperture for this
setClicked(Double center) Sets the center of the rectancle, associated with this

API details

Constructor

ExtractMultiplePixelSpectrumPanel()
The constructor of a new ExtractSinglePixelSpectrumPanel.

Methods

JPanel getPixelsPanel()
Returns the panel where to specify the radii for the apertures for this ExtractSinglePixelSpectrumPanel. **Return** **JPanel** Returns the panel where to specify the radii for the apertures for this AnnularSkyAoerturePhotometryPanel.

drawFigures()
Draws the circles on the image for this

drawFigures()

ExtractSinglePixelSpectrumPanel.

clearSpectrumExtraction()

Clears the annular sky aperture for this

ExtractSinglePixelSpectrumPanel.

setClicked(Double center)

Sets the center of the rectancle, associated with this

ExtractSinglePixelSpectrumPanel to the given point (in UserCoordinates).

Argument

`Double` **center** `[INPUT, MANDATORY]`

2.115. ExtractRegionPixelSpectrumTask

Full Name:	herschel.ia.toolbox.cube.ExtractRegionPixelSpectrumTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import ExtractRegionPixelSpectrumTask

Description

Task which Extract an averaged Spectrum from a set of pixels,

from a simplecube.

In the CubeSpectrumAnalysisToolbox (via the SpectrumAvgPlotting GUI), this task process a set of contiguous pixels and can be used in association with some FILTERRING, the output of this task in this kind of usage is therefore sent directly to the next tasks.

The command line can be used to retrieve manually some spectrum or to include it in scripts. this task use SimpleCube and return

Example

Example 1: How to use the Single pixel spectrum extraction in jide

```
regionExtraction = ExtractRegionPixelSpectrumTask
regionExtraction.setValue("simplecube",Cube)
regionExtraction.setValue("wholeImg",False)
regionExtraction.setValue("posArray",arrayofpixel)
regionExtraction.execute()
spectrum =(Double1d) regionExtraction.getValue("spectrum")
Spectrum1d spectrum1d =(Double1d) regionExtraction.getValue("spectrum")
{@link #__abs__()} futur
```

API Summary

Properties
SimpleCube **simplecube** [INPUT, MANDATORY, default=no default value]
Boolean **wholeImg** [INPUT, no default value, default=no default value]
Double2d **posArray** [INPUT, MANDATORY, default=no default value]
Integer **nbPixels** [INPUT, MANDATORY, default=no default value]
Integer **arithmetics** [INPUT, MANDATORY, default=no default value]
Double1d **spectrum** [OUTPUT, MANDATORY, default=no default value]
Spectrum1d **finalspectrum** [OUTPUT, MANDATORY, default=no default value]
float **totalWeight** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

SimpleCube simplecube [INPUT, MANDATORY, default=no default value]

The Cube containing the spectra to extract

Boolean wholeImg [INPUT, no default value, default=no default value]

A flag to define the usage whole image or region of this task

Double2d posArray [INPUT, MANDATORY, default=no default value]

The Array of pixels to be read in the cube must contain the X,Y and weight information [X,Y,weight]

Integer nbPixels [INPUT, MANDATORY, default=no default value]

The number of pixel to be read

Integer arithmetics [INPUT, MANDATORY, default=no default value]

a value defining the kind of arithmetic to use for the resulting spectra: choice between average(1) median(2) sum(3) default = sum

Double1d spectrum [OUTPUT, MANDATORY, default=no default value]

The flux of the spectrum extracted at the given position

Spectrum1d finalspectrum [OUTPUT, MANDATORY, default=no default value]

The spectrum extracted at the given position in a Spectrum1d

float totalWeight [OUTPUT, MANDATORY, default=no default value]

the 'weight' of the spectrum , ne exact number of pixel from which the spectrum was read

See also

- ???
- ???
- herschel.ia.dataset.spectrum.Spectrum1d;

History

- 2008-06-17 - AG: first complet description
- 2008-07-03 - AG: Modification of the input Parameters
- 2008-09-08 - AG: add the error computation
- 2009-06-08

2.116. ExtractSinglePixelSpectrumPanel

Full Name:	herschel.ia.gui.cube.ExtractSinglePixelSpectrumPanel
Type:	Java Class -
Import:	from herschel.ia.gui.cube import ExtractSinglePixelSpectrumPanel

Description

A panel for the SinglePixelSpectrum extraction task

API Summary

Constructor
ExtractSinglePixelSpectrumPanel()
The constructor of a new ExtractSinglePixelSpectrumPanel.

Methods
JPanel **getPixelsPanel()**
Returns the panel where to specify the X,Y pixel
drawFigures()
Draws the circles on the image for this
clearSpectrumExtraction()
Clears tthe spectrum extraction interface for this
setClicked(Double center)
Sets the center of the rectancle, associated with this

API details

Constructor

ExtractSinglePixelSpectrumPanel()
The constructor of a new ExtractSinglePixelSpectrumPanel.

Methods

JPanel getPixelsPanel()
Returns the panel where to specify the X,Y pixel position for this ExtractSinglePixelSpectrumPanel. **Return** **JPanel** Returns the panel where to specify the X,Y pixel position for this ExtractSinglePixel

drawFigures()
Draws the circles on the image for this

drawFigures()

ExtractSinglePixelSpectrumPanel.

clearSpectrumExtraction()

Clears tthe spectrum extraction interface for this

ExtractSinglePixelSpectrumPanel.

setClicked(Double center)

Sets the center of the rectancle, associated with this

ExtractSinglePixelSpectrumPanel to the given point (in UserCoordinates).

Argument

`Double` **center** `[INPUT, MANDATORY]`

2.117. ExtractSinglePixelSpectrumTask

Full Name:	herschel.ia.toolbox.cube.ExtractSinglePixelSpectrumTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import ExtractSinglePixelSpectrumTask

Description

Task which extract a Spectrum of a Simplecube from a Single pixel position given as

parameter.

This task is used in the GUI CubeSpectrumAnalysisToolbox for the Real time single spectrum visualization and in the the Single pixel Spectrum Extraction.

*

This task can be used in common with some filtering and fitting tasks. in this case the input parameters for these tasks are partly the result of this one. In the main GUI or in the JIDE the user will decide and define of the filter to apply.

Example

Example 1: How to use the Single pixel spectrum extraction

```
singlePixExtraction = ExtractSinglePixelSpectrumTask();
singlePixExtraction.setValue()
```

API Summary

Properties
SimpleCube **simplecube** [INPUT, MANDATORY, default=no default value]
Integer **posX** [INPUT, MANDATORY, default=no default value]
Integer **posY** [INPUT, MANDATORY, default=no default value]
Spectrum1d **finalspectrum** [OUTPUT, MANDATORY, default=no default value]
Double1d **spectrum** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

SimpleCube simplecube [INPUT, MANDATORY, default=no default value]

The Cube containing the spectra

Integer posX [INPUT, MANDATORY, default=no default value]

The X coordinate of the pixel to be read.

Integer posY [INPUT, MANDATORY, default=no default value]

The Y coordinate of the pixel to be read.

Spectrum1d finalspectrum [OUTPUT, MANDATORY, default=no default value]
The spectrum extracted at the given position in a Spectrum1d , default output parameter

Double1d spectrum [OUTPUT, MANDATORY, default=no default value]
The spectrum extracted at the given position

History

- 2008-06-17 - AG: first complete description
- 2008-07-03 - AG: Modification of the input Parameters
- 2008-07-24 - AG: added a new output parameters
- 2008-10-3 - AG: temporary removed the unit management
- 2009-01-31 - AG: inverted the output parameters order

2.118. FFT2dTask

Full Name:	herschel.ia.toolbox.image.FFT2dTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import FFT2dTask

Description

A Task for two dimensional Fast Fourier Transforms.

A Task that calculates the 2D Fast Fourier Transform and the power spectrum.

API Summary

Properties
Numeric2dData **image** [INPUT, MANDATORY, default=No default value]
Complex2d **transform** [OUTPUT, MANDATORY, default=No default value]
Double2d **spectrum** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Numeric2dData image [INPUT, MANDATORY, default=No default value]

The input image.

Complex2d transform [OUTPUT, MANDATORY, default=No default value]

The transform.

Double2d spectrum [OUTPUT, MANDATORY, default=No default value]

The spectrum.

2.119. FFT

Full Name:	herschel.ia.numeric.toolbox.xform.FFT
Alias:	FFT
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.xform import FFT

Description

Gives the Fast Fourier Transform <![CDATA[]]>.

Example

Example 1: Apply FFT

```
from java.lang.Math import PI
# Frequency modulated signal: parameters
ts = 1E-6          # Sampling period (sec)
fc = 200000        # Carrier frequency (Hz)
fm = 2000          # Modulation frequency (Hz)
beta = -.0003       # Modulation index (Hz)
n = 5000           # Number of samples
# Create signal in complex form
t = Double1d.range(n) * ts
signal = SIN(2 * PI * fc * t * (1 + beta * COS(2 * PI * fm * t)))
z_signal=Complex1d(signal)
# Get spectrum
spectrum = ABS(FFT(z_signal))
# Repeat with apodizing
z_signal=Complex1d(HAMMING(signal))
spectrum2 = ABS(FFT(z_signal))
```

API Summary

Jython Syntax

```
<y>=FFT(<x>)
```

Properties

Complex1d **x** [INPUT, MANDATORY, default=no default value]

Double1d **y** [INPUT, MANDATORY, default=no default value]

API details

Properties

Complex1d x [INPUT, MANDATORY, default=no default value]

Complex1d arrays only.

Double1d y [INPUT, MANDATORY, default=no default value]

Returns a Double1d

See also

- IFFT

2.120. FitsArchive

Full Name:	herschel.ia.io.fits.FitsArchive
Alias:	FitsArchive
Type:	Java Class -
Import:	from herschel.ia.io.fits import FitsArchive
Category:	class

Description

A class for reading and writing FITS files.

The FitsArchive provides a transparant way to store and retrieve Products as defined within the Herschel Data Processing software. FitsArchive is thread tolerant. It is not thread safe: do not share a FitsArchive object between several threads.

Examples

Example 1: default usage:

```
from herschel.ia.io.fits import FitsArchive
# read/write a Product in HCSS decorated format.
fits=FitsArchive()
product=fits.load("input.fits")
fits.save("output.fits",product)
```

Example 2: reading a HCSS FITS file which contains a removed class:

```
fits=FitsArchive()
product=fits.load("input.fits",FitsArchive.HANDLE_MISSING_CLASSES)
```

Example 3: reading a externally generated FITS file into a Product:

```
from herschel.ia.io.fits import FitsArchive
# setup a new FitsArchive, but change the reader type
from herschel.ia.io.fits.reader.standard import StandardFitsReader
fits = FitsArchive(reader = StandardFitsReader())
product=fits.load("input.fits")
# Saving the product will be done in HCSS decorated format.
fits.save("output.fits",product)
```

Example 4: saving an empty ArrayDataset is allowed:

```
from herschel.ia.io.fits import FitsArchive
fits=FitsArchive()
ads=ArrayDataset()
product=Product("with empty ArrayDataset")
product['ads'] = ads
fits.save("product.fits", product) # works: image extension without image
```

Example 5: saving an empty column in a TableDataset is NOT allowed:

```
from herschel.ia.io.fits import FitsArchive
fits=FitsArchive()
tds=TableDataset()
tds.addColumn(Column())
product=Product("with empty Column in TableDataset")
product['tds'] = tds
fits.save("product.fits", product) # fails: binary table extensions require
data
```

Example 6: saving the product minimizing product metadata keyword translations and making keywords duplicity.:

```
from herschel.ia.io.fits import FitsArchive
fits=FitsArchive()
product=Product("My Product")
fits.save("product.fits", product, 1, 1)
```

API Summary

Fields
`FitsReader HCSS_READER` HCSS FITS Reader
`FitsReader STANDARD_READER` Generic FITS Reader

Methods
`Product load(String name)` Loads a Product from a FITS file.
`Product load(String name, boolean handleMissingClasses)` Loads a Product from a FITS file.
`Product load(String file)` Loads a Product from a FITS file.
`Product load(String file, boolean handleMissingClasses)` Loads a Product from a FITS file.
`Product load(InputStream is)` Loads a Product from a FITS InputStream.
`Product load(InputStream is, boolean handleMissingClasses)` Loads a Product from a FITS InputStream.
`save(String name, [Optionally derived] Product. product)` Saves a Product to a FITS file.
`save(String name, [Optionally derived] Product. product, Boolean. minimizeTranslations, [Optionally derived] Product. keysDuplicity)` Saves a Product to a FITS file.
`save(File file, [Optionally derived] Product. product)` Saves a Product to a FITS file.
`save(File file, [Optionally derived] Product. product, Boolean. minimizeTranslations, [Optionally derived] Product. keysDuplicity)` Saves a Product to a FITS file.
`save(OutputStream os, [Optionally derived] Product. product)` Saves a Product to an OutputStream (creating a FITS file).
`save(OutputStream os, [Optionally derived] Product. product, Boolean. minimizeTranslations, [Optionally derived] Product. keysDuplicity)` Saves a Product to an OutputStream (creating a FITS file).

API details

Fields

`FitsReader HCSS_READER`

HCSS FITS Reader

A FITS reader that expects a FITS format that was produced by this archive implementation. This is a shared object among any FitsArchive instance. In a multithread environment, you should use a new instance of a reader.

It can handle nested structures, derived datasets and quantities of the data within FITS.

This is the default reader when you create a FitsArchive.

Examples

creating a new FitsArchive

```
fits=FitsArchive() # default
reader=FitsArchive.HCSS_READER
```

creating a new FitsArchive

```
fits=FitsArchive(reader=FitsArchive.HCSS_READER)
```

`FitsReader STANDARD_READER`

Generic FITS Reader

A generic FITS reader for FITS files that are not created by the HCSS FitsArchive. This is a shared object among any FitsArchive instance. In a multithread environment, you should use a new instance of a reader.

This reader can read FITS files that were generated by other software as long as it complies to the FITS standard and translates the contents into a Product.

Examples

import data from an externally generated FITS file:

```
fits=FitsArchive(reader=FitsArchive.STANDARD_READER)
product=fits.load("external.fits")
```

reusing this FitsArchive but changing the reader:

```
fits.reader=fits.HCSS_READER
product=fits.load("hcss.fits")
```

Methods

`Product load(String name)`

Loads a Product from a FITS file.

Loads a Product from a FITS file using the current reader.

Argument

`String` **`name`** `[INPUT, MANDATORY, default=no default value]`

Name of the FITS file

Product load(String name)

Return

Product

An object of the herschel.ia.dataset.Product family.

Product load(String name, boolean handleMissingClasses)

Loads a Product from a FITS file.

Loads a Product from a FITS file using the current reader.

Arguments

String **name** [INPUT, MANDATORY, default=no default value]

Name of the FITS file

boolean **handleMissingClasses** [INPUT, MANDATORY, default=no default value]

For creating dummy classes when a Hcss class is not found.

Return

Product

An object of the herschel.ia.dataset.Product family.

Product load(String file)

Loads a Product from a FITS file.

Loads a Product from a FITS file using the current reader.

Argument

String **file** [INPUT, MANDATORY, default=no default value]

FITS file

Return

Product

An object of the herschel.ia.dataset.Product family.

Product load(String file, boolean handleMissingClasses)

Loads a Product from a FITS file.

Loads a Product from a FITS file using the current reader.

Arguments

String **file** [INPUT, MANDATORY, default=no default value]

FITS file

boolean **handleMissingClasses** [INPUT, MANDATORY, default=no default value]

For creating dummy classes when a Hcss class is not found.

Return

Product

An object of the herschel.ia.dataset.Product family.

`Product load(InputStream is)`

Loads a Product from a FITS InputStream.

Loads a Product from a FITS InputStream using the current reader.

Argument

`InputStream` **`is`** `[INPUT, MANDATORY, default=no default value]`

InputStream to the FITS file

Return

Product

An object of the herschel.ia.dataset.Product family.

`Product load(InputStream is, boolean handleMissingClasses)`

Loads a Product from a FITS InputStream.

Loads a Product from a FITS InputStream using the current reader.

Arguments

`InputStream` **`is`** `[INPUT, MANDATORY, default=no default value]`

InputStream to the FITS file

`boolean` **`handleMissingClasses`** `[INPUT, MANDATORY, default=no default value]`

For creating dummy classes when a Hcss class is not found.

Return

Product

An object of the herschel.ia.dataset.Product family.

`save(String name, [Optionally derived] Product. product)`

Saves a Product to a FITS file.

Saves a Product to a FITS file with sufficient information to preserve the quantities of the data as well as the original dataset type and contents.

Arguments

`String` **`name`** `[INPUT, MANDATORY, default=no default value]`

Name of the FITS file

`[Optionally derived] Product.` **`product`** `[INPUT, MANDATORY, default=no default value]`

An object of the herschel.ia.dataset.Product family.

`save(String name, [Optionally derived] Product. product, Boolean. minimizeTranslations, [Optionally derived] Product. keysDuplicity)`

Saves a Product to a FITS file.

Saves a Product to a FITS file with sufficient information to preserve the quantities of the data as well as the original dataset type and contents.

Arguments

`String` **`name`** `[INPUT, MANDATORY, default=no default value]`

save(String name, [Optionally derived] Product. product, Boolean. minimizeTranslations, [Optionally derived] Product. keysDuplicity)

Name of the FITS file

`[Optionally derived] Product. product [INPUT, MANDATORY, default=no default value]`

An object of the herschel.ia.dataset.Product family.

`Boolean. minimizeTranslations [INPUT, MANDATORY, default=no default value]`

Specifies if some keywords that are not in any dictionary will be transalted without using 'META' following some rules.

`[Optionally derived] Product. keysDuplicity [INPUT, MANDATORY, default=no default value]`

Specifies if a keyword will be translated to several FITS keywords.

save(File file, [Optionally derived] Product. product)

Saves a Product to a FITS file.

Saves a Product to a FITS file with sufficient information to preserve the quantities of the data as well as the original dataset type and contents.

Arguments

`File file [INPUT, MANDATORY, default=no default value]`

FITS file

`[Optionally derived] Product. product [INPUT, MANDATORY, default=no default value]`

An object of the herschel.ia.dataset.Product family.

save(File file, [Optionally derived] Product. product, Boolean. minimizeTranslations, [Optionally derived] Product. keysDuplicity)

Saves a Product to a FITS file.

Saves a Product to a FITS file with sufficient information to preserve the quantities of the data as well as the original dataset type and contents.

Arguments

`File file [INPUT, MANDATORY, default=no default value]`

FITS file.

`[Optionally derived] Product. product [INPUT, MANDATORY, default=no default value]`

An object of the herschel.ia.dataset.Product family.

`Boolean. minimizeTranslations [INPUT, MANDATORY, default=no default value]`

Specifies if some keywords that are not in any dictionary will be transalted without using 'META' following some rules.

`[Optionally derived] Product. keysDuplicity [INPUT, MANDATORY, default=no default value]`

Specifies if a keyword will be translated to several FITS keywords.

save(OutputStream os, [Optionally derived] Product. product)

Saves a Product to an OutputStream (creating a FITS file).

save(OutputStream os, [Optionally derived] Product. product)

Saves a Product to an OutputStream, creating a FITS file with sufficient information to preserve the quantities of the data as well as the original dataset type and contents. The OutputStream is closed by this method.

Arguments

`OutputStream` **`os`** `[INPUT, MANDATORY, default=no default value]`

OutputStream.

`[Optionally derived] Product.` **`product`** `[INPUT, MANDATORY, default=no default value]`

An object of the herschel.ia.dataset.Product family.

save(OutputStream os, [Optionally derived] Product. product, Boolean. minimizeTranslations, [Optionally derived] Product. keysDuplicity)

Saves a Product to an OutputStream (creating a FITS file).

Saves a Product to an OutputStream, creating a FITS file with sufficient information to preserve the quantities of the data as well as the original dataset type and contents. The OutputStream is closed by this method.

Arguments

`OutputStream` **`os`** `[INPUT, MANDATORY, default=no default value]`

OutputStream.

`[Optionally derived] Product.` **`product`** `[INPUT, MANDATORY, default=no default value]`

An object of the herschel.ia.dataset.Product family.

`Boolean.` **`minimizeTranslations`** `[INPUT, MANDATORY, default=no default value]`

Specifies if some keywords that are not in any dictionary will be transalted without using 'META' following some rules.

`[Optionally derived] Product.` **`keysDuplicity`** `[INPUT, MANDATORY, default=no default value]`

Specifies if a keyword will be translated to several FITS keywords.

2.121. fitsReader

Full Name:	herschel.ia.toolbox.util.FitsReaderTask
Alias:	fitsReader
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import FitsReaderTask
Category:	task

Description

The FitsReaderTask task.

Creates a "suitable" product from a FITS file, not necessarily from Herschel Currently it deals with images, (partially, only wave based) spectra, cubes and spectral cubes.

Examples

Example 1: FitsReaderTask with a file parameter

```
filepath = -"path_to_file"
product=fitsReader(file=filepath)
```

Example 2: FitsReaderTask to read an image

```
filepath = -"path_to_file"
product=fitsReader(file=filepath,
fitstype=herschel.ia.toolbox.util.FitsReaderTask.FitsType.IMAGE)
```

API Summary

Jython Syntax

```
product=fitsReader(<file>[, <FitsType>])
```

Properties

`String` **`file`** `[INPUT, MANDATORY, default=null]`

`FitsReaderTask.FitsType` **`fitstype`** `[INPUT, OPTIONAL, default=FitsType.UNKNOWN]`

`Object` **`product`** `[OUTPUT, MANDATORY, default=null]`

API details

Properties

`String file [INPUT, MANDATORY, default=null]`

The path of the FITS file to be read.

`FitsReaderTask.FitsType fitstype [INPUT, OPTIONAL, default=FitsType.UNKNOWN]`

The type of object the fits file contains (default is unknown).

Object product [OUTPUT, MANDATORY, default=null]
The Product (dataset for spectra) read from the FITS file.

History

- `2008-08-16 - JDS`: initial commit (not allowed dependencies)
- `2009-09-04 - JDS`: initial release (only images can be displayed, graphical editors fail to show)
- `2009-09-30 - JSS`: modifiers are created through getCustomModifiers (SCR HCSS-8253)
- `2009-10-22 - JDS`: release to be backported to 1.2 (no general solution for Spectra yet)

2.122. FitterFunction

Full Name:	herschel.ia.toolbox.fit.FitterFunction
Alias:	FitterFunction
Type:	Java Class -
Import:	from herschel.ia.toolbox.fit import FitterFunction

Description

Specialization of RealFunction that fits some given data.

Example

Example 1: Implicit fitting

```
x = Double1d([ 0,0.5,1,2, 3, 4, 5,  6,  10,    12])
y = Double1d([-3,  2,4,5,12,37,92,189,1237,2325])
f = FitterFunction(x, y, PolynomialModel(3))
i = SimpsonIntegrator(1, 10)
print i.integrate(f)  # 2668.499999999972
Explicit fitting
x = Double1d([ 0,0.5,1,2, 3, 4, 5,  6,  10,    12])
y = Double1d([-3,  2,4,5,12,37,92,189,1237,2325])
model = CubicSplinesModel(x)
fitter = AmoebaFitter(x, model)
fitter.setSimplex(params, range)  # customize the fitter as you want
fitter.fit(y)
f = FitterFunction(model)  # or f = FitterFunction(fitter)
# remaining code like before
```

API Summary

Jython Syntax
<f>=FitterFunction(<x>,<y>,<m>[,<c>])
<f>=FitterFunction(<m>)
<f>=FitterFunction(<F>)

Properties
Double1d of abscissas **x** [INPUT, MANDATORY, default=no default value]
Double1d of values **y** [INPUT, MANDATORY, default=no default value]
AbstractModel **m** [INPUT, MANDATORY, default=no default value]
Class of Fitter **c** [INPUT, OPTIONAL, default=Fitter.class]
Fitter **F** [INPUT, MANDATORY, default=no default value]
RealFunction **f** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

Double1d of abscissas x [INPUT, MANDATORY, default=no default value]

Abscissas; it is only mandatory for the constructors where it appears in the synopsis.

Double1d of values y [INPUT, MANDATORY, default=no default value]

Values corresponding to the abscissas; it is only mandatory for 1st constructors.

AbstractModel m [INPUT, MANDATORY, default=no default value]

Unitialized model for 1st constructors, or already customized model for 2nd constructor.

Class of Fitter c [INPUT, OPTIONAL, default=Fitter.class]

Allows specifying the fitter class to be used in 1st constructor. FitterFunction provides some useful constants: LINEAR (for Fitter.class), AMOEBA (for AmoebaFitter.class) and LEVENBERG (for LevenbergMarquardtFitter.class).

Fitter F [INPUT, MANDATORY, default=no default value]

It is only mandatory for 3rd constructor.

RealFunction f [OUTPUT, MANDATORY, default=no default value]

Function object that fits the provided data with the specified model.

2.123. Fitter

Full Name:	herschel.ia.numeric.toolbox.fit.Fitter
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.fit import Fitter

Description

An introduction to the use of fit package can be found

here. At least once have a look at the background on the organization and structure of the package.

Example

Example 1: The fit/demo directory contains worked

```
<a href="../../../ia/numeric/toolbox/fit/demo/jython.html">examples</a>
on almost all aspects of of the package.
```

Limitations

The calculation of the evidence is an Gaussian approximation which is only exact for linear models with a fixed scale.

2.124. FitterTask

Full Name:	herschel.ia.toolbox.fit.FitterTask
Alias:	FitterTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.fit import FitterTask
Category:	generic task

Description

generic module: FitterTask

Task shell around the package herschel.ia.numeric.toolbox.fit. Both a command line and a GUI interface are provided. With the GUI interface there is more of the Fitter package accessable than on this tasks command line. However not everything possible within the fitter package is accessable via this task, GUI or otherwise. Most text fields in the GUI accept either numerics or JIDE variables or JIDE expressions.

Example

Example 1: FitterTask

```
<pre>
from herschel.hifi.generic.task import FitterTask
# Assume that `tt' and/or `data' are Double1d's
# usage on command line:
ft = FitterTask()( x=tt, y=data, modelname="GaussModel" -)
ft.fittername = -"LevenbergMarquardtFitter"
ft()            # performs the execute method
print ft.result        # parameters of the fit
print ft.stdev        # standard deviations
print ft.fittername    # name of the fitter
# Etcetera, etc.
# use the GUI.
ft = FitterTask()
ft.gui = 1         # start the GUI
# from the GUI select the data, model, fitter, properties etc and run.
print ft.result        # parameters of the fit
print ft.stdev        # standard deviations
# Etcetera as before.
</pre>
```

API Summary

Jython Syntax
see example below

Properties
NumericData **x** [INPUT, OPTIONAL, default=null]
DoubleArray **y** [INPUT, MANDATORY, default=no]
Boolean **indexview** [INPUT, OPTIONAL, default=true]
DoubleArray **weights** [INPUT, OPTIONAL, default=null]
AbstractModel **model** [INPUT, OPTIONAL, default=null]
String **modelname** [INPUT, OPTIONAL, default=no]

Properties
Array1dData **modelarg** [INPUT, OPTIONAL, default=null]
Fitter **fitter** [INPUT, OPTIONAL, default=null]
String **fittername** [INPUT, OPTIONAL, default=no]
Double1d **result** [OUTPUT, OPTIONAL, default=n/a]
Double1d **parameters** [OUTPUT, OPTIONAL, default=n/a]
Double1d **stdev** [OUTPUT, OPTIONAL, default=n/a]
Double **chisq** [OUTPUT, OPTIONAL, default=n/a]
DoubleArray **yfit** [OUTPUT, OPTIONAL, default=n/a]
DoubleArray **yband** [OUTPUT, OPTIONAL, default=n/a]
Double1d **prior** [INPUT, OPTIONAL, default=null]
Double **evidence** [OUTPUT, OPTIONAL, default=n/a]
Double **scale** [OUTPUT, OPTIONAL, default=n/a]
Boolean **auto** [INPUT, OPTIONAL, default=true]
Double **fixed** [INPUT, OPTIONAL, default=1.0]
Double **mixed** [INPUT, OPTIONAL, default=0.0]
Double **tolerance** [INPUT, OPTIONAL, default=0.01]
Integer **iterations** [INPUT, OPTIONAL, default=10000]
Double **temperature** [INPUT, OPTIONAL, default=0.0]
Double **cooling** [INPUT, OPTIONAL, default=0.95]
Integer **tempsteps** [INPUT, OPTIONAL, default=100]
Double1d **initialpars** [INPUT, OPTIONAL, default=from model]
Double1d **highlimits** [INPUT, OPTIONAL, default=null]
Double1d **lowlimits** [INPUT, OPTIONAL, default=null]
Int1d **keepfixed** [INPUT, OPTIONAL, default=null]
Double1d **fixedvalues** [INPUT, OPTIONAL, default=null]
Boolean **gui** [INPUT, OPTIONAL, default=false]

Limitations

Not everything which is possible using the package directly is accessable via this task.

API details

Properties

NumericData x [INPUT, OPTIONAL, default=null]

The independent variable(s) of the fit problem. If not provided, it will use indices ranging from 0 to len(y). If y is more-dimensional the proper 2-d indices are provided.

DoubleArray y [INPUT, MANDATORY, default=no]

The data to be fitted. It can be more-dimensional. E.g. a 2-dimensional map.

Boolean indexview [INPUT, OPTIONAL, default=true]

Applicable parameters appear in the same order as in the y DoubleArray This parameter is only active when y has 2 dimensions or more.

DoubleArray weights [INPUT, OPTIONAL, default=null]

The weights to be used in the fit. Can be more-dimensional. When provided it should be the same size as parameter y.

AbstractModel model [INPUT, OPTIONAL, default=null]

The model to be fitted. One of "model" or "modelname" is MANDATORY

String modelname [INPUT, OPTIONAL, default=no]

The name of the model to be fitted. One of "model" or "modelname" is MANDATORY

Array1dData modelarg [INPUT, OPTIONAL, default=null]

Arguments, if any, needed in the Constructor of the model.

Fitter fitter [INPUT, OPTIONAL, default=null]

The fitter to be used. One of "fitter" or "fittername" is MANDATORY

String fittername [INPUT, OPTIONAL, default=no]

The name of the fitter to be used. One of "fitter" or "fittername" is MANDATORY

Double1d result [OUTPUT, OPTIONAL, default=n/a]

The parameters of the fit. Also the default result of the task.

Double1d parameters [OUTPUT, OPTIONAL, default=n/a]

The parameters of the fit. (same as result)

Double1d stdev [OUTPUT, OPTIONAL, default=n/a]

The standard deviations pertaining to the parameters.

Double chisq [OUTPUT, OPTIONAL, default=n/a]

Chi-squared of the fit.

DoubleArray yfit [OUTPUT, OPTIONAL, default=n/a]

An array of the same size as the data, containing the fitted values.

DoubleArray yband [OUTPUT, OPTIONAL, default=n/a]

An array of the same size as the data, containing a 1-# MonteCarlo error at each point.

Double1d prior [INPUT, OPTIONAL, default=null]

Prior ranges for the parameters, needed when the evidence is requested. When noise scaling is set to auto=true (default), the prior needs 1 extra value as prior for the noise scale.

Double evidence [OUTPUT, OPTIONAL, default=n/a]

Relative evidence the model carries w.r.t. the data It needs values for prior, as many as the number of parameters and one more if auto-scaling is set.

Double scale [OUTPUT, OPTIONAL, default=n/a]

Noise scale of the data (when auto or mixed is selected)

Boolean auto [INPUT, OPTIONAL, default=true]

Select automatic noise scaling. The noise level in the data is not exactly known.

Double fixed [INPUT, OPTIONAL, default=1.0]

Fixed noise scale. The noise level is known.

Double mixed [INPUT, OPTIONAL, default=0.0]

Automatic noise scaling with a minimum. The noise level is not exactly known, but a minimum level is known.

Double tolerance [INPUT, OPTIONAL, default=0.01]

Stopping criterion for iterative fitting.

Integer iterations [INPUT, OPTIONAL, default=10000]

Maximum number of iterations in iterative fitters.

Double temperature [INPUT, OPTIONAL, default=0.0]

Starting temperature in annealing amoeba fitting.

Double cooling [INPUT, OPTIONAL, default=0.95]

Cooling step in annealing amoeba fitting.

Integer tempsteps [INPUT, OPTIONAL, default=100]

Number of exploratory steps at each temperature.

Double1d initialpars [INPUT, OPTIONAL, default=from model]

Initial parameters in iterative fitters.

Double1d highlimits [INPUT, OPTIONAL, default=null]

Upper limits of the parameters (only in AmoebaFitter)

Double1d lowlimits [INPUT, OPTIONAL, default=null]

Lower limits of the parameters (only in AmoebaFitter)

Int1d keepfixed [INPUT, OPTIONAL, default=null]

Keep these parameters fixed. (Parameter numbering starts at 0)

Double1d fixedvalues [INPUT, OPTIONAL, default=null]

Values at which the parameters should be kept.

Boolean gui [INPUT, OPTIONAL, default=false]

Allows to handle this task using a gui.

History

- 15-10-2006 DK

2.125. FixedMask

Full Name:	herschel.ia.numeric.toolbox.mask.FixedMask
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.mask import FixedMask

Description

FixedMask represents the more "traditional" mask form, where a mask is defined at a fixed bit offset position.

The class represents only the definition, and does not allocate any data array itself. Defining a single mask array requires a minimum of 8 bits per data element (if byte is used) up to 64 bits (if long is used). All integer types are supported (byte/short/int/long). However, masks can be combined in the same array, so if 64 masks were stored in a long, it would be fully packed, with no memory wastage. This also means that there is a practical limit of 64 on the number of masks that can be defined. This mask still makes perfect sense when exported to an external format. It also integrates well with standard numeric library functionality. Note that the mask data itself is not stored in this class.

Examples

Example 1: Define some mask bits/setters

```
MASTER = FixedMask (0, -"Master")
NOISY  = FixedMask (2, -"Noisy")
GLITCH = FixedMask (4, -"Glitch")
#where 0, 2, and 4 are bit offset
#Since a long integer can only holds 64 bits,an exception will be thrown out
if
  #TOOBIG=FixedMask(100,"Too Big")
#java.lang.IllegalArgumentException: bit offset must be >= 0 and less than
64, not 100
```

Example 2: Mask bits can be printed (continued from the previous example):

```
print MASTER
# Master @ 0 = 1
print NOISY
# Noisy @ 2 = 4
print GLITCH
# Glitch @ 4 = 16
print NOISY.getName()
#Noisy
print GLITCH.getValue()
#16
```

Example 3: Set/Unset mask data (continued from the previous example):

```
#A mask data x can be set/unset by different mask setters:
x = 0
x = GLITCH.set (x)
print x
#16
x = MASTER.set (x)
print x
# 17
x = GLITCH.unset (x)
print x
```

Example 3: Set/Unset mask data (continued from the previous example):

```
# 1
```

Example 4: Check mask data (continued from the previous example):

```
#The status of mask data x can be checked for different mask setters:
print MASTER.isSet(x)
# 1
print GLITCH.isSet(x)
# 0
# The mask checking can be ignored:
MASTER.setIgnore(1)
print MASTER.isSet(x)
#0
# The mask checking can be resumed:
MASTER.setIgnore(0)
print MASTER.isSet(x)
#1
```

Example 5: Use mask bits on a mask data array (continued from the previous example):

```
#One can also use mask bits/setters to work on a mask data array a:
a = Int1d([1,2,3,4,5,6,7,8,9])
print a.where (MASTER)
#[0,2,4,6,8]  (Note. The method -"where" returns the indices where the mask
MASTER is set.)
print MASTER.isSet (a)
#[true,false,true,false,true,false,true,false,true]
print MASTER.unset (a)
#[0,2,2,4,4,6,6,8,8]
print MASTER.set (a)
#[1,3,3,5,5,7,7,9,9]
MASTER.setIgnore(1)
print MASTER.isSet(a)
#[false,false,false,false,false,false,false,false,false]
print a.where(MASTER)
#[]
MASTER.setIgnore(0)
```

Example 6: More examples to show mask is set, is not set, and the combined masks are set (continued from the previous example):

```
b = Int1d.range(20)
#Check where Master is set
print b.where(MASTER.isSet(b))
#[1,3,5,7,9,11,13,15,17,19]
#Check where Glitch is set
print b.where(GLITCH.isSet(b))
#[16,17,18,19]
#Check where Glitch is not set
print b.where(~GLITCH.isSet(b))
#[0,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15]
#Check where Glitch or Master are set
print b.where(GLITCH.isSet(b) -| MASTER.isSet(b))
#[1,3,5,7,9,11,13,15,16,17,18,19]
#Check where Glitch and Master are set
print b.where(GLITCH.isSet(b) & MASTER.isSet(b))
#[17,19]
```

Example 7: The mask data array can be in high dimension (continued from the previous example):

```
aa = Int2d([[1,2,3],[4,5,6]])
print NOISY.isSet(aa)
#[ [false,false,false], [true,true,true] -]
```

Example 7: The mask data array can be in high dimension (continued from the previous example):

```
print aa.where(NOISY)
#[3,4,5]
```

Example 8: Mask bits/setters can be combined (continued from the previous example):

```
M_or_N = MASTER|NOISY
print M_or_N
#Master -| Noisy @ --1 = 5
b=Int1d([0,0,0,0,0,0])
print M_or_N.set(b)
#[5,5,5,5,5,5]
#which is equivelent to set MASTER and then NOISY:
M_or_N.unset(b)
print MASTER.set(b)
#[1,1,1,1,1,1]
print NOISY.set(b)
#[5,5,5,5,5,5]
#
M_and_N=MASTER & NOISY
print M_and_N
#Master & Noisy @ --1 = 0
print M_and_N.set(b)
#[5,5,5,5,5,5]
#Nothing is set because MASTER_AND_NOISY's value is 0 (they are different
single bit setters)
#
```

History

- June 2006 Original prototype
- September 2006 second go not using enum, subclass AbstractArrayPredicate
- February 2007 third iteration
- July 2007 fourth iteration
- May 2009 SPR-6833, SCR-4734
- November 2009 SCR-6541: registration

2.126. FixedSkyAperturePhotometryExplorer

Full Name:	herschel.ia.gui.image.FixedSkyAperturePhotometryExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import FixedSkyAperturePhotometryExplorer

Description

An explorer for FixedSkyAperturePhotometryProducts.

An explorer for FixedSkyAperturePhotometryProducts.

API Summary

Constructors
FixedSkyAperturePhotometryExplorer() The construction of a new FixedSkyAperturePhotometryExplorer.
FixedSkyAperturePhotometryExplorer(Object object) The construction of a new FixedSkyAperturePhotometryExplorer associated with the given object.

Methods
boolean **canHandle**(Class className) Checks whether this FixedSkyAperturePhotometryExplorer can handle objects of the given class.
setObject(Object object) Sets the object.
FixedSkyAperturePhotometryProduct **getObject**() Returns the object.
Class **getVariableType**() Returns the expected variable type.
JScrollPane **getParameterTable**() Returns the parameter table.
JScrollPane **getResultsTable**() Returns the results table.
JPanel **getPlotPanel**() Returns the plot panel.

API details

Constructors

FixedSkyAperturePhotometryExplorer()
The construction of a new FixedSkyAperturePhotometryExplorer. The construction of a new FixedSkyAperturePhotometryExplorer.

FixedSkyAperturePhotometryExplorer(Object object)

The construction of a new FixedSkyAperturePhotometryExplorer associated with the given object.

The construction of a new FixedSkyAperturePhotometryExplorer associated with the given object.

Argument

Object **object** [INPUT, MANDATORY]

Methods

boolean canHandle(Class className)

Checks whether this FixedSkyAperturePhotometryExplorer can handle objects of the given class.

Returns true if this FixedSkyAperturePhotometryExplorer can handle objects of the given class.

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true of this FixedSkyAperturePhotometryExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this AperturePhotometryExplorer to the given object.

Argument

Object **object** [INPUT, MANDATORY]

FixedSkyAperturePhotometryProduct getObject()

Returns the object.

Returns the object for this FixedSkyAperturePhotometryExplorer.

Return

FixedSkyAperturePhotometryProduct

Returns the object for this FixedSkyAperturePhotometryExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this FixedSkyAperturePhotometryExplorer.

Return

Class

Returns the expected variable type for this FixedSkyAperturePhotometryExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

JScrollPane getParameterTable()

Constructs and returns the parameter table for this FixedSkyAperturePhotometryExplorer.

Return

JScrollPane

Returns the parameter table for this FixedSkyAperturePhotometryExplorer.

JScrollPane getResultsTable()

Returns the results table.

Constructs and returns the results table for this AperturePhotometryExplorer.

Return

JScrollPane

Returns the results table for this AperturePhotometryExplorer.

JPanel getPlotPanel()

Returns the plot panel.

Constructs and returns the plot panel for this FixedSkyAperturePhotometryExplorer.

Return

JPanel

Returns the plot panel for this FixedSkyAperturePhotometryExplorer.

2.127. FixedSkyAperturePhotometryPanel

Full Name:	herschel.ia.toolbox.image.gui.FixedSkyAperturePhotometryPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import FixedSkyAperturePhotometryPanel

Description

A panel for the FixedSkyAperturePhotometryTask.

A panel to serve as GUI for the FixedSkyAperturePhotometryTask.

API Summary

Constructor
FixedSkyAperturePhotometryPanel() The construction of a new FixedSkyAperturePhotometryPanel.

Methods
JPanel **getAperturesPanel()** Returns the panel where to specify the target radius and the sky value.
JPanel **getTargetAperturePanel()** Returns the panel where to specify the target radius
JComponent **getSkyApertureComponent()** Returns the component where to specify the sky value.
drawFigures() Draws the circle on the image.
moveConfirmedFigures() Allows to move/resize the figures bounding the apertures.
transferFromModifierToSelectionMap() Transfers the information from the modifier to the selection map.
clearSkyAperture() Clears the sky aperture.

API details

Constructor

FixedSkyAperturePhotometryPanel()
The construction of a new FixedSkyAperturePhotometryPanel. The construction of a new FixedSkyAperturePhotometryPanel.

Methods

JPanel getAperturesPanel()
Returns the panel where to specify the target radius and the sky value.

JPanel getAperturesPanel()

Returns the panel where to specify the target radius and the sky value for this FixedSkyAperturePhotometryPanel.

Return

JPanel

Returns the panel where to specify the target radius and the sky value for this FixedSkyAperturePhotometryPanel.

JPanel getTargetAperturePanel()

Returns the panel where to specify the target radius

Returns the panel where to specify the target radius for this FixedAperturePhotometryPanel.

Return

JPanel

Returns the panel where to specify the target radius for this FixedAperturePhotometryPanel.

JComponent getSkyApertureComponent()

Returns the component where to specify the sky value.

Returns the component where to specify the sky value for this FixedSkyAperturePhotometryPanel.

Return

JComponent

Returns the component where to specify the sky value for this FixedSkyAperturePhotometryPanel.

drawFigures()

Draws the circle on the image.

Draws the circle on the image for this FixedSkyAperturePhotometryPanel.

moveConfirmedFigures()

Allows to move/resize the figures bounding the apertures.

Allows to move/resize the figures bounding the apertures for this FixedAperturePhotometryPanel.

transferFromModifierToSelectionMap()

Transfers the information from the modifier to the selection map.

Transfers the information for this FixedSkyAperturePhotometryPanel from the modifier to the selection map.

clearSkyAperture()

Clears the sky aperture.

Clears the sky aperture for this FixedAperturePhotometryPanel.

2.128. FixedSkyAperturePhotometryProduct

Full Name:	herschel.ia.dataset.image.FixedSkyAperturePhotometryProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import FixedSkyAperturePhotometryProduct

Description

A class to deal with the results of aperture photometry with a circular

target aperture and a fixed sky value.

API Summary

Constructor
`FixedSkyAperturePhotometryProduct()` The constructor of a new FixedSkyAperturePhotometryProduct.

Methods
`setSkyValue(double sky)` Sets the sky value for this FixedSkyAperturePhotometryProduct to the
`setResultsTable(Double2d resultsTable)` Sets the results table for this AperturePhotometryProduct to the
`double` **`getSkyValue()`** Returns the sky value for this FixedSkyAperturePhotometryProduct.
`double` **`getIntensityPerSkyPixel()`** Returns the intensity per pixel for the sky for this FixedSkyAperturePhotometryProduct.
`double` **`getTargetTotal()`** Returns the total flux for the target (sky subtracted) for this
`double` **`getNbOfTargetPixels()`** Returns the number of pixels for the target (sky subtracted) for this
`double` **`getIntensityPerTargetPixel()`** Returns the intensity per pixel for the target (sky subtracted) for this
`double` **`getTargetError()`** Returns the error for the target (sky subtracted) for this

Miscellaneous

Aperture specific information is stored in meta data, all other data (results of calculations) are stored in TableDatasets.

API details

Constructor

`FixedSkyAperturePhotometryProduct()`
The constructor of a new FixedSkyAperturePhotometryProduct.

Methods

setSkyValue(double sky)

Sets the sky value for this FixedSkyAperturePhotometryProduct to the

given sky value.

Argument

`double` **`sky`** `[INPUT, MANDATORY]`

setResultsTable(Double2d resultsTable)

Sets the results table for this AperturePhotometryProduct to the

given table.

Argument

`Double2d` **`resultsTable`** `[INPUT, MANDATORY]`

double getSkyValue()

Returns the sky value for this FixedSkyAperturePhotometryProduct.

Return

double

Returns the sky value for this FixedSkyAperturePhotometryProduct.

double getIntensityPerSkyPixel()

Returns the intensity per pixel for the sky for this FixedSkyAperturePhotometryProduct.

Return

double

Returns the intensity per pixel for the sky for this FixedSkyAperturePhotometryProduct.

double getTargetTotal()

Returns the total flux for the target (sky subtracted) for this

FixedSkyAperturePhotometryProduct.

Return

double

Returns the total flux for the target (sky subtracted) for this FixedSkyAperturePhotometryProduct.

double getNbOfTargetPixels()

Returns the number of pixels for the target (sky subtracted) for this

FixedSkyAperturePhotometryProduct.

Return

double

`double getNbOfTargetPixels()`

Returns the number of pixels for the target (sky subtracted) for this FixedSkyAperturePhotometryProduct.

`double getIntensityPerTargetPixel()`

Returns the intensity per pixel for the target (sky subtracted) for this

FixedSkyAperturePhotometryProduct.

Return

double

Returns the intensity per pixel for the target (sky subtracted) for this FixedSkyAperturePhotometryProduct.

`double getTargetError()`

Returns the error for the target (sky subtracted) for this

FixedSkyAperturePhotometryProduct.

Return

double

Returns the error for the target (sky subtracted) for this FixedSkyAperturePhotometryProduct.

2.129. FixedSkyAperturePhotometryTask

Full Name:	herschel.ia.toolbox.image.FixedSkyAperturePhotometryTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import FixedSkyAperturePhotometryTask

Description

A Task for aperture photometry.

A Task for aperture photometry with a circular target aperture and a fixed value for the sky.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **centerX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **centerY** [INPUT, OPTIONAL, default=Default value : NaN]
String **centerRA** [INPUT, OPTIONAL, default=Default value : "centerRA"]
String **centerDEC** [INPUT, OPTIONAL, default=Default value : "centerDec"]
Double **radiusPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **radiusArcsec** [INPUT, OPTIONAL, default=Default value : NaN]
Double **sky** [INPUT, MANDATORY, default=Default value : 0.0]
boolean **fractional** [INPUT, OPTIONAL, default=Default value : true]
AperturePhotometryProduct **result** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double centerX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the target center.

Double centerY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the target center.

String centerRA [INPUT, OPTIONAL, default=Default value : "centerRA"]

The right ascension of the target center.

String centerDEC [INPUT, OPTIONAL, default=Default value : "centerDec"]

The declination of the target center.

Double radiusPixels [INPUT, OPTIONAL, default=Default value : NaN]

The target radius (i.e. the radius of the circular target aperture) in pixels.

Double radiusArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The target radius in arcsec.

Double sky [INPUT, MANDATORY, default=Default value : 0.0]

The value for the sky.

boolean fractional [INPUT, OPTIONAL, default=Default value : true]

The type of pixels.

AperturePhotometryProduct result [OUTPUT, MANDATORY, default=No default value]

The result.

2.130. FIX

Full Name:	herschel.ia.numeric.toolbox.basic.Fix
Alias:	FIX
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Fix

Description

Gives the largest long less than or equal to x.

Returns a long array. Only float or double arrays are allowed as input argument.

Example

Example 1: Apply FIX on a Float1d

```
x=Float1d([1.0,2.1,3.5,4.9])
print FIX(x) # [1,2,3,4]
#To change the returned array type into an Int1d array:
i = Int1d(FIX(x))
```

API Summary

Jython Syntax

```
<y>=FIX(<x>)
```

Properties

any array of any rank **x** [INPUT, MANDATORY, default=no default value]

long array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of any rank x [INPUT, MANDATORY, default=no default value]

The input array can be an array of rank 1. Only float or double arrays are allowed.

long array y [OUTPUT, MANDATORY, default=no default value]

Returns a long array. In order to create an array of a different type, you have to create the new array type using the returned array as an argument to the constructor (see examples).

See also

- CEIL
- FLOOR
- ROUND

2.131. Flag

Full Name:	herschel.ia.dataset.image.Flag
Alias:	Flag
Type:	Java Class -
Import:	from herschel.ia.dataset.image import Flag
Category:	Image

Description

A class to describe Flags for images (SimpleImage, SimpleCube, SimpleStack, SlicedImage, SlicedCube and SlicedStack).

This class represents different kinds of flags in n-dimensions. The Flag is defined as an ArrayDataset. The different flag types are defined in the metadata of the ArrayDataset, a Shortnd describes the flags.

Example

Example 1: A basic example on how to create a Flag for an SimpleImage with dimensions 310 x 200.

```
flag = Flag(200, 310)
# Only the -"UNVALID" flag type is available after constructing the Flag.
# Adding an extra -"GLITCH" flag type.
flag.addFlagType("GLITCH", -"Flag for signals affected by a cosmic ray hit")
# Adding information about the flagged pixels.
# validFlagData is a Bool2d, with the same dimensions of the flag (310 x 200)
flag.setFlag("UNVALID", validFlagData)
flag.setFlag("GLITCH", glitchFlagData)
# Getting information on Flagged pixels
print flag.getFlag("GLITCH")
```

API Summary

Constructors
Flag() The standard constructor for a Flag
Flag(int k) Constructor for a 1 dimensional flag
Flag(int k, int l) Constructor for a 2 dimensional flag
Flag(int k, int l, int m) Constructor for a 3 dimensional flag
Flag(int k, int l, int m, int n) A constructor for a four-dimensional flag of given dimensions.
Flag(int k, int l, int m, int n, int o) Constructor for a 5 dimensional flag
Flag(Flag flag) The copy constructor

Methods
`Flag copy()` The copy method returns a new Flag which is a copy of the original flag
`addFlagType(String flagType, String description)` Defines a new flag type.
`String1d getFlagTypes()` Give a list with the defined flag types.
`boolean hasFlag(String name)` Checks if the flag exists.
`AbstractArrayData getFlag(String flagType)` Gives the flag for this specific flag type.
`AbstractArrayData getFlag()` Gives the flag.
`AbstractArrayData getFlagAsShortnd()` Gives the flag.
`setFlag(String flagType, AbstractArrayData flag)` Sets the flag for this specific flag type.
`setFlag(String flagType, int index, boolean flag)` Sets the flag of a certain pixel.
`setFlag(String flagType, int row, int column, boolean flag)` Sets the flag of a certain pixel.
`setFlag(String flagType, int index1, int index2, int index3, boolean flag)` Sets the flag of a certain pixel.
`setFlag(String flagType, int index1, int index2, int index3, int index4, boolean flag)` Sets the flag of a certain pixel.
`setFlag(String flagType, int index1, int index2, int index3, int index4, int index5, boolean flag)` Sets the flag of a certain pixel.

API details

Constructors

`Flag()`
The standard constructor for a Flag A constructor for a flag. After construction, 1 flagtype is available : UNVALID

`Flag(int k)`
Constructor for a 1 dimensional flag A constructor for a one-dimensional flag of given dimension. A Flag of k elements in 1 dimension is made. No pixels are masked out. After construction, 1 flagtype is available : UNVALID **Argument**

Flag(int k)

int **k** [INPUT, MANDATORY]

Example

Typical example on how to create a one-dimensional Flag.

```
flag = Flag(100)
```

Flag(int k, int l)

Constructor for a 2 dimensional flag

A constructor for a two-dimensional flag of given dimensions. A Flag of (k, l) elements in 2 dimensions is made. No pixels are masked out. After construction, 1 flagtype is available : UNVALID

Arguments

int **k** [INPUT, MANDATORY]

int **l** [INPUT, MANDATORY]

Example

Typical example on how to create a 2-dimensional Flag.

```
flag = Flag(100, 50)
```

Flag(int k, int l, int m)

Constructor for a 3 dimensional flag

A constructor for a three-dimensional flag of given dimensions. A Flag of (k, l, m) elements in 3 dimensions is made. No pixels are masked out. After construction, 1 flagtype is available : UNVALID

Arguments

int **k** [INPUT, MANDATORY]

int **l** [INPUT, MANDATORY]

int **m** [INPUT, MANDATORY]

Example

Typical example on how to create a 3-dimensional Flag.

```
flag = Flag(100, 50, 75)
```

Flag(int k, int l, int m, int n)

A constructor for a four-dimensional flag of given dimensions.

A Flag of (k, l, m, n) elements in 4 dimensions is made. No pixels are masked out. After construction, 1 flagtype is available : UNVALID

Arguments

int **k** [INPUT, MANDATORY]

int **l** [INPUT, MANDATORY]

int **m** [INPUT, MANDATORY]

int **n** [INPUT, MANDATORY]

Example

Typical example on how to create a 4-dimensional Flag.

Flag(int k, int l, int m, int n)

```
flag = Flag(100, 50, 75, 125)
```

Flag(int k, int l, int m, int n, int o)

Constructor for a 5 dimensional flag

A constructor for a five-dimensional flag of given dimensions. A Flag of (k, l, m, n, o) elements in 5 dimensions is made. No pixels are masked out. After construction, 1 flagtype is available : UNVALID

Arguments

`int k [INPUT, MANDATORY]`
`int l [INPUT, MANDATORY]`
`int m [INPUT, MANDATORY]`
`int n [INPUT, MANDATORY]`
`int o [INPUT, MANDATORY]`

Example

Typical example on how to create a 5-dimensional Flag.

```
flag = Flag(100, 50, 75, 125, 25)
```

Flag(Flag flag)

The copy constructor

The copy constructor makes an exact copy of the flag.

Argument

`Flag flag [INPUT, MANDATORY]`

Methods

Flag copy()

The copy method returns a new Flag which is a copy of the original flag

The copy method returns a new Flag which is a copy of the original flag

Return

Flag

Dataset A new Flag which is a copy of the current Flag.

addFlagType(String flagType, String description)

Defines a new flag type.

Define a new flag type : a temporary flag type that can be used at the user's discretion in the processing. This method guarantees that the identifier used does not interfere with existing identifiers. There can be no more than 16 different flag types.

Arguments

`String flagType [INPUT, MANDATORY]`
`String description [INPUT, MANDATORY]`

String1d getFlagTypes()

Give a list with the defined flag types.

Give a list of the defined flag types. A String1d with all defined flag types is returned.

Return

String1d

The list of the mask type identifiers

boolean hasFlag(String name)

Checks if the flag exists.

Checks if the flag type exists. Returns true if the flag has the given flag type.

Argument

String **name** [INPUT, MANDATORY]

Return

boolean

The list of the mask type identifiers Returns true if the flag has the given flag type.

AbstractArrayData getFlag(String flagType)

Gives the flag for this specific flag type.

Gives the flag for this specific flag type as an AbstractArrayData. Depending on the dimensions of the flag, a Boolnd is returned with the flag for a given flag type.

Argument

String **flagType** [INPUT, MANDATORY]

Return

AbstractArrayData

A Boolnd (depending on the dimension of the flag), describing the flag of the given flagType.

AbstractArrayData getFlag()

Gives the flag.

Gives the flag as an AbstractArrayData. Depending on the dimensions of the flag, a Boolnd is returned with the flag.

Return

AbstractArrayData

A Boolnd (depending on the dimension of the flag), describing the flag

AbstractArrayData getFlagAsShortnd()

Gives the flag.

Gives the flag as an AbstractArrayData. Depending on the dimensions of the flag, a Shortnd is returned with the flag.

AbstractArrayData getFlagAsShortnd()

Return

AbstractArrayData

A Shortnd (depending on the dimension of the flag), describing the flag

setFlag(String flagType, AbstractArrayData flag)

Sets the flag for this specific flag type.

Sets the flag for this specific flag type as an AbstractArrayData. A boolnd can be given for a flag type. If the boolnd does not have the same dimension as the dimension of the flag, an IllegalArgumentException is thrown.

Arguments

`String` **flagType** [INPUT, MANDATORY]

`AbstractArrayData` **flag** [INPUT, MANDATORY]

setFlag(String flagType, int index, boolean flag)

Sets the flag of a certain pixel.

Set a certain flag of a certain flagType to a certain value

Arguments

`String` **flagType** [INPUT, MANDATORY]

`int` **index** [INPUT, MANDATORY]

`boolean` **flag** [INPUT, MANDATORY]

setFlag(String flagType, int row, int column, boolean flag)

Sets the flag of a certain pixel.

Set a certain flag of a certain flagType to a certain value

Arguments

`String` **flagType** [INPUT, MANDATORY]

`int` **row** [INPUT, MANDATORY]

`int` **column** [INPUT, MANDATORY]

`boolean` **flag** [INPUT, MANDATORY]

setFlag(String flagType, int index1, int index2, int index3, boolean flag)

Sets the flag of a certain pixel.

Set a certain flag of a certain flagType to a certain value

Arguments

`String` **flagType** [INPUT, MANDATORY]

`int` **index1** [INPUT, MANDATORY]

`int` **index2** [INPUT, MANDATORY]

`int` **index3** [INPUT, MANDATORY]

`boolean` **flag** [INPUT, MANDATORY]

setFlag(String flagType, int index1, int index2, int index3, int index4, boolean flag)

Sets the flag of a certain pixel.

Set a certain flag of a certain flagType to a certain value

Arguments

- `String` **flagType** [INPUT, MANDATORY]
- `int` **index1** [INPUT, MANDATORY]
- `int` **index2** [INPUT, MANDATORY]
- `int` **index3** [INPUT, MANDATORY]
- `int` **index4** [INPUT, MANDATORY]
- `boolean` **flag** [INPUT, MANDATORY]

setFlag(String flagType, int index1, int index2, int index3, int index4, int index5, boolean flag)

Sets the flag of a certain pixel.

Set a certain flag of a certain flagType to a certain value

Arguments

- `String` **flagType** [INPUT, MANDATORY]
- `int` **index1** [INPUT, MANDATORY]
- `int` **index2** [INPUT, MANDATORY]
- `int` **index3** [INPUT, MANDATORY]
- `int` **index4** [INPUT, MANDATORY]
- `int` **index5** [INPUT, MANDATORY]
- `boolean` **flag** [INPUT, MANDATORY]

See also

- SimpleImage
- SimpleCube

2.132. FlagPixels

Full Name:	herschel.ia.toolbox.spectrum.FlagPixels
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import FlagPixels

Description

Task for flagging pixels pf spectra included in a spectrum container.

The flagging task always modifies the input data.

You have different alternatives to specify a 'mask' with the pixel indices to be flagged.

- General mask: For each segment within a specific point spectrum specify an entry in a dictionary, with keys given by tuples (i,j) (where i stands for the point spectrum index and j for the segment index) and values specifying the list of pixel to be flagged.
- Uniform masks: For all the point spectra (possibly restricted by a suitable selection model - see the 'selection' parameter below) the same mask apply. This is given again by a dictionary where the keys specify the segment index (an integer) and the values specify the list of pixel indices to be flagged. Alternatively, you can directly specify a java.util.Map with Integer keys and herschel.ia.dataset.Selection as values. The values specified as Selection's contain the indices of the pixels to be flagged. Alternatively, instead of a Selection you can also specify an Int1d cointaining the indices or a Bool1d with 'true' at the positions the flag should be set.
- Uniform masks, uniform for several segments: Specify a list of pixel indices to be flagged. This mask applies to all the segments and point spectra - possibly restricted by a suitable 'selection' and 'segments' indices.

As input spectra you can specify not only a single spectrum container but also a list of spectrum containers. Alternatively, you can specify a list of tuples with the first argument in the tuple specifying the spectrum container and the second argument the mask with the pixels to be flagged.

Example

Example 1: from Jide:

```
# Set flag 2 in point spectrum 2 and segments 1 at the pixel indices 1,2,667
and
# in point spectrum 2 and segment 3 at the pixel indices 30,690.
flagPixels(ds=spectra, mask={(2,1):[1,20,667], (2,3):[30,690]}, flag=2)
# Set flag 2 in segments 1 and 2 at the indices 1,2,667 and 30,690
respectively.
flagPixels(ds=spectra, mask={1:[1,20,667], 2:[30,690]}, flag=2)
# flag power(2,30) is set at the same positions.
flagPixels(ds=spectra, mask={1:[1,20,667], 2:[30,690]})
# Set flag 2 in segments 1 and 2 at the indices 1,2,667 and 30,690
respectively,
# but only in the point spectra with indices [0,1,2,3]
# For further ways of how to specify selections see e.g. the AverageSpectrum-
task
flagPixels(ds=spectra, selection=[0,1,2,3], mask={1:[1,20,667], 2:[30,690]},
flag=2)
# Set flag 2 at the pixels 1,20,667 in the segments 1,2,3 in point spectra
with the bbtype-attribute equal to 6031.
flagPixels(ds=spectra, mask=[1,20,667], segments=[1,2,3], selection={"bbtype":
[6031]}, flag=2)
# For spectra1 and spectra2 two SpectrumContainers:
# Set flag 2 at the pixels 1,20,667 in the segments 1,2,3 for spectra1 and
```

Example 1: from Jide:

```
# for spectra2 in point spectrum 2 and segments 1 at the pixel indices
1,2,667 and
# in point spectrum 2 and segment 3 at the pixel indices 30,690.
flagPixels(ds=[(spectra1,[1,20,667]),(spectra2,{(2,1):[1,20,667], (2,3):
[30,690]})], segments=[1,2,3], flag=2)
# With a single container you can just specify one tuple:
flagPixels(ds=(spectra,{(2,1):[1,20,667], (2,3):[30,690]}), flag=2)
```

API Summary

Properties
Object **ds** [INOUT, MANDATORY, default=no default value.]
Object **mask** [INPUT, OPTIONAL, default=None.]
Object **selection** [INPUT, OPTIONAL, default=None.]
int **flag** [INPUT, OPTIONAL, default=2 up to the power of 30 = 1073741824.]
Boolean **setFluxToNaN** [INPUT, OPTIONAL, default=False.]

API details

Properties

Object ds [INOUT, MANDATORY, default=no default value.]

The input container(s) in which pixels should be flagged. See examples below.

Object mask [INPUT, OPTIONAL, default=None.]

Specification of the pixels to flag. See the description above and the examples below.

Object selection [INPUT, OPTIONAL, default=None.]

Specification of what point spectra the flagging mask should be applied to. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra for which the mask should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

int flag [INPUT, OPTIONAL, default=2 up to the power of 30 = 1073741824.]

The flag value to set for the specified pixel.

Boolean setFluxToNaN [INPUT, OPTIONAL, default=False.]

Boolean to indicate that the flux value of the pixels to flag should be set to NaN. This will typically remove the pixel from plots.

History

- `2009-04-29 - meli`: initial
- `2009-05-31 - meli`: first extensions

2.133. FlagSaturatedPixelsCubeTask

Full Name:	herschel.ia.toolbox.cube.FlagSaturatedPixelsCubeTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import FlagSaturatedPixelsCubeTask

Description

A Task to flag saturated pixels in a cube.

API Summary

Properties
Cube **cube** [INPUT, MANDATORY, default=No default value]
Double **value** [INPUT, MANDATORY, default=No default value]
Cube **result** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Cube cube [INPUT, MANDATORY, default=No default value]

The cube.

Double value [INPUT, MANDATORY, default=No default value]

The value of saturation.

Cube result [OUTPUT, MANDATORY, default=No default value]

The resulting cube.

2.134. FlagSaturatedPixelsTask

Full Name:	herschel.ia.toolbox.image.FlagSaturatedPixelsTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import FlagSaturatedPixelsTask

Description

A Task to flag saturated pixels.

A Task to flag saturated pixels in an image.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double value [INPUT, MANDATORY, default=No default value]`
`Image flaggedImage [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image.

`Double value [INPUT, MANDATORY, default=No default value]`

The value of saturation.

`Image flaggedImage [OUTPUT, MANDATORY, default=No default value]`

The resulting image.

2.135. Float1d

Full Name:	herschel.ia.numeric.Float1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Float1d

Description

A rectangular numeric float array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.136. Float2d

Full Name:	herschel.ia.numeric.Float2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Float2d

Description

A rectangular numeric float array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.137. Float3d

Full Name:	herschel.ia.numeric.Float3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Float3d

Description

A rectangular numeric float array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.138. Float4d

Full Name:	herschel.ia.numeric.Float4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Float4d

Description

A rectangular numeric float array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.139. Float5d

Full Name:	herschel.ia.numeric.Float5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Float5d

Description

A rectangular numeric float array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.140. FLOOR

Full Name:	herschel.ia.numeric.toolbox.basic.Floor
Alias:	FLOOR
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Floor

Description

Gives the largest integer less than or equal to x.

Returns a float array for float input array and double array for any other numeric array type.

Example

Example 1: Apply FLOOR on a Float1d

```
x=Float1d([0.1,0.5,0.9])
print FLOOR(x) # [0.0,0.0,0.0]
```

API Summary

Jython Syntax
<y>=FLOOR(<x>)

Properties
any array of any rank **x** [INPUT, MANDATORY, default=no default value]
float or double array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of any rank x [INPUT, MANDATORY, default=no default value]

The input array can be an array of rank 1

float or double array y [OUTPUT, MANDATORY, default=no default value]

Returns a float array for float input array and double array for any other numeric array type.

See also

- CEIL
- ROUND

2.141. FoldSpectrum

Full Name:	herschel.ia.toolbox.spectrum.FoldSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import FoldSpectrum

Description

Task for folding frequency-switched spectra.

The folded spectra are constructed by averaging the original spectra with a shifted and inverted copy. This algorithm corresponds to the most simple scheme described in article {\it "Recovering line profiles from frequency-switched spectra}, H.Liszt, Astron. Astrophys. Suppl. Ser. 124, 183-188 (1997)}. By default, the task modifies the input spectra. Note that the operation is performed on a per segment basis. For that reason you may consider stitching the segments before folding.

API Summary

Properties
SpectrumContainer **ds** [INPUT, MANDATORY, default=no default value.]
SpectrumContainer **result** [OUTPUT, MANDATORY, default=no default value.]
Double **freqThrow** [INPUT, MANDATORY, default=0.0.]
String **unit** [INPUT, OPTIONAL, default=no default value.]
Boolean **shift** [INPUT, OPTIONAL, default=False.]
Boolean **overwrite** [INPUT, OPTIONAL, default=True.]

API details

Properties

SpectrumContainer ds [INPUT, MANDATORY, default=no default value.]

Input container with the spectra to be folded.

SpectrumContainer result [OUTPUT, MANDATORY, default=no default value.]

Output container with the folded spectra.

Double freqThrow [INPUT, MANDATORY, default=0.0.]

The frequency throw in the spectra to be folded. The same specified value is applied to all the spectra in the container.

String unit [INPUT, OPTIONAL, default=no default value.]

Specify the unit the frequency throw is expressed in. If no unit is specified it is assumed that the unit of the frequency throw is assumed to be the same as the one found on the wave scale. Typical values are "GHz" or "MHz".

Boolean shift [INPUT, OPTIONAL, default=False.]

If true, the spectrum is shifted in frequency scale by half the throw distance so that the resulting spectrum is centred between the original and the "switched" spectrum.

Boolean overwrite [INPUT, OPTIONAL, default=True.]

Specify whether the input data container can be reused - the values found therein are overwritten. If set to false, a new container is created and the spectral segments are reduced in shape by the frequency throw distance.

2.142. FullQuery

Full Name:	herschel.ia.pal.query.FullQuery
Type:	Java Class -
Import:	from herschel.ia.pal.query import FullQuery

Description

A data mining query formulates a query the full interface of a

Product. As such, one can query any aspect of a Product. Typically this type of query is quite slow and should be used in combination with query refinements.

Example

Example 1: Example of a data mining query

```
q=FullQuery(MyProduct.class,"p",  -"ANY(p['array'].data<2)")
```

See also

- ???

2.143. GAMMALN

Full Name:	herschel.ia.numeric.toolbox.basic.GammaLn
Alias:	GAMMALN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import GammaLn

Description

Computes the natural log of the Gamma function.

Example

Example 1: Apply GAMMALN on a Double1d

```
x = Double1d([1.0,2.0,3.0,4.0,5.0,6.0])
gn = GAMMALN(x)
print gn  # [0.0,-4.440892098500626E-16,0.6931471805599443,
            1.791759469228055,3.1780538303479453,4.787491742782044]
```

API Summary

Jython Syntax
<y>=GAMMALN(<x>)

Properties
an double array or a number **x** [INPUT, MANDATORY, default=.]
returns an array **y** [OUTPUT, (or a number if the input is a number), default=no default value]

API details

Properties

an double array or a number x [INPUT, MANDATORY, default=.]

returns an array y [OUTPUT, (or a number if the input is a number), default=no default value]

where each element is the natural logarithm of the Gamma function of the corresponding element of the input array.

See also

- GammaP
- GammaQ

2.144. GammaP

Full Name:	herschel.ia.numeric.toolbox.basic.GammaP
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import GammaP

Description

Computes the incomplete Gamma function P(a,x).

Example

Example 1: Apply GammaP on a Double1d

```
a = 0.5
x = Double1d([0.0316228,0.0707107,5.0,1.04881,2.44949,25.4951])
gp = GammaP(a)(x)
print gp  # [0.19856221732013887,0.2931279825202761,0.9984345977771615,
            0.8524713739638958,0.9731274396553844,0.9999999999990717]
]
```

API Summary

Jython Syntax
<y>=GammaP(a)(<x>)

Properties
a double value **a** [INPUT, MANDATORY, default=.]
a double array or number **x** [INPUT, MANDATORY, default=.]
returns an double or float array (or a number **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

a double value a [INPUT, MANDATORY, default=.]

a double array or number x [INPUT, MANDATORY, default=.]

returns an double or float array (or a number y [OUTPUT, MANDATORY, default=no default value]

if the input is a number) where each element is the incomplete Gamma function of the corresponding element of the input array.

See also

- GammaQ
- GAMMALN

2.145. GammaQ

Full Name:	herschel.ia.numeric.toolbox.basic.GammaQ
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import GammaQ

Description

Computes the complement of incomplete Gamma function Q(a,x).

Example

Example 1: Apply GammaQ on a Double1d

```
a = 0.5
x = Double1d([0.5,0.0316228,0.0707107,5.0,1.04881,2.44949,25.4951])
gq = GammaQ(a)(x)
print gq  # [0.31731050863888255,0.8014377826798611,0.7068720174797238,

0.001565402222838555,0.14752862603610417,0.026872560344615565,9.282826956361127E-13]
```

API Summary

Jython Syntax
<y>=GammaQ(a)(<x>)

Properties
a double value **a** [INPUT, MANDATORY, default=.]
a double array or number **x** [INPUT, MANDATORY, default=.]
returns an array (or a number if the input is a number) **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

a double value a [INPUT, MANDATORY, default=.]

a double array or number x [INPUT, MANDATORY, default=.]

returns an array (or a number if the input is a number) y [OUTPUT, MANDATORY, default=no default value]

where each element is the complement of the incomplete Gamma function of the corresponding element of the input array.

See also

- GammaP
- GAMMALN

2.146. GaussFitTask

Full Name:	herschel.ia.toolbox.fit.GaussFitTask
Alias:	GaussFitTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.fit import GaussFitTask
Category:	generic task

Description

generic module: GaussFitTask

Task shell around the package herschel.ia.numeric.toolbox.fit. Both a command line and a GUI interface are provided. With the GUI interface there is more of the Fitter package accessable than on this tasks command line. However not everything possible within the fitter package is accessable via this task, GUI or otherwise. Most text fields in the GUI accept either numerics or JIDE variables or JIDE expressions.

Example

Example 1: GaussFitTask

```
<pre>
from herschel.hifi.generic.task import GaussFitTask
# Assume that `tt' and/or `data' are Double1d's
# usage on command line:
ft = GaussFitTask()( x=tt, y=data -)
ft.fitter = -"LevenbergMarquardtFitter"
ft()            # performs the execute method
print ft.result        # parameters of the fit
print ft.stdev        # standard deviations
print ft.fitter        # name of the fitter
# Etcetera, etc.
# use the GUI.
ft = GaussFitTask()
ft.gui = 1         # start the GUI
# from the GUI select the data, model, fitter, properties etc and run.
print ft.result        # parameters of the fit
print ft.stdev        # standard deviations
print ft.fitter        # name of the fitter
# Etcetera as before.
</pre>
```

API Summary

Jython Syntax

```
see example below
```

Properties

NumericData **x** [INPUT, OPTIONAL, default=null]
DoubleArray **y** [INPUT, MANDATORY, default=no]
Boolean **indexview** [INPUT, OPTIONAL, default=true]
DoubleArray **weights** [INPUT, OPTIONAL, default=null]
AbstractModel **model** [INPUT, OPTIONAL, default=null]

Properties
String **modelname** [INPUT, OPTIONAL, default=no]
Array1dData **modelarg** [INPUT, OPTIONAL, default=null]
Fitter **fitter** [INPUT, OPTIONAL, default=null]
String **fittername** [INPUT, true, default=no]
String **autoinit** [INPUT, OPTIONAL, default=""]
Integer **smooth** [INPUT, OPTIONAL, default=1]
Double1d **result** [OUTPUT, OPTIONAL, default=n/a]
Double1d **parameters** [OUTPUT, OPTIONAL, default=n/a]
Double1d **stdev** [OUTPUT, OPTIONAL, default=n/a]
Double **chisq** [OUTPUT, OPTIONAL, default=n/a]
DoubleArray **yfit** [OUTPUT, OPTIONAL, default=n/a]
DoubleArray **yband** [OUTPUT, OPTIONAL, default=n/a]
Double1d **prior** [INPUT, OPTIONAL, default=null]
Double **evidence** [OUTPUT, OPTIONAL, default=n/a]
Double **scale** [OUTPUT, OPTIONAL, default=n/a]
Boolean **auto** [INPUT, OPTIONAL, default=false]
Double **fixed** [INPUT, OPTIONAL, default=1.0]
Double **mixed** [INPUT, OPTIONAL, default=0.0]
Double **tolerance** [INPUT, OPTIONAL, default=0.01]
Integer **iterations** [INPUT, OPTIONAL, default=10000]
Double **temperature** [INPUT, OPTIONAL, default=0.0]
Double **cooling** [INPUT, OPTIONAL, default=0.95]
Integer **tempsteps** [INPUT, OPTIONAL, default=100]
Double1d **initialpars** [INPUT, OPTIONAL, default=from model]
Double1d **highlimits** [INPUT, OPTIONAL, default=null]
Double1d **lowlimits** [INPUT, OPTIONAL, default=null]
Int1d **keepfixed** [INPUT, OPTIONAL, default=null]
Double1d **fixedvalues** [INPUT, OPTIONAL, default=null]
Boolean **gui** [INPUT, OPTIONAL, default=false]

Limitations

Not everything which is possible using the package directly is accessable via this task.

API details

Properties

NumericData x [INPUT, OPTIONAL, default=null]
The independent variable(s) of the fit problem. If not provided, it will use indices ranging from 0 to len(y). If y is more-dimensional the proper 2-d indices are provided.

DoubleArray y [INPUT, MANDATORY, default=no]
The data to be fitted. It can be more-dimensional. E.g. a 2-dimensional map.

Boolean indexview [INPUT, OPTIONAL, default=true]

Applicable parameters appear in the same order as in the y DoubleArray This parameter is only active when y has 2 dimensions or more.

DoubleArray weights [INPUT, OPTIONAL, default=null]

The weights to be used in the fit. Can be more-dimensional. When provided it should be the same size as parameter y.

AbstractModel model [INPUT, OPTIONAL, default=null]

The model to be fitted. Default: GaussModel (for 1d data) or Gauss2DModel (for 2d data)

String modelname [INPUT, OPTIONAL, default=no]

The model to be fitted. Default: GaussModel (for 1d data) or Gauss2DModel (for 2d data)

Array1dData modelarg [INPUT, OPTIONAL, default=null]

Arguments, if any, needed in the Constructor of the model.

Fitter fitter [INPUT, OPTIONAL, default=null]

Fitter to be used. Default: LevenbergMarquardtFitter

String fittername [INPUT, true, default=no]

Fitter to be used. Default: LevenbergMarquardtFitter

String autoinit [INPUT, OPTIONAL, default=""]

Automated search for initial params. options: "high", "low", "center"

Integer smooth [INPUT, OPTIONAL, default=1]

Smooth data with BoxCarFilter before auto-search. smooth > 1.

Double1d result [OUTPUT, OPTIONAL, default=n/a]

The parameters of the fit.

Double1d parameters [OUTPUT, OPTIONAL, default=n/a]

The parameters of the fit. (same as result)

Double1d stdev [OUTPUT, OPTIONAL, default=n/a]

The standard deviations pertaining to the parameters.

Double chisq [OUTPUT, OPTIONAL, default=n/a]

Chi-squared of the fit.

DoubleArray yfit [OUTPUT, OPTIONAL, default=n/a]

An array of the same size as the data, containing the fitted valued

DoubleArray yband [OUTPUT, OPTIONAL, default=n/a]

An array of the same size as the data, containing a 1-# MonteCarlo error at each point.

Double1d prior [INPUT, OPTIONAL, default=null]

Prior ranges for the parameters, needed when the evidence is requested.

Double evidence [OUTPUT, OPTIONAL, default=n/a]

Relative evidence the model carries w.r.t. the data. It needs values for prior, as many as the number of parameters and one more if auto-scaling is set.

Double scale [OUTPUT, OPTIONAL, default=n/a]

Noise scale of the data (when auto or mixed is selected)

Boolean auto [INPUT, OPTIONAL, default=false]

Select automatic noise scaling.

Double fixed [INPUT, OPTIONAL, default=1.0]

Fixed noise scale.

Double mixed [INPUT, OPTIONAL, default=0.0]

Automatic noise scaling with a minimum.

Double tolerance [INPUT, OPTIONAL, default=0.01]

Stopping criterion for iterative fitting.

Integer iterations [INPUT, OPTIONAL, default=10000]

Maximum number of iterations.

Double temperature [INPUT, OPTIONAL, default=0.0]

Starting temperature in annealing amoeba fitting.

Double cooling [INPUT, OPTIONAL, default=0.95]

Cooling step in annealing amoeba fitting.

Integer tempsteps [INPUT, OPTIONAL, default=100]

Number of exploratory steps at each temperature.

Double1d initialpars [INPUT, OPTIONAL, default=from model]

Initial parameters in iterative fitters.

Double1d highlimits [INPUT, OPTIONAL, default=null]

Upper limits of the parameters (only in AmoebaFitter)

Double1d lowlimits [INPUT, OPTIONAL, default=null]

Lower limits of the parameters (only in AmoebaFitter)

Int1d keepfixed [INPUT, OPTIONAL, default=null]

Keep these parameters fixed. (Parameter numbering starts at 0)

Double1d fixedvalues [INPUT, OPTIONAL, default=null]

Values at which the parameters should be kept.

Boolean gui [INPUT, OPTIONAL, default=false]

Allows to handle this task using a gui.

History

- 15-10-2006 DK

2.147. GaussianFilter

Full Name:	herschel.ia.numeric.toolbox.filter.GaussianFilter
Alias:	GaussianFilter
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.filter import GaussianFilter

Description

Creates a Gaussian filter, that can be applied to numeric arrays of rank 1.

Example

Example 1: Apply GaussianFilter on a Int1d

```
x=Int1d([1,3,2,4,6,5])
f=GaussianFilter(0.2)
print f(x) # [0.10650697891920073,1.1065069789192006,
             2.6804790632423976, 2.319520936757602,
             3.9999999999999996, 5.680479063242397]
```

API Summary

Jython Syntax

```
<f>=GaussianFilter(<sigma> [,<center>=true|false]
[,<edge>=Convolution.ZEROES|CIRCULAR|REPEAT])
<x>=<f>(<x>)
```

Properties

real **sigma** [INPUT, MANDATORY, default=no default value]

boolean **center** [INPUT, NOT MANDATORY, default=false]

Convolution.ZEROES|CIRCULAR|REPEAT **center** [INPUT, NOT MANDATORY, default=Convolution.ZEROES]

API details

Properties

real sigma [INPUT, MANDATORY, default=no default value]

It must be a real.

boolean center [INPUT, NOT_MANDATORY, default=false]

Set center to true or false.

Convolution.ZEROES|CIRCULAR|REPEAT center [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]

Set edge to true or false

- edge=Convolution.ZEROES: Set result to zero at edges.

Convolution.ZEROES|CIRCULAR|REPEAT center [INPUT, NOT_MANDATORY, default=Convolution.ZEROES]
• edge=Convolution.CIRCULAR: Wrap around at edges (circular convolution). • edge=Convolution.REPEAT: Repeat the edge values of input array.

See also

- BoxCarFilter
- Convolution

2.148. GaussianSmoothingTask

Full Name:	herschel.ia.toolbox.image.GaussianSmoothingTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import GaussianSmoothingTask

Description

A Task to smooth an image using a convolution with a gaussian.

A Task to smooth an image by convolving it with a gaussian function.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double sigma [INPUT, MANDATORY, default=Default value : Double(3.0)]`
`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image before smoothing.

`Double sigma [INPUT, MANDATORY, default=Default value : Double(3.0)]`

The standard deviation of the gaussian.

`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

The image after smoothing.

2.149. HAMMING

Full Name:	herschel.ia.numeric.toolbox.xform.Hamming
Alias:	HAMMING
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.xform import Hamming

Description

Hamming function for multiplying with input arrays.

This function performs an element-by-element multiplication of a input array with a Hamming function having the same number of elements. The Hamming function is defined by the following equation:

```
Hamming[i] = 0.54 + 0.46 * cos(2#( i-# -) -/ N)
where:
Hamming[i] is the value of the Hamming function at array index i, where 0#i\
#(N-1)
N is the length of the array for which the Hamming function is calculated.
# is the phase shift, defined as # = N/2.0
```

Input:

The input array should be a `Double1d` or `Float1d` and have length N#3.

Output:

The output array is a floating point array of length N that contains the element-by-element multiplication of the input array with the Hamming function.

Symmetry:

This equation produces a Hamming function with a unique point at index `i=0`. For even length arrays, the maximum amplitude is located at `N/2.0`. For odd length arrays, there are two amplitude maxima located at `ceiling(N/2.0)` and `floor(N/2.0)`.

Syntax:

To apply an element-by-element multiplication of the array `x` by the Hamming function, use any of the following options while coding in Jython:

1. `p = HAMMING(x) #Area normalized`
2. `p = HAMMING.AREA(x) #Area normalized, alternative syntax`
3. `q = HAMMING.AMPLITUDE(x) #Amplitude normalized`
4. `r = HAMMING.ENERGY(x) #Energy normalized`

Example

Example 1: Apply Hamming function to an input array x in java:

```
<pre>
 Double1d x = new Double1d(100,1.0); -// create array of 100 1's
 Double1d p = (Double1d)x.apply(Hamming.AREA); -// Area normalized
 Double1d p2 = (Double1d)x.apply(Hamming.PROCEDURE);  -//Area normalized,
alternative syntax
```

Example 1: Apply Hamming function to an input array x in java:

```
 Double1d q = (Double1d)x.apply(Hamming.AMPLITUDE);  -//Amplitude normalized
 Double1d r = (Double1d)x.apply(Hamming.ENERGY);  -//Energy normalized
</pre>
 In Jython:
<pre>
x = Double1d(100,1.0)
p = HAMMING(x) #Area normalized
p2 = HAMMING.AREA(x) #Area normalized, alternative syntax
q = HAMMING.AMPLITUDE(x) #Amplitude normalized
r = HAMMING.ENERGY(x) #Energy normalized
</pre>
```

API Summary

Jython Syntax
<y>=HAMMING.[<normalization> = AREA|AMPLITUDE|ENERGY] (<x>)

Properties
Double1d or Float1d **x** [INPUT, MANDATORY, default=No default value]
Double1d or Float1d **y** [OUTPUT, OPTIONAL, default=No default value]
AMPLITUDE|ENERGY|AREA|PROCEDURE **normalization** [INPUT, OPTIONAL, default=No default value]

Limitations

This function on operates on `Double1d` and `Float1d` arrays. It does not work for `Complex1d` arrays.

API details

Properties

Double1d or Float1d x [INPUT, MANDATORY, default=No default value]

The input array to be multiplied by the Hamming function.

Double1d or Float1d y [OUTPUT, OPTIONAL, default=No default value]

Outputs an array containing the element-by-element multiplication of the input array with the Hamming function.

AMPLITUDE|ENERGY|AREA|PROCEDURE normalization [INPUT, OPTIONAL, default=No default value]

The type of normalization of the Hamming function.

See also

- HAMMING

History

- 2007-Nov-23 (ZW) Added two new types of normalization.

- Changed the private constructor to take in one String parameter
- in order to have 3 types of normalization of the window functions.
- Changed some javadoc.
- 2008-Mar-07 (PK) Added static PROCEDURE member, modified n2 division and refactored.
- Used double to calculate n2 peak of the Hamming function thus affecting the symmetry of function.
- 2008-Mar-13 (PK) Changed to use a unique static member for each normalization.

2.150. HANNING

Full Name:	herschel.ia.numeric.toolbox.xform.Hanning
Alias:	HANNING
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.xform import Hanning

Description

Hanning function for multiplying with input arrays.

This function performs an element-by-element multiplication of a input array with a Hanning function having the same number of elements. The Hanning function is defined by the following equation:

```
Hanning[i] = 0.50 + 0.50 * cos(2#( i-# -) -/ N)
where:
Hanning[i] is the value of the Hanning function at array index i, where 0#i\
#(N-1)
N is the length of the array for which the Hanning function is calculated.
# is the phase shift, defined as # = N/2.0
```

Input:

The input array should be a `Double1d` or `Float1d` and have length N#3.

Output:

The output array is a floating point array of length N that contains the element-by-element multiplication of the input array with the Hanning function.

Symmetry:

This equation produces a Hanning function with a unique point at index `i=0`. For even length arrays, the maximum amplitude is located at `N/2.0`. For odd length arrays, there are two amplitude maxima located at `ceiling(N/2.0)` and `floor(N/2.0)`.

Syntax:

To apply an element-by-element multiplication of the array `x` by the Hanning function, use any of the following options while coding in Jython:

1. `p = HANNING(x) #Area normalized`
2. `p = HANNING.AREA(x) #Area normalized, alternative syntax`
3. `q = HANNING.AMPLITUDE(x) #Amplitude normalized`
4. `r = HANNING.ENERGY(x) #Energy normalized`

Example

Example 1: Apply Hanning function to an input array x in java:

```
<pre>
 Double1d x = new Double1d(100,1.0); -// create array of 100 1's
 Double1d p = (Double1d)x.apply(Hanning.AREA); -// Area normalized
 Double1d p2 = (Double1d)x.apply(Hanning.PROCEDURE);  -//Area normalized,
alternative syntax
```

Example 1: Apply Hanning function to an input array x in java:

```
 Double1d q = (Double1d)x.apply(Hanning.AMPLITUDE);  -//Amplitude normalized
 Double1d r = (Double1d)x.apply(Hanning.ENERGY);  -//Energy normalized
</pre>
 In Jython:
<pre>
x = Double1d(100,1.0)
p = HANNING(x) #Area normalized
p2 = HANNING.AREA(x) #Area normalized, alternative syntax
q = HANNING.AMPLITUDE(x) #Amplitude normalized
r = HANNING.ENERGY(x) #Energy normalized
</pre>
```

API Summary

Jython Syntax
<y>=HANNING.[<normalization> = AREA|AMPLITUDE|ENERGY] (<x>)

Properties
Double1d or Float1d **x** [INPUT, MANDATORY, default=No default value]
Double1d or Float1d **y** [OUTPUT, OPTIONAL, default=No default value]
AMPLITUDE|ENERGY|AREA|PROCEDURE **normalization** [INPUT, OPTIONAL, default=No default value]

Limitations

This function on operates on `Double1d` and `Float1d` arrays. It does not work for `Complex1d` arrays.

API details

Properties

Double1d or Float1d x [INPUT, MANDATORY, default=No default value]

The input array to be multiplied by the Hanning function.

Double1d or Float1d y [OUTPUT, OPTIONAL, default=No default value]

Outputs an array containing the element-by-element multiplication of the input array with the Hanning function.

AMPLITUDE|ENERGY|AREA|PROCEDURE normalization [INPUT, OPTIONAL, default=No default value]

The type of normalization of the Hanning function.

See also

- HANNING

History

- 2007-Nov-23 (ZW) Added two new types of normalization.

- Changed the private constructor to take in one String parameter
- in order to have 3 types of normalization of the window functions.
- Changed some javadoc.
- 2008-Mar-07 (PK) Added static PROCEDURE member, modified n2 division and refactored.
- Used double to calculate n2 peak of the Hanning function thus affecting the symmetry of function.
- 2008-Mar-13 (PK) Changed to use a unique static member for each normalization.

2.151. HduHeaders

Full Name:	herschel.ia.io.fits.HduHeaders
Alias:	HduHeaders
Type:	Java Class -
Import:	from herschel.ia.io.fits import HduHeaders
Category:	class

Description

A class for working with FITS HDUs. HDU data is loaded only when requested.

Restrictions:

- Only HCSS FITS files (version 4) can be modified and saved.
- Avoid working with several datasets at the same time if you are planning to modify them.
- Only FITS files can be modified (fits from an InputStream cannot be updated).
- If the HDU is a compositeDataset, the children are returned when asking for the HDU dataset.
- If you modify a CompositeDataset, only its Metadata can be updated. If you want to add or remove a CompositeDataset child, you must work with it directly (add/remove CompositeDataset children directly).
- If you remove a CompositeDataset, its children are removed also.
- When modifying/updating/removing HDUs, a temporary file is created.

Examples

Example 1: default usage:

```
fa = FitsArchive();
#fa.reader = FitsArchive.STANDARD_READER #for reading non HCSS FITS files.
fh = fa.getFitsHduHeaders(path)
print fh
#get last dataset
ds = fh.headers[fh.numHeaders-1].dataset
print ds
#or
h = fh.headers[fh.numHeaders-1]
ds = h.dataset
print ds
```

Example 2: modify a metadata/fits header:

```
fa = FitsArchive();
fh = fa.getFitsHduHeaders(path)
print fh
#get last dataset
h = fh.headers[fh.numHeaders-1]
ds = h.dataset
print ds
ds.description = -'new description'
h.updateDataset(ds)
#or
fh.updateDataset(fh.numHeaders-1, ds)
```

Example 3: add a new dataset/HDU:

```
fa = FitsArchive();
fh = fa.getFitsHduHeaders(path)
ds = ArrayDataset(Int1d([1,2,3]))
fh.addDataset('new_dataset_id',ds)
```

Example 4: remove a HDU:

```
fa = FitsArchive();
fh = fa.getFitsHduHeaders(path)
#remove last header
fh.removeHeader(fh.numHeaders-1)
```

2.152. help

Full Name:	herschel.ia.toolbox.util.HelpTask
Alias:	help
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import HelpTask
Category:	task

Description

The help task for interactive help.

Users can access the help system by calling help from the command line. Help opens a pop up window displaying the specific help topic for the specifed item or the main entry of documentation if no entry is specified or specific help can found.

The current implementation displays the specific help only for tasks, Plot and Image.

Examples

Example 1: overview help

```
help()
```

Example 2: help on help

```
help(help)
```

Example 3: help on plot (1)

```
p = PlotXY
help(p)
```

Example 4: help on plot (2)

```
help("plotxy")
```

Example 5: help on display (1)

```
d = Display()
help(d)
```

Example 6: help on display (2)

```
help("display")
```

API Summary

Jython Syntax
help() help(item)

Property
Object **item** [INPUT, NO, default=help]

Limitations

The current implementation displays the specific help only for tasks, Plot and Image.

Miscellaneous

No miscellaneous

API details

Property

Object item [INPUT, NO, default=help]
The item to look for in the help. Currently supported: Task(s), Plot, Image (see examples)

See also

- references

History

- 2004-07-13 - NdC: first release.

2.153. Histogram

Full Name:	herschel.ia.numeric.toolbox.basic.Histogram
Alias:	Histogram
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Histogram

Description

Create a histogram on a Numeric data type, using a user-specified

bin size.

Examples

Example 1: Apply Histogram on a Double1d

```
from herschel.ia.numeric import *
from herschel.ia.numeric.toolbox.random import RandomGauss
from herschel.ia.numeric.toolbox.basic import Histogram
from herschel.ia.numeric.toolbox.basic import BinCentres
hist=Histogram (1)
x=Double1d( [1,2,3,4] -)
print hist(x)  [1,1,1,1]
```

Example 2: Plot histogram over bin centres

```
d = Double1d(200000,10)
d[99000:110000] = 15
d[99900:101000] = 20.0
rnd = RandomGauss()
for ix in range(200000):
   d[ix] += rnd.calc(1.0)
p = PlotXY (d)
binsize = STDDEV (d) * 2.35
print binsize
hist=Histogram(binsize)
bins=BinCentres(binsize)
p=PlotXY(bins(d),hist(d)
# or you could try:  p = PlotXY (Histogram(binsize), BinCentres (binSize)
style=p.getStyle()
style.setChartType(Style.HISTOGRAM)
```

API Summary

Jython Syntax

```
<histogram>=Histogram(binSize)
<H>=histogram(<x>)
```

Properties

```
type binSize [INPUT, MANDATORY, default=no default value]
any array type x [INPUT, MANDATORY, default=no default value]
```

API details

Properties

type binSize [INPUT, MANDATORY, default=no default value]

Size of the histogram bins. See BinCentres for a description of the array of x-values for the centers of a histogram

any array type x [INPUT, MANDATORY, default=no default value]

See also

- BinCentres

2.154. Histogram

Full Name:	herschel.ia.toolbox.image.gui.Histogram
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import Histogram

Description

An implementation of making a histogram. You can choose the kind of area

of which to make a histogram, give the cut levels and the number of bins, used for the histogram. When you push the plot-button, the histogram will be shown and the eventual region will be marked on the image.

API Summary

Constructors
Histogram(ImageAnalysisToolbox toolbox) The standard constructor for Histogram. This constructor creates a window
Histogram(boolean useAsComponent, ImageAnalysisToolbox toolbox) Constructor for Histogram. When the new Histogram is

Methods
PlotXY **getPlot**() Returns the PlotXY shown in this Histogram.
JPanel **getPanel**() Returns the panel of this Histogram.
int **getUsedArea**() Returns the used type of area for this Histogram.
int **getUsedRegion**() Returns the used type of region for this Histogram.
int **getNumberOfEdges**() Returns the number of edges, if the region of interest is a
int **getUsedCutLevels**() Returns the used type of cut levels for this Histogram.
double[] **getCutlevels**() Returns the used cut levels (min, max) for this Histogram.
int **getNumberOfBins**() Returns the used number of bins for this Histogram.
int **getBinWidth**() Returns the width of the bins for this Histogram.
int **getNbOfClicks**() Returns the number of valid clicks (i.e. in the image) you made.
boolean **checkInput**() Returns true if the given input is correct; false otherwise. The

Methods
boolean **checkArea**() Checks whether the input area is correct. The error message is
boolean **checkParameters**() Checks whether the input parameters are correct. The error message
boolean **checkCutLevels**() Checks whether the input cut levels are correct. The error message
boolean **checkNumberOfBins**() Checks whether the input number of bins is correct. The error
ArrayList **getImageFigures**() Returns all ImageFigures used for this AreaHistogram (the eventual

API details

Constructors

Histogram(ImageAnalysisToolbox toolbox)

The standard constructor for Histogram. This constructor creates a window

in which you can make a histogram. In that window you give the input and retrieve the output.

Argument

ImageAnalysisToolbox **toolbox** [INPUT, MANDATORY]

Histogram(boolean useAsComponent, ImageAnalysisToolbox toolbox)

Constructor for Histogram. When the new Histogram is

component-based, a window for plotting the histogram is opened; otherwise nothing will be shown.

Arguments

boolean **useAsComponent** [INPUT, MANDATORY]

ImageAnalysisToolbox **toolbox** [INPUT, MANDATORY]

Methods

PlotXY getPlot()

Returns the PlotXY shown in this Histogram.

Return

PlotXY

Returns the PlotXY shown in this Histogram.

JPanel getPanel()

Returns the panel of this Histogram.

Return

JPanel

Returns the panel of this Histogram.

`int getUsedArea()`

Returns the used type of area for this Histogram.

Return

int

Returns the used type of area for this Histogram.

`int getUsedRegion()`

Returns the used type of region for this Histogram.

Return

int

Returns the used type of region for this Histogrem.

`int getNumberOfEdges()`

Returns the number of edges, if the region of interest is a

polygon; otherwise -1 is returned.

Return

int

Returns the number of edges, if the region of interest is a polygon; otherwise -1 is returned.

`int getUsedCutLevels()`

Returns the used type of cut levels for this Histogram.

Return

int

Returns the used type of cut levels for this Histogram.

`double[] getCutlevels()`

Returns the used cut levels (min, max) for this Histogram.

Return

double[]

Returns the used cut levels (min, max) for this Histogram.

`int getNumberOfBins()`

Returns the used number of bins for this Histogram.

Return

int

Returns the used number of bins for this Histogram.

`int getBinWidth()`

Returns the width of the bins for this Histogram.

Return

`int getBinWidth()`

int

Returns the width of the bins for this Histogram.

`int getNbOfClicks()`

Returns the number of valid clicks (i.e. in the image) you made.

Return

int

Returns the number of valid clicks (i.e. in the image) you made.

`boolean checkInput()`

Returns true if the given input is correct; false otherwise. The

eventual appropriate error message is also constructed here.

Return

boolean

Returns true if the given input is correct; false otherwise.

`boolean checkArea()`

Checks whether the input area is correct. The error message is

adapted, when errors occur.

Return

boolean

Returns true if the input area is correct; false otherwise.

`boolean checkParameters()`

Checks whether the input parameters are correct. The error message

is adapted, when errors occur.

Return

boolean

Returns true if the input parameters are correct; false otherwise.

`boolean checkCutLevels()`

Checks whether the input cut levels are correct. The error message

is adapted, when errors occur.

Return

boolean

Returns true if the input cut levels are correct; false otherwise.

`boolean checkNumberOfBins()`

Checks whether the input number of bins is correct. The error

message is adapted, when errors occur.

Return

boolean

Returns true if the input number of bins is correct; false otherwise.

`ArrayList getImageFigures()`

Returns all ImageFigures used for this AreaHistogram (the eventual

region of interest).

Return

ArrayList

Returns all ImageFigures used for this AreaHistogram (the eventual region of interest).

2.155. HistogramPanel

Full Name:	herschel.ia.toolbox.image.gui.HistogramPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import HistogramPanel

Description

A panel for the HistogramTask.

A panel to serve as GUI for the HistogramTask

API Summary

Constructor
HistogramPanel() The construction of a new HistogramPanel.

Methods
JPanel **getImagePanel()** Returns a display of the image.
JPanel **getParameterPanel()** Returns the parameter panel.
JPanel **getButtonPanel()** Returns the button panel.
setSiteEventHandler(SiteEventHandler handler) Setting the site event handler.
setTask(TaskApi task) Associating the task.
setVariableSelection(VariableSelection selection) Setting the variable selection.
Display **getDisplay()** Returns the display for this HistogramPanel.
Image **getImage()** Returns the associated image.
TaskApi **getTask()** Returns the associated image.
Map **getMap()** Returns the associated map.
SiteEventHandler **getHandler()** Returns the associated site event handler.
Double **getInputLowCut()** Returns the input low cut level.
getInputHighCut() Returns the input high cut level.

Methods
getInputNbOfBins() Returns the input number of bins.
PlotXY **getHistogram()** Returns the associated histogram.
setPoint(MouseEvent me) Storing the given mouse event in pixel coordinates.
setPoint(Double point) Storing the given screen coordinates in pixel coordinates.
updateFigure() Updates the associated figure.
ArrayList **getClickedPoints()** Returns the clicked points in pixel coordinates.
int **getNbOfClickedPoints()** Returns the number of times there was clicked before on the image.
increaseClicks() Increases the number of clicks made before on the image.
drawFigure() Draws the figure on the associated image.
trigger() Triggers the execution of the associated task.
updateHistogram() Updates the associated histogram.

API details

Constructor

HistogramPanel()
The construction of a new HistogramPanel. The construction of a new HistogramPanel.

Methods

JPanel getImagePanel()
Returns a display of the image. Returns a panel that displays the image for this HistogramPanel. **Return** **JPanel** Returns a panel that displays the image for this HistogramPanel.

JPanel getParameterPanel()
Returns the parameter panel.

JPanel getParameterPanel()

Returns the parameter panel for this HistogramPanel.

Return

JPanel

Returns the parameter panel for this HistogramPanel.

JPanel getButtonPanel()

Returns the button panel.

Returns the button panel for this HistogramPanel.

Return

JPanel

Returns the button panel for this HistogramPanel.

setSiteEventHandler(SiteEventHandler handler)

Setting the site event handler.

Sets the site event handler for this HistogramPanel to the given site event handler.

Argument

`SiteEventHandler` **`handler`** `[INPUT, MANDATORY]`

setTask(TaskApi task)

Associating the task.

Associates the given task with this HistogramPanel.

Argument

`TaskApi` **`task`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the variable selection for this HistogramPanel to the given variable selection.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

Display getDisplay()

Returns the display for this HistogramPanel.

Returns the display for this HistogramPanel.

Return

Display

Returns the display for this HistogramPanel.

Image getImage()

Returns the associated image.

`Image getImage()`

Returns the image associated with this HistogramPanel.

Return

Image

Returns the image associated with this HistogramPanel.

`TaskApi getTask()`

Returns the associated image.

Returns the task associated with this HistogramPanel.

Return

TaskApi

Returns the task associated with this HistogramPanel.

`Map getMap()`

Returns the associated map.

Returns the map associated with this HistogramPanel.

Return

Map

Returns the map associated with this HistogramPanel.

`SiteEventHandler getHandler()`

Returns the associated site event handler.

Returns the site event handler associated with this HistogramPanel.

Return

SiteEventHandler

Returns the site event handler associated with this HistogramPanel.

`Double getInputLowCut()`

Returns the input low cut level.

Returns the input low cut level for this HistogramPanel.

Return

Double

Returns the input low cut level for this HistogramPanel.

`getInputHighCut()`

Returns the input high cut level.

Returns the input high cut level for this HistogramPanel.

getInputNbOfBins()

Returns the input number of bins.

Returns the input number of bins for this HistogramPanel.

PlotXY getHistogram()

Returns the associated histogram.

Returns the histogram associated with this HistogramPanel.

Return

PlotXY

Returns the histogram associated with this HistogramPanel.

setPoint(MouseEvent me)

Storing the given mouse event in pixel coordinates.

Sets the position of the given mouse event at the appropriate place (i.e. at the index that corresponds with the number of times there was clicked before) in the list of clicked points for this HistogramPanel in pixel coordinates.

Argument

`MouseEvent` **me** `[INPUT, MANDATORY]`

setPoint(Double point)

Storing the given screen coordinates in pixel coordinates.

Sets the given screen coordinates at the appropriate place (i.e. at the index that corresponds with the number of times there was clicked before) in the list of clicked points for this HistogramPanel in pixel coordinates.

Argument

`Double` **point** `[INPUT, MANDATORY]`

updateFigure()

Updates the associated figure.

Updates the figure associated with this HistogramPanel.

ArrayList getClickedPoints()

Returns the clicked points in pixel coordinates.

Returns the clicked points for this HistogramPanel in pixel coordinates.

Return

ArrayList

Returns the clicked points for this HistogramPanel in pixel coordinates.

int getNbOfClickedPoints()

Returns the number of times there was clicked before on the image.

`int getNbOfClickedPoints()`

Returns the number of times there was clicked before on the image for this HistogramPanel.

Return

int

Returns the number of times there was clicked before on the image for this HistogramPanel.

`increaseClicks()`

Increases the number of clicks made before on the image.

Increases the number of clicks made before on the image for this HistogramPanel.

`drawFigure()`

Draws the figure on the associated image.

Draws the figure on the image associated with this HistogramPanel.

`trigger()`

Triggers the execution of the associated task.

Triggers the execution of the task associated with this HistogramPanel.

`updateHistogram()`

Updates the associated histogram.

Updates the histogram associated with this HistogramPanel.

2.156. HistogramTask

Full Name:	herschel.ia.toolbox.image.HistogramTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import HistogramTask

Description

An abstract Task to make histograms.

An abstract Task for making a histogram of an image as a whole or of a certain region of interest, which is bounded by a circle, an ellipse, a rectangle or a polygon. Its subclasses/subtasks are ImageHistogramTask, CircleHistogramTask, EllipseHistogramTask, RectangleHistogramTask and PolygonHistogramTask.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double lowCut [INPUT, OPTIONAL, default=Default value : NaN]`
`Double highCut [INPUT, OPTIONAL, default=Default value : NaN]`
`Double bins [INPUT, MANDATORY, default=Default value : new Integer(2000)]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image.

`Double lowCut [INPUT, OPTIONAL, default=Default value : NaN]`

The lower cut level.

`Double highCut [INPUT, OPTIONAL, default=Default value : NaN]`

The upper cut level.

`Double bins [INPUT, MANDATORY, default=Default value : new Integer(2000)]`

The number of bins.

2.157. IaProcessImpl

Full Name:	herschel.ia.dataflow.IaProcessImpl
Type:	Java Class -
Import:	from herschel.ia.dataflow import IaProcessImpl

Description

Implementation of the interface {@link IaProcess}

It has additional helper methods to make a developer's life easier. It is the base class for building event-based processes. A developer may inherit from this class in order to use it within the dataflow framework.

Examples

Example 1: how to implement a event-based process

```
<pre>
import herschel.ia.dataflow.*;
import herschel.ia.numeric.Complex1d;
public class ProcessFFT extends IaProcessImpl implements InputListener {
private final ProcessInput _input;
private final ProcessOutput _output;
public ProcessFFT(String name) {
     super(name);
     _input = createInput("input", Complex1d.class);
     _output = createOutput("output", Complex1d.class);
     -// It will always listen to events.
     _input.addInputListener( this -);
 -}
 public void inputHandler(ProcessInputEvent ev) {
             Product product = (Complex1d) ev.getData();
             -// a doStuff method should be defined and would do the
processing.
             Product new_product = doStuff(product);
             _output.dataReady( new_product -);
  -}
}
</pre>
```

Example 2: how to implement a event-based process with Launchable

```
<pre>
import herschel.ia.dataflow.*;
import herschel.ia.numeric.Complex1d;
public class ProcessFFT extends IaProcessImpl implements InputListener,
Launchable {
private final ProcessInput _input;
private final ProcessOutput _output;
public ProcessFFT(String name) {
     super(name);
     _input = createInput("input", Complex1d.class);
     _output = createOutput("output", Complex1d.class);
 -}
 public void inputHandler(ProcessInputEvent ev) {
             Product product = (Complex1d) ev.getData();
             -// a doStuff method should be defined and would do the
processing.
             Product new_product = doStuff(product);
             _output.dataReady( new_product -);
  -}
  public void start() {
```

Example 2: how to implement a event-based process with Launchable

```
      _input.addInputListener( this -);
  -}
  public void stop() {
      _input.removeInputListener( this -);
   -}
}
</pre>
```

Example 3: how to use a process.

```
<pre>
from myProcesses import ProcessFFT
c = Complex1d.range(100);
p = ProcessFFT("fft")
p.getConnector("input").pass(c)
p.getConnector("output").pass(c);
print c
</pre>
```

Limitations

no limitation

See also

- reference

History

- 26-5-2005 jcg: change javadoc format for help support.

2.158. IFFT

Full Name:	herschel.ia.numeric.toolbox.xform.IFFT
Alias:	IFFT
Type:	Unknown (XML-based documentation) -
Import:	from herschel.ia.numeric.toolbox.xform import IFFT

Description

Gives the inverse of the Fast Fourier Transform.

Example

Example 1: Apply IFF

```
from java.lang.Math import PI # Frequency modulated signal: parameters ts =
1E-6 # Sampling period (sec) fc = 200000 # Carrier frequency (Hz) fm = 2000
# Modulation frequency (Hz) beta = -.0003 # Modulation index (Hz) n = 5000
# Number of samples # Create signal in complex form t = Double1d.range(n)
* ts signal = SIN(2 * PI * fc * t * (1 + beta * COS(2 * PI * fm * t)))
z_signal=Complex1d(signal) # Get spectrum spectrum = ABS(FFT(z_signal))
# Repeat with apodizing z_signal=Complex1d(HAMMING(signal)) spectrum2 =
ABS(FFT(z_signal))
```

API Summary

Jython Syntax

```
<y>=IFFT(<x>)
```

Properties

Complex1d **x** [INPUT, MANDATORY, default=no default value]

Array of float, double, complex. **y** [INPUT, MANDATORY, default=no default value]

Limitations

Does not work for Complex1d.

API details

Properties

Complex1d x [INPUT, MANDATORY, default=no default value]

Complex1d arrays only.

Array of float, double, complex. y [INPUT, MANDATORY, default=no default value]

Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type. The result is in radians.

See also

- FFT

2.159. ImageAbsTask

Full Name:	herschel.ia.toolbox.image.ImageAbsTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageAbsTask

Description

A Task that takes the absolute intensity values of an image.

A Task that replaces the intensity values in an image with their absolute value.

API Summary

Properties
`Image` **`image`** `[INPUT, MANDATORY, default=No default value]`
`Image` **`absolute`** `[OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image absolute [OUTPUT, MANDATORY, default=No default value]`

The output image, being the image with the absolute values of the input image.

2.160. ImageAddTask

Full Name:	herschel.ia.toolbox.image.ImageAddTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageAddTask

Description

A Task to add images.

A Task that allows to add two images pixel-to-pixel or co-add based on the Wcs coordinates, or to add a scalar to all intensity values in an image.

API Summary

Properties
Image **image1** [INPUT, MANDATORY, default=No default value]
Image **image2** [INPUT, OPTIONAL, default=No default value]
Integer **ref** [INPUT, OPTIONAL, default=No default value]
Number **scalar** [INPUT, OPTIONAL, default=No default value]
Image **sum** [OUTPUT, OPTIONAL, default=No default value]

API details

Properties

Image image1 [INPUT, MANDATORY, default=No default value]

The first image term/addend.

Image image2 [INPUT, OPTIONAL, default=No default value]

The second image term/addend.

Integer ref [INPUT, OPTIONAL, default=No default value]

The reference frame for the calculation of the sum.

Number scalar [INPUT, OPTIONAL, default=No default value]

The scalar term/addend.

Image sum [OUTPUT, OPTIONAL, default=No default value]

The sum.

2.161. ImageAddTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ImageAddTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageAddTaskSignatureComponent

Description

The task dialog for the ImageAddTask.

A task dialog to serve as GUI for the ImageAddTask.

API Summary

Constructor
`ImageAddTaskSignatureComponent()` The construction of a new ImageAddTaskSignatureComponent.

Methods
`JLabel getFirstArgument()` Returns the label for the first addend.
`JLabel getSecondArgument()` Returns the label for the second addend.

API details

Constructor

`ImageAddTaskSignatureComponent()`

The construction of a new ImageAddTaskSignatureComponent.

The construction of a new ImageAddTaskSignatureComponent.

Methods

`JLabel getFirstArgument()`

Returns the label for the first addend.

Returns the label for the first addend.

Return

JLabel

Returns the label for the first addend.

`JLabel getSecondArgument()`

Returns the label for the second addend.

Returns the label for the second addend.

`JLabel getSecondArgument()`

Return

JLabel

Returns the label for the second addend.

2.162. ImageAnalysis

Full Name:	herschel.ia.toolbox.image.gui.ImageAnalysis
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageAnalysis

Description

A class to deal with ImageAnalysis (in the current version :

ProfilePlotting, AperturePhotometry, AreaHistogra, and ContourPlotting).

API Summary

Constructor
`ImageAnalysis(ImageAnalysisToolbox toolbox, String title)`
Standard constructor for ImageAnalysis. A new window with the

Methods
`JFrame getFrame()`
Method that returns the JFrame of this ImageAnalysis.
`ImageAnalysisToolbox getToolbox()`
Returns the ImageAnalysisToolbox, associated with this
`Container getComponent()`
Returns the Content Pane of the JFrame of this
`ArrayList getImageFigures()`
Returns all ImageFigures used for this ImageAnalysis.

API details

Constructor

`ImageAnalysis(ImageAnalysisToolbox toolbox, String title)`

Standard constructor for ImageAnalysis. A new window with the

given title and associated with the given ImageAnalysisToolbox is crested.

Arguments

`ImageAnalysisToolbox` **`toolbox`** `[INPUT, MANDATORY]`

`String` **`title`** `[INPUT, MANDATORY]`

Methods

`JFrame getFrame()`

Method that returns the JFrame of this ImageAnalysis.

Return

JFrame

JFrame getFrame()

Returns the JFrame of this ImageAnalysis.

ImageAnalysisToolbox getToolbox()

Returns the ImageAnalysisToolbox, associated with this

ImageAnalysis.

Return

ImageAnalysisToolbox

Returns the ImageAnalysisToolbox, associated with this ImageAnalysis.

Container getComponent()

Returns the Content Pane of the JFrame of this

ImageAnalysis.

Return

Container

Returns the Content Pane of the JFrame of this ImageAnalysis.

ArrayList getImageFigures()

Returns all ImageFigures used for this ImageAnalysis.

Return

ArrayList

Returns all ImageFigures used for this ImageAnalysis.

2.163. ImageAnalysisToolbox

Full Name:	herschel.ia.toolbox.image.gui.ImageAnalysisToolbox
Alias:	ImageAnalysisToolbox
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageAnalysisToolbox

Description

A class to perform image analysis.

In the current version you can do the following : 1) You can draw a 2D profile plot of a straight line, starting at a point you clicked on with the mouse, and ending at the current mouse position (in the image) or at the 2nd point you clicked on with the mouse. 2) You can perform aperture photometry on the image, either with an annular or a rectangular sky aperture, and with a chosen sky estimation algorithm. 3) You can make a histogram, either of the whole image, or of a selected region (bounded by a circle, an ellipse, a rectangle or a polygon). You can choose the cut levels and the number of bins for the histogram. 4) You can perform contour plotting on the image. You can give the contour values for which you wish the contours to be generated manually or let them be calculated (then you should specify the number of contour levels, the extreme contour values and the distribution of the contour levels). You can also increase/decrease the minimum length for contours to be drawn. In all cases the image analysis is performed on the shown layer and shown in a JTabbedPane on the right hand side.

Example

Example 1: A basic example on how to open a toolbox for image analysis on an

```
ImageDataset imds -:
iat = ImageAnalysisToolbox(idms)
or
iat = ImageAnalysisToolbox() iat.setImage(imds)
```

API Summary

Constructors
ImageAnalysisToolbox() The standard constructor for ImageAnalysisToolbox. This
ImageAnalysisToolbox(Image image) Constructor for ImageAnalysisToolbox. This constructor shows an
ImageAnalysisToolbox(Array2dData array2d) Constructor for ImageAnalysisToolbox. This constructor shows an
ImageAnalysisToolbox(Array3dData array3d) Constructor for ImageAnalysisToolbox. This constructor shows an

Methods
setLayer() Sets the image of this ImageAnalysisToolbox, using a file chooser.
addLayer() Sets the image of this ImageAnalysisToolbox, using a file chooser.
exit() Exits this ImageanalysisToolbox (closes (the window of) this

Methods
setImage(Image image) Sets the image you wish to analyze with this ImageAnalysisToolbox,
setImage(Array2dData array2d) Sets the image you wish to analyse with this ImageAnalysisToolbox,
setImage(Array3dData array3d) Sets the image you wish to analyze with this ImageAnalysisToolbox,
addImage(Image image) Adds the given image to the image, analyzed with
addImage(Array2dData array2d) Adds the given image to the images, analyzed with
addImage(Array3dData array3d) Adds the given image to the images, analyzed with
closeActiveTab() Closes the active tab, if there is one.
closeAllTabs() Closes all tabs, if there are any.
setEnabled(boolean enabled) Disables/enables all tabs on the tabbed pane and the menus for
boolean **isEnabled**() Returns whether the tabbed pane and menus for closing tabs and
JFrame **getFrame**() Method that returns the frame of this ImageAnalysisToolbox.
JPanel **getPanel**() Method that returns the panel of this ImageAnalysisToolbox.
JTabbedPane **getTabbedPane**() Method that returns the tabbed pane of this ImageAnalysisToolbox.
Image **getImage**() Returns the displayed image.
Display **getDisplay**() Returns the Display of the image you are analyzing with
int **getSelectedLayer**() Returns the index of the shown layer, or the index of the selected
int **getSelectedTab**() Returns the index of the tab, selected for the shown layer.
JTabbedPane **getTabOnPane**() Returns the tab (tabbed pane) on the tabbed pane, that is
boolean **isInImage**(MouseEvent me) Checks whether the given MouseEvent has occurred within the image
boolean **isInImage**(double pixX, double pixY) Checks whether the point with given pixel coordinates (pixX, pixY)
boolean **hasWCS**()

Methods
Returns true if sky coordinates are available for the image,
plotProfile2D() Draws straight line on the image, starting at the point in the you
aperturePhotometry() Performs aperture photometry on the image you are analyzing with
histogram() Makes an area histogram. You can choose the kind of area you want
ArrayList **getAllFigures()** Returns all ImageFigures used for this ImageAnalysisToolbox.
addFigures(ArrayList figures) Adds the ImageFigures belonging to the selected tab up front to
updateImage() Updates the image, when another tab is made active.
removeAllAnnotations() Makes all annotations invisible.
createSpaceOnTabbedPane() Creates a free space at the end of the ArrayList of ArrayLists of
createSpaceInTab() Creates a free space at index 0 in the ArrayList of CanvasFigures,

API details

Constructors

ImageAnalysisToolbox()
The standard constructor for ImageAnalysisToolbox. This constructor shows an empty ImageAnalysisToolbox window in 2 parts, with only a title, buttons for maximizing, minimizing and closing the window, a menu bar (File, Image, Help) and a color bar and a status bar at the bottom.

ImageAnalysisToolbox(Image image)
Constructor for ImageAnalysisToolbox. This constructor shows an ImageAnalysisToolbox window in 2 parts, with a title, buttons for maximizing, minimizing and closing the window, a menu bar (file, Image, Help) and a color bar and a status bar at the bottom. Also the image, you wish to analyze is displayed. **Argument** Image **image** [INPUT, MANDATORY]

ImageAnalysisToolbox(Array2dData array2d)
Constructor for ImageAnalysisToolbox. This constructor shows an empty ImageAnalysisToolbox window in 2 parts, with a title, buttons for maximizing, minimizing and closing the window, and a menubar (file, Image, Help). Also the image you wich to analyse, is displayed.

ImageAnalysisToolbox(Array2dData array2d)

Argument

`Array2dData` **`array2d`** `[INPUT, MANDATORY]`

ImageAnalysisToolbox(Array3dData array3d)

Constructor for ImageAnalysisToolbox. This constructor shows an

empty ImageAnalysisToolbox window in 2 parts, with a title, buttons for maximizing, minimizing and closing the window, and a menu ar (file, Image, Help). Also the image you wish to analyze, is displayed.

Argument

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

Methods

setLayer()

Sets the image of this ImageAnalysisToolbox, using a file chooser.

addLayer()

Sets the image of this ImageAnalysisToolbox, using a file chooser.

exit()

Exits this ImageanalysisToolbox (closes (the window of) this

ImageAnalysisToolbox).

setImage(Image image)

Sets the image you wish to analyze with this ImageAnalysisToolbox,

to the given image.

Argument

`Image` **`image`** `[INPUT, MANDATORY]`

setImage(Array2dData array2d)

Sets the image you wish to analyse with this ImageAnalysisToolbox,

to the given ImageDataset.

Argument

`Array2dData` **`array2d`** `[INPUT, MANDATORY]`

setImage(Array3dData array3d)

Sets the image you wish to analyze with this ImageAnalysisToolbox,

to the given ImageDataset.

Argument

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

addImage(Image image)

Adds the given image to the image, analyzed with

addImage(Image image)

this ImageAnalysisToolbox.

Argument

`Image` **`image`** `[INPUT, MANDATORY]`

addImage(Array2dData array2d)

Adds the given image to the images, analyzed with

this ImageAnalysisToolbox.

Argument

`Array2dData` **`array2d`** `[INPUT, MANDATORY]`

addImage(Array3dData array3d)

Adds the given image to the images, analyzed with

this ImageAnalysisToolbox.

Argument

`Array3dData` **`array3d`** `[INPUT, MANDATORY]`

closeActiveTab()

Closes the active tab, if there is one.

closeAllTabs()

Closes all tabs, if there are any.

setEnabled(boolean enabled)

Disables/enables all tabs on the tabbed pane and the menus for

closing tabs and performing image analysis, of this ImageAnalysisToolbox.

Argument

`boolean` **`enabled`** `[INPUT, MANDATORY]`

boolean isEnabled()

Returns whether the tabbed pane and menus for closing tabs and

performing image analysis, of this ImageAnalysisToolbox are enabled/disabled.

Return

boolean

Returns true is the tabbed pane and menus for closing tabs and performing image analysis, of this ImageAnalysisToolbox are enabled; false otherwise.

JFrame getFrame()

Method that returns the frame of this ImageAnalysisToolbox.

Return

JFrame

The frame of this ImageAnalysisToolbox.

JPanel getPanel()

Method that returns the panel of this ImageAnalysisToolbox.

Return

JPanel

The panel of this ImageAnalysisToolbox.

JTabbedPane getTabbedPane()

Method that returns the tabbed pane of this ImageAnalysisToolbox.

Return

JTabbedPane

The tabbed pane of this ImageAnalysisToolbox.

Image getImage()

Returns the displayed image.

Return

Image

Returns the displayed image.

Display getDisplay()

Returns the Display of the image you are analyzing with

this ImageAnalysisToolbox.

Return

Display

Returns the display of the image you are analyzing with this ImageAnalysisToolbox.

int getSelectedLayer()

Returns the index of the shown layer, or the index of the selected

tab on the tabbed pane.

Return

int

Returns the index of the shown layer,or the index of the selected tab on the tabbed pane.

int getSelectedTab()

Returns the index of the tab, selected for the shown layer.

Return

int

The index of the tab, selected for the shown layer.

JTabbedPane getTabOnPane()

Returns the tab (tabbed pane) on the tabbed pane, that is

JTabbedPane getTabOnPane()

selected.

Return

JTabbedPane

Returns the tab (tabbed pane) on the tabbed pane, that is selected.

boolean isInImage(MouseEvent me)

Checks whether the given MouseEvent has occurred within the image

we are analyzing with this ImageAnalysisToolbox.

Argument

MouseEvent **me** [INPUT, MANDATORY]

Return

boolean

Returns true if the given MouseEvent has occurred within the image that is being analyzed with this ImageAnalysisToolbox; false otherwise.

boolean isInImage(double pixX, double pixY)

Checks whether the point with given pixel coordinates (pixX, pixY)

lies in the image we are analyzing with this ImageAnalysisToolbox.

Arguments

double **pixX** [INPUT, MANDATORY]

double **pixY** [INPUT, MANDATORY]

Return

boolean

Returns true if the point with given pixel coordinates (pixX, pixY) lies in the image we are analyzing with this ImageAnalysisToolbox; false otherwise.

boolean hasWCS()

Returns true if sky coordinates are available for the image,

analyzed with this ImageAnalysisToolbox; false otherwise.

Return

boolean

Returns true if sky coordinates are available for the image, analyzed with this ImageAnalysisToolbox; false otherwise.

plotProfile2D()

Draws straight line on the image, starting at the point in the you

clicked on with the mouse the 1st time, and ending at the current mouse position (in the image), or at the 2nd point (in the image) you clicked on, and plots the intensity along that straight line. When you click or move outside of the image, no straight line is drawn and no plot is shown.

aperturePhotometry()

Performs aperture photometry on the image you are analyzing with

this ImageAnalysisToolbox, either with an annular sky aperture or a rectangular sky aperture, and with a chosen sky estimation algorithm.

histogram()

Makes an area histogram. You can choose the kind of area you want

to make the histogram of (the whole image, or a region bounded by a circle, an ellipse, a rectangle or a polygon), given the cut levels and the number of bins for the histogram.

ArrayList getAllFigures()

Returns all ImageFigures used for this ImageAnalysisToolbox.

Return

ArrayList

Returns all ImageFigures used for this ImageAnalysisToolbox.

addFigures(ArrayList figures)

Adds the ImageFigures belonging to the selected tab up front to

the list of ImageFigures, used for this ImageAnalysisToolbox.

Argument

`ArrayList` **figures** `[INPUT, MANDATORY]`

updateImage()

Updates the image, when another tab is made active.

removeAllAnnotations()

Makes all annotations invisible.

createSpaceOnTabbedPane()

Creates a free space at the end of the ArrayList of ArrayLists of

ArrayLists of ImageFigures, that belong to the image analysis on the shown layer.

createSpaceInTab()

Creates a free space at index 0 in the ArrayList of CanvasFigures,

belonging to a new image analysis on the shown layer.

See also

- ???
- ???
- ???

- ???
- ???
- ???

2.164. ImageArithmeticsTask

Full Name:	herschel.ia.toolbox.image.ImageArithmeticsTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageArithmeticsTask

Description

An abstract Task for image arithmetics.

An abstract Task for image arithmetics. The subclasses/subtasks are ImageAddTask (adding), ImageSubtractTask (subtracting), ImageMultiplyTask (multiply), ImageDivideTask (dividing) and ImageModuloTask (modulo).

API Summary

Properties
Image **image1** [INPUT, MANDATORY, default=No default value]
Image **image2** [INPUT, OPTIONAL, default=No default value]
Integer **ref** [INPUT, OPTIONAL, default=Default value : 0]
Number **scalar** [INPUT, OPTIONAL, default=No default value]

API details

Properties

Image image1 [INPUT, MANDATORY, default=No default value]

The input first image.

Image image2 [INPUT, OPTIONAL, default=No default value]

The input second image.

Integer ref [INPUT, OPTIONAL, default=Default value : 0]

The input reference frame for the calculation.

Number scalar [INPUT, OPTIONAL, default=No default value]

The input scalar.

2.165. ImageArithmeticsTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ImageArithmeticsTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageArithmeticsTaskSignatureComponent

Description

The task dialog for the ImageArithmeticsTask.

A task dialog to serve as GUI for the ImageArithmeticsTask.

API Summary

Constructor
ImageArithmeticsTaskSignatureComponent() The construction of a new ImageArithmeticsTaskSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
getParameters() Returns a map of parameters and modifiers storing the values selected by the user.
setSignature(SignatureApi signature) Setting the signature.
setVariableSelection(VariableSelection selection) Setting the variable selection.
JLabel **newLabel**(String title, String tooltip) Returns a label with the given title and tooltip.
JComponent **getComponent**() Returns the component.
JLabel **getFirstArgument**() Returns the label for the first argument.
JLabel **getSecondArgument**() Returns the label for the second argument.

API details

Constructor

ImageArithmeticsTaskSignatureComponent()
The construction of a new ImageArithmeticsTaskSignatureComponent.

ImageArithmeticsTaskSignatureComponent()

The construction of a new ImageArithmeticsTaskSignatureComponent.

Methods

check()

Validates the current modifications.

Validates the current modifications for this ImageArithmeticsTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this ImageArithmeticsTaskSignatureComponent.

getParameters()

Returns a map of parameters and modifiers storing the values selected by the user.

Returns a map of parameters and modifiers storing the values selected by the user for this ImageArithmeticsTaskSignatureComponent.

setSignature(SignatureApi signature)

Setting the signature.

Sets the given signature as the signature for this ImageArithmeticsTaskSignatureComponent.

Argument

`SignatureApi` **`signature`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this ImageArithmeticsTaskSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

JLabel newLabel(String title, String tooltip)

Returns a label with the given title and tooltip.

Returns a label with the given title and tooltip.

Arguments

`String` **`title`** `[INPUT, MANDATORY]`

`String` **`tooltip`** `[INPUT, MANDATORY]`

Return

JLabel

Returns a label with the given title and tooltip.

JComponent getComponent()

Returns the component.

Returns the component for this ImageArithmeticsTaskSignatureComponent.

Return

JComponent

Returns the component for this ImageArithmeticsTaskSignatureComponent.

JLabel getFirstArgument()

Returns the label for the first argument.

Returns the label for the first argument for this ImageArithmeticsTaskSignatureComponent.

Return

JLabel

Returns the label for the first argument for this ImageArithmeticsTaskSignatureComponent.

JLabel getSecondArgument()

Returns the label for the second argument.

Returns the label for the second argument for this ImageArithmeticsTaskSignatureComponent.

Return

JLabel

Returns the label for the second argument for this ImageArithmeticsTaskSignatureComponent.

2.166. ImageAxis

Full Name:	herschel.ia.gui.image.ImageAxis
Type:	Java Class -
Import:	from herschel.ia.gui.image import ImageAxis
Category:	Display

Description

Axes for image display.

This class can change the look of the axes of an image display. A grid can also be enabled.

API Summary

Methods
disable() Disables the axis
enable() Enables the axis
setLabel(String newLabel) Set the label of the axis
String **getLabel**() Returns the label
setBackground(Color newBackground) Sets the Background.
Position **getOrientation**() Returns the orientation of the axis
setOrientation(Position orientation) Sets the orientation of the axis
setAxisStroke(int stroke) Sets the axis stroke
int **getAxisStroke**() Returns the stroke of the axis.
setTicksColor(Color color) Sets the color of the ticks of the axis
Color **getTicksColor**() Returns the color of the ticks of the axis.
setAxisColor(Color color) Sets the color of the axis
Color **getAxisColor**() Returns the color of the axis.
setLabelFont(Font labelFont) Sets the font for the label.
Font **getLabelFont**()

Methods
Returns the font for the label
`Color getLabelFontColor()`
Returns the color of the label
`setLabelFontColor(Color labelFontcolor)`
Sets the color for the label
`showColorTable(boolean showColorTable)`
Shows or hides the color table for this axis.
`setWorldCoordinates(boolean wcs)`
Show or hide the world coordinates
`setTickLabelFont(int newSize)`
Sets the size of the font for the ticks.
`setTickLabelFont(Font tickLabelFont)`
Sets the font of the ticks
`Font getTickLabelFont()`
Returns the font of the ticks.
`Color getTickLabelFontColor()`
Returns the color of the font of the ticks
`setTickLabelFontColor(Color color)`
Sets the color of the ticks font
`setInnerTickLength(int length)`
Sets the length of the inner ticks
`int getInnerTickLength()`
Returns the inner tick length
`setOuterTickLength(int length)`
Sets the length of the outer ticks
`int getOuterTickLength()`
Returns the outer tick length
`setMainTicks(int ticks)`
Sets the number of main ticks
`int getMainTicks()`
Returns the number of main ticks.
`setMinorTicks(int ticks)`
Sets the number of minor ticks
`int getMinorTicks()`
Returns the number of minor ticks.
`setTickDistance(int pixels)`
Sets the tick distance
`int getTickDistance()`
Returns the number of pixels between two ticks on the axis.
`showGridLines(boolean gl)`
Enables or disables the grid

Methods
boolean **getShowGridLines**() Returns the status of the grid
setGridColor(Color gridColor) Sets the color of the grid
Color **getGridColor**() Returns the color of the grid

API details

Methods

disable()
Disables the axis Disables the axis

enable()
Enables the axis Enables the axis

setLabel(String newLabel)
Set the label of the axis The label of the axis is set. If no label is needed, an empty string should be given as label **Argument** String **newLabel** [INPUT, MANDATORY]

String getLabel()
Returns the label Returns the label of the axis. **Return** **String** The label of the axis.

setBackground(Color newBackground)
Sets the Background. Sets the Background. **Argument** Color **newBackground** [INPUT, MANDATORY]

Position getOrientation()
Returns the orientation of the axis

`Position getOrientation()`

Returns the orientation of the axis

Return

Position

The orientation (as a Position)

`setOrientation(Position orientation)`

Sets the orientation of the axis

Changes the orientation of the axis.

Argument

`Position` **`orientation`** `[INPUT, MANDATORY]`

`setAxisStroke(int stroke)`

Sets the axis stroke

Sets the stroke (line width) of the axis (in pixels)

Argument

`int` **`stroke`** `[INPUT, MANDATORY]`

`int getAxisStroke()`

Returns the stroke of the axis.

Returns the stroke (line width) of the axis.

Return

int

The stroke of the axis.

`setTicksColor(Color color)`

Sets the color of the ticks of the axis

Sets the color of the ticks of the axis.

Argument

`Color` **`color`** `[INPUT, MANDATORY]`

`Color getTicksColor()`

Returns the color of the ticks of the axis.

Returns the color of the ticks of the axis

Return

Color

Color The color of the ticks of the axis.

`setAxisColor(Color color)`

Sets the color of the axis

setAxisColor(Color color)

Sets the color of the axis.

Argument

Color **color** [INPUT, MANDATORY]

Color getAxisColor()

Returns the color of the axis.

Returns the color of the axis

Return

Color

Color The color of the axis.

setLabelFont(Font labelFont)

Sets the font for the label.

Sets the font for the label.

Argument

Font **labelFont** [INPUT, MANDATORY]

Font getLabelFont()

Returns the font for the label

Returns the font for the label of the axis.

Return

Font

The font for the label.

Color getLabelFontColor()

Returns the color of the label

Returns the color of the label.

Return

Color

the color of the label.

setLabelFontColor(Color labelFontcolor)

Sets the color for the label

Sets the color for the label

Argument

Color **labelFontcolor** [INPUT, MANDATORY]

showColorTable(boolean showColorTable)

Shows or hides the color table for this axis.

showColorTable(boolean showColorTable)

Shows (true) or hides (false) the color table for this axis.

Argument

`boolean` **`showColorTable`** `[INPUT, MANDATORY]`

setWorldCoordinates(boolean wcs)

Show or hide the world coordinates

Shows the world coordinates (True) or the pixel coordinates (False)

Argument

`boolean` **`wcs`** `[INPUT, MANDATORY]`

setTickLabelFont(int newSize)

Sets the size of the font for the ticks.

Sets the size of the font for the ticks.

Argument

`int` **`newSize`** `[INPUT, MANDATORY]`

setTickLabelFont(Font tickLabelFont)

Sets the font of the ticks

Sets the font of the ticks

Argument

`Font` **`tickLabelFont`** `[INPUT, MANDATORY]`

Font getTickLabelFont()

Returns the font of the ticks.

Returns the font of the ticks.

Return

Font

The font of the ticks,

Color getTickLabelFontColor()

Returns the color of the font of the ticks

Returns the color of the font of the ticks

Return

Color

The color of the ticks font.

setTickLabelFontColor(Color color)

Sets the color of the ticks font

setTickLabelFontColor(Color color)

Sets the color of the ticks font

Argument

`Color` **color** [INPUT, MANDATORY]

setInnerTickLength(int length)

Sets the length of the inner ticks

Sets the distance that the ticks enter in the image

Argument

`int` **length** [INPUT, MANDATORY]

int getInnerTickLength()

Returns the inner tick length

Returns the distance that the ticks enter in the image.

Return

int

The distance that the ticks enter in the image.

setOuterTickLength(int length)

Sets the length of the outer ticks

Sets the distance that the ticks go out of the image

Argument

`int` **length** [INPUT, MANDATORY]

int getOuterTickLength()

Returns the outer tick length

Returns the distance that the ticks go out of the image.

Return

int

The distance that the ticks go out of the image.

setMainTicks(int ticks)

Sets the number of main ticks

Sets the number of main ticks. Main ticks are labeled and are slightly longer than the other (minor) ticks. If the number of ticks is less than two, automatic selection of the number of ticks is enabled.

Argument

`int` **ticks** [INPUT, MANDATORY]

int getMainTicks()

Returns the number of main ticks.

int getMainTicks()

Returns the number of main (labeled) ticks.

Return

int

The number of main ticks.

setMinorTicks(int ticks)

Sets the number of minor ticks

Sets the number of minor ticks between 2 main ticks. Minor ticks are not labeled. Negative values will take the standard value of 4 minor ticks.

Argument

`int` **`ticks`** `[INPUT, MANDATORY]`

int getMinorTicks()

Returns the number of minor ticks.

Returns the number of minor (non-labeled) ticks, between two main ticks.

Return

int

The number of minor ticks between two main ticks.

setTickDistance(int pixels)

Sets the tick distance

Sets the distance (in pixels) between two (minor) ticks. Negative (or 0) values will enable automatic selection of the distance.

Argument

`int` **`pixels`** `[INPUT, MANDATORY]`

int getTickDistance()

Returns the number of pixels between two ticks on the axis.

Returns the number of pixels between two ticks on the axis. A negative value means the automatic selection of the tick distance is enabled.

Return

int

int The distance (in pixels) between two ticks.

showGridLines(boolean gl)

Enables or disables the grid

Shows or hides the grid for this axis. The grid can only be displayed if the magnification is at least 4!

Argument

showGridLines(boolean gl)

boolean **gl** [INPUT, MANDATORY]

boolean getShowGridLines()

Returns the status of the grid

Returns true if the grid is shown.

Return

boolean

True if the grid is shown

setGridColor(Color gridColor)

Sets the color of the grid

Sets the color of the grid for this axis.

Argument

Color **gridColor** [INPUT, MANDATORY]

Color getGridColor()

Returns the color of the grid

Returns the color of the grid

Return

Color

The color of the grid.

2.167. ImageCeilTask

Full Name:	herschel.ia.toolbox.image.ImageCeilTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageCeilTask

Description

A Task to ceil intensity values.

A Task that takes the ceiled intensity values of an image.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Image ceiled [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image ceiled [OUTPUT, MANDATORY, default=No default value]`

The output ceiled image.

2.168. ImageContour

Full Name:	herschel.ia.dataset.image.ImageContour
Type:	Java Class -
Import:	from herschel.ia.dataset.image import ImageContour

Description

A class to deal with ImageContours.

API Summary

Constructors
ImageContour() This constructor for ImageContour creates a new ImageContour.
ImageContour(Image image) This constructor for ImageContour creates a new ImageContour,
ImageContour(Image image, int nbOfContourValues) This constructor for ImageContour creates a new ImageContour,
ImageContour(Image image, int nbOfContourLevels, double[] extremeContourValues, String distribution) This constructor for ImageContour creates a new ImageContour,

Methods
addContourLevel(ContourLevel contourLevel, double contourValue) Adds the given ContourLevel for the given contour value to this
addContourLevel(ContourLevel contourLevel, String key) Adds the given ContourLevel to this ImageContour with the given
setWcs(Wcs wcs) Sets the Wcs for this ImageContour.
Wcs **getWcs()** Returns the Wcs for this ImageContour.
boolean **hasWcs()** Checks whether a Wcs is attached to this ImageContour.
boolean **hasValidWcs()** Checks whether a valid Wcs is attached to this ImageContour.

API details

Constructors

ImageContour()
This constructor for ImageContour creates a new ImageContour.

ImageContour(Image image)
This constructor for ImageContour creates a new ImageContour,

ImageContour(Image image)

associated with the given image.

Argument

`Image` **`image`** `[INPUT, MANDATORY]`

ImageContour(Image image, int nbOfContourValues)

This constructor for ImageContour creates a new ImageContour,

associated with the given image and with the given number of contour levels.

Arguments

`Image` **`image`** `[INPUT, MANDATORY]`

`int` **`nbOfContourValues`** `[INPUT, MANDATORY]`

ImageContour(Image image, int nbOfContourLevels, double[] extremeContourValues, String distribution)

This constructor for ImageContour creates a new ImageContour,

associated with the given image and with the given number of contour levels, the given extreme contour values and the given distribution of the contour levels.

Arguments

`Image` **`image`** `[INPUT, MANDATORY]`

`int` **`nbOfContourLevels`** `[INPUT, MANDATORY]`

`double[]` **`extremeContourValues`** `[INPUT, MANDATORY]`

`String` **`distribution`** `[INPUT, MANDATORY]`

Methods

addContourLevel(ContourLevel contourLevel, double contourValue)

Adds the given ContourLevel for the given contour value to this

ImageContour.

Arguments

`ContourLevel` **`contourLevel`** `[INPUT, MANDATORY]`

`double` **`contourValue`** `[INPUT, MANDATORY]`

addContourLevel(ContourLevel contourLevel, String key)

Adds the given ContourLevel to this ImageContour with the given

key.

Arguments

`ContourLevel` **`contourLevel`** `[INPUT, MANDATORY]`

`String` **`key`** `[INPUT, MANDATORY]`

setWcs(Wcs wcs)

Sets the Wcs for this ImageContour.

Argument

setWcs(Wcs wcs)

Wcs **wcs** [INPUT, MANDATORY]

Wcs getWcs()

Returns the Wcs for this ImageContour.

Return

Wcs

Returns the Wcs for this ImageContour.

boolean hasWcs()

Checks whether a Wcs is attached to this ImageContour.

Return

boolean

Returns true if a Wcs is attached to this ImageContour, false otherwise.

boolean hasValidWcs()

Checks whether a valid Wcs is attached to this ImageContour.

Return

boolean

Returns true if a valid Wcs is attached to this ImageContour; false otherwise.

2.169. ImageDivideTask

Full Name:	herschel.ia.toolbox.image.ImageDivideTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageDivideTask

Description

A Task to divide images.

A Task that allows to divide two images pixel-to-pixel or to divide based on the Wcs coordinates, or to divide all intensity values in an image by a scalar.

API Summary

Properties
Image **image1** [INPUT, MANDATORY, default=No default value]
Integer **ref** [INPUT, OPTIONAL, default=No default value]
Number **scalar** [INPUT, OPTIONAL, default=No default value]
Image **quotient** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image1 [INPUT, MANDATORY, default=No default value]

The image dividend.

Integer ref [INPUT, OPTIONAL, default=No default value]

The reference frame for the calculation of the quotient.

Number scalar [INPUT, OPTIONAL, default=No default value]

The scalar divisor.

Image quotient [OUTPUT, MANDATORY, default=No default value]

The quotient.

2.170. ImageDivideTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ImageDivideTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageDivideTaskSignatureComponent

Description

The task dialog for the ImageDivideTask.

A task dialog to serve as GUI for the ImageDivideTask.

API Summary

Constructor
`ImageDivideTaskSignatureComponent()` The construction of a new ImageDivideTaskSignatureComponent.

Methods
`JLabel getFirstArgument()` Returns the label for the dividend.
`JLabel getSecondArgument()` Returns the label for the divisor.

API details

Constructor

`ImageDivideTaskSignatureComponent()`

The construction of a new ImageDivideTaskSignatureComponent.

The construction of a new ImageDivideTaskSignatureComponent.

Methods

`JLabel getFirstArgument()`

Returns the label for the dividend.

Returns the label for the dividend.

Return

JLabel

Returns the label for the dividend.

`JLabel getSecondArgument()`

Returns the label for the divisor.

Returns the label for the divisor.

`JLabel getSecondArgument()`

Return

JLabel

Returns the label for the divisor.

2.171. ImageExp10Task

Full Name:	herschel.ia.toolbox.image.ImageExp10Task
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageExp10Task

Description

exp10, OUTPUT, Image, MANDATORY, No default value

The output image, being the exp10 scaled image.

API Summary

Property
`Image image [INPUT, MANDATORY, default=No default value]`

API details

Property

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

2.172. ImageExpNTask

Full Name:	herschel.ia.toolbox.image.ImageExpNTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageExpNTask

Description

A Task that allows to change the intensity values of an image

according to an expN scaling.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double n [INPUT, MANDATORY, default=Default value : 2.0]`
`Image expN [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Double n [INPUT, MANDATORY, default=Default value : 2.0]`

The input exponent.

`Image expN [OUTPUT, MANDATORY, default=No default value]`

The output image, being the expN scaled image.

2.173. ImageExpTask

Full Name:	herschel.ia.toolbox.image.ImageExpTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageExpTask

Description

A Task that allows to change the intensity values of an image

according to an exp scaling.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Image exp [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image exp [OUTPUT, MANDATORY, default=No default value]`

The ouput image, being the exp scaled image.

2.174. ImageFloorTask

Full Name:	herschel.ia.toolbox.image.ImageFloorTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageFloorTask

Description

A Task to floor intensity values.

A Task that takes the floored intensity values of an image.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Image floored [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image floored [OUTPUT, MANDATORY, default=No default value]`

The output floored image.

2.175. ImageHistogramExplorer

Full Name:	herschel.ia.gui.image.ImageHistogramExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import ImageHistogramExplorer

Description

An explorer for ImageHistogramProducts.

An explorer for ImageHistogramProducts.

API Summary

Constructors
ImageHistogramExplorer() The construction of a new ImageHistogramExplorer.
ImageHistogramExplorer(Object object) The construction of a new ImageHistogramExplorer associated with the given object.

Methods
String **getName**() Returns the name.
String **getDescription**() Returns the description.
boolean **canHandle**(Class className) Checks whether this ImageHistogramExplorer can handle objects of the given class.
setObject(Object object) Sets the object.
ImageHistogramProduct **getObject**() Returns the object.
Class **getVariableType**() Returns the expected variable type.
JComponent **getComponent**() Returns the component that is responsible for displaying the data object.
JScrollPane **getParameterTable**() Returns the parameter table.
JComponent **getHistogram**() Returns the histogram.
addDataObjectListener(DataObjectListener listener) Adds the given listener.
removeDataObjectListener(DataObjectListener listener) Removes the given listener.

API details

Constructors

ImageHistogramExplorer()

The construction of a new ImageHistogramExplorer.

The construction of a new ImageHistogramExplorer.

ImageHistogramExplorer(Object object)

The construction of a new ImageHistogramExplorer associated with the given object.

The construction of a new ImageHistogramExplorer associated with the given object.

Argument

`Object` **object** [INPUT, MANDATORY]

Methods

String getName()

Returns the name.

Returns the name for this ImageHistogramExplorer.

Return

String

Returns the name for this ImageHistogramExplorer.

String getDescription()

Returns the description.

Returns the description for this ImageHistogramExplorer.

Return

String

Returns the description for this ImageHistogramExplorer.

boolean canHandle(Class className)

Checks whether this ImageHistogramExplorer can handle objects of the given class.

Returns true if this ImageHistogramExplorer can handle objects of the given class; false otherwise.

Argument

`Class` **className** [INPUT, MANDATORY]

Return

boolean

Returns true if this ImageHistogramExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this ImageHistogramExplorer to the given object.

Argument

`Object` **object** [INPUT, MANDATORY]

ImageHistogramProduct getObject()

Returns the object.

Returns the object for this ImageHistogramExplorer.

Return

ImageHistogramProduct

Returns the object for this ImageHistogramExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this ImageHistogramExplorer.

Return

Class

Returns the expected variable type for this ImageHistogramExplorer.

JComponent getComponent()

Returns the component that is responsible for displaying the data object.

Returns the component that is responsible for displaying the data object for this ImageHistogramExplorer.

Return

JComponent

Returns the component that is responsible for displaying the data object for this ImageHistogramExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

Returns the parameter table for this ImageHistogramExplorer.

Return

JScrollPane

Returns the parameter table for this ImageHistogramExplorer.

JComponent getHistogram()

Returns the histogram.

JComponent getHistogram()

Returns the histogram for this ImageHistogramExplorer.

Return

JComponent

Returns the histogram component for this ImageHistogramExplorer.

addDataObjectListener(DataObjectListener listener)

Adds the given listener.

Adds the given listener to this ImageHistogramExplorer to receive data object events from it.

Argument

`DataObjectListener` **`listener`** `[INPUT, MANDATORY]`

removeDataObjectListener(DataObjectListener listener)

Removes the given listener.

Removes the given listener for this ImageHistogramExplorer, so that it no longer receives data object events by this explorer.

Argument

`DataObjectListener` **`listener`** `[INPUT, MANDATORY]`

2.176. ImageHistogramProduct

Full Name:	herschel.ia.dataset.image.ImageHistogramProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import ImageHistogramProduct

Description

A class to deal with the results of an image histogram.

API Summary

Constructor
ImageHistogramProduct() The constructor of a new ImageHistogramProduct.

Methods
setCutLevels(double lowCut, double highCut) Sets the cut levels for this ImageHistogramProduct
setNbOfBins(int bins) Sets the number of bins for this
setHistogram(Double1d values, Double1d frequencies) Sets the histogram for this ImageHistogramProduct to a
setUnit(Unit unit) Sets the unit for this ImageHistogramProduct to the given unit.
double **getLowCut**() Returns the minimum cut level for this
double **getHighCut**() Returns the maximum cut level for this
int **getNbOfBins**() Returns the number of bins for this
TableDataset **getHistogram**() Returns the histogram for this ImageHistogramProduct.
Double1d **getValues**() Returns the values for the histogram for this
Double1d **getFrequencies**() Returns the frequencies for the histogram for this
String **getUnit**() Returns the unit for this ImageHistogramProduct.

API details

Constructor

ImageHistogramProduct()
The constructor of a new ImageHistogramProduct.

Methods

setCutLevels(double lowCut, double highCut)

Sets the cut levels for this ImageHistogramProduct

to the given cut levels.

Arguments

`double` **`lowCut`** `[INPUT, MANDATORY]`

`double` **`highCut`** `[INPUT, MANDATORY]`

setNbOfBins(int bins)

Sets the number of bins for this

ImageHistogramProduct to the given number of bins.

Argument

`int` **`bins`** `[INPUT, MANDATORY]`

setHistogram(Double1d values, Double1d frequencies)

Sets the histogram for this ImageHistogramProduct to a

histogram with the given values and frequencies.

Arguments

`Double1d` **`values`** `[INPUT, MANDATORY]`

`Double1d` **`frequencies`** `[INPUT, MANDATORY]`

setUnit(Unit unit)

Sets the unit for this ImageHistogramProduct to the given unit.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

double getLowCut()

Returns the minimum cut level for this

ImageHistogramProduct.

Return

double

Returns the minimum cut level for this ImageHistogramProduct.

double getHighCut()

Returns the maximum cut level for this

ImageHistogramProduct.

Return

double

Returns the maximum cut level for this ImageHistogramProduct.

`int getNbOfBins()`

Returns the number of bins for this

ImageHistogramProduct.

Return

int

Returns the number of bins for this ImageHistogramProduct.

`TableDataset getHistogram()`

Returns the histogram for this ImageHistogramProduct.

Return

TableDataset

Returns the histogram for this ImageHistogramProduct.

`Double1d getValues()`

Returns the values for the histogram for this

ImageHistogramProduct.

Return

Double1d

Returns the values for the histogram for this

`Double1d getFrequencies()`

Returns the frequencies for the histogram for this

ImageHistogramProduct.

Return

Double1d

Returns the frequencies for the histogram for this ImageHistogramProduct.

`String getUnit()`

Returns the unit for this ImageHistogramProduct.

Return

String

Returns the unit for this ImageHistogramProduct.

2.177. ImageHistogramTask

Full Name:	herschel.ia.toolbox.image.ImageHistogramTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageHistogramTask

Description

A Task to make a histogram of an image.

A Task to make a histogram of an image as a whole.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **lowCut** [INPUT, OPTIONAL, default=Default value : NaN]
Double **highCut** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **bins** [INPUT, MANDATORY, default=Default value : new Integer(2000)]
ImageHistogramProduct **histogram** [OUTPUT, MANDATORY, default=Default value : new ImageHistogramProduct()]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double lowCut [INPUT, OPTIONAL, default=Default value : NaN]

The lower cut level.

Double highCut [INPUT, OPTIONAL, default=Default value : NaN]

The upper cut level.

Integer bins [INPUT, MANDATORY, default=Default value : new Integer(2000)]

The number of bins.

ImageHistogramProduct histogram [OUTPUT, MANDATORY, default=Default value : new ImageHistogramProduct()]

The histogram.

2.178. ImageHistogramTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ImageHistogramTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageHistogramTaskSignatureComponent

Description

The task dialog for the ImageHistogramTask.

A Task dialog to serve as GUI for the ImageHistogramTask.

API Summary

Constructor
ImageHistogramTaskSignatureComponent() The construction of a new ImageHistogramTaskSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
Map **getParameters()** Returns a map of parameters and modifiers storing the value selected by the user.
setSignature(SignatureApi signature) Setting the signature.
setVariableSelection(VariableSelection selection) Setting the variable selection.
JLabel **newLabel**(String title, String tooltip) Returns a label with the given title and tooltip.
JComponent **getComponent()** Returns the component for this ImageHistogramTaskSignatureComponent.

API details

Constructor

ImageHistogramTaskSignatureComponent()
The construction of a new ImageHistogramTaskSignatureComponent. The construction of a new ImageHistogramTaskSignatureComponent.

Methods

check()
Validates the current modifications.

check()

Validates the current modifications for this ImageHistogramTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this ImageHistogramTaskSignatureComponent.

Map getParameters()

Returns a map of parameters and modifiers storing the value selected by the user.

Returns a map of parameters and modifiers storing the value selected by the user for this ImageHistogramTaskSignatureComponent.

Return

Map

Returns a map of parameters and modifiers storing the value selected by the user for this ImageHistogramTaskSignatureComponent.

setSignature(SignatureApi signature)

Setting the signature.

Sets the given signature as the signature for this ImageHistogramTaskSignatureComponent.

Argument

SignatureApi **signature** [INPUT, MANDATORY]

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this ImageHistogramTaskSignatureComponent.

Argument

VariableSelection **selection** [INPUT, MANDATORY]

JLabel newLabel(String title, String tooltip)

Returns a label with the given title and tooltip.

Returns a label with the given title and tooltip.

Arguments

String **title** [INPUT, MANDATORY]

String **tooltip** [INPUT, MANDATORY]

Return

JLabel

Returns a label with the given title and tooltip.

JComponent getComponent()

Returns the component for this ImageHistogramTaskSignatureComponent.

JComponent getComponent()

Returns the component for this ImageHistogramTaskSignatureComponent.

Return

JComponent

Returns the component for this ImageHistogramTaskSignatureComponent.

2.179. ImageLog10Task

Full Name:	herschel.ia.toolbox.image.ImageLog10Task
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageLog10Task

Description

A Task that allows to change the intensity values of an image according to a log10 scaling.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Image **log10** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The input image.

Image log10 [OUTPUT, MANDATORY, default=No default value]

The ouput image, being the log10 scaled image.

2.180. ImageLogNTask

Full Name:	herschel.ia.toolbox.image.ImageLogNTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageLogNTask

Description

A Task that allows to change the intensity values of an image

according to a logN scaling.

API Summary

Properties
`Image.class image [INPUT, MANDATORY, default=No default value]`
`Double.class n [INPUT, MANDATORY, default=No default value]`
`Image.class logN [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image.class image [INPUT, MANDATORY, default=No default value]`

The input image.

`Double.class n [INPUT, MANDATORY, default=No default value]`

The input n.

`Image.class logN [OUTPUT, MANDATORY, default=No default value]`

The output logN scaled image.

2.181. ImageLogTask

Full Name:	herschel.ia.toolbox.image.ImageLogTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageLogTask

Description

A Task that allows to cahnge the intensity values of an image

according to a log scaling.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Image log [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image log [OUTPUT, MANDATORY, default=No default value]`

The ouput image, being the log scaled image.

2.182. ImageModuloTask

Full Name:	herschel.ia.toolbox.image.ImageModuloTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageModuloTask

Description

A Task for modulo calculation with images.

A Task that allows to take the modulus of an image, either with another image or with a scalar.

API Summary

Properties
Image **image1** [INPUT, MANDATORY, default=No default value]
Image **image2** [INPUT, OPTIONAL, default=No default value]
Integer **ref** [INPUT, OPTIONAL, default=No default value]
Number **scalar** [INPUT, OPTIONAL, default=No default value]
Image **remainder** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image1 [INPUT, MANDATORY, default=No default value]

The image dividend.

Image image2 [INPUT, OPTIONAL, default=No default value]

The image divisor.

Integer ref [INPUT, OPTIONAL, default=No default value]

The reference frame for the calculation of the modulus.

Number scalar [INPUT, OPTIONAL, default=No default value]

The scalar divisor.

Image remainder [OUTPUT, MANDATORY, default=No default value]

The remainder after division.

2.183. ImageModuloTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ImageModuloTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageModuloTaskSignatureComponent

Description

The task dialog for the ImageModuloTask.

A task dialog to serve as GUI for the ImageModuloTask.

API Summary

Constructor
ImageModuloTaskSignatureComponent() The construction of a new ImageModuloTaskSignatureComponent.

Methods
JLabel **getFirstArgument()** Returns the label for the dividend.
JLabel **getSecondArgument()** Returns the label for the divisor.

API details

Constructor

ImageModuloTaskSignatureComponent()

The construction of a new ImageModuloTaskSignatureComponent.

The construction of a new ImageModuloTaskSignatureComponent.

Methods

JLabel getFirstArgument()

Returns the label for the dividend.

Returns the label for the dividend.

Return

JLabel

Returns the label for the dividend.

JLabel getSecondArgument()

Returns the label for the divisor.

Returns the label for the divisor.

`JLabel getSecondArgument()`

Return

JLabel

Returns the label for the divisor.

2.184. ImageMultiplyTask

Full Name:	herschel.ia.toolbox.image.ImageMultiplyTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageMultiplyTask

Description

A Task multiply images.

A Task that allows to multiply two images pixel-to-pixel or to multiply based on the Wcs coordinates, or to multiply all intensity values in an image with a scalar.

API Summary

Properties
Image **image1** [INPUT, MANDATORY, default=No default value]
Image **image2** [INPUT, OPTIONAL, default=No default value]
Integer **ref** [INPUT, OPTIONAL, default=No default value]
Number **scalar** [INPUT, OPTIONAL, default=No default value]
Image **product** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image1 [INPUT, MANDATORY, default=No default value]

The image multiplier.

Image image2 [INPUT, OPTIONAL, default=No default value]

The image multiplicand.

Integer ref [INPUT, OPTIONAL, default=No default value]

The reference frame for the calculation of the product.

Number scalar [INPUT, OPTIONAL, default=No default value]

The scalar multiplicand.

Image product [OUTPUT, MANDATORY, default=No default value]

The product.

2.185. ImageMultiplyTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ImageMultiplyTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageMultiplyTaskSignatureComponent

Description

The task dialog for the ImageMultiplyTask.

A task dialog to serve as GUI for the ImageMultiplyTask.

API Summary

Constructor
`ImageMultiplyTaskSignatureComponent()` The construction of a new ImageMultiplyTaskSignatureComponent.

Methods
`JLabel getFirstArgument()` Returns the label for the multiplier.
`JLabel getSecondArgument()` Returns the label for the multiplicand.

API details

Constructor

`ImageMultiplyTaskSignatureComponent()`

The construction of a new ImageMultiplyTaskSignatureComponent.

The construction of a new ImageMultiplyTaskSignatureComponent.

Methods

`JLabel getFirstArgument()`

Returns the label for the multiplier.

Returns the label for the multiplier.

Return

JLabel

Returns the label for the multiplier.

`JLabel getSecondArgument()`

Returns the label for the multiplicand.

Returns the label for the multiplicand.

`JLabel getSecondArgument()`

Return

JLabel

Returns the label for the multiplicand.

2.186. ImagePowerTask

Full Name:	herschel.ia.toolbox.image.ImagePowerTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImagePowerTask

Description

A Task that changes images according to a power scaling.

A Task that changes the intensity values of an image according to a power scaling.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **n** [INPUT, MANDATORY, default=Default value : 2.0]
Image **powered** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The input image.

Double n [INPUT, MANDATORY, default=Default value : 2.0]

The input power.

Image powered [OUTPUT, MANDATORY, default=No default value]

The output image.

2.187. ImageRoundTask

Full Name:	herschel.ia.toolbox.image.ImageRoundTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageRoundTask

Description

A Task to round intensity values.

A Task that takes the rounded intensity values of an image.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Image rounded [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image rounded [OUTPUT, MANDATORY, default=No default value]`

The output rounded image.

2.188. ImageSaverTask

Full Name:	herschel.ia.toolbox.image.ImageSaverTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageSaverTask
Category:	task/image

Description

A Task to save images.

A task which translates and creates a grey colors JPEG file from an image, not taking into account annotations or cut levels.

Example

Example 1: Saving a grey color image to a file

```
ImageSaverTask()(image = im, filename = -"test.jpg")
```

API Summary

Jython Syntax

```
ImageSaverTask()(image, filename)
```

Properties

```
Image image [INPUT, MANDATORY, default=No default value]
String filename [INPUT, MANDATORY, default=No default value]
```

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image to save.

`String filename [INPUT, MANDATORY, default=No default value]`

The filename for the save image.

2.189. ImageSqrtTask

Full Name:	herschel.ia.toolbox.image.ImageSqrtTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageSqrtTask

Description

A Task that changes images according to a sqrt scaling.

A Task that changes the intensity values of an image according to a sqrt scaling.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Image sqrt [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image sqrt [OUTPUT, MANDATORY, default=No default value]`

The output image, being the image changed according to a sqrt scaling.

2.190. ImageSquareTask

Full Name:	herschel.ia.toolbox.image.ImageSquareTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageSquareTask

Description

A Task that changes images according to a square scaling.

A Task that allows to change the intensity values of an image according to a square scaling.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Image square [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Image square [OUTPUT, MANDATORY, default=No default value]`

The output image, being the squared image.

2.191. ImageSubtractTask

Full Name:	herschel.ia.toolbox.image.ImageSubtractTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImageSubtractTask

Description

A Task to subtract images.

A Task that allows to subtract two images pixel-to-pixel or based on the Wcs coordinates, or subtract a scalar from all intensity values of an image.

API Summary

Properties
`Image image1 [INPUT, MANDATORY, default=No default value]`
`Image image2 [INPUT, OPTIONAL, default=No default value]`
`Integer ref [INPUT, OPTIONAL, default=No default value]`
`Number scalar [INPUT, OPTIONAL, default=No default value]`
`Image difference [OUTPUT, OPTIONAL, default=No default value]`

API details

Properties

`Image image1 [INPUT, MANDATORY, default=No default value]`

The image minuend.

`Image image2 [INPUT, OPTIONAL, default=No default value]`

The image subtrahend.

`Integer ref [INPUT, OPTIONAL, default=No default value]`

The reference frame for the calculation of the difference.

`Number scalar [INPUT, OPTIONAL, default=No default value]`

The scalar subtrahend.

`Image difference [OUTPUT, OPTIONAL, default=No default value]`

The difference.

2.192. ImageSubtractTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ImageSubtractTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ImageSubtractTaskSignatureComponent

Description

The task dialog for the ImageSubtractTask.

A task dialog for the ImageSubtractTask.

API Summary

Constructor
`ImageSubtractTaskSignatureComponent()` The construction of a new ImageSubtractTaskSignatureComponent.

Methods
`JLabel getFirstArgument()` Returns the label for the minuend.
`JLabel getSecondArgument()` Returns the label for the subtrahend.

API details

Constructor

`ImageSubtractTaskSignatureComponent()`

The construction of a new ImageSubtractTaskSignatureComponent.

The construction of a new ImageSubtractTaskSignatureComponent.

Methods

`JLabel getFirstArgument()`

Returns the label for the minuend.

Returns the label for the minuend.

Return

JLabel

Returns the label for the minuend.

`JLabel getSecondArgument()`

Returns the label for the subtrahend.

Returns the label for the subtrahend.

`JLabel getSecondArgument()`

Return

JLabel

Returns the label for the subtrahend.

2.193. importCube

Full Name:	herschel.ia.toolbox.cube.ImportCubeTask
Alias:	importCube
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import ImportCubeTask
Category:	task/cube

Description

The ImportCube task for Cubes.

A task which imports a Cube from a fits file

Example

Example 1: Import a fits file

```
importCube(simplecube = cube, filename = -"myFile.fits")
```

API Summary

Jython Syntax

```
importCube(cube, filename)
```

Properties

```
Cube simplecube [IO, MANDATORY, default=No default value]
string filename [INPUT, MANDATORY, default=no default value]
```

API details

Properties

`Cube simplecube [IO, MANDATORY, default=No default value]`

The input Cube to load

`string filename [INPUT, MANDATORY, default=no default value]`

The file to import

2.194. importImage

Full Name:	herschel.ia.toolbox.image.ImportImageTask
Alias:	importImage
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImportImageTask
Category:	task/image

Description

A Task to import images into an Image object.

A task which imports an Image from a file (bmp, gif, jpg, png, pnm, tiff or fits format). It is also possible to import a FITS file.

Example

Example 1: Import a jpg file

```
importImage(image = im, filename = -"myFile.jpg")
```

API Summary

Jython Syntax

```
importImage(image, filename)
```

Properties

```
Image image [INOUT, MANDATORY, default=No default value]
string filename [INPUT, MANDATORY, default=no default value]
```

API details

Properties

`Image image [INOUT, MANDATORY, default=No default value]`

The input Image to load.

`string filename [INPUT, MANDATORY, default=no default value]`

The file to import.

2.195. importRgbImage

Full Name:	herschel.ia.toolbox.image.ImportRgbImageTask
Alias:	importRgbImage
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ImportRgbImageTask
Category:	task/image

Description

A Task to import color images into an RgbImage object.

A task which imports an Image from a file (bmp, gif, jpg, png, pnm, tiff or fits format).

Example

Example 1: Import a jpg file

```
importRgbImage(image = im, filename = -"myFile.jpg")
```

API Summary

Jython Syntax

```
importRgbImage(image, filename)
```

Properties

```
Image image [INOUT, MANDATORY, default=No default value]
string filename [INPUT, MANDATORY, default=no default value]
```

API details

Properties

`Image image [INOUT, MANDATORY, default=No default value]`

The input Image to load.

`string filename [INPUT, MANDATORY, default=no default value]`

The file to import.

2.196. importSpectralCube

Full Name:	herschel.ia.toolbox.cube.ImportSpectralCubeTask
Alias:	importSpectralCube
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import ImportSpectralCubeTask
Category:	task/cube

Description

The ImportSpectralCube task for SpectralSimpleCubes.

A task which imports a SpectralSimpleCube from a fits file

Example

Example 1: Import a fits file

```
importSpectralCube(spectralcube = cube, filename = -"myFile.fits")
```

API Summary

Jython Syntax

```
importSpectralCube(spectralcube, filename)
```

Properties

```
Cube spectralcube [IO, MANDATORY, default=No default value]
string filename [INPUT, MANDATORY, default=no default value]
```

API details

Properties

Cube spectralcube [IO, MANDATORY, default=No default value]

The input SpectralCube to load

string filename [INPUT, MANDATORY, default=no default value]

The file to import

2.197. importUfDirToPal

Full Name:	herschel.ia.toolbox.util.ImportUfDirToPalTask
Alias:	importUfDirToPal
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import ImportUfDirToPalTask
Category:	task

Description

Imports an observation context from an user friendly directory structure into a pool.

The importUfDirToPal task is used to ingest observations from a user friendly directory structure into a HIPE pool, so that they can be used with HIPE. The whole observation described by the XML file will be imported and a reference returned in a new variable.

Example

Example 1: Simple example pref = importUfDirToPal(pool=poolDst, dirin="/sourcedir",

```
xml="111111111-herschel.ia.obs.ObservationContext-0.xml")
```

API Summary

Jython Syntax

```
pref = importUfDirToPal(<pool>, <dirin>, <xml>)
```

Properties

ProductPool **pool** [INPUT, MANDATORY, default=No default value The pool to export products from.]

String **dirin** [INPUT, MANDATORY, default=No default value The directory where the user friendly]

String **xml** [INPUT, MANDATORY, default=No default value The xml file that describes the]

ProductRef **productRef** [OUTPUT, MANDATORY, default=no default value The Product ref imported to]

Limitations

The whole observation described by the XML file will be imported.

API details

Properties

ProductPool pool [INPUT, MANDATORY, default=No default value The pool to export products from.]

String dirin [INPUT, MANDATORY, default=No default value The directory where the user friendly]

structure of products resides.

String xml [INPUT, MANDATORY, default=No default value The xml file that describes the]
observation to import.

ProductRef productRef [OUTPUT, MANDATORY, default=no default value The Product ref imported to]
the pool.

See also

- ???

History

- 16-01-2009 Created
- `2009-03-17 - Added`: output
- `2009-09-30 - Modifiers`: are created through getCustomModifiers (SCR HCSS-8253)

2.198. info

Full Name:	herschel.ia.inspector.InfoTask
Alias:	info
Type:	Java Task -
Import:	from herschel.ia.inspector import InfoTask
Category:	task/general

Description

A task for inspecting the content of a variable in the jython session.

Users can inspect a variable by calling info from the command line. The task opens a pop up window displaying the structure of the specifed item.

Examples

Example 1: info of myvariable

```
info("myvariable")
```

Example 2: info of myvariable setting a refresh rate of 2 seconds (2000 milliseconds)

```
info("myvariable", 2000)
```

API Summary

Jython Syntax

```
info("item")<br>
info("item", 5)
```

Properties

```
String item [INPUT, YES, default=No default value]
Object refresh [INPUT, NO, default=5000]
```

Limitations

No limitation

Miscellaneous

No miscellaneous

API details

Properties

String item [INPUT, YES, default=No default value]

The item to display the structure

Object refresh [INPUT, NO, default=5000]
The refresh rate (milliseconds)

See also

- references

History

- `2004-12-05 - NdC`: first release.

2.199. InputImageNSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.InputImageNSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import InputImageNSignatureComponent

Description

The task dialog if only an image and n should be given as input.

A task dialog to serve as GUI if only an image and n should be given as input.

API Summary

Constructor
`InputImageNSignatureComponent()`
The construction of a new InputImageNSignatureComponent.

Methods
`check()`
Validates the current modifications.
`clear()`
Clears the current modifications.
`Map` **`getParameters()`**
Returns a map of parameters and modifiers storing the value selected by the user.
`setSignature``(SignatureApi signature)`
Setting the signature.
`setVariableSelection``(VariableSelection selection)`
Setting the variable selection.
`JLabel` **`newLabel`**`(String title, String tooltip)`
Returns a label with the given title and tooltip.
`JComponent` **`getComponent()`**
Returns the component.

API details

Constructor

`InputImageNSignatureComponent()`
The construction of a new InputImageNSignatureComponent. The construction of a new InputImageNSignatureComponent.

Methods

`check()`
Validates the current modifications.

check()

Validates the current modifications for this InputImageNSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this InputImageNSignatureComponent

Map getParameters()

Returns a map of parameters and modifiers storing the value selected by the user.

Returns a map of parameters and modifiers storing the value selected by the user for this InputImageNSignatureComponent.

Return

Map

Returns a map of parameters and modifiers storing the value selected by the user for this InputImageNSignatureComponent.

setSignature(SignatureApi signature)

Setting the signature.

Sets the given signature as the signature for this InputImageNSignatureComponent.

Argument

`SignatureApi` **`signature`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this InputImageNSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

JLabel newLabel(String title, String tooltip)

Returns a label with the given title and tooltip.

Returns a label with the given title and tooltip.

Arguments

`String` **`title`** `[INPUT, MANDATORY]`

`String` **`tooltip`** `[INPUT, MANDATORY]`

Return

JLabel

Returns a label with the given title and tooltip.

JComponent getComponent()

Returns the component.

JComponent getComponent()

Returns the component for this InputImageNSignatureComponent.

Return

JComponent

Returns the component for this InputImageNSignatureComponent.

2.200. InputImageSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.InputImageSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import InputImageSignatureComponent

Description

The task dialog if only an image should be given as input.

A task dialog to serve as GUI if only an image should be given as input.

API Summary

Constructor
InputImageSignatureComponent() The construction of a new InputImageSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
Map **getParameters()** Returns a map of parameters and modifiers storing the value selected by the user.
setSignature(SignatureApi signature) Setting the signature.
setVariableSelection(VariableSelection selection) Setting the variable selection.
JLabel **newLabel**(String title, String tooltip) Returns a label with the given title and tooltip.
JComponent **getComponent()** Returns the component.

API details

Constructor

InputImageSignatureComponent()
The construction of a new InputImageSignatureComponent. The construction of a new InputImageSignatureComponent.

Methods

check()
Validates the current modifications.

check()

Validates the current modifications for this InputImageSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this InputImageSignatureComponent.

Map getParameters()

Returns a map of parameters and modifiers storing the value selected by the user.

Returns a map of parameters and modifiers storing the value selected by the user for this InputImageSignatureComponent.

Return

Map

Returns a map of parameters and modifiers storing the value selected by the user for this InputImageSignatureComponent.

setSignature(SignatureApi signature)

Setting the signature.

Sets the given signature as the signature for this InputImageSignatureComponent.

Argument

`SignatureApi` **`signature`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this InputImageSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

JLabel newLabel(String title, String tooltip)

Returns a label with the given title and tooltip.

Returns a label with the given title and tooltip.

Arguments

`String` **`title`** `[INPUT, MANDATORY]`

`String` **`tooltip`** `[INPUT, MANDATORY]`

Return

JLabel

Returns a label with the given title and tooltip.

JComponent getComponent()

Returns the component.

JComponent getComponent()
Returns the component for this InputImageSignatureComponent. **Return** **JComponent** Returns a label with the given title and tooltip.

2.201. Int1d

Full Name:	herschel.ia.numeric.Int1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Int1d

Description

A rectangular numeric int array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.202. Int2d

Full Name:	herschel.ia.numeric.Int2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Int2d

Description

A rectangular numeric int array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.203. Int3d

Full Name:	herschel.ia.numeric.Int3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Int3d

Description

A rectangular numeric int array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.204. Int4d

Full Name:	herschel.ia.numeric.Int4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Int4d

Description

A rectangular numeric int array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.205. Int5d

Full Name:	herschel.ia.numeric.Int5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Int5d

Description

A rectangular numeric int array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.206. IntegratedMapDisplay

Full Name:	herschel.ia.gui.cube.IntegratedMapDisplay
Type:	Java Class -
Import:	from herschel.ia.gui.cube import IntegratedMapDisplay

Description

A class to deal with IntegratedMap.

API Summary

Methods
setBegin(Double begin) Sets the begin of the straight line, associated with this
setEnd(Double end) Sets the end of the straight line, associated with this
ImageFigure **getLine**() Returns the straight line (ImageFigure), of which we wish to plot
Double **getBegin**() Returns the begin of the drawn line in PixelCoordinates.
Double **getEnd**() Returns the end of the drawn line in PixelCoordinates.
ArrayList **getIntegratedMaps**() Returns the end of the drawn line in PixelCoordinates.
String **getSkyCoordinates**() Returns the String version of the sky coordinates

API details

Methods

setBegin(Double begin)

Sets the begin of the straight line, associated with this

Velocity position map to the given point (in UserCoordinates).

Argument

Double **begin** [INPUT, MANDATORY]

setEnd(Double end)

Sets the end of the straight line, associated with this

Velocity position map to the given point (in UserCoordinates).

Argument

Double **end** [INPUT, MANDATORY]

ImageFigure getLine()

Returns the straight line (ImageFigure), of which we wish to plot

the intensity in this IntegratedMapDisplay.

Return

ImageFigure

The straight line (ImageFigure), of which we wish to plot the intensity in this IntegratedMapDisplay.

Double getBegin()

Returns the begin of the drawn line in PixelCoordinates.

Return

Double

Returns the begin of the drawn line in PixelCoordinates.

Double getEnd()

Returns the end of the drawn line in PixelCoordinates.

Return

Double

Returns the end of the drawn line in PixelCoordinates.

ArrayList getIntegratedMaps()

Returns the end of the drawn line in PixelCoordinates.

Return

ArrayList

Returns the end of the drawn line in PixelCoordinates.

String getSkyCoordinates()

Returns the String version of the sky coordinates

(WorldCoordinates) of the begin and end of the drawn straight line.

Return

String

Returns the String version of the sky coordinates (WorldCoordinates) of the begin and end of the drawn straight line.

2.207. IntegrateMapFromCubeTask

Full Name:	herschel.ia.toolbox.cube.IntegrateMapFromCubeTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import IntegrateMapFromCubeTask

Description

Task which integrate one or more "map" or images from a Cube.

In the CubeSpectrumAnalysisToolbox (via the integratedmapdisplay GUI), this task integrate one or more set of contiguous images defined by ranges. The output of this task is a set of simpleImages

API Summary

Properties
Cube **cube** [INPUT, MANDATORY, default=no default value]
integer **bbStack** [INPUT, default value 1, default=no default value]
Double2d **startArray** [INPUT, MANDATORY, default=no default value]
Double2d **endArray** [INPUT, MANDATORY, default=no default value]
SimpleImages[] **imageArray** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

Cube cube [INPUT, MANDATORY, default=no default value]

The Cube containing the spectra to extract

integer bbStack [INPUT, default value 1, default=no default value]

give the number of image to inegrate

Double2d startArray [INPUT, MANDATORY, default=no default value]

The Array of spectral values for the start of each integration the dimension of this array is the number of integration to execute

Double2d endArray [INPUT, MANDATORY, default=no default value]

The Array of spectral values for the end of each integration the dimension of this array is the number of integration to execute

SimpleImages[] imageArray [OUTPUT, MANDATORY, default=no default value]

an array of simpleimages containing the result of each integration

See also

- ???

- ???

History

- 2009-05-20 - AG: creation

2.208. Integrator

Full Name:	herschel.ia.numeric.toolbox.integr.Integrator
Alias:	Integrator
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.integr import Integrator

Description

Interface for all integrators.

Available integrators are: - GaussHermiteIntegrator (closed interval) - GaussianQuad4Integrator (open interval) - GaussianQuad5Integrator (open interval) - GaussJacobiIntegrator (closed interval) - GaussLaguerreIntegrator (closed interval) - GaussLegendreIntegrator (open interval) - RectangularIntegrator (open interval) - TrapezoidalIntegrator (open interval) - SimpsonIntegrator (open interval) - RombergIntegrator (open interval)

Example

Example 1: Integration using the Romberg's method

```
from herschel.ia.numeric.all import *
class MyFunction(RealFunction):
  def calc(self,x):
  return x*x
f = MyFunction()
i = RombergIntegrator(-3, 3)
print i.integrate(f)   # 18.0
```

API Summary

Jython Syntax

```
<r>=SomeOpenIntervalIntegrator(<a>,<b>).integrate(<f>)
<r>=SomeShutIntervalIntegrator().integrate(<f>)
```

Properties

double **a** [INPUT, MANDATORY, default=no default value]
double **b** [INPUT, MANDATORY, default=no default value]
RealFunction **f** [INPUT, MANDATORY, default=no default value]
double **r** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

double a [INPUT, MANDATORY, default=no default value]

Lower limit of integration, only mandatory for open interval integrators.

double b [INPUT, MANDATORY, default=no default value]

Upper limit of integration, only mandatory for open interval integrators. It must be greater or equal than the lower limit.

RealFunction f [INPUT, MANDATORY, default=no default value]
The function must implement the calc method; see example below.

double r [OUTPUT, MANDATORY, default=no default value]
Returns the integral of the given function between the specified limits; that is, the area behind the function within these limits.

2.209. IntensityCalculator

Full Name:	herschel.ia.toolbox.image.IntensityCalculator
Type:	Java Class -
Import:	from herschel.ia.toolbox.image import IntensityCalculator

Description

A class to apply sky estimtion algorithms.

A class to estimate the sky intensity through five different sky estimation algorithms : average, median, mean-median, synthetic mode and daophot.

API Summary

Methods
`double` **`getAverageIntensity`**`(Double1d intensities, Double1d fractions, boolean fractional)` Returns the average intensity.
`double` **`getAverageIntensityFractionalPixels`**`(Double1d intensities, Double1d fractions)` Returns the average intensity for fractional pixels.
`double` **`getAverageIntensityEntirePixels`**`(Double1d intensities)` Returns the average intensity for entire pixels.
`double` **`getMedianIntensity`**`(Double1d intensities, Double1d fractions, boolean fractional)` Returns the median intensity.
`double` **`getMedianIntensityFractionalPixels`**`(Double1d intensities, Double1d fractions)` Returns the median intensity for fractional pixels.
`double` **`getMedianIntensityEntirePixels`**`(Double1d intensities)` Returns the median intensity for entire pixels.
`double[]` **`getMeanMedianIntensityAndError`**`(Double1d intensities, Double1d fractions, boolean fractional)` Returns the mean-median intensity and error.
`double[]` **`getSyntheticModeIntensityAndError`**`(Double1d intensities, Double1d fractions, boolean fractional)` Returns the synthetic mode intensity and error.
`double[]` **`getDaophotIntensityAndError`**`(Double1d intensities, Double1d fractions, boolean fractional)` Returns the daophot intensity and error.
`sort``(Double1d intensities, Double1d fractions)` Sorting.
`quickSort``(Double1d intensities, Double1d fractions, int lo0, int hi0)` Quick sort.

API details

Methods

double getAverageIntensity(Double1d intensities, Double1d fractions, boolean fractional)

Returns the average intensity.

Returns the average intensity for the given list of intensities and corresponding fractions.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

boolean **fractional** [INPUT, MANDATORY]

Return

double

Returns the average intensity for the given list of intensities and corresponding fractions.

double getAverageIntensityFractionalPixels(Double1d intensities, Double1d fractions)

Returns the average intensity for fractional pixels.

Returns the average intensity for the given list of intensities and corresponding fractions for fractional pixels.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

Return

double

Returns the average intensity for the given list of intensities and corresponding fraction for fractional pixels.

double getAverageIntensityEntirePixels(Double1d intensities)

Returns the average intensity for entire pixels.

Returns the average intensity for the given list of intensities and corresponding fractions for entire pixels.

Argument

Double1d **intensities** [INPUT, MANDATORY]

Return

double

Returns the average intensity for the given list of intensities for entire pixels.

double getMedianIntensity(Double1d intensities, Double1d fractions, boolean fractional)

Returns the median intensity.

double getMedianIntensity(Double1d intensities, Double1d fractions, boolean fractional)

Returns the median intensity for the given list of intensities and corresponding fractions.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

boolean **fractional** [INPUT, MANDATORY]

Return

double

Returns the median intensity for the given list of intensities and corresponding fractions.

double getMedianIntensityFractionalPixels(Double1d intensities, Double1d fractions)

Returns the median intensity for fractional pixels.

Returns the median intensity for the given list of intensities and corresponding fractions for fractional pixels.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

Return

double

Returns the median intensity for the given list of intensities and corresponding fraction for fractional pixels.

double getMedianIntensityEntirePixels(Double1d intensities)

Returns the median intensity for entire pixels.

Returns the median intensity for the given list of intensities and corresponding fractions for entire pixels.

Argument

Double1d **intensities** [INPUT, MANDATORY]

Return

double

Returns the median intensity for the given list of intensities for entire pixels.

double[] getMeanMedianIntensityAndError(Double1d intensities, Double1d fractions, boolean fractional)

Returns the mean-median intensity and error.

Returns the mean-median intensity and error for the given list of intensities and corresponding intensities.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

double[] getMeanMedianIntensityAndError(Double1d intensities, Double1d fractions, boolean fractional)

Double1d **fractions** [INPUT, MANDATORY]

boolean **fractional** [INPUT, MANDATORY]

Return

double[]

Returns the mean-median intensity and error for the given list of intensities and corresponding intensities.

double[] getSyntheticModeIntensityAndError(Double1d intensities, Double1d fractions, boolean fractional)

Returns the synthetic mode intensity and error.

Returns the synthetic mode intensity and error for the given list of intensities and corresponding fractions.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

boolean **fractional** [INPUT, MANDATORY]

Return

double[]

Returns the synthetic mode intensity and error for the given list of intensities and corresponding fractions.

double[] getDaophotIntensityAndError(Double1d intensities, Double1d fractions, boolean fractional)

Returns the daophot intensity and error.

Returns the daophot intensity and error for the given list of intensities and corresponding fractions.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

boolean **fractional** [INPUT, MANDATORY]

Return

double[]

Returns the daophot intensity and error for the given list of intensities and corresponding fractions.

sort(Double1d intensities, Double1d fractions)

Sorting.

Sorts the given list of intensities in ascending order and sorts the list of fractions in the same way.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

quickSort(Double1d intensities, Double1d fractions, int lo0, int hi0)

Quick sort.

Sorts the given list of intensities and fractions for elements between the given indices, in ascending order.

Arguments

Double1d **intensities** [INPUT, MANDATORY]

Double1d **fractions** [INPUT, MANDATORY]

int **lo0** [INPUT, MANDATORY]

int **hi0** [INPUT, MANDATORY]

2.210. IntensityMapGui

Full Name:	herschel.ia.gui.cube.IntensityMapGui
Type:	Java Class -
Import:	from herschel.ia.gui.cube import IntensityMapGui

Description

A class to deal with line intensity map

API Summary

Method
`ArrayList` **`getIntegratedMaps()`** Returns the end of the drawn line in PixelCoordinates.

API details

Method

`ArrayList getIntegratedMaps()`

Returns the end of the drawn line in PixelCoordinates.

Return

ArrayList

Returns the end of the drawn line in PixelCoordinates.

2.211. InverseDFT2dTask

Full Name:	herschel.ia.toolbox.image.InverseDFT2dTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import InverseDFT2dTask

Description

A Task for two dimensional inverse Fast Fourier Transforms.

A Task that calculates the inverse 2D Discrete Fourier Transform and the power spectrum.

API Summary

Properties
`Numeric2dData image [INPUT, MANDATORY, default=No default value]`
`Complex2d transform [OUTPUT, MANDATORY, default=No default value]`
`Double2d spectrum [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Numeric2dData image [INPUT, MANDATORY, default=No default value]`

The input image.

`Complex2d transform [OUTPUT, MANDATORY, default=No default value]`

The transform.

`Double2d spectrum [OUTPUT, MANDATORY, default=No default value]`

The spectrum.

2.212. InverseFFT2dTask

Full Name:	herschel.ia.toolbox.image.InverseFFT2dTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import InverseFFT2dTask

Description

A Task for two dimensional inverse Fast Fourier Transforms.

A Task that calculates the inverse 2D Fast Fourier Transform and the power spectrum.

API Summary

Properties
`Numeric2dData image [INPUT, MANDATORY, default=No default value]`
`Complex2d transform [OUTPUT, MANDATORY, default=No default value]`
`Double2d spectrum [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Numeric2dData image [INPUT, MANDATORY, default=No default value]`

The input image.

`Complex2d transform [OUTPUT, MANDATORY, default=No default value]`

The transform.

`Double2d spectrum [OUTPUT, MANDATORY, default=No default value]`

The spectrum.

2.213. INVERSE

Full Name:	herschel.ia.numeric.toolbox.matrix.MatrixInverse
Alias:	INVERSE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import MatrixInverse

Description

Returns the inverse of a square matrix.

Example

Example 1: Apply INVERSE to a Float2d matrix

```
x=Float2d([ [1,2],[3,4] -])
print INVERSE(x) # [ [-2.0,1.0], [1.5,-0.5] -]
```

API Summary

Jython Syntax

```
<y>=INVERSE(<x>)
```

Properties

`any square matrix x [INPUT, MANDATORY, default=no default value]`

`double y [INPUT, NOT_MANDATORY, default=false]`

Miscellaneous

Does not work for complex matrices.

API details

Properties

`any square matrix x [INPUT, MANDATORY, default=no default value]`

Any square matrix

`double y [INPUT, NOT_MANDATORY, default=false]`

Returns a double

2.214. IS_FINITE

Full Name:	herschel.ia.numeric.toolbox.basic.IsFinite
Alias:	IS_FINITE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import IsFinite

Description

Returns a boolean array where each element is true if the corresponding element input array is a finite number, false otherwise.

Example

Example 1: Apply IS_FINITE on a Double1d

```
x=Double1d([1,Double.NaN,Double.NEGATIVE_INFINITY,Double.POSITIVE_INFINITY])
print IS_FINITE(x) # [true,false,false,false]
```

API Summary

Jython Syntax

```
<y>=IS_FINITE (<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns a boolean array (or a boolean if the input is not an array) where each element is true if the corresponding element input array is a finite number, false otherwise

See also

- IS_NAN
- IS_INFINITE

2.215. IS_INFINITE

Full Name:	herschel.ia.numeric.toolbox.basic.IsInfinite
Alias:	IS_INFINITE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import IsInfinite

Description

Returns a boolean array where each element is true if the corresponding element

input array is infinitely large in magnitude, false otherwise.

Example

Example 1: Apply IS_INFINITE on a Double1d

```
x=Double1d([1,Double.NaN,Double.NEGATIVE_INFINITY,Double.POSITIVE_INFINITY])
print IS_INFINITE(x) # [false,false,true,true]
```

API Summary

Jython Syntax

```
<y>=IS_INFINITE (<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns a boolean array (or a boolean if the input is not an array) where each element is true if the corresponding element input array is input array is infinitely large in magnitude, false otherwise.

See also

- IS_NAN
- IS_FINITE

2.216. IS_NAN

Full Name:	herschel.ia.numeric.toolbox.basic.IsNaN
Alias:	IS_NAN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import IsNaN

Description

Returns a boolean array where each element is true if the corresponding element

input array is flagged as Not a Number, false otherwise.

Example

Example 1: Apply IS_FINITE on a Double1d

```
x=Double1d([1,Double.NaN,Double.NEGATIVE_INFINITY,Double.POSITIVE_INFINITY])
print IS_NAN(x) # [false,true,false,false]
```

API Summary

Jython Syntax

```
<y>=IS_NAN(<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns a boolean array (or a boolean if the input is not an array) where each element is true if the corresponding element of the input array is flagged as Not a Number, false otherwise.

See also

- IS_FINITE
- IS_INFINITE

2.217. KURTOSIS

Full Name:	herschel.ia.numeric.toolbox.basic.Kurtosis
Alias:	KURTOSIS
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Kurtosis

Description

Yields the kurtosis of the elements in the input array.

The kurtosis is the fourth moment divided by the standard deviation raised to the fourth power. In addition, this implementation subtracts 3 since 3 is the kurtosis for a normal distribution.

Example

Example 1: Apply KURTOSIS on a Float1d

```
x=Float1d([1,3,2,3,4])
print KURTOSIS(x) # --1.74840236686
```

API Summary

Jython Syntax

```
<y>=KURTOSIS(<x>)
```

Properties

```
any scalar array x [INPUT, MANDATORY, default=no default value]
double y [OUTPUT, MANDATORY, default=no default value]
```

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array integral or floating-point arrays; the former implicitly transformed to a double array.

double y [OUTPUT, MANDATORY, default=no default value]

Returns a double

See also

- MEAN
- MEDIAN
- SKEWNESS
- STDDEV

- VARIANCE

2.218. LayerStruct

Full Name:	herschel.ia.gui.explorer.table.LayerStruct
Type:	Java Class -
Import:	from herschel.ia.gui.explorer.table import LayerStruct

Description

LayerStruct is a data structure used in OverPlotter/TablePlotter. It has many methods which allow users to access extracted data and flags. It has many setters (setXXX) and getters (getXXX). It works as a bookkeeping as well. It keeps tracks on the properties of the active layer. It saves all the personalities of an active layer when the layer becomes inactive and re-display them when the layer becomes active.

API Summary

Constructors
`LayerStruct(TableDataset table)`
`LayerStruct(paramType table, String layerName)`
`LayerStruct(TableDataset table, Bool2d flags)`
`LayerStruct(TableDataset table, Bool1d flags)`

Methods
`TableDataset getExtractedTableDataset()`
`BooleanArray getFlags()`

API details

Constructors

`LayerStruct(TableDataset table)`

Argument

`TableDataset` **`table`** `[INPUT, MANDATORY, default=no default value]`

The input table contains one or more column and each column can have numeric or none numeric data or multi-dimension. However, such columns will be filtered out when the table is plotted.

`LayerStruct(paramType table, String layerName)`

Arguments

`paramType` **`table`** `[INPUT, MANDATORY, default=no default value]`

The input table contains one or more column and each column can have numeric or none numeric data or multi-dimension. However, such columns will be filtered out when the table is plotted.

`String` **`layerName`** `[INPUT, MANDATORY, default=no default value]`

The layerName must be unique for each table.

LayerStruct(TableDataset table, Bool2d flags)

Arguments

TableDataset **table** [INPUT, MANDATORY, default=no default value]

The input table contains one or more column and each column can have numeric or none numeric data or multi-dimension. However, such columns will be filtered out when the table is plotted.

Bool2d **flags** [INPUT, MANDATORY, default=no default value]

The flags must have the same rank and size as the table parameter

LayerStruct(TableDataset table, Bool1d flags)

Arguments

TableDataset **table** [INPUT, MANDATORY, default=no default value]

The input table contains one or more column and each column can have numeric or none numeric data or multi-dimension. However, such columns will be filtered out when the table is plotted.

Bool1d **flags** [INPUT, MANDATORY, default=no default value]

The the length of the flags array must equal to the number of columns of the input table

Methods

TableDataset getExtractedTableDataset()

Return

TableDataset

- return the extracted dataset

BooleanArray getFlags()

Return

BooleanArray

- return the flags. The flags can be either Bool1d or Bool2d.

History

- 2006-11-06 - first: version
- 2008-04-22 re-factored this code
- 2008-12-14 - adding: URM documentation

2.219. LevenbergMarquardtFitter

Full Name:	herschel.ia.numeric.toolbox.fit.LevenbergMarquardtFitter
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.fit import LevenbergMarquardtFitter

Description

An introduction to the use of fit package can be found

here. At least once have a look at the background on the organization and structure of the package.

Example

Example 1: The fit/demo directory contains worked

```
<a href="../../../ia/numeric/toolbox/fit/demo/jython.html">examples</a>
on almost all aspects of of the package.
```

Limitations

1. LevenbergMarquardtFitter is **not** guaranteed to find the global minimum.

2. The calculation of the evidence is an Gaussian approximation which is only exact for linear models with a fixed scale.

2.220. LinearInterpolator

Full Name:	herschel.ia.numeric.toolbox.interp.LinearInterpolator
Alias:	LinearInterpolator
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.interp import LinearInterpolator

Description

Creates an linear interpolation function from a set of knots (x,y), that can

be applied to numeric arrays of rank 1.

Example

Example 1: Create and apply a LinearInterpolator on a Double1d

```
# create some knots
x=Double1d.range(10) # [0.0,1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0]
f=LinearInterpolator(x,SQUARE(x))
u=Double1d([1,1.5,2,2.5,3,3.5])
print f(u) # [1.0,2.5,4.0,6.5,9.0,12.5]
```

API Summary

Jython Syntax

```
<f>=LinearInterpolator(<x>,<y>[,allowExtrapolation])
```

Properties

Double1d **x** [INPUT, MANDATORY, default=no default value]

Double1d **y** [INPUT, NOT_MANDATORY, default=false]

boolean **allowExtrapolation** [INPUT, NOT_MANDATORY, default=false]

API details

Properties

Double1d x [INPUT, MANDATORY, default=no default value]

The knots are Double1d

Double1d y [INPUT, NOT_MANDATORY, default=false]

The knots are Double1d

boolean allowExtrapolation [INPUT, NOT_MANDATORY, default=false]

Extrapolation is not allowed by default. Boolean.TRUE allows extrapolation.

See also

- CubicSplineInterpolator

- NearestNeighborInterpolator

2.221. LineIntensityMapTask

Full Name:	herschel.ia.toolbox.cube.LineIntensityMapTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import LineIntensityMapTask

Description

LineIntensityMapTask

a task to conpute a line intensity integration map

API Summary

Properties
Cube **cube** [INPUT, MANDATORY, default=no default value]
Cube **cube** [INPUT, MANDATORY, default=no default value]
Integer **continuumSubtraction** [INPUT, MANDATORY, default=no default value]
Double1d **regionStartArray** [INPUT, MANDATORY, default=no default value]
Double1d **regionEndArray** [INPUT, MANDATORY, default=no default value]
type **PolyDegree** [Integer, MANDATORY, default=no default value]
String **fitModel** [INPUT, MANDATORY, default=no default value]
String **mode** [INPUT, MANDATORY, default=no default value]
type **centralPos** [double, MANDATORY, default=no default value]
Double1d **rangeForFit** [INPUT, MANDATORY, default=no default value]
String **typeOfLine** [INPUT, MANDATORY, default=no default value]
SimpleImage **lineIntMap** [OUTPUT, MANDATORY, default=no default value]
SimpleCube **fittedLineCube** [OUTPUT, MANDATORY, default=no default value]
SimpleCube **continuumCube** [OUTPUT, MANDATORY, default=no default value]
Cube **cubeWithoutContinuum** [OUTPUT, MANDATORY, default=no default value]
Cube **residualCube** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

Cube cube [INPUT, MANDATORY, default=no default value]

The Cube from which we want to compute a line intensity map.

Cube cube [INPUT, MANDATORY, default=no default value]

The Cube from which we want to compute a line intensity map.

Integer continuumSubtraction [INPUT, MANDATORY, default=no default value]

the continuum subtraction mode: 0 No subtraction , 1 fit on an region of the spectrum, (this mode need the parameter regionStartArray regionEndArray to be filled) 2 continuum subtraction combined with the line fitt in one model

Double1d regionStartArray [INPUT, MANDATORY, default=no default value]

The array of the firsts indexes of the regions to be use for the continuum subtraction

Double1d regionEndArray [INPUT, MANDATORY, default=no default value]

The array of the lasts indexes of the regions to be use for the continuum subtraction

type PolyDegree [Integer, MANDATORY, default=no default value]

the degree of the polynomial for the continuum fit.

String fitModel [INPUT, MANDATORY, default=no default value]

the name of the model to be used for the line fitting. in the first release can only be "Gaussian" but in the futur voight profil and sinc (??) will be added

String mode [INPUT, MANDATORY, default=no default value]

define the fitting mode (automatic or manual , with initial guesses)

type centralPos [double, MANDATORY, default=no default value]

the guess on the central position if needed

Double1d rangeForFit [INPUT, MANDATORY, default=no default value]

an array containing the limit on the validity domain for the Fitt : is sued to reject false detection

String typeOfLine [INPUT, MANDATORY, default=no default value]

a string which said if the line to fitt is an EMISSION line or an ABSORPTION line

SimpleImage lineIntMap [OUTPUT, MANDATORY, default=no default value]

The main output , the map of the integrated flux on the fitted lines without continuum

SimpleCube fittedLineCube [OUTPUT, MANDATORY, default=no default value]

The cube containing the final fitted line, without the continuum

SimpleCube continuumCube [OUTPUT, MANDATORY, default=no default value]

The cube of the fitted continumm

Cube cubeWithoutContinuum [OUTPUT, MANDATORY, default=no default value]

Contain the original cube after subtraction of the continuum cube: Each spectrum is "flattened"

Cube residualCube [OUTPUT, MANDATORY, default=no default value]
the residual Cube which contain the final residual from cube m inus continuum minus fitted line

See also

- ???
- ???

2.222. ListContext

Full Name:	herschel.ia.pal.ListContext
Type:	Java Class -
Import:	from herschel.ia.pal import ListContext

Description

Groups products (or other Contexts that in turn group products) in a

list-like structure. Products grouped in a ListContext can be subsequently retrieved by an index (with index=0 corresponding to the first product in the list), through the 'refs' method. Note: users may be confused as to why there is a need to have to go though a 'refs' method to add or access products from a ListContext. This is due to a technical limitation in the design which will be addressed in due course.

Examples

Example 1: Adding a product to a ListContext product = Product() ref =

```
storage.save(product) # the ref is a ProductRef object listcontext
= ListContext() listcontext.refs.add(ref)
```

Example 2: Getting the first product from a ListContext ref_first =

```
lcontext.refs.get(0) product = ref_first.product
```

Example 3: Saving a ListContext to ProductStorage (same way as any other

```
product) ref_context = storage.save(listcontext)
```

API Summary

Method
`List getRefs()`
get the list of ProductRefs stored. From this list, you can put

API details

Method

`List getRefs()`

get the list of ProductRefs stored. From this list, you can put

products into the ListContext, or retrieve products by index.

Return

List

A list of product refs.

Examples

Putting a product into the the ListContext ref =

List getRefs()

```
storage.save(product) # the ref is a ProductRef object
listcontext.refs.add(ref)
```

Getting the first product from the ListContext ref_first =

```
lcontext.refs.get(0)
```

See also

- ???

2.223. localStoreWriter

Full Name:	herschel.ia.toolbox.util.LocalStoreWriterTask
Alias:	localStoreWriter
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import LocalStoreWriterTask
Category:	task

Description

Saves a product in a Local Store, either already defined, or a new

one chosen by name by the user.

Example

Example 1: Saving a product into a local store

```
p = Product()
store = PoolManager.getPool("mib")
localStoreWriter(product = p, store = store)
```

API Summary

Jython Syntax

`localStoreWriter(<product>,<store>)`

Properties

`Product product [INPUT, MANDATORY, default=null]`

`String store [INPUT, MANDATORY, default=null]`

API details

Properties

`Product product [INPUT, MANDATORY, default=null]`

Product to be saved.

`String store [INPUT, MANDATORY, default=null]`

LocalStore id where to save the product.

History

- `2008-11-11` - `JSS`: first release
- `2009-02-20` - `JDS`: cleanup
- `2009-08-30` - `JSS`: store name and location fields separated in the modifier

2.224. LOG10

Full Name:	herschel.ia.numeric.toolbox.basic.Log10
Alias:	LOG10
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Log10

Description

Gives the logarithm with base 10 of a number or a numeric array: $y=LOG_{10}(x)$.

Example

Example 1: Apply LOG10 on a Double1d

```
x=Double1d([1,10,100])
print LOG10(x)        # [0.0,0.9999999999999999,1.9999999999999998]
print ROUND(LOG10(x)) # [0.0,1.0,2.0]
```

API Summary

Jython Syntax

```
<y>=LOG10(<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns an array (or a number if the input is not an array) where each element is the the logarithm with base 10 of the corresponding element of the input array

See also

- LOG
- LogN

2.225. LOG

Full Name:	herschel.ia.numeric.toolbox.basic.Log
Alias:	LOG
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Log

Description

Computes the function $y=LOG_e(x)$, the natural logarithm.

Example

Example 1: Apply LOG on a Double1d

```
x=Double1d([0,1])
print LOG(EXP(x)) #  [0.0,1.0]
```

API Summary

Jython Syntax

```
<y>=LOG(<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns an array (or a number if the input is not an array) where each element is the the natural logarithm of the corresponding element of the input array

See also

- LOG10
- LogN

2.226. LogN

Full Name:	herschel.ia.numeric.toolbox.basic.LogN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import LogN

Description

Gives the logarithm with base N of a number or a numeric array: $y=LOG_n(x)$.

Example

Example 1: Apply LogN on a Int1d

```
x=2**Int1d.range(6)           # [1,2,4,8,16,32]
print Int1d(ROUND(LogN(2)(x))) # [0,1,2,3,4,5]
print Int1d(ROUND(x.apply(LogN(2)))) # [0,1,2,3,4,5]
```

API Summary

Jython Syntax

```
<y>=LogN(<base>)(<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]

a number **base** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

Limitations

Does not work for complex values.

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

a number base [INPUT, MANDATORY, default=no default value]

The base n

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns an array (or a number if the input is not an array) where each element is the the logarithm with base n of the corresponding element of the input array

See also

- LOG
- LOG10

2.227. Long1d

Full Name:	herschel.ia.numeric.Long1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Long1d

Description

A rectangular numeric long array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.228. Long2d

Full Name:	herschel.ia.numeric.Long2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Long2d

Description

A rectangular numeric long array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.229. Long3d

Full Name:	herschel.ia.numeric.Long3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Long3d

Description

A rectangular numeric long array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.230. Long4d

Full Name:	herschel.ia.numeric.Long4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Long4d

Description

A rectangular numeric long array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.231. Long5d

Full Name:	herschel.ia.numeric.Long5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Long5d

Description

A rectangular numeric long array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.232. LUDecomposition

Full Name:	herschel.ia.numeric.toolbox.matrix.LUDecomposition
Alias:	LUDecomposition
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import LUDecomposition

Example

Example 1: # Cava, Matrix Test Report:

```
#########################
#### LUDecomposition ####
#########################
#
### HIPE ###
#
A = Double2d([[ 2.0,  1.0,  1.0],[ 4.0, --6.0,  0.0],[-2.0,  7.0,  2.0]])
print A
[
[2.0,1.0,1.0],
[4.0,-6.0,0.0],
[-2.0,7.0,2.0]
]
B = Double2d([[3.0],[-8.0],[10.0]])
print B
[
[3.0],
[-8.0],
[10.0]
]
res=B.apply(LUDecomposition(A))
print res
[
[1.0],
[2.0],
[-1.0]
]
#
```

API Summary

Jython Syntax

```
A=Double2d()
B=Double2d()
res=B.apply(LUDecomposition(A))
lud = LUDecomposition(A)
res = B.apply(lud)
lowerTriangularFactor = lud.l
uppperTrangularFactor = lud.u
determinant = lud.det
integerPivot = lud.pivot
doublePivot = lud.doublePivot
flag = lud.isSingular();
```

Property
Double2d **A** [INPUT, MANDATORY, default=no default value]

API details

Property

Double2d A [INPUT, MANDATORY, default=no default value]
Input must be a Double2d or Float2d array.

2.233. ManualContourPanel

Full Name:	herschel.ia.toolbox.image.gui.ManualContourPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ManualContourPanel

Description

A panel for the ManualContourTask.

A panel to serva as GUI for the ManualConputTask.

API Summary

Constructor
ManualContourPanel() The construction of a new ManualContourPanel.

Methods
JPanel **getButtonPanel**() Returns the button panel.
setSiteEventHandler(SiteEventHandler handler) Setting the site event handler.
setTask(TaskApi task) Associating the task.
setVariableSelection(VariableSelection selection) Setting the variable selection
Map **getSelectionMap**() Returns the associated selection map.
SiteEventHandler **getHandler**() Returns the associated site event handler.
TaskApi **getTask**() Returns the associates task.
Double1d **getContourValues**() Returns the contour values.
DefaultListModel **getContourValuesModel**() Returns the default list model for the contour values.

API details

Constructor

ManualContourPanel()
The construction of a new ManualContourPanel. The construction of a new ManualContourPanel.

Methods

JPanel getButtonPanel()

Returns the button panel.

Returns the button panel for this ManualContourPanel.

Return

JPanel

Returns the button panel for this ManualContourPanel.

setSiteEventHandler(SiteEventHandler handler)

Setting the site event handler.

Sets the site event handler for this ManualContourPanel to the given site event handler.

Argument

`SiteEventHandler` **`handler`** `[INPUT, MANDATORY]`

setTask(TaskApi task)

Associating the task.

Associates the given task to this ManualContourPanel.

Argument

`TaskApi` **`task`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection

Sets the variable selection for this ManualContourPanel to the given variable selection.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

Map getSelectionMap()

Returns the associated selection map.

Returns the selection map associated with this ManualContourPanel.

Return

Map

Returns the selection map associated with this ManualContourPanel.

SiteEventHandler getHandler()

Returns the associated site event handler.

Returns the site event handler associated with this ManualContourPanel.

Return

SiteEventHandler

SiteEventHandler getHandler()

Returns the site event handler associated with this ManualContourPanel.

TaskApi getTask()

Returns the associates task.

Returns the task associated with this ManualContourPanel.

Return

TaskApi

Returns the task associated with this ManualContourPanel.

Double1d getContourValues()

Returns the contour values.

Returns the contour values for this ManualContourPanel.

Return

Double1d

Returns the contour values for this ManualContourPanel.

DefaultListModel getContourValuesModel()

Returns the default list model for the contour values.

Returns the default list model for the contour values for this ManualContourPanel.

Return

DefaultListModel

Returns the default list model for this contour values for this ManualContourPanel.

2.234. ManualContourTask

Full Name:	herschel.ia.toolbox.image.ManualContourTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ManualContourTask

Description

A Task for making contours.

A Task for making an ImageContour for a given image for a given list of contour values.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double1d values [INPUT, MANDATORY, default=No default value]`
`ImageContour contours [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image.

`Double1d values [INPUT, MANDATORY, default=No default value]`

The contour values.

`ImageContour contours [OUTPUT, MANDATORY, default=No default value]`

The ImageContour.

2.235. ManyToOneSpectrumTask

Full Name:	herschel.ia.toolbox.spectrum.ManyToOneSpectrumTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import ManyToOneSpectrumTask

Description

Abstract base class for tasks processing {@link SpectrumContainer} data structures or arrays of such by typically applying the processing on a suitable selection of point spectra included in the containers.

Various selection mechanisms are in place that allow selecting specific individual spectra for the processing.

This family of operations typically reduces the spectra to a single spectrum, hence we call it a 'many-to-one operation'. Typical example is the average.

API Summary

Properties
Object **ds** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection_lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection_index** [INPUT, OPTIONAL, default=No default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Boolean **overwrite** [INPUT, OPTIONAL, default=False.]
String **variant** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

Object ds [INPUT, OPTIONAL, default=no default value.]

Input data to be processed by the task. Several types are possible:

- SpectrumContainer
- Array of SpectrumContainer, i.e. SpectrumContainer[]
- List of SpectrumContainer, i.e. List
- Any product with implementations of `SpectrumContainer` inside.

Object selection [INPUT, OPTIONAL, default=None.]

Specify what point spectra to restrict to. Different ways to specify these selections are possible:

Object selection [INPUT, OPTIONAL, default=None.]

- Specify a list of indices (in jython) of the point spectra for which the processing should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments to restrict to. There are two options available:

- Either pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.
- Specify a PyList of segment indices.

Boolean overwrite [INPUT, OPTIONAL, default=False.]

Specify whether the input data container can be reused - the values found therein is overwritten.

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-wave" / "flux-wave-weight" / "flux-flag-wave" / "flux-weight-flag-wave"

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

History

- `2009-05-20 - meli`: Initial.

2.236. MapContext

Full Name:	herschel.ia.pal.MapContext
Type:	Java Class -
Import:	from herschel.ia.pal import MapContext

Description

Groups products (or other Contexts that in turn group products) in a

map-like structure. Products grouped in a MapContext can be subsequently retrieved by key, through the 'refs' method. Note: users may be confused as to why there is a need to have to go though a 'refs' method to add or access products from a MapContext. This is due to a technical limitation in the design which will be addressed in due course.

Examples

Example 1: Adding a product to a MapContext product = Product() ref =

```
storage.save(product) # the ref is a ProductRef object mapcontext =
MapContext() mapcontext.refs.put("john",ref)
```

Example 2: Getting a product from a MapContext ref_john =

```
mapcontext.refs.get("john") product = ref_john.product
```

Example 3: Saving a MapContext to ProductStorage (same way as any other

```
product) ref_context = storage.save(mapcontext)
```

API Summary

Method
`Map getRefs()`
get the 'map' of ProductRefs stored. From this 'map', you can put

API details

Method

`Map getRefs()`

get the 'map' of ProductRefs stored. From this 'map', you can put

products into the MapContext, or retrieve products by key.

Return

Map

A map of product refs.

Examples

Putting a product into the the MapContext ref =

Map getRefs()

```
storage.save(product) # the ref is a ProductRef object
storage.save(product) # the ref is a ProductRef object
mapcontext.refs.put("john", ref)
```

Getting the product from the MapContext with key "john"

```
ref_john = lcontext.refs.get("john")
```

See also

- ???

2.237. MatrixMultiply

Full Name:	herschel.ia.numeric.toolbox.matrix.MatrixMultiply
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import MatrixMultiply

Description

Performs matrix multiplication of numeric or logical matrices.

Examples

Example 1: Different syntax forms

```
# spelled out:
c=MatrixMultiply(b)(a)
c=a.apply(MatrixMultiply(b))
#
# reusing an instance of a matrix-multiplier:
f=MatrixMultiply(b)
c=f(a)
c=a.apply(f)
```

Example 2: Matrix multiplication examples

```
A = Int2d([[1,2,3], [2,3,4]])
B = Int2d([[1,2], [2,3], [3,4]])
X = Int1d([1,2])
Y = Int1d([1,2,3])
#
print A.apply(MatrixMultiply(B))
[[14, 20], [20, 29]]
print X.apply(MatrixMultiply(A))
[5, 8, 11]
print A.apply(MatrixMultiply(Y))
[14, 20]
```

API Summary

Jython Syntax

```
<y>=MatrixMultiply(<b>)(<a>)
```

Properties

Array1dData or Array2dData **a** [INPUT, MANDATORY, default=no default value]
Array1dData or Array2dData **b** [INPUT, MANDATORY, default=no default value]

Miscellaneous

Complex arrays are not supported yet.

API details

Properties

Array1dData or Array2dData a [INPUT, MANDATORY, default=no default value]

Input must be a rank one or rank two array of any type, but String or Complex.

Array1dData or Array2dData b [INPUT, MANDATORY, default=no default value]

Input must be an array of the same type as 'a'. If 'a' has rank one, 'b' must have rank two. If 'b' has rank one, 'a' must have rank two.

2.238. MatrixSolve

Full Name:	herschel.ia.numeric.toolbox.matrix.MatrixSolve
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import MatrixSolve

Description

Solves systems of linear equations of type A x = b.

A system of equations is a collection of equations that you deal with all together at once.

Example

Example 1: Apply MatrixSolve

```
# Solve
#  -| 1  2 -| -|x1|   -| 8|
#  -|      -| -|  -| = -|  -|
#  -| 3  4 -| -|x2|   -|18|
#
A=Float2d([ [1,2],[3,4] -])
b=Double1d([8.0,18.0])
print MatrixSolve(b)(A) # [2.0,3.0]
print A.apply(MatrixSolve(b))
```

API Summary

Jython Syntax

```
<x>=MatrixSolve(<b>)(<A>)
```

Properties

any matrix **A** [INPUT, MANDATORY, default=no default value]

Double1d **b** [INPUT, MANDATORY, default=no default value]

Miscellaneous

Does not work for complex matrices.

API details

Properties

any matrix A [INPUT, MANDATORY, default=no default value]

Any matrix

Double1d b [INPUT, MANDATORY, default=no default value]

Input must be a Double1d array.

2.239. MAX

Full Name:	herschel.ia.numeric.toolbox.basic.Max
Alias:	MAX
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Max

Description

Yields the numerically largest element in the input array.

Returns a scalar of the same type as the type of the input array.

Example

Example 1: Apply MAX on a Int2d

```
x=Int2d( [ [1,2], [-1,3] -])
print MAX(x)    # 3
print MAX(x, 0) # [1,3]
print MAX(x, 1) # [2,3]
```

API Summary

Jython Syntax

```
<y>=MAX(<x>, [,<dim>])
```

Properties

any scalar array **x** [INPUT, MANDATORY, default=no default value]

integer **dim** [INPUT, MANDATORY, default=no default value]

float or double array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array can be any scalar array.

integer dim [INPUT, MANDATORY, default=no default value]

The dimension to compute the calculation along

float or double array y [OUTPUT, MANDATORY, default=no default value]

Returns a scalar of the same type as the type of the input array.

See also

- MIN

2.240. MEAN

Full Name:	herschel.ia.numeric.toolbox.basic.Mean
Alias:	MEAN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Mean

Description

Yields the average value of the elements in the input array.

Example

Example 1: Apply MEAN on a Float1d

```
x=Float1d([1,3,2,3,4])
print MEAN(x) # 2.6
```

API Summary

Jython Syntax

```
<y>=MEAN(<x>)
```

Properties

any scalar array **x** [INPUT, MANDATORY, default=no default value]

double **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array integral or floating-point arrays; the former implicitly transformed to a double array.

double y [OUTPUT, MANDATORY, default=no default value]

Returns a double

See also

- MEDIAN
- STDDEV
- VARIANCE

2.241. MeanSmoothingTask

Full Name:	herschel.ia.toolbox.image.MeanSmoothingTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import MeanSmoothingTask

Description

A Task to smooth an image by applying a mean filter.

A Task to smooth an image using the average (mean) filter. The average filter computes the sum of all pixel values in the filter window and then divides the sum by the number of pixels in the filter window. In order to filter pixels located near the edges of the image.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Integer width [INPUT, MANDATORY, default=Default value : Integer(3)]`
`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image before smoothing.

`Integer width [INPUT, MANDATORY, default=Default value : Integer(3)]`

The width of the filter window.

`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

The image after smoothing.

2.242. MEDIANDEV

Full Name:	herschel.ia.numeric.toolbox.basic.MedianAbsoluteDeviation
Alias:	MEDIANDEV
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import MedianAbsoluteDeviation

Description

The median standard deviation is one of several ways to estimate an error of the median.

Algorithm:

For an array **data** the algorithm calculates the new array | data[i] - median(data) | for all values i (| indicates the absolute, positve value of the difference). The algorithm returns the median of the resulting array.

Example

Example 1: apply MedianStandardDeviation to an Int1d array

```
data = Int1d.range(9)
median = MEDIAN(data)
dev = data.apply( MedianStandardDeviation(median) -)
```

API Summary

Properties
any 1-5d array of integral type **x** [INPUT, MANDATORY, default=no default value]
the median of the input array x **median** [INPUT, MANDATORY, default=no default value]

API details

Properties

any 1-5d array of integral type x [INPUT, MANDATORY, default=no default value]

the median of the input array x median [INPUT, MANDATORY, default=no default value]

2.243. MEDIAN

Full Name:	herschel.ia.numeric.toolbox.basic.Median
Alias:	MEDIAN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Median

Description

Yields the central value of the elements in integral and floating point arrays.

Example

Example 1: Apply MEDIAN on a Float1d

```
x=Float1d([1,3,2,3,4])
print MEDIAN(x) # 3.0
```

API Summary

Jython Syntax
<y>=MEDIAN(<x>)

Properties
any scalar array **x** [INPUT, MANDATORY, default=no default value]
double **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array integral or floating-point arrays; the former implicitly transformed to a double array.

double y [OUTPUT, MANDATORY, default=no default value]

Returns a double

See also

- MEAN
- STDDEV
- VARIANCE

2.244. MedianSmoothingTask

Full Name:	herschel.ia.toolbox.image.MedianSmoothingTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import MedianSmoothingTask

Description

A Task to smooth an image by applying a median filter.

A Task to smooth an image using the median filter. The median filter computes the median of all pixel values in the filter window.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Integer width [INPUT, MANDATORY, default=Default value : Integer(3)]`
`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image before smoothing.

`Integer width [INPUT, MANDATORY, default=Default value : Integer(3)]`

The width of the filter window.

`Image smoothed [OUTPUT, MANDATORY, default=No default value]`

The image after smoothing.

2.245. MetaQuery

Full Name:	herschel.ia.pal.query.MetaQuery
Type:	Java Class -
Import:	from herschel.ia.pal.query import MetaQuery

Description

Meta data query formulates a query on the meta data of a Product.

Typically this type of query is slower than an Attribute Query, but faster than a full query on the Product Access Layer.

Example

Example 1: Example of an query on meta data q=MetaQuery(MyProduct.class,"p",

```
"p.meta['creator'].value == -'Me'")
```

See also

- ???

2.246. MIN

Full Name:	herschel.ia.numeric.toolbox.basic.Min
Alias:	MIN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Min

Description

Yields the numerically smallest element in the input array.

Returns a scalar of the same type as the type of the input array.

Example

Example 1: Apply MIN on a Int2d

```
x=Int2d( [ [1,2], [-1,3] -])
print MIN(x)    # --1
print MIN(x, 0) # [-1, 2]
print MIN(x, 1) # [ 1,-1]
```

API Summary

Jython Syntax

```
<y>=MIN(<x>, [,<dim>])
```

Properties

- any scalar array **x** [INPUT, MANDATORY, default=no default value]
- integer **dim** [INPUT, MANDATORY, default=no default value]
- float or double array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array can be any scalar array.

integer dim [INPUT, MANDATORY, default=no default value]

The dimension to compute the calculation along

float or double array y [OUTPUT, MANDATORY, default=no default value]

Returns a scalar of the same type as the type of the input array.

See also

- MAX

2.247. MosaicTask

Full Name:	herschel.ia.toolbox.image.MosaicTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import MosaicTask

Description

A Task for making mosaics.

A Task to make mosaics in a naive way (i.e. by simple co-adding).

API Summary

Properties
ArrayList **images** [INPUT, MANDATORY, default=No default value]
boolean **oversample** [INPUT, OPTIONAL, default=Default value : true]
SimpleImage **mosaic** [OUTPUT, MANDATORY, default=No default value]

Miscellaneous

Two blank maps are created : one to represent the total signal and one to represent the total exposure. For each pixel in each image, the pixel value is added into the total signal map and its exposure (or one) in the total exposure map (if not flagged out), taking only the overlap into account. After all pixels in each image have been mapped, the total signal map is divided by the total exposure map to produce the mosaic.

API details

Properties

ArrayList images [INPUT, MANDATORY, default=No default value]

The input images.

boolean oversample [INPUT, OPTIONAL, default=Default value : true]

Indication whether oversampling should be done.

SimpleImage mosaic [OUTPUT, MANDATORY, default=No default value]

The mosaic.

2.248. MultiplySpectrum

Full Name:	herschel.ia.toolbox.spectrum.MultiplySpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import MultiplySpectrum

Description

Task for multiplying the flux data included in a spectrum container with a scalar or for multiplying two spectrum containers with each other on a spectrum-by-spectrum basis.

For the scalar mode, 'ds' and 'param' need to specified - for the pair-wise mode, 'ds1' and 'ds2' need to be set. In the pairwise mode, the task iterates through the two containers and computes the pair-operation. In case the size of the two containers is different, the iteration stops at the minimum size. Hence, the remaining spectra in the larger container are ignored. In case one of the datasets only contains a single spectrum, the task always refers to this single spectrum while iterating over all the spectra in the other dataset.

Different selection schemes are available for selecting the point spectra or the segments to be processed. The most simple scheme is to specify lists of point spectrum indices (`selection=[1,3,4,2]`). In this case, the operation (scalar- or pair-operation) is just taken over the point spectra with corresponding indices. Instead of specifying a list of indices (which requires the knowledge of these) other recipes to specify a selection are available. Typical recipes test attribute values to match certain values or to be included in a given interval. These recipes we refer to as selection models. The different options to specify selections can be combined. Here, an AND logic is adopted.

Similarly, you can specify what segments to consider. In the most simple case, you can just specify the indices of segments to be considered (for the scalar operation `segments=[1,3,4]` and for the pair operation `segments1=[1,3,4], segments1=[3,6,5]`). In more advanced situations you can use a `SegmentSelection` object. Note that the pairs of segments to be processed need to be consistent - otherwise the processing will fail.

You can specify whether the orginal datasets should be overwritten with the 'overwrite' flag. By default no data is overwritten. In the pair-wise mode, it is not always possible to overwrite the data - in particular if non-trivial segment selections are specified.

For the pair-wise mode, there are further options that can be selected by the 'variant' (e.g. whether to use flags and weights).

Example

Example 1: from Jide:

```
from herschel.ia.toolbox.spectrum import MultiplySpectrum
multiply = MultiplySpectrum()
multipliedByFactor = multiply(ds=spectra, param=2.1)
multipliedByFactor = multiply(ds=spectra, selection={"bbtype":[6031]},
param=2.1)
multipliedByFactor = multiply(ds=spectra, selection=[0,1,2,3], param=2.1)
multipliedByFactor = multiply(ds=spectra, selection={"Chopper":
([-4.4,5.9],0.2), -"bbtype":[6031]}, param=2.1)
multipliedByFactor = multiply(ds=spectra, selection={"LoFrequency":
(4000.0,5000.0)}, param=2.1)
multipliedPairWise = multiply(ds1=spectra1, ds2=spectra2)
multipliedPairWise = multiply(ds1=spectra1, ds2=spectra2, selection={"bbtype":
[6031]})
multipliedPairWise = multiply(ds1=spectra1, ds2=spectra2, selection=[0,1,2,3])
```

Example 1: from Jide:

```
multipliedPairWise = multiply(ds1=spectra1, ds2=spectra2, selection={"Chopper":
([-4.4,5.9],0.2), -"bbtype":[6031]})
multipliedPairWise = multiply(ds1=spectra1, ds2=spectra2,
selection={"LoFrequency":(4000.0,5000.0)})
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, OPTIONAL, default=no default value.]
Double **param** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection_lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection_index** [INPUT, OPTIONAL, default=No default value.]
Boolean **overwrite** [INPUT, OPTIONAL, default=False.]
SpectrumContainer **ds1** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **ds2** [INPUT, OPTIONAL, default=no default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Object **segments1** [INPUT, OPTIONAL, default=no default value.]
Object **segments2** [INPUT, OPTIONAL, default=no default value.]
String **variant** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

SpectrumContainer ds [INPUT, OPTIONAL, default=no default value.]

Input container to be processed by the task in case the task is used as a scalar operation.

Double param [INPUT, OPTIONAL, default=no default value.]

The scalar parameter to be considered when the task is used as scalar operation.

Object selection [INPUT, OPTIONAL, default=None.]

Specify what point spectra the operation should be applied to. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra for which the add should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.

Object selection [INPUT, OPTIONAL, default=None.]

- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

Boolean overwrite [INPUT, OPTIONAL, default=False.]

Specify whether the input data container can be reused - the values found therein is overwritten.

SpectrumContainer ds1 [INPUT, OPTIONAL, default=no default value.]

First input container for pair-wise operations.

SpectrumContainer ds2 [INPUT, OPTIONAL, default=no default value.]

Second input container for pair-wise operations.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments the operation should be applied to. There are two options available:

- Either pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.
- Specify a PyList of segment indices.

Object segments1 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds1'.

Object segments2 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds2'.

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-wave" / "flux-wave-weight" / "flux-flag-wave" / "flux-weight-flag-wave"

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

See also

- SpectrumTask

History

- `2007-08-17 - meli`: initial.
- `2008-03-16 - meli`: major refactoring of the toolbox.
- `2008-10-03 - meli`: segments, javadoc

2.249. NearestNeighborInterpolator

Full Name:	herschel.ia.numeric.toolbox.interp.NearestNeighborInterpolator
Alias:	NearestNeighborInterpolator
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.interp import NearestNeighborInterpolator

Description

Creates an linear interpolation function from a set of knots (x,y),

that can be applied to numeric arrays of rank 1.

Example

Example 1: Create and apply a NearestNeighborInterpolator on a Double1d

```
# create some knots
x=Double1d.range(10) # [0.0,1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0]
f=NearestNeighborInterpolator(x,SQUARE(x))
u=Double1d([1,1.1,2,2.6,3,3.9])
print f(u) # [1.0,1.0,4.0,9.0,9.0,16.0]
```

API Summary

Jython Syntax

```
<f>=NearestNeighborInterpolator(<x>,<y>[,allowExtrapolation])
```

Properties

Double1d **x** [INPUT, MANDATORY, default=no default value]

Double1d **y** [INPUT, NOT_MANDATORY, default=false]

boolean **allowExtrapolation** [INPUT, NOT_MANDATORY, default=false]

API details

Properties

Double1d x [INPUT, MANDATORY, default=no default value]

The knots are Double1d

Double1d y [INPUT, NOT_MANDATORY, default=false]

The knots are Double1d

boolean allowExtrapolation [INPUT, NOT_MANDATORY, default=false]

Extrapolation is not allowed by default. Boolean.TRUE allows extrapolation.

See also

- CubicSplineInterpolator

- LinearInterpolator

2.250. NearestNeighbourProjectionTask

Full Name:	herschel.ia.toolbox.spectrum.projection.NearestNeighbourProjectionTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum.projection import NearestNeighbourProjectionTask
Category:	task

Description

NearestNeighbourProjectionTask

Creates a spectral cube by converting an image grid's pixels into world coordinates and assigning the nearest spectral data to each pixel.

Spectral Data

Three types of spectral data may be used as input:

1. 3D arrays of corresponding flux, ra, dec, wave, flag, and error data
2. A `SpectralSimpleCube`
3. A list of `SpectralSimpleCube`(s)

Target Grid

Data is projected onto a target grid. The shape of the spectral cube output is determined by the target grid. If not provided by the user, a target grid may be calculated by the `targetGrid` method directly from the RA and DEC data.

Examples

Example 1: How to create a spectral cube.

```
# Given:
# 1. 3D arrays of flux, ra, and dec input (with variable names flux, ra and
dec).
# 2. A target image (a TargetGrid object) (with variable name target).
# Create a task.
nnTask = NearestNeighbourProjectionTask()
# Execute the task and create spectral cube.
spectralCube = nnTask(flux = flux, ra = ra, dec = dec, target = target)
```

Example 2: How to create a target grid.

```
# One may generate a target automatically by calling the targetGrid method.
# This method will use the directions defined by 3D arrays of ra and dec to
create a target
# that encloses the data.
# Create image target grid.
target = nnTask.targetGrid(ra,dec,wave)
```

Example 3: How to create a spectral cube from a list of SpectrometerDetectorSpectrum's.

```
# Given:
# 1. sdsList, an array of SpectrometerDetectorSpectrum objects.
# 2. detectorArray, a string identifying the detector array to process ("SLW"
or -"SSW").
```

Example 3: How to create a spectral cube from a list of SpectrometerDetectorSpectrum's.

```
# Create a SpirePreprocessedCube with SpirePreprocessCubeTask.
task = SpirePreprocessCubeTask()
ppCube = task(sdsList)
flux = ppCube.getFlux(detectorArray)
error = ppCube.getError(detectorArray)
flag = ppCube.getFlag(detectorArray)
ra = ppCube.getRa(detectorArray)
dec = ppCube.getDec(detectorArray)
wave =  ppCube.getWave()
# Create NearestNeighbourProjectionTask
nnTask = NearestNeighbourProjectionTask()
# Create target grid
targetGrid = nnTask.targetGrid(ra, dec, wave)
# Execute the task and create spectral cube.
nnCube = nnTask(flux = flux, error = error, flag = flag, ra = ra, dec = dec,
target = targetGrid)
```

API Summary

Properties
SpectralSimpleCube **cube** [INPUT, OPTIONAL, default=no default value]
SpectralSimpleCube[] **cubeList** [INPUT, OPTIONAL, default=no default value]
Double3d **dec** [INPUT, OPTIONAL, default=no default value]
Double3d **ra** [INPUT, OPTIONAL, default=no default value]
Double3d **error** [INPUT, OPTIONAL, default=no default value]
Flag **flag** [INPUT, OPTIONAL, default=no default value]
Double3d **flux** [INPUT, OPTIONAL, default=no default value]
TargetGrid **target** [INPUT, MANDATORY, default=no default value]
MetaData **meta** [INPUT, OPTIONAL, default=no default value]
Unit?> **fluxUnit** [INPUT, OPTIONAL, default=no default value]
SpectralSimpleCube **spectralSimpleCube** [OUTPUT, no default value, default=no default value]

API details

Properties

SpectralSimpleCube cube [INPUT, OPTIONAL, default=no default value]

SpectralSimpleCube element to be projected

SpectralSimpleCube[] cubeList [INPUT, OPTIONAL, default=no default value]

List of SpectralSimpleCube elements to be projected

Double3d dec [INPUT, OPTIONAL, default=no default value]

Declination values corresponding to flux values, having dimensions [Wavenumber,X,Y]. Wavenumber is a spectral dimension. X and Y are spatial dimensions.

Double3d ra [INPUT, OPTIONAL, default=no default value]

Right ascension values corresponding to flux, having dimensions [Wavenumber,X,Y]. Wavenumber is a spectral dimension. X and Y are spatial dimensions.

Double3d error [INPUT, OPTIONAL, default=no default value]

Error on the flux, having dimensions [Wavenumber, X, Y]. Wavenumber is a spectral dimension. X and Y are spatial dimensions.

Flag flag [INPUT, OPTIONAL, default=no default value]

Flag indicating which spectra are invalid, having dimensions [Wavenumber,X,Y]. Wavenumber is a spectral dimension. X and Y are spatial dimensions.

Double3d flux [INPUT, OPTIONAL, default=no default value]

Flux data having dimensions [Wavenumber, X,Y]. Wavenumber is a spectral dimension. X and Y are spatial dimensions.

TargetGrid target [INPUT, MANDATORY, default=no default value]

The target coordinates as a world coordinate system with three axes (two spatial and one spectral).

MetaData meta [INPUT, OPTIONAL, default=no default value]

Metadata to propagate to the SpectralSimpleCube. Regardless of whether this parameter is provided, the task will create the mandatory metadata parameters (e.g. "creator").

Unit?> fluxUnit [INPUT, OPTIONAL, default=no default value]

Flux unit to set in the SpecralSimpleCube output.

SpectralSimpleCube spectralSimpleCube [OUTPUT, no default value, default=no default value]

The resulting projected cube.

See also

- ???
- ???

History

- 2009-04-22 - CM: [SPIRE SCR-1474] First version in order to meet the requirements of the SCR
- 2009-08-25 - PK: [SPIRE SCR-1474] Updated for new SpectralProjectionAlgorithm interface (see [HCSS-7600]). Implemented project method for 3d arrays. Implemented targetGrid methods for 3d arrays.
- 2009-09-17 - DS: [SPIRE ACT-1976] Added metadata entry to output; Name:"level", Value:"20".
- 2009-09-24 - DS: [SPIRE SPR-1996] Added parameter "meta" to task to allow metadata propagation. Added metadata propagation.
- 2009-10-24 - DS: [SPIRE SPR-1996] Added unit propagation.

- `2009-11-20 - DS`: [SPIRE SCR-1474] Added extrapolation to project methods. Added new project methods. Added default target grid method.

2.251. Normalize

Full Name:	herschel.ia.numeric.toolbox.basic.Normalize
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Normalize

Description

This functionality normalizes sets of data.

Normalization can be done by multiplying the independent variable, by a scaling factor so that the data will have a user-specified peak value or mean value over a user-specified range of dependent variables.

Input data sets is a list of vectors containing N elements, where a single vector can be written as (x1,x2,x3,...,xN-1, y). The Normalize class provides four valid options of normalization.

-Option 1: It multiplies the y values such that the peak y value will have a user-specified constant value.

-Option 2: It normalizes the y values such that the peak y value will be same as the peak value of a user-specified "fiducial" vector set.

-Option 3: It normalizes the y values so that the mean of the y values over a user-specified x-range will have a user-specified constant value.

-Option 4: It normalizes the y values so that the mean of the y values over a user-specified x-range will be same as the mean of a user-specified "fiducial" vector set over the x-range.

Notes:

-The x-range must be specified as a range in all N-1 dimensions.

-The dimentions of input data must be same as the dimentions of the fiducial array.

-When the peak/mean value of input data set equals to zero, an error [condition] is issued.

-When the peak/mean value of input data set has different sign from user-supplied peak/mean value, an error [condition] is issued.

-When there are no data within the x-range within the fiducial data set, an error [condition] is issued.

-The routine can handle any dimension N where N >= 2, and can handle all real and integer data types.

Example

Example 1: from herschel.ia.numeric import *

```
from herschel.ia.numeric.toolbox.basic import Normalize
# Perform normalizations using four valid types.
# Type 1: Normalize y values to the common peak, a user-specified constant.
# Input data array.
arr = Double2d([(0.,1.,8.,40.),(10.,10.,4.,60.),(2.,0.,4.,120.)])
# User specified peak value.
peak = 45.
# Normalize.
norm1 = Normalize(peak,Normalize.PEAK_CNST)(arr)
# Check output.
print norm1
# Output: [[0.0,1.0,8.0,15.0],[10.0,10.0,4.0,22.5],[2.0,0.0,4.0,45.0]]
# Type 2: Normalize y values to the max of a user-supplied -"fiducial" array.
# Input data array.
arr = Int2d([(0,1,8,40),(10,10,4,60),(2,0,4,120)])
```

Example 1: from herschel.ia.numeric import *

```
# User supplied fiducial array.
fiducial = Int2d([(1,1,1,10),(2,2,8,30),(4,6,10,20)])
# Normalize.
norm2 = Normalize(fiducial,Normalize.PEAK_FIDUCIAL)(arr)
# Check output.
print norm2
# Output: [[0,1,8,10],[10,10,4,15],[2,0,4,30]]
# Type 3: Normalize y values to have a user-specified constant mean value
# over a x range.
# Input data array.
arr = Double2d([(0.,1.,8.,40.),(1.,10.,4.,60.),(2.,0.,4.,120.)])
# User specified mean value.
mean = 25.
# User specified x range array.
xrange = Double2d([(0.,0.,0.),(2.,5.,10.)])
norm3 = Normalize(mean,xrange,Normalize.MEAN_CNST)(arr)
# Check output.
print norm3
# Output: [[0.0,1.0,8.0,12.5],[1.0,10.0,4.0,18.75],[2.0,0.0,4.0,37.5]]
# Type 4: Normalize y values to the mean value of a user-supplied fiducial
# array over a x range.
# Input data array.
arr = Double2d([(0.,1.,8.,40.),(10.,10.,4.,60.),(2.,0.,4.,120.)])
# User supplied fiducial array.
fiducial = Double2d([(1.,1.,1.,15.),(2.,2.,8.,45),(4.,6.,10.,25.)])
# User specified x range array.
xrange = Double2d([(0.,0.,0.),(3.,3.,10.)])
# Normalize.
norm4 = Normalize(fiducial,xrange,Normalize.MEAN_FIDUCIAL)(arr)
# Check results.
print norm4
# Output: [[0.0,1.0,8.0,15.0],[10.0,10.0,4.0,22.5],[2.0,0.0,4.0,45.0]]
```

API Summary

Jython Syntax

```
<result>=Normalize(<a>,[<b>,]<type>)(<input>)
```

Properties

its value depends on the Normalize type specified **a** [INPUT, MANDATORY, default=no default value]
its value depends on the Normalize type specified **b** [INPUT, OPTIONAL, default=no default value]
Normalization type **type** [INPUT, MANDATORY, default=no default value]
Input data sets **input** [INPUT, MANDATORY, default=no default value]
the normalized array **result** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

its value depends on the Normalize type specified a [INPUT, MANDATORY, default=no default value]

-Normalize.PEAK_CNST type: common peak value to use when normalizing the input values ('' **argument is not required). -Normalize.PEAK_FIDUCIAL type: 'fiducial' array**

its value depends on the Normalize type specified a [INPUT, MANDATORY, default=no default value]

where the maximun value to use when normalizing the input values, is extracted ('' argument is not required). -Normalize.MEAN_CNST type: mean value, over an 'x' range (argument ''), to be obtained when normalizing the input values (requires '' argument). -Normalize.MEAN_FIDUCIAL type: 'fiducial' array where the mean value, over an 'x' range (argument ''), to be obtained when normalizing the input values, is extracted (requires '' argument).

its value depends on the Normalize type specified b [INPUT, OPTIONAL, default=no default value]

-Normalize.MEAN_CNST type: 'x' range where the normalized input values must have the specified mean value (argument '). -Normalize.MEAN_FIDUCIAL type: 'x' range where the normalized input values must have the specified mean value extracted from a fiducial array (argument ').

Normalization type type [INPUT, MANDATORY, default=no default value]

-Normalize.PEAK_CNST: It multiplies the 'y' values such that the peak 'y' value will have a user-specified constant value -Normalize.PEAK_FIDUCIAL: It normalizes the 'y' values such that the peak 'y' value will be same as the peak value of a user-specified "fiducial" vector set. -Normalize.MEAN_CNST: It normalizes the 'y' values so that the mean of the 'y' values over a user-specified x-range will have a user-specified constant value. -Normalize.MEAN_FIDUCIAL: It normalizes the 'y' values so that the mean of the 'y' values over a user-specified x-range will be same as the mean of a user-specified "fiducial" vector set over the x-range.

Input data sets input [INPUT, MANDATORY, default=no default value]

List of vectors containing N elements, where a single vector can be written as (x1,x2,x3,...,xN-1, y)

the normalized array result [OUTPUT, MANDATORY, default=no default value]

ie: norm[(x1_1,x2_1,x3_1,...,xN-1_1, yNorm_1), (x1_2,x2_2,x3_2,...,xN-1_2, yNorm_2), ...]

2.252. NotPresent

Full Name:	herschel.ia.numeric.toolbox.basic.NotPresent
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import NotPresent

Description

Tests whether none of the bits in specified mask are present in the elements of the input array.

The input array must be of integral type (e.g. bytes,integers) and the result is a boolean array.

Example

Example 1: Apply NotPresent on a Int1d: test if a binary 'and' comparison, item by item, with '3' (as mask) is equals to '0'

```
x=Int1d([0,1,2,3])
print NotPresent(3)(x)
#=> [   (0 & 3) == 0,   (1 & 3) == 0,   (2 & 3) == 0,   (3 & 3) == 0   -] =
[true,false,false,false]
print x.apply(NotPresent(3)) #Another way for using NotPresent
```

API Summary

Jython Syntax

```
<y>=NotPresent(<bitmask>)(<x>)
```

Properties

any array of integral type **x** [INPUT, MANDATORY, default=no default value]

any array of booleans **bitmask** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of integral type x [INPUT, MANDATORY, default=no default value]

The input array must be of integral type (e.g. bytes,integers)

any array of booleans bitmask [INPUT, MANDATORY, default=no default value]

An array of booleans

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns a boolean array (or a boolean if the input is not an array) where each element is true if the corresponding element in the input array is present, false otherwise.

See also

- AllPresent
- AnyPresent

2.253. NumberedDataset

Full Name:	herschel.ia.dataset.spectrum.NumberedDataset
Type:	Java Class -
Import:	from herschel.ia.dataset.spectrum import NumberedDataset
Category:	Datasets

Description

NumberedDataset is an alternative for the non-existing VectorDataset.

NumberedDataset is an extension of CompositeDataset, which contains datasets identified by number. It contains an iterator over the stored datasets.

Example

Example 1: In Jide:

```
vds = NumberedDataset()        # create a NumberedDataset
s1 = Spectrum1d()             # create some Datasets
s2 = Spectrum2d()
s3 = ArrayDataset( -)
vds.set( s1 -)             # set s1 at number -"1"
vds.set( s2 -)             # set s2 at number -"2"
vds.set( s3, 4 -)             # set s3 at number -"4"
s4 = vds.get( 1 -)             # s4 equals s1
print vds.getCount()         # yields 3 (3 sets in vds)
print vds.getLastIndex()         # yields 4 (last one is at 4)
it = vds.iterator()          # iterator over the datasets.
while it.hasNext(): print it.next().__class__   # print classes
vds.remove( 2 -)             # leaves sets at 1 and 4
vds.collapse()             # renumbers sets to 1 and 2
vds.remove()            # removes last one, leaves only nr 1
```

Limitations

NumberedDataset still **is** a CompositeDataset and can be addressed as such. If you do so, the special methods of NumberDataset are **not** guarandeed to work.

History

- 06-03-2006 DK.

2.254. ObservationContext

Full Name:	herschel.ia.obs.ObservationContext
Type:	Java Class -
Import:	from herschel.ia.obs import ObservationContext

Description

An Observation Context is a container of Products applicable to an

specific observation. It provides associations to products which are specific to a single observation (e.g. Telemetry Product, and reduced data products) as well as associations to Products that are appliable to multiple observations (such as the calibration products).

Example

Example 1: from herschel.ia.obs import *

```
from herschel.share.fltdyn.time import FineTime
from herschel.ia.pal import MapContext
obs = ObservationContext()
auxContext = MapContext()
obs.auxiliary=auxContext #error
print obs.isInitialized() #0 (false)
obs.id=1L
obs.odNumber=2L
obs.instrument="HIFI"
obs.modelName="0"
obs.startTime=FineTime(1L)
obs.endTime=FineTime(2L)
print obs.isInitialized() #1 (true)
obs.auxiliary=auxContext #ok
print obs.auxiliary #{description="Unknown", meta=[type, creator,
creationDate, instrument, modelName, startDate, endDate], datasets=[],
history=None, refs=[]}
print obs.isPrepared() #0 (false)
obs.calibration = MapContext()
print obs.isPrepared() #1 (true)
obs.level['level0']=productContext   #ok
print obs.level['level0']    #{description="Unknown", meta=[type, creator,
creationDate, instrument, modelName, startDate, endDate], datasets=[],
history=None, refs=[]}
print obs.isReduced() #0 (false)
obs.level['level1']=MapContext()
print obs.isReduced() #1 (true)
```

API Summary

Jython Syntax

```
<obs>=ObservationContext()
```

Property

ObservationContext **obs** [OUTPUT, MANDATORY, default=no default value]

API details

Property

ObservationContext obs [OUTPUT, MANDATORY, default=no default value]
Returns an empty ObservationContext

See also

- ???
- MapContext
- ProductRef
- ???

2.255. OpDayGenerator

Full Name:	herschel.ia.pg.od.OpDayGenerator
Type:	Java Class -
Import:	from herschel.ia.pg.od import OpDayGenerator

History

- 19 Oct 2007: better exeption handling.
- 19 Nov 2007: add PCAL plugin

2.256. openFile

Full Name:	herschel.ia.toolbox.util.OpenFileTask
Alias:	openFile
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import OpenFileTask
Category:	task

Description

opens a variable in a viewer

Allows to open via script viewers associated to variables. TODO: document viewers

Examples

Example 1: Opening a jythom script with the editor

```
openFile("/home/user/myscript.py")
```

Example 2: Opening a fits file with its default viewer

```
openFile("/home/user/product.fits")
```

API Summary

Jython Syntax

```
openFile(<variable> [, <viewer>])
```

Properties

`String file [INPUT, MANDATORY, default=null]`

`String viewer [INPUT, OPTIONAL, default=null]`

API details

Properties

`String file [INPUT, MANDATORY, default=null]`

The path of the file to open

`String viewer [INPUT, OPTIONAL, default=null]`

The ID of the viewer to open the file with

History

- `2009-02-08 - JDS`: first release
- `2009-09-30 - JSS`: modifiers are created through getCustomModifiers (SCR HCSS-8253)

2.257. openTask

Full Name:	herschel.ia.toolbox.util.OpenTaskTask
Alias:	openTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import OpenTaskTask
Category:	task

Description

opens a task in its viewer

Allows to open via script viewers associated to registered tasks.

Example

Example 1: Opening FitsReader task filling the file field with variable filename

```
filename = -"/home/user/my.fits"
openTask("fitsReader", variablename="filename")
```

API Summary

Jython Syntax

```
openTask(<taskname> [, primeinputname] [, <varname>])
```

Properties

```
String taskname [INPUT, MANDATORY, default=null]
String primeinputname [INPUT, OPTIONAL, default=null]
String variablename [INPUT, OPTIONAL, default=null]
```

API details

Properties

String taskname [INPUT, MANDATORY, default=null]

Name of the task to be opened

String primeinputname [INPUT, OPTIONAL, default=null]

Name of the prime input variable if needed to distinguish between tasks with the same name but different prime inputs

String variablename [INPUT, OPTIONAL, default=null]

Name of the variable to fill the prime input with

History

- 2009-11-03 - JDS: first release

2.258. openVariable

Full Name:	herschel.ia.toolbox.util.OpenVariableTask
Alias:	openVariable
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import OpenVariableTask
Category:	task

Description

opens a variable in a viewer

Allows to open via script viewers associated to variable types. TODO: document viewers

Example

Example 1: Opening a product variable with its default viewer

```
p = Product()
openVariable("p")
```

API Summary

Jython Syntax

```
openVariable(<variable> [, <viewer>])
```

Properties

`String` **`variable`** `[INPUT, MANDATORY, default=null]`

`String` **`viewer`** `[INPUT, OPTIONAL, default=null]`

API details

Properties

`String variable [INPUT, MANDATORY, default=null]`

Path of the file to be opened

`String viewer [INPUT, OPTIONAL, default=null]`

Viewer to open the variable with

History

- `2008-12-15 - JDS`: first release
- `2008-12-16 - JDS`: added optional parameter viewer

2.259. OverPlotter

Full Name:	herschel.ia.gui.explorer.table.OverPlotter
Type:	Java Class -
Import:	from herschel.ia.gui.explorer.table import OverPlotter

Description

Overview of OverPlotter

```
OverPlotter is an extension of TablePlotter and  allow users to overlay dat\
a on top of
each other and to compare. The OverPlotter can be seen as stacking many tra\
nsparent
TablePlotters as layers on top of each other. Most TablePlotter features  w\
ork in
OverPlotter, especially when working on an individual layer. OverPlotter la\
yers have three
states, active, secondary active and in active.   Each OverPlotter layer ha\
s
its own personalities.  The personalities are unchanged no matter the layer\
 is active,
secondary active and inactive. \
```

Example

Example 1: Invoke OverPlotter in command line

```
<pre>
from herschel.ia.io.fits import FitsArchive
from herschel.ia.dataset import TableDataset
from herschel.ia.dataset import Product
from herschel.ia.gui.explorer.table import *
from herschel.share.component import *
fits=FitsArchive();
path="/home/zhang/Development/data/"
filename = -"loadCurve.fits"
try:
    fits.reader = FitsArchive.HCSS_READER
    p = fits.load(path+filename)
except java.io.IOException:
    fits.reader = FitsArchive.STANDARD_READER
    p = fits.load(path+filename)
table =p.default
wm=WindowManager.getDefault()
#Load OverPlotter
overPlotter=OverPlotter(table)
wm.addWindow('test', overPlotter.component, 1)
#add a new layer
table1=table
overPlotter.object=table1
</pre>
```

API Summary

Constructors
OverPlotter() The default constructor
OverPlotter(TableDataset tds)

Constructors
A constructor

Methods
`JComponent` **`getComponent()`** This method will return OverPlotter as a pluggable component
`String` **`getDescription()`**
`String` **`getName()`**
`setObject``(TableDataset data)` Initiate a new instance of OverPlotter or add a new layer to the existing OverPlotter.

API details

Constructors

`OverPlotter()`
The default constructor This constructor is used to initializes the _layerCounter to 0.

`OverPlotter(TableDataset tds)`

A constructor
 	
This constructor is used to initiate an instance of TablePlotter from the command line.
Argument
`TableDataset` **`tds`** `[INPUT, MANDATORY]`
Example
- Invoke OverPlotter in command line
`from herschel.ia.gui.explorer.table import OverPlotter  #import OverPlotter`
`opl=OverPlotter(tbs)  #dts is a TableDataset defined somewhere`
`else`

Methods

`JComponent getComponent()`
This method will return OverPlotter as a pluggable component This method allows TablePlotter to be used as a plug-ins. The user can plug OverPlotter to his/her own applications. **Return** **JComponent** the OverPlotter as a component **Example** Use OverPlotter as a plug-in `<pre>`

JComponent getComponent()

```
from herschel.share.component import *
from javax.swing import *
from java.awt import *
from herschel.ia.io.fits import FitsArchive
from herschel.ia.dataset import TableDataset
from herschel.ia.dataset import Product
from herschel.ia.dataset.gui import *
from herschel.ia.gui.explorer.table import OverPlotter
fits=FitsArchive();
#Change to your data path
path="/home/zhang/Development/data/"
filename = -"loadCurve.fits"
#load the table
try:
  fits.reader = FitsArchive.HCSS_READER
  p = fits.load(path+filename)
except java.io.IOException:
  fits.reader = FitsArchive.STANDARD_READER
   p = fits.load(path+filename)
#create a TableDataset
table =p.default
#create a container to hold the controls/components
pane=JPanel()
#set the layout, there are many different kinds users can choose according
to his/her need
pane.setLayout(BoxLayout(pane, BoxLayout.Y_AXIS))
#add control one, a label
title = JLabel("Please see OverPlotter below")
pane.add(title)
#Add OverPlotter to the pane
overPlotter=OverePlotter(table)
pane.add(overPlotter.component)
pane.setPreferredSize(Dimension(overPlotter.component.width,
overPlotter.component.height))
#add to your application
frame =JFrame("OverPlotter as Plug-in demo");
frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE)
frame.getContentPane().add(pane, BorderLayout.CENTER)
frame.pack
frame.visible=1
</pre>
```

String getDescription()

Return

String

the description of the OverPlotter

String getName()

Return

String

the name of this explorer

setObject(TableDataset data)

Initiate a new instance of OverPlotter or add a new layer to the existing OverPlotter.

When this method is called the first time, it will initiate a new instance of OverPlotter and then assign the class variable _activeOverPlotter to the newly created object. When it is called again, it will add a new OverPlotter layer on to the existing OverPlotter object, _activeOverPlotter.

setObject(TableDataset data)

Argument

`TableDataset` **`data`** `[INPUT, MANDATORY, default=no default value]`

data is a TableDataset. It will be passed as an active data structure to be plotted.

Example

Create a new OverPlotter with one layer and then add the second layer

```
<pre>
 from herschel.ia.gui.explorer.table import OverPlotter
 overPlotter = OverPlotter(dataset1)
 overPlotter.object = dataset2
 </pre>
```

History

- `2008-10-02 - First`: release
- `2009-01-14 - Implemented`: SPR-5598 and SPR-5783
- `2009-07-16 - Implemented`: HCSS-5973 and HCSS-6703
- 7/16/09
- Implemented HCSS-5973 and HCSS-6703:
- Removed the time offset menuitem in preference menu.
- Removed Color drop down box
- Removed the statement and methods to set up the color using the color drop down box
- Add two check box for x and y time offset
- Add methods to set and get the color when all layers active when the layer is added
- Add event handlers to turn the time offset on/off.
- Add statement to hide and unhide the time offset check box according to whether the
- column data is time or not

2.260. PackedMask

Full Name:	herschel.ia.numeric.toolbox.mask.PackedMask
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.mask import PackedMask

Description

PackedMask creates and stores compressed mask array data which can be set, unset and checked.

This way no memory is wasted. Also no limit on the total bits of mask (in FixedMask, the maximum number of bits in one mask data is 64.)

Examples

Example 1: #An 2x3 2-d mask array is create by

```
mask=PackedMask("maskname", [2,3,129])
#The previous command defines a mask holding 129 bits for each element of a
2x3 array.
#However, since mask bits are stored as integers, and an integer is 32 bits
long, five
#integers (129/32 + 1) are needed to store <emphasis>at least</emphasis> 129
bits for
#each array element (four integers would stop at 128 bits). Therefore the
mask ends up
#holding 32 x 5 = 160 bits.
#The mask is stored internally as a 2x3x5 integer array, as shown by the
following command:
print mask.getMask()
#[ [ [0,0,0,0,0], [0,0,0,0,0], [0,0,0,0,0] -], [ [0,0,0,0,0], [0,0,0,0,0],
[0,0,0,0,0] -] -]
print mask.getName()
#maskname
```

Example 2: Set/Unset mask (continued from the previous example)

```
#One mask data in the array can be set by
print mask.set([1,2,3]) # The [1,2] mask data is set by bit offset 3
#[ [ [0,0,0,0,0], [0,0,0,0,0], [0,0,0,0,0] -], [ [0,0,0,0,0], [0,0,0,0,0],
[8,0,0,0,0] -] -]
#and unset by
print mask.unset([1,2,3])
#[ [ [0,0,0,0,0], [0,0,0,0,0], [0,0,0,0,0] -], [ [0,0,0,0,0], [0,0,0,0,0],
[0,0,0,0,0] -] -]
```

Example 3: Check mask (continued from the previous example)

```
#The mask data can be checked by
print mask.isSet([1,2,3])
#1
print mask.isSet([1,1,2])
#0
```

Example 4: How to set other integers (continued from the previous example)

```
# The bit offset 0-31 to set the first integer, 32-63 the second, -....
print mask.set([1,0,65]) #FixedMask can only set 64 bits.
#[ [ [0,0,0,0,0], [0,0,0,0,0], [0,0,0,0,0] -], [ [0,0,2,0,0], [0,0,0,0,0],
[0,0,0,0,0] -] -]
print mask.set([0,1,157])
```

Example 4: How to set other integers (continued from the previous example)

```
#[ [ [0,0,0,0,0], [0,0,0,0,536870912], [0,0,0,0,0] -], [ [0,0,2,0,0],
[0,0,0,0,0], [0,0,0,0,0] -] -]
```

Example 5: High dimension mask array, up to 5d:

```
mask1=PackedMask("m1", [33])
print mask1.getMask()
#[0,0]
print mask1.set([3])
#[8,0]
mask2=PackedMask("m2", [2,100])
print mask2.getMask()
#[ [0,0,0,0], [0,0,0,0] -]
print mask2.set([1,4])
#[ [0,0,0,0], [16,0,0,0] -]
mask3=PackedMask("m3", [2,3,64])
print mask3.getMask()
#[ [ [0,0], [0,0], [0,0] -], [ [0,0], [0,0], [0,0] -] -]
print mask3.set([0,1,5])
#[ [ [0,0], [32,0], [0,0] -], [ [0,0], [0,0], [0,0] -] -]
mask4=PackedMask("m4", [2,3,4,129])
print mask4.getMask()
print mask4.set([1,2,3,150])
mask5=PackedMask("m5", [2,3,4,5,129])
print mask5.getMask()
print mask5.set([1,2,3,4,150])
```

See also

- FixedMask

History

- July 2007 Original, based on MW code
- June 2009 SPR HCSS-6831. Set wrong mask data.
- Sept 2009 SCR HCSS-6832 and 6834. UM and URM.

2.261. pacs2HipeDouble3d

Full Name:	herschel.ia.toolbox.cube.pacs2HipeDouble3d
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import pacs2HipeDouble3d

Description

A Task which reshape PACS 3 dimensional data

Example

Example 1: Rotate a cube pacs3d[Depth,Height,Width] in a cube hipe3d[Depth,Height,Width]

```
importCube(simplecube = cube, filename = -"myFile.fits")
```

API Summary

Properties
Cube **simplecube** [IO, MANDATORY, default=No default value]
string **filename** [INPUT, MANDATORY, default=no default value]

API details

Properties

Cube simplecube [IO, MANDATORY, default=No default value]

The input Cube to load

string filename [INPUT, MANDATORY, default=no default value]

The file to import

2.262. pause

Full Name:	herschel.ia.toolbox.util.PauseTask
Alias:	pause
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import PauseTask
Category:	task

Description

Pause the execution of jython code

The pause task is used to pause the execution of jython. When executed a debug dialog appears displaying the current local namespace in a inspector window and a new console for executing statements into the localized namespace.

Users can add/alter the values in the namespace, the values affects the code still to be executed.

Examples

Example 1: Pause the execution of jython code

```
pause()
```

Example 2: pause the execution of my_function beetwen the assignemnt of x and

```
its printing, assigment done to x from the debugger window are reflected by
the print
def my_function():
 x=100
 pause()
 print x
my_function()
```

Limitations

no Limitation

Miscellaneous

No miscellaneous

See also

- pause

History

- `2007-10-11 - NdC`: first release.

2.263. pointHistoryDisplay

Full Name:	herschel.ia.toolbox.pointing.PointHistoryDisplayTask
Alias:	pointHistoryDisplay
Type:	Java Task -
Import:	from herschel.ia.toolbox.pointing import PointHistoryDisplayTask
Category:	utility task

Description

Task for displaying graphs of pointing information

This takes a PointingProduct and produces graphs of the data contained in the product.

Example

Example 1: PointHistoryDisplayTask

```
<pre>
 -...
 pp = pool.getProduct(urn)
 phdt = PointHistoryDisplayTask()
 graphs = String1d(["RAC-Time", -"RAG-Time"])
 phdt(pp, graphs, -"mosaic")
 -...
</pre>
```

API Summary

Jython Syntax

```
PointHistoryDisplayTask()(pp, graphs, mosaic)
see examples
```

Properties

```
PointingProduct PointingProduct [INPUT, true, default=null]
String1d plotPairs [INPUT, true, default=null]
String layout [INPUT, true, default="mosaic"]
```

API details

Properties

PointingProduct PointingProduct [INPUT, true, default=null]

PointingProduct

String1d plotPairs [INPUT, true, default=null]

String1d containing strings specifying parameter pairs to be plotted. These are pairs of Strings separated by a hyphen.

Allowed Strings are

String1d plotPairs [INPUT, true, default=null]

- "Time"
- "RAC" (Commanded RA)
- "RAG" (Gyro-propagated RA)
- "RAF" (Filtered RA)
- "DecC" (Commanded Dec)
- "DecG" (Gyro-propagated RA)
- "DecF" (Filtered RA)
- "PAC" (Commanded Position angle)
- "PAG" (Gyro-propagated position angle)
- "PAF" (Filtered position angle)
- "AngVel1" (first angular velocity value)
- "AngVel2" (second angular velocity value)
- "AngVel3" (third angular velocity value)

String layout [INPUT, true, default="mosaic"]

String with value "mosaic" or "overlay" to specify how multiple plots should be organised.

2.264. Polygon

Full Name:	herschel.ia.toolbox.image.Polygon
Type:	Java Class -
Import:	from herschel.ia.toolbox.image import Polygon

Description

A polygon shape.

API Summary

Constructors
Polygon() The construction of a new Polygon without coordinates.
Polygon(double[] coords) The construction of a new Polygon with the given vertices
Polygon(double x, double y) The construction of a new Polygon with a single starting point.
Polygon(int size) The construction of a new Polygon with space for the given

Method
boolean **contains**(double x, double y) Checks whether the point with the given pixel coordinates is inside this Polygon.

Miscellaneous

This class extends the existing diva.util.java2d.Polygon2D.Double, because the contains() method was implemented incorrectly there.

API details

Constructors

Polygon()

The construction of a new Polygon without coordinates.

Polygon(double[] coords)

The construction of a new Polygon with the given vertices

in the format [x0, y0, x1, y1,...].

Argument

double[] **coords** [INPUT, MANDATORY]

Polygon(double x, double y)

The construction of a new Polygon with a single starting point.

Polygon(double x, double y)

Arguments

double **x** [INPUT, MANDATORY]

double **y** [INPUT, MANDATORY]

Polygon(int size)

The construction of a new Polygon with space for the given

number of vertices.

Argument

int **size** [INPUT, MANDATORY]

Method

boolean contains(double x, double y)

Checks whether the point with the given pixel coordinates is inside this Polygon.

Arguments

double **x** [INPUT, MANDATORY]

double **y** [INPUT, MANDATORY]

Return

boolean

Return true if the point with the given pixel coordinates is inside this Polygon; false otherwise.

2.265. PolygonHistogramExplorer

Full Name:	herschel.ia.gui.image.PolygonHistogramExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import PolygonHistogramExplorer

Description

An explorer for PolygonHistogramProducts.

An explorer for PolygonHistogramProducts.

API Summary

Constructors
PolygonHistogramExplorer() The construction of a new PolygonHistogramExplorer.
PolygonHistogramExplorer(Object object) The construction of a new PolygonHistogramExplorer associated with the given object.

Methods
String **getName()** Returns the name.
String **getDescription()** Returns the description.
boolean **canHandle(Class className)** Checks whether this PolygonHistogramExplorer can handle objects of the given class.
setObject(Object object) Sets the object.
PolygonHistogramProduct **getObject()** Returns the object.
Class **getVariableType()** Returns the expected variable type.
JScrollPane **getParameterTable()** Returns the parameter table.

API details

Constructors

PolygonHistogramExplorer()
The construction of a new PolygonHistogramExplorer. The construction of a new PolygonHistogramExplorer.

PolygonHistogramExplorer(Object object)
The construction of a new PolygonHistogramExplorer associated with the given object.

PolygonHistogramExplorer(Object object)

The construction of a new PolygonHistogramExplorer associated with the given object.

Argument

Object **object** [INPUT, MANDATORY]

Methods

String getName()

Returns the name.

Returns the name for this PolygonHistogramExplorer.

Return

String

Returns the name for this PolygonHistogramExplorer.

String getDescription()

Returns the description.

Returns the description for this PolygonHistogramExplorer.

Return

String

Returns the description for this PolygonHistogramExplorer.

boolean canHandle(Class className)

Checks whether this PolygonHistogramExplorer can handle objects of the given class.

Returns true if this PolygonHistogramExplorer can handle objects of the given class; false otherwise.

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true if this PolygonHistogramExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this PolygonHistogramExplorer to the given object.

Argument

Object **object** [INPUT, MANDATORY]

PolygonHistogramProduct getObject()

Returns the object.

PolygonHistogramProduct getObject()

Returns the object for this PolygonHistogramExplorer.

Return

PolygonHistogramProduct

Returns the object for this PolygonHistogramExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this PolygonHistogramExplorer.

Return

Class

Returns the expected variable type for this PolygonHistogramExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

Returns the parameter table for this EllipseHistogramExplorer.

Return

JScrollPane

Returns the parameter table for this EllipseHistogramExplorer.

2.266. PolygonHistogramPanel

Full Name:	herschel.ia.toolbox.image.gui.PolygonHistogramPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import PolygonHistogramPanel

Description

A panel for the PolygonHistogramTask.

A panel to serve as GUI for the PolygonHistogramTask.

API Summary

Constructor
`PolygonHistogramPanel()`
The construction of a new PolygonHistogramPanel.

Methods
`drawFigure()`
Drawing the rectangle on the associated image.
`updateFigure()`
Updates the associated polygon.
`trigger()`
Trigger the execution of the associated task.
`updateHistogram()`
Updates the associated histogram.

API details

Constructor

`PolygonHistogramPanel()`
The construction of a new PolygonHistogramPanel. The construction of a new PolygonHistogramPanel.

Methods

`drawFigure()`
Drawing the rectangle on the associated image. Draws the rectangle on the image associated with this RectangleHistogramPanel.

`updateFigure()`
Updates the associated polygon. Updates the polygon associated with this PolygonHistogramPanel.

trigger()
Trigger the execution of the associated task. Triggers the execution of the task associated with this PolygonHistogramPanel.

updateHistogram()
Updates the associated histogram. Updates the histogram associated with this PolygonHistogramPanel.

2.267. PolygonHistogramProduct

Full Name:	herschel.ia.dataset.image.PolygonHistogramProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import PolygonHistogramProduct

Description

A class to deal with the results of a polygon histogram.

API Summary

Constructor
PolygonHistogramProduct() The constructor of a new PolygonHistogramProduct.

Methods
setEdges(Double1d edgesPixels) Sets the edges for this PolygonHistogramProduct to the given
setEdges(Double1d edgesPixels, String1d edgesSky) Sets the edges for this PolygonHistogramProduct to the given list
CompositeDataset **getEdges**() Returns the edges for this PolygonHistogramProduct.
int **getNbOfEdges**() Returns the number of edges for this
TableDataset **getEdgesPixelCoordinates**() Returns the edges for this PolygonHistogramProduct in
Double2d **getEdgesPixelCoordinatesDouble2d**() Returns the pixel coordinates of the edges as Double2d.
TableDataset **getEdgesSkyCoordinates**() Returns the edges for this PolygonHistogramProduct in

API details

Constructor

PolygonHistogramProduct()
The constructor of a new PolygonHistogramProduct.

Methods

setEdges(Double1d edgesPixels)
Sets the edges for this PolygonHistogramProduct to the given pixel coordinates. **Argument**

setEdges(Double1d edgesPixels)

Double1d **edgesPixels** [INPUT, MANDATORY]

setEdges(Double1d edgesPixels, String1d edgesSky)

Sets the edges for this PolygonHistogramProduct to the given list

of pixel and sky coordinates.

Arguments

Double1d **edgesPixels** [INPUT, MANDATORY]

String1d **edgesSky** [INPUT, MANDATORY]

CompositeDataset getEdges()

Returns the edges for this PolygonHistogramProduct.

Return

CompositeDataset

Returns the edges for this PolygonHistogramProduct.

int getNbOfEdges()

Returns the number of edges for this

PolygonHistogramProduct.

Return

int

Returns the number of edges for this PolygonHistogramTask.

TableDataset getEdgesPixelCoordinates()

Returns the edges for this PolygonHistogramProduct in

pixel coordinates.

Return

TableDataset

Returns the edges for this PolygonHistogramProduct in pixel coordinates.

Double2d getEdgesPixelCoordinatesDouble2d()

Returns the pixel coordinates of the edges as Double2d.

Return

Double2d

Returns the pixel coordinates of the edges as a Double2d.

TableDataset getEdgesSkyCoordinates()

Returns the edges for this PolygonHistogramProduct in

sky coordinates.

`TableDataset getEdgesSkyCoordinates()`

Return

TableDataset

Returns the edges for this Polygon in sky coordinates.

2.268. PolygonHistogramTask

Full Name:	herschel.ia.toolbox.image.PolygonHistogramTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import PolygonHistogramTask

Description

A Task to make a histogram within a polygon.

A Task to make a histogram of a region of interest, which is bounded by a polygon.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **lowCut** [INPUT, OPTIONAL, default=No default value]
Double **highCut** [INPUT, OPTIONAL, default=No default value]
Integer **bins** [INPUT, MANDATORY, default=No default values]
PolygonHistogramProduct **histogram** [OUTPUT, MANDATORY, default=No default value]
Double1d **frequencies** [OUTPUT, MANDATORY, default=No default value]
Double1d **edgesPixel** [INPUT, OPTIONAL, default=No default value]
String1d **edgesSky** [INPUT, OPTIONAL, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double lowCut [INPUT, OPTIONAL, default=No default value]

The lower cut level.

Double highCut [INPUT, OPTIONAL, default=No default value]

The upper cut level.

Integer bins [INPUT, MANDATORY, default=No default values]

The number of bins.

PolygonHistogramProduct histogram [OUTPUT, MANDATORY, default=No default value]

The histogram.

Double1d frequencies [OUTPUT, MANDATORY, default=No default value]

The frequencies.

Double1d edgesPixel [INPUT, OPTIONAL, default=No default value]

The edges of the polygon in pixel coordinates.

String1d edgesSky [INPUT, OPTIONAL, default=No default value]

The edges of the polygon in sky coordinates.

2.269. Polynomial

Full Name:	herschel.ia.numeric.toolbox.basic.Polynomial
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Polynomial

Description

Calculates the y points of a polynomial for a given input array.

The input array is an integral or floating-point numeric array (e.g. Double5d) and the coefficients is a double array.

Example

Example 1: Apply Polynomial on a Int1d

```
print Polynomial(Double1d([1]))(Double1d.range(5)) # [1.0,1.0,1.0,1.0,1.0]
print Polynomial(Double1d([0,1]))(Double1d.range(5)) # [0.0,1.0,2.0,3.0,4.0]
print Polynomial(Double1d([0,0,1]))(Double1d.range(5)) # [0.0,1.0,4.0,9.0,16.0]
#or
print Double1d.range(5).apply(Polynomial(Double1d([1]))) #
[1.0,1.0,1.0,1.0,1.0]
print Double1d.range(5).apply(Polynomial(Double1d([0,1]))) #
[0.0,1.0,2.0,3.0,4.0]
print Double1d.range(5).apply(Polynomial(Double1d([0,0,1]))) #
[0.0,1.0,4.0,9.0,16.0]
```

API Summary

Jython Syntax

```
<y>=Polynomial(<coefficients>)(<x>)
```

Properties

an integral or floating-point numeric array **x** [INPUT, MANDATORY, default=no default value]

a double array **coefficients** [INPUT, MANDATORY, default=no default value]

array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

an integral or floating-point numeric array x [INPUT, MANDATORY, default=no default value]

The input array is an integral or floating-point numeric array.

a double array coefficients [INPUT, MANDATORY, default=no default value]

The number of element to shift

array y [OUTPUT, MANDATORY, default=no default value]
Returns an array.

2.270. poolDataReader

Full Name:	herschel.ia.toolbox.util.PoolDataReaderTask
Alias:	poolDataReader
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import PoolDataReaderTask
Category:	utility task

Description

Task for reading a product from a pool.

Data will be readed through a ProductStorage by default. If no storage is specified, a new one will be created (unless the parameter 'useStorage' is false). Only the product identifier is required (an urn or a tag).

Examples

Example 1: Read by urn

```
...
product = PoolDataReader(id='urn:poolid:producClass:N')
print product
...
```

Example 2: Read by tag

```
...
product = PoolDataReader(id='myTag',storage=myStorage)
print product
...
```

Example 3: Read two products using the same storage

```
...
ps = ProductStorage()
pool = PoolManager.getPool("mypoolname")
ps.register(pool)
product1 = PoolDataReader(id='myTag1',storage=ps)
print product1
product2 = PoolDataReader(id='myTag2',storage=ps)
print product2
...
```

Example 4: Read two products using the same default storage

```
...
pdrt = PoolDataReaderTask()
product1 = pdrt(id='myTag1')
print product1
ps = pdrt.storage
product2 = pdrt(id='myTag2',storage=ps)
print product2
...
```

API Summary

Jython Syntax

```
product=PoolDataReaderTask()(urn='urn:poolid')
```

Jython Syntax
`see examples`

Properties
`String id [INPUT, true, default=null]`
`ProductStorage storage [INOUT, false, default=new ProductStorage]`
`ProductPool pool [INPUT, false, default=null (deprecated) PAL default pool]`
`String poolid [INPUT, false, default=null]`
`Boolean useStorage [INPUT, false, default=true]`
`Product product [OUTPUT, true, default=null]`

API details

Properties

`String id [INPUT, true, default=null]`

Product identifier, either an urn or a tag. A Tag can be used when reading through storage only.

`ProductStorage storage [INOUT, false, default=new ProductStorage]`

If storage is specified, pool and poolid parameters are not allowed. If storage is specified and useStorage parameter is false, an exception will be raised. If no storage is specified, pool or poolid parameters will be used and a new storage will be created (unless useStorage is false) and will be available as an output parameter.

`ProductPool pool [INPUT, false, default=null (deprecated) PAL default pool]`

If storage is specified, the pool parameter is not allowed. If a pool is specified, the poolid parameter is not allowed. DEPRECATED: If no pool is specified, the default pool will be used. (see {@link herschel.ia.pal}) A product storage will be created (unless useStorage is false) and that storage will be available as an ouput parameter

`String poolid [INPUT, false, default=null]`

Pool identifier. {@link herschel.ia.pal.PoolManager} will be used to find the pool. If storage is specified, the poolid parameter is not allowed. If a poolid is specified, the pool parameter is not allowed. DEPRECATED: If no poolid is specified, the default pool will be used. (see {@link herschel.ia.pal}) A product storage will be created (unless useStorage is false) and that storage will be available as an ouput parameter.

`Boolean useStorage [INPUT, false, default=true]`

Enable/Disable storage usage. If this parameter is false and storage is specified, an exception will be raised. If this parameter is true and no storage is specified, a new {@link herschel.ia.pal.ProductStorage} will be created and will be available as an output parmeter.

`Product product [OUTPUT, true, default=null]`

The loaded product.

History

- 22-11-2007 JCS

- `2009-02-17 - JDS`: (default pool, SPR-6006)
- `2009-07-07 - JDS`: Using PoolManager.getPool("standard")

2.271. poolDataWriter

Full Name:	herschel.ia.toolbox.util.PoolDataWriterTask
Alias:	poolDataWriter
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import PoolDataWriterTask
Category:	utility task

Description

Task for writing a product into a pool.

Data will be saved through a ProductStorage by default. If no storage is specified, a new one will be created and available (unless the parameter 'useStorage' is false).

Examples

Example 1: write product

```
p = Product()
pdwt = PoolDataWriterTask()
urn = pdwt(product=p)
print urn
```

Example 2: write product with a tag and read it later

```
p = Product()
pdwt = PoolDataWriterTask()
urn = pdwt(product=p,tag='myTag')
print urn
...
pdrt = PoolDataReaderTask()
product = pdrt(id='myTag',pool=ProductPool)
print product
```

Example 3: write two products using the same storage

```
ps = ProductStorage()
pool = PoolManager.getPool("standard")
ps.register(pool)
pdwt = PoolDataWriterTask()
urn1 = pdrt(product=Product(),tag='myTag1',storage=ps)
print urn1
urn2 = pdrt(product=Product(),tag='myTag2',storage=ps)
print urn2
```

Example 4: write two products using the same default storage

```
pdwt = PoolDataWriterTask()
urn1 = pdwt(product=Product(),tag='myTag1')
print urn1
ps = pdwt.storage
urn2 = pdwt(product=Product(),tag='myTag2',storage=ps)
print urn2
```

API Summary

Jython Syntax

```
urn=PoolDataWriterTask()(product=Product())
```

Jython Syntax
`See examples.`

Properties
`Product product [INPUT, true, default=null]`
`String tag [INPUT, false, default=null]`
`ProductStorage storage [INOUT, false, default=new ProductStorage]`
`ProductPool pool [INPUT, false, default=PAL default pool]`
`String poolid [INPUT, false, default=null]`
`String urn [OUTPUT, MANDATORY, default=null]`
`Boolean useStorage [INPUT, false, default=true]`

API details

Properties

`Product product [INPUT, true, default=null]`

The product to be saved.

`String tag [INPUT, false, default=null]`

Product tag. A Tag can be used when saving through storage only.

`ProductStorage storage [INOUT, false, default=new ProductStorage]`

If storage is specified, pool and poolid parameters are not allowed. If storage is specified and useStorage parameter is false, an exception will be raised. If no storage is specified, pool or poolid parameters will be used and a new storage will be created (unless useStorage is false) and will be availabe as an output parameter.

`ProductPool pool [INPUT, false, default=PAL default pool]`

If storage is specified, the pool parameter is not allowed. If a pool is specified, the poolid parameter is not allowed. DEPRECATED: If no pool is specified, the default pool will be used. (see {@link herschel.ia.pal}) A product storage will be created (unless useStorage is false) and that storage will be availabe as an ouput parameter

`String poolid [INPUT, false, default=null]`

Pool identifier. {@link herschel.ia.pal.PoolManager} will be used to find the pool. If storage is specified, the poolid parameter is not allowed. If a poolid is specified, the pool parameter is not allowed. DEPRECATED: If no poolid is specified, the default pool will be used. (see {@link herschel.ia.pal}) A product storage will be created (unless useStorage is false) and that storage will be availabe as an ouput parameter.

`String urn [OUTPUT, MANDATORY, default=null]`

The urn of the product just written.

`Boolean useStorage [INPUT, false, default=true]`

Enable/Disable storage usage. If this parameter is false and storage is specified, an exception will be raised. If this parameter is true and no storage is specified, a new {@link herschel.ia.pal.ProductStorage} will be created and will be available as an output parmeter.

History

- 22-11-2007 JCS
- `2008-12-15 - JDS`: (added deprecation marks to jtags)
- `2009-02-17 - JDS`: (default pool, SPR-6006)
- `2009-07-07 - JDS`: Using PoolManager.getPool("standard")

2.272. PositionList

Full Name:	herschel.ia.dataset.image.PositionList
Type:	Java Class -
Import:	from herschel.ia.dataset.image import PositionList

Description

Position list.

A list of positions.

API Summary

Methods
`double getRa(int row)` Returns the RA at a given row.
`double getDec(int row)` Returns the Dec at a given row.
`int getSize()` Returns the number of positions.

API details

Methods

`double getRa(int row)`

Returns the RA at a given row.

Returns the RA for the position for this PositionList at the given row in the list.

Argument

`int row [INPUT, MANDATORY]`

Return

double

Returns the RA for the position for this PositionList at the given row in the list.

`double getDec(int row)`

Returns the Dec at a given row.

Returns the Dec for the position for this PositionList at the given row in the list.

Argument

`int row [INPUT, MANDATORY]`

Return

double

Returns the Dec for the position for this PositionList at the given row in the list.

`int getSize()`

Returns the number of positions.

Returns the number of positions for this PositionList.

Return

int

Returns the number of positions for this PositionList.

2.273. PowerSpectrum

Full Name:	herschel.ia.gui.explorer.table.PowerSpectrum
Type:	Java Class -
Import:	from herschel.ia.gui.explorer.table import PowerSpectrum

Description

PowerSpectrum Generator OverView

The PowerSpectrum generator is a GUI tool which allows users to generate PowerSpectrum inactively. The tool allows users to specify the time data and unit. By default, the tool will look for the time data in the table. If there are several time column data, the lowest column index will be used as a time data to calculate frequency.

API Summary

Constructor
`PowerSpectrum(TableDataset table)`

Methods
`setObject(TableDataset data)`
`JComponent getComponent()`

API details

Constructor

`PowerSpectrum(TableDataset table)`

Argument

`TableDataset` **`table`** `[INPUT, MANDATORY, default=no default value]`

The input table must contain one or more time column data.

Methods

`setObject(TableDataset data)`

Argument

`TableDataset` **`data`** `[INPUT, MANDATORY, default=no default value]`

The input table must contain at least one time column data.

`JComponent getComponent()`

Return

JComponent

- this GUI component

History

- `2007-12-02 - first`: version
- `2008-04-03 - Move`: the code to calculate PowerSpectrum to ia_numeric_toolbox_xform
- `2008-11-21 - Major`: GUI change to allow users to choose time data and its unit

2.274. PowerSpectrum

Full Name:	herschel.ia.toolbox.astro.PowerSpectrum
Type:	Java Class -
Import:	from herschel.ia.toolbox.astro import PowerSpectrum

Examples

Example 1: java example import herschel.ia.numeric.toolbox.xform. *;

```
TableDataset table; -//defined somewhere double flimit = 0.1; double
sigma = 0.4; boolean deglitch = true;
TableDataset pw_table = PowerSpectrum.getPowerSpectrum(flimit,
sigma, deglitch, table);
```

Example 2: jython example from herschel.ia.numeric.toolbox.xform import *

```
flimt = 0.1 sima = 0.4 deglitch= 1 pw_table =
PowerSpectrum.powerSpectrum(flimit, sigma, deglitch, table)
```

See also

- ???

History

- Feb 22, 2008 - first version

2.275. Pow

Full Name:	herschel.ia.numeric.toolbox.basic.Pow
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Pow

Description

Gives the array raised to the specified power: $y=(x)^{power}$

Example

Example 1: Apply Pow on a Int1d

```
x=Double1d([1,2,3,4])
print Pow(2)(x) # [1.0,4.0,9.0,16.0]
print x.apply(Pow(2)) # [1.0,4.0,9.0,16.0]
```

API Summary

Jython Syntax

```
<y>=Pow(<power>)(<x>)
```

Properties

any array or number **x** [INPUT, MANDATORY, default=no default value]
a number **power** [INPUT, MANDATORY, default=no default value]
a number or an array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array or number x [INPUT, MANDATORY, default=no default value]

An array or a number

a number power [INPUT, MANDATORY, default=no default value]

The power

a number or an array y [OUTPUT, MANDATORY, default=no default value]

The result is a number or an array depending on the input

See also

- Pow

2.276. PreviousInterpolator

Full Name:	herschel.ia.numeric.toolbox.interp.PreviousInterpolator
Alias:	PreviousInterpolator
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.interp import PreviousInterpolator

Description

Creates an linear interpolation function from a set of knots (x,y),

that can be applied to numeric arrays of rank 1.

Example

Example 1: Create and apply a PreviousInterpolator on a Double1d

```
# create some knots
x=Double1d.range(10) # [0.0,1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0]
f=PreviousInterpolator(x,SQUARE(x))
u=Double1d([1,1.1,2,2.6,3,3.9])
print f(u) # [1.0,1.0,4.0,4.0,9.0,9.0]
```

API Summary

Jython Syntax

```
<f>=PreviousInterpolator(<x>,<y>[,allowExtrapolation])
```

Properties

Double1d **x** [INPUT, MANDATORY, default=no default value]

Double1d **y** [INPUT, NOT_MANDATORY, default=false]

boolean **allowExtrapolation** [INPUT, NOT_MANDATORY, default=false]

API details

Properties

Double1d x [INPUT, MANDATORY, default=no default value]

The knots are Double1d

Double1d y [INPUT, NOT_MANDATORY, default=false]

The knots are Double1d

boolean allowExtrapolation [INPUT, NOT_MANDATORY, default=false]

Extrapolation is not allowed by default. Boolean.TRUE allows extrapolation.

See also

- CubicSplineInterpolator

- LinearInterpolator

2.277. ProcessDistributor

Full Name:	herschel.ia.dataflow.ProcessDistributor
Type:	Java Class -
Import:	from herschel.ia.dataflow import ProcessDistributor

Description

Decouples the chain of execution of processes, i.e, makes a event-based process to behave as thread-based one.

Helper class that allows one or more Event-based processes (or connectables in general) to be run in a different thread.

This is intented to be used as is.

As typical example, a dataflow containing three Event-based processes A, B, C, whose flow is:

```
A----B
|
---C
```

The user (or developer) sees that he needs better performance running B process in another thread, so a PD (product-distributor) process is added to the dataflow this way:

```
A----PD----B
|
---C
```

In case B and C must run in the same thread, the dataflow can be modified like this:

```
A----PD----B
|
---C
```

The ProcessProductDistributor has an input called "input" and a output called "output".

Example

Example 1: how to use a process distributor.

```
<pre>
from herschel.ia.dataflow import *
from myProcesses import *
df = DataFlow("mydf")
df.createProcess("avg", AverageProcess)
df.createProcess("viewer", ViewerProcess)
p = ProcessDistributor("distrib", Double1d)
df.addProcess(p)
df.connect("avg.output", -"distrib.input")
df.connect("distrib.output", -"viewer.input")
df.start()
</pre>
```

Limitations

no limitation

See also

- reference

History

- 26-5-2005 jcg: change javadoc format for help support.

2.278. PRODUCT

Full Name:	herschel.ia.numeric.toolbox.basic.Product
Alias:	PRODUCT
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Product

Description

Yields the product of all elements in the input array.

Returns a scalar of the same type as the type of the input array.

Example

Example 1: Apply PRODUCT on a Int2d

```
x=Int2d( [ [1,2], [-1,3] -])
print PRODUCT(x)    # --6
print PRODUCT(x, 0) # [-1, 6]
print PRODUCT(x, 1) # [ 2,-3]
```

API Summary

Jython Syntax

```
<y>=PRODUCT(<x>, [,<dim>])
```

Properties

any scalar array **x** [INPUT, MANDATORY, default=no default value]

integer **dim** [INPUT, MANDATORY, default=no default value]

float or double array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array can be any scalar array.

integer dim [INPUT, MANDATORY, default=no default value]

The dimension to compute the calculation along

float or double array y [OUTPUT, MANDATORY, default=no default value]

Returns a scalar of the same type as the type of the input array.

See also

- SUM

2.279. ProductRef

Full Name:	herschel.ia.pal.ProductRef
Type:	Java Class -
Import:	from herschel.ia.pal import ProductRef

Description

A ProductRef provides a reference to a product that is held in a

product storage or to a product in memory. Typically a ProductRef is returned by the load, save and select methods of a ProductStorage. A Product reference is providing a mechanism to inspect the meta data of a stored product without loading the complete product into memory.

Example

Example 1: Usage of a product reference p=Product(creator="me")

```
ref=storage.save(p)
print ref.type # herschel.ia.dataset.Product print ref.urn #
urn:simple.default:herschel.ia.dataset.Product:23674 print
ref.meta['creator'] # me print ref.product.creator # me (product
loaded into memory!)
```

API Summary

Methods
getProduct() Returns the Product class to which this Product reference is
getType() Returns the Product class to which this Product reference is

API details

Methods

getProduct()

Returns the Product class to which this Product reference is

pointing to.

getType()

Returns the Product class to which this Product reference is

pointing to.

See also

- ???

2.280. ProductStorage

Full Name:	herschel.ia.pal.ProductStorage
Type:	Java Class -
Import:	from herschel.ia.pal import ProductStorage

Description

The ProductStorage is a storage mechanism to provide read, write and

query on Products stored in registered Product Pools.

Examples

Example 1: creation and registering myStore=ProductStorage()

```
myStore.register(LocalStoreFactory.getStore("foo")) # the foo
lstore pool
```

Example 2: loading a Product from this store

```
ref=myStore.load("urn:foo:herschel.ia.dataset.Product:123" -)
```

Example 3: Untitled

```
saving a Product product=Product(...) ref=myStorage.save(product)
```

Example 4: select Products based on a query query=AttribQuery(....)

```
results=myStorage.select(query)
```

API Summary

Constructors

ProductStorage()
Creates an empty ProductStorage with no pools registered.
ProductStorage(ProductPool pool)
Creates a ProductStorage with the given pool registered, which
ProductStorage(ProductPool[] pools)
Creates a ProductStorage with the given pools registered.
ProductStorage(String poolName)
Creates a ProductStorage with the the pools corresponding to the
ProductStorage(String[] poolNames)
Creates a ProductStorage with the the pools corresponding to the

Methods

setSharedMode(boolean sharedMode)

Methods
Sets whether the last version info is to be updated before each
`register(ProductPool pool)`
Registers a ProductPool to the ProductStorage. The first
`register(ProductStorage[] stores)`
Chain storage registrations, register storages in storages. The
`register(ProductStorage. The product pools that store)`
Chain storage registrations, register pools in another storage.
`register(ProductPool array pools)`
Registers ProductPools to the ProductStorage. The first
`getPools()`
Provides the set of ProductPools registered, in order in which
`getWritablePool()`
Returns the writable pool, which is the first registered pool.
`Set getProductClasses()`
Provides all Product class definitions found in this pool.
`remove(String urn)`
Removes a product of given URN from the storage.
`ProductRef load(String id)`
Loads a Product from this store.
`ProductRef save(Product product)`
Saves a Product to this store. If the product is a context that
`ProductRef saveHeadOnly(Product product)`
Saves a Product to this store. If the product is a context that
`Set select(StorageQuery query)`
Returns a set of references to products that match the specified
`Set select(StorageQuery query, Set previous)`
Returns a set of references to products that match the specified

API details

Constructors

`ProductStorage()`
Creates an empty ProductStorage with no pools registered.

`ProductStorage(ProductPool pool)`
Creates a ProductStorage with the given pool registered, which happens to be the writable one. **Argument** `ProductPool pool [INPUT, MANDATORY]` **Example** Creating a storage initialized with a pool.

ProductStorage(ProductPool pool)

```
storage = ProductStorage(pool) # pool is the writable one
```

ProductStorage(ProductPool[] pools)

Creates a ProductStorage with the given pools registered.

The first provided pool is the writable one.

Argument

`ProductPool[] pools [INPUT, MANDATORY]`

Example

Creating a storage initialized with pools.

```
pool1 = PoolManager.getPool("pool1")
pool2 = PoolManager.getPool("pool2")
pool3 = PoolManager.getPool("pool3")
storage = ProductStorage([pool1, pool2, pool3]) # pool1 is the
writable one
```

ProductStorage(String poolName)

Creates a ProductStorage with the the pools corresponding to the

given name. This pool is the writable one.

Argument

`String poolName [INPUT, MANDATORY]`

Example

Creating a storage initialized with pools. # the following line

```
storage = ProductStorage("pool") # is equivalent to
pool = PoolManager.getPool("pool")
storage = ProductStorage(pool)
```

ProductStorage(String[] poolNames)

Creates a ProductStorage with the the pools corresponding to the

given names registered. The first provided pool is the writable one.

Argument

`String[] poolNames [INPUT, MANDATORY]`

Example

Creating a storage initialized with pools. # the following line

```
storage = ProductStorage(["pool1", -"pool2", -"pool3"]) # is
equivalent to
pool1 = PoolManager.getPool("pool1")
pool2 = PoolManager.getPool("pool2")
pool3 = PoolManager.getPool("pool3")
storage = ProductStorage([pool1, pool2, pool3])
```

Methods

setSharedMode(boolean sharedMode)

Sets whether the last version info is to be updated before each

setSharedMode(boolean sharedMode)

operation on the storage. Set it to `true` if you expect any other ProductStorage may update the products from the outside.

This can be set also in the initialization of the application, by the property `hcss.ia.pal.sharedMode`.

Argument

`boolean` **`sharedMode`** `[INPUT, MANDATORY, default=Whether the storage is]`

accessed for writing by several processes at the same time.

register(ProductPool pool)

Registers a ProductPool to the ProductStorage. The first

ProductPool will be the one for which save operations would write products to. The remaining pools registered will be read-only.

Argument

`ProductPool` **`pool`** `[INPUT, MANDATORY, default=The product pool that]`

will be added to this product storage.

Example

How to register a product pool

```
storage.register(pool)
```

register(ProductStorage[] stores)

Chain storage registrations, register storages in storages. The

first ProductPool that registered will be the one for which save operations would write products to. The remaining pools registered will be read-only.

Argument

`ProductStorage[]` **`stores`** `[INPUT, MANDATORY]`

Example

How to register a product storage

```
storage.register(store)
```

register(ProductStorage. The product pools that store)

Chain storage registrations, register pools in another storage.

The first ProductPool that registered will be the one for which save operations would write products to. The remaining pools registered will be read-only.

Argument

`ProductStorage. The product pools that` **`store`** `[INPUT, MANDATORY, default=no default value]`

registered in that storage will be added to this product storage.

Example

How to register a product storage

register(ProductStorage. The product pools that store)

```
storage.register(store)
```

register(ProductPool array pools)

Registers ProductPools to the ProductStorage. The first

ProductPool will be the one for which save operations would write products to. The remaining pools registered will be read-only.

Argument

`ProductPool array` **`pools`** `[INPUT, MANDATORY, default=The product pools]`

that will be added to this product storage.

Example

How to register many pools at the same time

```
storage.register([pool1, pool2, pool3])
```

getPools()

Provides the set of ProductPools registered, in order in which

they were initially registered.

getWritablePool()

Returns the writable pool, which is the first registered pool.

Set getProductClasses()

Provides all Product class definitions found in this pool.

Return

Set

a collection of Product classes

remove(String urn)

Removes a product of given URN from the storage.

Argument

`String` **`urn`** `[INPUT, MANDATORY, default=The URN to the Product that]`

should be removed.

ProductRef load(String id)

Loads a Product from this store.

Argument

`String` **`id`** `[INPUT, MANDATORY, default=The URN or tag to the Product]`

Return

ProductRef

A reference to the Product corresponding to the input URN or tag.

ProductRef save(Product product)

Saves a Product to this store. If the product is a context that

has descendents, all those descendents will be copied if they do not already exist in the destination storage (this is a deep-copy or cloning operation).

Argument

`Product` **`product`** `[INPUT, MANDATORY, default=The product that should be]`

saved.

Return

ProductRef

A reference to the Product saved into the store.

ProductRef saveHeadOnly(Product product)

Saves a Product to this store. If the product is a context that

has descendents, all those descendents will be copied if they do not already exist in the destination storage (this is a deep-copy or cloning operation).

Argument

`Product` **`product`** `[INPUT, MANDATORY, default=The product that should be]`

saved.

Return

ProductRef

A reference to the Product saved into the store.

Set select(StorageQuery query)

Returns a set of references to products that match the specified

query.

Argument

`StorageQuery` **`query`** `[INPUT, MANDATORY, default=The query applied to]`

this store.

Return

Set

A set of references to Products selected by the query

Set select(StorageQuery query, Set previous)

Returns a set of references to products that match the specified

query.

Arguments

`StorageQuery` **`query`** `[INPUT, MANDATORY, default=The query applied to]`

Set select(StorageQuery query, Set previous)

this store.

Set **previous** [INPUT, MANDATORY]

Return

Set

A set of references to Products selected by the query

See also

- ???

2.281. ProfileExplorer

Full Name:	herschel.ia.gui.image.ProfileExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import ProfileExplorer

Description

An explorer for Profiles.

An explorer for Profiles.

API Summary

Constructors
ProfileExplorer()
The construction of a new ProfileExplorer.
ProfileExplorer(Object object)
The construction of a new ProfileExplorer associated with the given object

Methods
String **getName**()
Returns the name.
String **getDescription**()
Returns the description.
boolean **canHandle**(Class className)
Checks whether this ProfileExplorer can handle objects of the given class.
setObject(Object object)
Setting the object.
Profile **getObject**()
Returns the object.
Class **getVariableType**()
Returns the expected variable type.
JComponent **getComponent**()
Returns the component that is responsible for displaying the data object.
JPanel **getCoordinatePanel**()
Returns the coordinate table.
JPanel **getProfilePlotPanel**()
Returns the profile plot component.
addDataObjectListener(DataObjectListener listener)
Adds the given listener.
removeDataObjectListener(DataObjectListener listener)
Removes the given listener.

API details

Constructors

ProfileExplorer()

The construction of a new ProfileExplorer.

The construction of a new ProfileExplorer.

ProfileExplorer(Object object)

The construction of a new ProfileExplorer associated with the given object

The construction of a new ProfileExplorer associated with the given object.

Argument

`Object` **object** `[INPUT, MANDATORY]`

Methods

String getName()

Returns the name.

Returns the name for this ProfileExplorer.

Return

String

Returns the name for this ProfileExplorer.

String getDescription()

Returns the description.

Returns the description for this ProfileExplorer.

Return

String

Returns the description for this ProfileExplorer.

boolean canHandle(Class className)

Checks whether this ProfileExplorer can handle objects of the given class.

Returns true if this ProfileExplorer can handle object of the given class; false otherwise.

Argument

`Class` **className** `[INPUT, MANDATORY]`

Return

boolean

Returns true of this ProfileExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Setting the object.

Sets the object for this ProfileExplorer to the given object.

Argument

`Object` **object** `[INPUT, MANDATORY]`

Profile getObject()

Returns the object.

Returns the object for this ProfileExplorer.

Return

Profile

Returns the object for this ProfileExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this ProfileExplorer.

Return

Class

Returns the expected variable type for this ProfileExplorer.

JComponent getComponent()

Returns the component that is responsible for displaying the data object.

Returns the component that is responsible for displaying the data object for this ProfileExplorer.

Return

JComponent

Returns the component that is responsible for displaying the data object for this ProfileExplorer.

JPanel getCoordinatePanel()

Returns the coordinate table.

Constructs and returns the coordinate table for this ProfileExplorer.

Return

JPanel

Returns the coordinate table for this ProfileExplorer.

JPanel getProfilePlotPanel()

Returns the profile plot component.

Returns the profile plot component for this ProfileExplorer.

JPanel getProfilePlotPanel()

Return

JPanel

Returns the profile plot component for this ProfileExplorer.

addDataObjectListener(DataObjectListener listener)

Adds the given listener.

Add the given listener to this ProfileExplorer to receive data object events from it.

Argument

DataObjectListener **listener** [INPUT, MANDATORY]

removeDataObjectListener(DataObjectListener listener)

Removes the given listener.

Removes the given listener for this ProfileExplorer, so that it no longer receives data object events by this explorer.

Argument

DataObjectListener **listener** [INPUT, MANDATORY]

2.282. Profile

Full Name:	herschel.ia.dataset.image.Profile
Type:	Java Class -
Import:	from herschel.ia.dataset.image import Profile

Description

A class to deal with the results of profile plotting.

API Summary

Constructor
`Profile()` The constructor of a new Profile.

Methods
`setBegin(double beginX, double beginY)` Sets the begin to the given pixel coordinates.
`setBegin(double beginX, double beginY, String beginRA, String beginDec)` Sets the begin to the given pixel and sky
`setEnd(double endX, double endY)` Sets the end to the given pixel coordinates.
`setEnd(double endX, double endY, String endRA, String endDec)` Sets the end to the given pixel and sky coordinates.
`setProfile(Double1d profile)` Sets the profile for this Profile to the given
`setUnit(Unit unit)` Sets the unit for this Profile.
`Double1d` **`getBeginPixelCoordinates()`** Returns the begin for this Profile in pixel coordinates.
`String1d` **`getBeginSkyCoordinates()`** Returns the begin for this Profile in sky coordinates.
`Double1d` **`getEndPixelCoordinates()`** Returns the end for this Profile in pixel coordinates.
`String1d` **`getEndSkyCoordinates()`** Returns the end for this Profile in sky coordinates.
`Double1d` **`getProfile()`** Returns the profile for this Profile.
`String` **`getUnit()`** Returns the unit for this Profile.

API details

Constructor

Profile()

The constructor of a new Profile.

Methods

setBegin(double beginX, double beginY)

Sets the begin to the given pixel coordinates.

Arguments

double **beginX** [INPUT, MANDATORY]

double **beginY** [INPUT, MANDATORY]

setBegin(double beginX, double beginY, String beginRA, String beginDec)

Sets the begin to the given pixel and sky

coordinates.

Arguments

double **beginX** [INPUT, MANDATORY]

double **beginY** [INPUT, MANDATORY]

String **beginRA** [INPUT, MANDATORY]

String **beginDec** [INPUT, MANDATORY]

setEnd(double endX, double endY)

Sets the end to the given pixel coordinates.

Arguments

double **endX** [INPUT, MANDATORY]

double **endY** [INPUT, MANDATORY]

setEnd(double endX, double endY, String endRA, String endDec)

Sets the end to the given pixel and sky coordinates.

Arguments

double **endX** [INPUT, MANDATORY]

double **endY** [INPUT, MANDATORY]

String **endRA** [INPUT, MANDATORY]

String **endDec** [INPUT, MANDATORY]

setProfile(Double1d profile)

Sets the profile for this Profile to the given

profile.

Argument

Double1d **profile** [INPUT, MANDATORY]

setUnit(Unit unit)

Sets the unit for this Profile.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

Double1d getBeginPixelCoordinates()

Returns the begin for this Profile in pixel coordinates.

Return

Double1d

Returns the begin for this Profile in pixel coordinates.

String1d getBeginSkyCoordinates()

Returns the begin for this Profile in sky coordinates.

Return

String1d

Returns the begin for this Profile in sky coordinates.

Double1d getEndPixelCoordinates()

Returns the end for this Profile in pixel coordinates.

Return

Double1d

Returns the end for this Profile in pixel coordinates.

String1d getEndSkyCoordinates()

Returns the end for this Profile in sky coordinates.

Return

String1d

Returns the end for this Profile in sky coordinates.

Double1d getProfile()

Returns the profile for this Profile.

Return

Double1d

Returns the profile for this Profile.

String getUnit()

Returns the unit for this Profile.

Return

String

Returns the unit for this Profile.

2.283. ProfilePanel

Full Name:	herschel.ia.toolbox.image.gui.ProfilePanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ProfilePanel

Description

A panel for the ProfileTask.

A panel to serve as GUI for the ProfileTask.

API Summary

Constructor
ProfilePanel() The construction of a new ProfilePanel.

Methods
JPanel **getImagePanel()** Returns a panel that displays the image.
JPanel **getButtonPanel()** Returns the button panel.
setSiteEventHandler(SiteEventHandler handler) Setting the site event handler
setTask(TaskApi task) Associating the task.
setVariableSelection(VariableSelection selection) Setting the variable selection.
Display **getDisplay()** Returns the display.
Image **getImage()** Returns the associated image.
ImageFigure **getLine()** Returns the straight line.
Double **getBegin()** Returns the begin of the straight line in pixel coordinates.
Double **getEnd()** Returns the end of the straight line in pixel coordinates.
TaskApi **getTask()** Returns the associated task.
Map **getMap()** Returns the associated map.
SiteEventHandler **getHandler()**

Methods
Returns the associated site event handler.
`PlotXY getPlot()` Returns the associated plot.
`int getNbOfClicks()` Returns the number of clicks made on the image.
`boolean isInImage(MouseEvent me)` Checks whether the given mouse event occurred inside the image.
`boolean isInImage(double pixX, double pixY)` Checks whether the given pixel coordinates lie inside the image.

API details

Constructor

`ProfilePanel()`
The construction of a new ProfilePanel. The construction of a new ProfilePanel.

Methods

`JPanel getImagePanel()`
Returns a panel that displays the image. Returns a panel that displays the image for this ProfilePanel. **Return** **JPanel** Returns a panel that displays the image for this ProfilePanel.

`JPanel getButtonPanel()`
Returns the button panel. Returns the button panel for this ProfilePanel. **Return** **JPanel** Returns the button panel for this ProfilePanel.

`setSiteEventHandler(SiteEventHandler handler)`
Setting the site event handler Sets the site event handler for this ProfilePanel to the given site event handler. **Argument** `SiteEventHandler handler [INPUT, MANDATORY]`

setTask(TaskApi task)

Associating the task.

Associates the given task with this ProfilePanel.

Argument

`TaskApi` **`task`** `[INPUT, MANDATORY]`

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the variable selection for this ProfilePanel to the given variable selection.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

Display getDisplay()

Returns the display.

Returns the display for this ProfilePanel.

Return

Display

Returns the display for this ProfilePanel.

Image getImage()

Returns the associated image.

Returns the image associated with this ProfilePanel.

Return

Image

Returns the image associated with this ProfilePanel.

ImageFigure getLine()

Returns the straight line.

Returns the straight line for this ProfilePanel.

Return

ImageFigure

Reurns the straight line for this ProfilePanel.

Double getBegin()

Returns the begin of the straight line in pixel coordinates.

Returns the begin of the straight line associated with this ProfilePanel in pixel coordinates.

Return

Double

Double getBegin()

Returns the begin of the straight line associated with this ProfilePanel in pixel coordinates.

Double getEnd()

Returns the end of the straight line in pixel coordinates.

Returns the end of the straight line associated with this ProfilePanel in pixel coordinates.

Return

Double

Returns the end of the straight line associated with this ProfilePanel in pixel coordinates.

TaskApi getTask()

Returns the associated task.

Returns the task associated with this ProfilePanel.

Return

TaskApi

Returns the task associated with this ProfilePanel.

Map getMap()

Returns the associated map.

Returns the map associated with this ProfilePanel.

Return

Map

Returns the map associated with this ProfilePanel.

SiteEventHandler getHandler()

Returns the associated site event handler.

Returns the site event handler associated with this ProfilePanel.

Return

SiteEventHandler

Returns the site event handler associated with this ProfilePanel.

PlotXY getPlot()

Returns the associated plot.

Returns the plot associated with this ProfilePanel.

Return

PlotXY

Returns the plot associated with this ProfilePanel.

int getNbOfClicks()

Returns the number of clicks made on the image.

Returns the number of clicks made on the image for this ProfilePanel.

Return

int

Returns the number of clicks made on the image for this ProfilePanel.

boolean isInImage(MouseEvent me)

Checks whether the given mouse event occurred inside the image.

Returns true of the given mouse event occurred inside the image for this ProfilePanel; false otherwise.

Argument

`MouseEvent` **me** [INPUT, MANDATORY]

Return

boolean

Returns true if the given mouse event occurred inside the image for this ProfilePanel; false otherwise.

boolean isInImage(double pixX, double pixY)

Checks whether the given pixel coordinates lie inside the image.

Returns true if the given pixel coordinates lie inside the image for this ProfilePanel; false otherwise.

Arguments

double **pixX** [INPUT, MANDATORY]

double **pixY** [INPUT, MANDATORY]

Return

boolean

Returns true if the given pixel coordinates lie inside the image for this ProfilePanel; false otherwise.

2.284. ProfilePlotting

Full Name:	herschel.ia.toolbox.image.gui.ProfilePlotting
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ProfilePlotting

Description

An implementation of profile plotting. In a separate window, you can plot the

intensity along a straight line over an image. There is also shown from which sky coordinate to which sky coordinate (if available) and from which pixel coordinate to which pixel coordinate, this straight line is drawn.

API Summary

Constructors
ProfilePlotting(ImageAnalysisToolbox toolbox) The standard constructor for ProfilePlotting. A new window, associated
ProfilePlotting(boolean useAsComponent, ImageAnalysisToolbox toolbox) Constructor for ProfilePlotting. When the new ProfilePlotting is

Methods
setBegin(Double begin) Sets the begin of the straight line associated with this
setEnd(Double end) Sets the end of the straight line, associated with this
PlotXY **getPlot**() Returns the PlotXY shown in this ProfilePlotting.
ImageFigure **getLine**() Returns the straight line along which we wish to plot
Double **getBegin**() Returns the begin of the drawn line in pixel coordinates.
Double **getEnd**() Returns the end of the drawn line in pixel coordinates.
int **getClicks**() Returns the number of valid clicks (i.e. in the image) you made.
String **getSkyCoordinates**() Returns the String version of the sky coordinates
String **getPixelCoordinates**() Returns the String version of the pixel coordinates of the begin.
boolean **isInImage**(double pixX, double pixY) Checks whether the given pixel coordinates lies
Double1d **getPlotPoints**()

Methods
Returns the intensity of the pixels along the straight line,
`ArrayList` **`getImageFigures()`** Returns all ImageFigures used for this ProfilePlotting (the

API details

Constructors

`ProfilePlotting(ImageAnalysisToolbox toolbox)`

The standard constructor for ProfilePlotting. A new window, associated

with the given ImageAnalysisToolbox is opened. It is on the image, analyzed with the given ImageAnalysisToolbox, we wish to draw a straight line, and plot the intensity along that straight line in the new ProfilePlotting window.

Argument

`ImageAnalysisToolbox` **`toolbox`** `[INPUT, MANDATORY]`

`ProfilePlotting(boolean useAsComponent, ImageAnalysisToolbox toolbox)`

Constructor for ProfilePlotting. When the new ProfilePlotting is

component-based, a window for plotting the intensity is opened; otherwise nothing will be shown.

Arguments

`boolean` **`useAsComponent`** `[INPUT, MANDATORY]`

`ImageAnalysisToolbox` **`toolbox`** `[INPUT, MANDATORY]`

Methods

`setBegin(Double begin)`

Sets the begin of the straight line associated with this

ProfilePlotting to the given point (in mouse coordinates).

Argument

`Double` **`begin`** `[INPUT, MANDATORY]`

`setEnd(Double end)`

Sets the end of the straight line, associated with this

ProfilePlotting to the given point (in mouse coordinates).

Argument

`Double` **`end`** `[INPUT, MANDATORY]`

`PlotXY getPlot()`

Returns the PlotXY shown in this ProfilePlotting.

Return

PlotXY

PlotXY getPlot()

Returns the PlotXY shown in this ProfilePlotting.

ImageFigure getLine()

Returns the straight line along which we wish to plot

the intensity in this ProfilePlotting.

Return

ImageFigure

The straight line along which we wish to plot the intensity in this ProfilePlotting.

Double getBegin()

Returns the begin of the drawn line in pixel coordinates.

Return

Double

Returns the begin of the drawn line in pixel coordinates.

Double getEnd()

Returns the end of the drawn line in pixel coordinates.

Return

Double

Returns the end of the drawn line in pixel coordinates.

int getClicks()

Returns the number of valid clicks (i.e. in the image) you made.

Return

int

Returns the number of valid clicks (i.e. in the image) you made.

String getSkyCoordinates()

Returns the String version of the sky coordinates

of the begin and end of the drawn straight line.

Return

String

Returns the String version of the sky coordinates of the begin and end of the drawn straight line.

String getPixelCoordinates()

Returns the String version of the pixel coordinates of the begin.

Return

String

String getPixelCoordinates()

Returns the String version of the pixel coordinates of the begin and end of the drawn line.

boolean isInImage(double pixX, double pixY)

Checks whether the given pixel coordinates lies

inside the image for this ProfilePlotting.

Arguments

`double` **pixX** `[INPUT, MANDATORY]`

`double` **pixY** `[INPUT, MANDATORY]`

Return

boolean

Returns true if the given pixel coordinates lie inside the image for this ProfilePlotting; false otherwise.

Double1d getPlotPoints()

Returns the intensity of the pixels along the straight line,

associated with this ProfilePlotting.

Return

Double1d

Returns the intensity of the pixels along the drawn straight line associated with this ProfilePlotting.

ArrayList getImageFigures()

Returns all ImageFigures used for this ProfilePlotting (the

straight line on the image).

Return

ArrayList

Returns all ImageFigures used for this ProfilePlotting (the straight line on the image).

2.285. ProfileTask

Full Name:	herschel.ia.toolbox.image.ProfileTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ProfileTask

Description

A Task to make intensity plots along a straight line.

A Task which determines the intensity of the pixels along a straight line on an image.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **beginX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **beginY** [INPUT, OPTIONAL, default=Default value : NaN]
Double **endX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **endY** [INPUT, OPTIONAL, default=Default value : NaN]
String **beginRA** [INPUT, OPTIONAL, default=Default value : "beginRA"]
String **beginDec** [INPUT, OPTIONAL, default=Default value : "beginDec"]
String **endRA** [INPUT, OPTIONAL, default=Default value : "endRA"]
String **endDec** [INPUT, OPTIONAL, default=Default value : "endDec"]
Profile **profile** [OUTPUT, MANDATORY, default=Default value : Profile()]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double beginX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the begin of the straight line.

Double beginY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the begin of the straight line.

Double endX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the end of the straight line.

Double endY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the end of the straight line.

String beginRA [INPUT, OPTIONAL, default=Default value : "beginRA"]

The right ascension of the begin of the straight line.

String beginDec [INPUT, OPTIONAL, default=Default value : "beginDec"]

The declination of the begin of the straight line.

String endRA [INPUT, OPTIONAL, default=Default value : "endRA"]

The right ascension of the end of the straight line.

String endDec [INPUT, OPTIONAL, default=Default value : "endDec"]

The declination of the end of the straight line.

Profile profile [OUTPUT, MANDATORY, default=Default value : Profile()]

The profile.

2.286. QRDecomposition

Full Name:	herschel.ia.numeric.toolbox.matrix.QRDecomposition
Alias:	QRDecomposition
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import QRDecomposition

Example

Example 1: A = Double2d([[2.0, 1.0, 1.0],[4.0, -6.0, 0.0],[-2.0, 7.0, 2.0]])

```
B=Double2d( [ [3.0],[-8.0],[10.0] -] -)
res=B.apply(QRDecomposition(A))
print res
[
[0.9999999999999971],
[1.9999999999999978],
[-0.9999999999999969]
]
QRD = QRDecomposition(A)
leastSquaresSolutionAXeqB = B.apply(QRD)
print leastSquaresSolutionAXeqB
[
[0.9999999999999971],
[1.9999999999999978],
[-0.9999999999999969]
]
isFullRank = QRD.isFullRank
print isFullRank
1
HouseholderVectors = QRD.h
print HouseholderVectors
[
[1.4082482904638631,0.0,0.0],
[0.8164965809277261,1.4099776105529318,0.0],
[-0.4082482904638631,-0.9120955864630134,2.0]
]
rightTriangularFactor = QRD.r
print rightTriangularFactor
[
[-4.898979485566356,7.3484692283495345,0.408248290463863],
[0.0,5.656854249492381,2.1213203435596424],
[0.0,0.0,-0.5773502691896262]
]
orthFactor = QRD.qs
print orthFactor
[
[-0.40824829046386313,0.7071067811865475,0.5773502691896257],
[-0.8164965809277261,5.551115123125783E-17,-0.5773502691896256],
[0.4082482904638631,0.7071067811865475,-0.577350269189626]
```

API Summary

Jython Syntax

```
A=Double2d()
B=Double2d()
res=B.apply(QRDecomposition(A))
QRD = QRDecomposition(A)
leastSquaresSolutionAXeqB = B.apply(QRD)
```

Jython Syntax
`isFullRank = QRD.isFullRank`
`HouseholderVectors = QRD.h`
`rightTriangularFactor = QRD.r`
`orthFactor = QRD.qs`

Property
`Double2d A [INPUT, MANDATORY, default=no default value]`

API details

Property

Double2d A [INPUT, MANDATORY, default=no default value]
Input must be a Double2d or Float2d array.

2.287. Query

Full Name:	herschel.ia.pal.query.Query
Type:	Java Class -
Import:	from herschel.ia.pal.query import Query

Example

Example 1: Example of an query: q=Query("type=='AbcProduct' and

```
creator=='Scott'")
q=Query("foo.Product","type=='AbcProduct' and creator=='Scott'")
```

2.288. RadialVelocityTask

Full Name:	herschel.ia.toolbox.astro.RadialVelocityTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.astro import RadialVelocityTask
Category:	toolbox

Description

The RadialVelocity Task.

Calculates S/C radial velocity projection in the direction of the pointing, optionally including Sun to LSR and Earth to Sun velocities to help in Doppler correction of observed frequencies.

Pointing and Orbit products should be contained in an observation context processed by the SPG. The corrections applied from the data obtained from products can include:

- RadialVelocityTask.Correction.NONE
- RadialVelocityTask.Correction.SUNTOLSR
- RadialVelocityTask.Correction.EARTHTOSUN (approx or fine (using Ephemeris))
- RadialVelocityTask.Correction.SUNANDEARTH (default)

The sign of the radial velocity is positive towards the target and negative otherwise.

Examples

Example 1: Providing an Ephemeris instance

```
from herschel.share.fltdyn.time import FineTime
from herschel.share.fltdyn.ephem import Ephemerides
orbitFile="/home/jadiaz/workspace/ia_toolbox_astro/H20090608_0001.LOE" #long
term, 2month span
ephemFile="/home/jadiaz/workspace/ia_toolbox_astro/ascp2007-2020.405" #de405,
weekly, 2month span
ephem=Ephemerides(orbitFile, ephemFile) #should be singleton, it is better to
specify a time interval
t = FineTime(pointing.startTime)
orbit = observation.getAuxiliary().getOrbitEphemeris()
pointing = observation.getPointing().getPointing()
v =
radialVelocity(pointing=pointing,orbit=orbit,time=t,ephemerides=ephem,corrections=RadialVelocit
```

Example 2: Without an Ephemeris instance, all corrections, getting value and direction

```
from herschel.share.fltdyn.time import FineTime
t = FineTime(pointing.startTime)
v = radialVelocity(pointing=pointing,orbit=orbit,time=t)
ra = radialVelocity.ra
dec = radialVelocity.dec
```

Example 3: Comparing uncorrected with corrected data

```
steps = 100
start = pointing.startTime
span= pointing.endTime -- start
step= span -/ steps;
```

Example 3: Comparing uncorrected with corrected data

```
vos=Double1d() #uncorrected
ves=Double1d() #corrected
ts=Double1d() #time
for OD in range(steps + 1):
    t = FineTime(start)
    ts.append(start)
    v = radialVelocity(pointing=pointing,orbit=orbit,time=t)
    vos.append(v)
    v =
radialVelocity(pointing=pointing,orbit=orbit,time=t,ephemerides=ephem,corrections=RadialVelocit
    ves.append(v)
    start = start + step
myPlot=PlotXY(ts, vos)
myPlot=PlotXY(ts,ves)
```

Example 4: Full example using the vectorized Java static function, checking for NaNs, Java code

```
FineTime[] finetimes = new FineTime[timestamps.length];
ObservationContext oc = -...; -//this comes from a processed observation
oep = ((AuxiliaryContext)observation.getAuxiliary()).getOrbitEphemeris();
pp = ((AuxiliaryContext)observation.getPointing()).getPointing();
for (int i = 0; i < timestamps.length; i++) {
    finetimes[i] = new FineTime(timestamps[i]);
}
try {
    double[] vscVals = RadialVelocityTask.getProjections(oep, pp, finetimes,
            RadialVelocityTask.SUNTOLSR + RadialVelocityTask.EARTHTOSUN, null);
    for (int i = 0; i < timestamps.length; i++) {
        if (Double.isNaN(vscVals[i])) {
            -//could not get the radial velocity for finetimes[i]
         -} else {
            -//valid data
         -}
    -}
} catch (RuntimeException e) {
    _log.log(Level.WARNING,"Radial velocity computation failed. Please check
the OrbitEphemerisProduct!", e);
}
```

API Summary

Jython Syntax
`v = radialVelocity((<storage> | <context> | <pointing>, <orbit>), <time> [, <ephemerides>, <corrections>])`
`ra = radialVelocity.ra`
`dec = radialVelocity.dec`
`You must use either storage or context or pointing and orbit as the S/C data source.`
`Corrections: RadialVelocityTask.Correction.NONE, RadialVelocityTask.Correction.SUNTOLSR,`
`RadialVelocityTask.Correction.EARTHTOSUN, RadialVelocityTask.Correction.SUNANDEARTH (default)`

Properties
`AuxiliaryContext` **`storage`** `[INPUT, OPTIONAL, default=null]`
`AuxiliaryContext` **`context`** `[INPUT, OPTIONAL, default=null]`
`ProductStorage` **`pointing`** `[INPUT, OPTIONAL, default=null]`

Properties
OrbitEphemerisProduct **orbit** [INPUT, OPTIONAL, default=null]
FineTime **time** [INPUT, MANDATORY, default=null]
Ephemerides **ephemerides** [INPUT, OPTIONAL, default=null]
RadialvelocityTask.CorrectionType **corrections** [INPUT, MANDATORY, default=SUNANDEARTH]
Double **velocity** [OUTPUT, MANDATORY, default=null]
Double **ra** [OUTPUT, OPTIONAL, default=null]
Double **dec** [OUTPUT, OPTIONAL, default=null]

Limitations

If you do not provide an Ephemerides EARTHTOSUN correction will be approximate. The error without an Ephemerides object is up to +- 1.5 Km/s

API details

Properties

AuxiliaryContext storage [INPUT, OPTIONAL, default=null]

The ProductStorage applicable to the observation we are working with. When storage parameter is used context, pointing and orbit cannot be used.

AuxiliaryContext context [INPUT, OPTIONAL, default=null]

The AuxiliaryContext applicable to the observation we are working with. When context parameter is used storage, pointing and orbit cannot be used.

ProductStorage pointing [INPUT, OPTIONAL, default=null]

The PointingProduct applicable to the observation we are working with. When pointing is used, orbit must be used too; storage and context cannot be used.

OrbitEphemerisProduct orbit [INPUT, OPTIONAL, default=null]

The OrbitEphemerisProduct applicable to the observation we are working with. When orbit is used, pointing must be used too: storage and context cannot be used.

FineTime time [INPUT, MANDATORY, default=null]

The time for which we want to get the radial velocity.

Ephemerides ephemerides [INPUT, OPTIONAL, default=null]

The Ephemerides object used in the corrections. If not used, corrections will be approximated. The error without an Ephemerides object is up to +- 1.5 Km/s

RadialvelocityTask.CorrectionType corrections [INPUT, MANDATORY, default=SUNANDEARTH]

The corrections flags to be applied to the velocity. Possible values are: NONE, SUNTOLSR, EARTHTOSUN, SUNANDEARTH

Double velocity [OUTPUT, MANDATORY, default=null]

The (signed) velocity projection in the pointing direction (radial velocity), in km/s Positive towards the target, negative otherwise. This is in J2000.

Double ra [OUTPUT, OPTIONAL, default=null]
RA of the pointing at t. Range = 0 .. 2*PI

Double dec [OUTPUT, OPTIONAL, default=null]
DEC of the pointing at t. Range - PI/2 .. PI/2

See also

- RadialVelocityTask
- ???
- ???
- ???
- ???

History

- 2008-10-10 - JDS: first interface candidate release
- 2008-12-12 - JDS: added precession algorithm
- 2009-02-02 - JDS: fixed degrees and radians
- 2009-02-11 - JDS: added more documentation (units)
- 2009-05-15 - JDS: moved to using a constant Sun speed vector in J2000, include Earth velocity
- 2009-06-26 - JDS: Initial task version, with tests, using Ephemeris
- 2009-07-01 - JDS: Doc corrections
- 2009-07-14 - JDS: Removed old RadialVelocity class, added Java static function with arrays, improved Task GUI
- 2009-11-02 - JDS: Doc added about error
- 2009-11-23 - JDS: Added info about sign of the radial velocity in several places

2.289. RandomGauss

Full Name:	herschel.ia.numeric.toolbox.random.RandomGauss
Alias:	RandomGauss
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.random import RandomGauss

Description

Generates or populates an array with normally N(0,1) distributed pseudo random numbers

Examples

Example 1: example usage of a random function

```
f=RandomGauss()
f=RandomGauss(seed=72654)
y=f(x)         # creates a random array with same dimensions and type as x
y=x.apply(f)   # like wise, but java style
x.perform(f)   # changes the values in x
```

Example 2: To generate 100 Double values normally distributed with mean=0 and sigma = 1.0

```
f = RandomGauss()
y = Double1d(100).apply(f)
# To make it with mean=mean and sigma=s
ynew = mean + y*s
```

API Summary

Jython Syntax

```
f = RandomGauss([seed=<seed>])
```

Property

OPTIONAL **seed** [INPUT, the seed for the random generator, default=no default value]

API details

Property

OPTIONAL seed [INPUT, the seed for the random generator, default=no default value]

2.290. RandomPoisson

Full Name:	herschel.ia.numeric.toolbox.random.RandomPoisson
Alias:	RandomPoisson
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.random import RandomPoisson

Description

Generates Poisson random numbers sequence with given mean

Examples

Example 1: example usage of a random function

```
f=RandomPoisson(20)
f=RandomPoisson(15,seed=72654)
y=f(x)         # creates a random array with same dimensions and type as x
y=x.apply(f)   # like wise, but java style
x.perform(f)   # changes the values in x
```

Example 2: To generate 100 Double values who follow Poisson distribution with mean 5

```
f = RandomPoisson(5.0)
y = Long1d(100).apply(f)
```

API Summary

Jython Syntax

```
f = RandomPoisson(<mean>,seed=<seed>)
```

Properties

MANDATORY **mean** [INPUT, the Poisson expectation value (mean), default=no default value]

OPTIONAL **seed** [INPUT, the seed for the random generator, default=no default value]

API details

Properties

MANDATORY mean [INPUT, the Poisson expectation value (mean), default=no default value]

OPTIONAL seed [INPUT, the seed for the random generator, default=no default value]

2.291. RandomUniform

Full Name:	herschel.ia.numeric.toolbox.random.RandomUniform
Alias:	RandomUniform
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.random import RandomUniform

Description

Generates arrays with uniformly-distributed random numbers.

Generates or populates an array with uniformly-distributed pseudo-random numbers in the range 0 <= x < max.

Examples

Example 1: example usage of a random function

```
x=Double1d(20)
f=RandomUniform(15,seed=72654)
y=f(x)         # creates a random array with same dimensions and type as x
y=x.apply(f)   # like wise, but java style
x.perform(f)   # changes the values in x
```

Example 2: To generate 100 Double values in [0,1)

```
f = RandomUniform()
y = Double1d(100).apply(f)
# To generate 100 Integer values in [0,100)
fx = RandomUniform(100.0)
yint = Int1d(100).apply(fx)
```

API Summary

Jython Syntax

```
f = RandomUniform([<max>],seed=<seed>) # between [0,max), default max=1.
```

Properties

OPTIONAL **max** [INPUT, if set the random sequence is in [0, default=max) otherwise in [0]

OPTIONAL **seed** [INPUT, the seed for the random generator, default=no default value]

API details

Properties

OPTIONAL max [INPUT, if set the random sequence is in [0, default=max) otherwise in [0]

OPTIONAL seed [INPUT, the seed for the random generator, default=no default value]

2.292. RangeExtractionGui

Full Name:	herschel.ia.gui.cube.RangeExtractionGui
Type:	Java Class -
Import:	from herschel.ia.gui.cube import RangeExtractionGui

Description

A class to extract a sub Range on a cube containing a large spectrum

API Summary

Method
setPlot() initiate the PlotXY, shown in this Range extraction GUI GUI which contain the global spectrum of the GUI.

API details

Method

setPlot()
initiate the PlotXY, shown in this Range extraction GUI GUI which contain the global spectrum of the GUI.

2.293. RangeExtractionTask

Full Name:	herschel.ia.toolbox.cube.RangeExtractionTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import RangeExtractionTask

Description

RangeExtractionTask

A class to extract a part of the cube given in parameter and to store the result as a new simplespectralcube the extraction can concentrate on the spectral domain or the spatial domain or both

API Summary

Properties
Cube **simplecube** [INPUT, MANDATORY, default=no default value]
integer **startindex** [INPUT, MANDATORY, default=no default value]
integer **endIndex** [INPUT, MANDATORY, default=no default value]
boolean **Crop** [INPUT, MANDATORY, default=no default value]
integer **Xmin** [INPUT, MANDATORY, default=no default value]
integer **Xmax** [INPUT, MANDATORY, default=no default value]
integer **Ymin** [INPUT, MANDATORY, default=no default value]
integer **Ymax** [INPUT, MANDATORY, default=no default value]
string **log** [OUTPUT, MANDATORY, default=no default value]
integer **error** [OUTPUT, MANDATORY, default=no default value]
Cube **rangeCube** [OUTPUT, MANDATORY, default=no default value]
Cube **specRangeCube** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

Cube simplecube [INPUT, MANDATORY, default=no default value]

The Cue from whichwe want to extract a smaller part

integer startindex [INPUT, MANDATORY, default=no default value]

The first spectral index from which we start the extraction

integer endIndex [INPUT, MANDATORY, default=no default value]

The lest spectral index for the selection which we start the extraction

boolean Crop [INPUT, MANDATORY, default=no default value]

A flag for activating a spatial extraction

integer Xmin [INPUT, MANDATORY, default=no default value]

the Xmin value for the spatial extraction

integer Xmax [INPUT, MANDATORY, default=no default value]

the Xmax value for the spatial extraction

integer Ymin [INPUT, MANDATORY, default=no default value]

the Ymin value for the spatial extraction

integer Ymax [INPUT, MANDATORY, default=no default value]

the Ymax value for the spatial extraction

string log [OUTPUT, MANDATORY, default=no default value]

a string containing a log of the extraction when something went wrong

integer error [OUTPUT, MANDATORY, default=no default value]

a code for the error if something wrong happen

Cube rangeCube [OUTPUT, MANDATORY, default=no default value]

a SpectralSimpleCube containing the cube extracted on the spectral dimension only

Cube specRangeCube [OUTPUT, MANDATORY, default=no default value]

a SpectralSimpleCube containing the cube extracted on the spectral and spatial dimension only

See also

- ???
- ???

2.294. RealFunction

Full Name:	herschel.ia.numeric.toolbox.RealFunction
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox import RealFunction

Example

Example 1: Untitled

```
class Inverse(RealFunction):<br>
&amp;nbsp;&amp;nbsp;def calc(self, x):<br>
&amp;nbsp;&amp;nbsp;&amp;nbsp;&amp;nbsp;return 1 -/ x<br>
</code>
```

2.295. REBIN

Full Name:	herschel.ia.numeric.toolbox.interp.Rebin
Alias:	REBIN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.interp import Rebin
Category:	numeric

Description

*

The Rebin class resizes a vector or array to dimensions given by the parameters Di. The supplied dimensions must be integral multiples or factors of the original dimension. The expansion or compression of each dimension is independent of the others, so that each dimension can be expanded or compressed by a different value. If the dimensions of the desired result are not integer multiples of the original dimensions, use the REGRID function. The SAMPLE keyword: Normally, REBIN uses bilinear interpolation when magnifying and neighborhood averaging when minifying. Set the SAMPLE keyword to use nearest neighbor sampling for both magnification and minification. If Rebin is initialized without error, the algorithm in IDL is strickly followed. If the Rebin is initialized with error, the weigted mean is used at compression when SAMPLE is not set.

Examples

Example 1: Apply Rebin on Int1d array

```
from herschel.ia.toolbox.basic.interp import Rebin;
Int1d x;
int dimension;
y = x.apply(new Rebin(dimension));
```

Example 2: Apply Rebin on Double2d array

```
from herschel.ia.toolbox.basic.interp import Rebin;
Double2d x, y;
y=x.apply(new Rebin(d1,d2));
```

Example 3: In Jython

```
from herschel.ia.toolbox.basic.interp import Rebin;
x=Int1d.range(12)
y=x.apply(Rebin(24))
or
y=Rebin(24)(x)
```

Example 4: expansion

```
signal=Double1d.range(10)
dim = 20
rebin = Rebin(dim)
rSignal=rebin(signal)
print rSignal
[0.0,0.5,1.0,1.5,2.0,2.5,3.0,3.5,4.0,4.5,5.0,5.5,6.0,6.5,7.0,7.5,8.0,8.5,9.0,9.0]
```

Example 5: calcualte error

```
signal=Double1d.range(20)+1
```

Example 5: calcualte error

```
inError = SQRT(signal)
dim = 10
rebin = Rebin(dim)
rSignal=rebin(signal)
p_error = rebin.getError(inError)
print p_error
[0.8660254037844387,1.3228756555322954,1.6583123951777,1.9364916731037087,2.179449471770337,
2.3979157616563596,2.598076211353316,2.7838821814150108,2.958039891549808,3.1224989991991996]
```

Example 6: Use SAMPLE keyword

```
signal=Double1d.range(10)
dim = 20
rebin = Rebin(dim, Rebin.SAMPLE)
rSignal=rebin(signal)
print rSignal
[0.0,0.0,1.0,1.0,2.0,2.0,3.0,3.0,4.0,4.0,5.0,5.0,6.0,6.0,7.0,7.0,8.0,8.0,9.0,9.0]
```

Example 7: Use wighted error

```
signal=Double1d.range(20)+1
inError = SQRT(signal)
dim = 10
rebin = Rebin(dim, inError)
rSignal=rebin(signal)
p_error = rebin.getError()
print p_error
[0.6666666666666666,1.7142857142857142,2.7272727272727275,3.7333333333333343,4.736842105263158,
5.739130434782608,6.7407407407407405,7.741935483870969,8.742857142857142,9.743589743589745]
```

API Summary

Jython Syntax
<y>=Rebin(<d1[,d2,d3,d4,d5]>)(<x>)
or
<y>=Rebin(<int d[]>)(<x>)
where <x>=input
<di> = new dimensions of output array
d[] = an array containing the new dimensions
<y>=output resampled onto dimensions.

Properties
type **di INPUT** [the dimension of the corresponding array index, MANDATORY, default=no default value]
array of integer **x** [INPUT, short, default=long or double taken the form of Int1(2]
type **sample Normally** [REBIN uses bilinear interpolation when magnifying and neighborhood averaging, MANDATORY, default=no default value]

Limitations

The supplied dimensions must be integral multiples or factors of the original dimension. Let f = n/m, the ratio of the size of the original vector, X to the size of the result. 1/f must be an integer if n < m (expansion). f must be an integer if compressing, (n > m).

API details

Properties

type di INPUT [the dimension of the corresponding array index, MANDATORY, default=no default value]

array of integer x [INPUT, short, default=long or double taken the form of Int1(2]

type sample Normally [REBIN uses bilinear interpolation when magnifying and neighborhood averaging, MANDATORY, default=no default value]

when minifying. Set the SAMPLE to Rebin.SAMPLE to use nearest neighbor sampling for both magnification and minification. Bilinear interpolation gives higher quality results but requires more time.

History

- `2006-08-30 - first`: version
- `2009-03-23 - error`: propagation (SCR-4833) is added.

2.296. RectangleHistogramExplorer

Full Name:	herschel.ia.gui.image.RectangleHistogramExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import RectangleHistogramExplorer

Description

An explorer for RectangleHistogramProducts.

An explorer for RectangleHistogramProducts.

API Summary

Constructors
RectangleHistogramExplorer() The construction of a new RectangleHistogramExplorer.
RectangleHistogramExplorer(Object object) The construction of a new RectangleHistogramExplorer associated with the given object.

Methods
String **getName**() Returns the name.
String **getDescription**() Returns the description.
boolean **canHandle**(Class className) Checks whether this RectangleHistogramExplorer can handle objects of the given class.
setObject(Object object) Sets the object.
RectangleHistogramProduct **getObject**() Returns the object.
Class **getVariableType**() Returns the expected variable type.
JScrollPane **getParameterTable**() Returns the parameter table.

API details

Constructors

RectangleHistogramExplorer()
The construction of a new RectangleHistogramExplorer. The construction of a new RectangleHistogramExplorer.

RectangleHistogramExplorer(Object object)
The construction of a new RectangleHistogramExplorer associated with the given object.

RectangleHistogramExplorer(Object object)

The construction of a new RectangleHistogramExplorer associated with the given object.

Argument

Object **object** [INPUT, MANDATORY]

Methods

String getName()

Returns the name.

Returns the name for this RectangleHistogramExplorer.

Return

String

Returns the name for this RectangleHistogramExplorer.

String getDescription()

Returns the description.

Returns the description for this RectangleHistogramExplorer.

Return

String

Returns the description for this RectangleHistogramExplorer.

boolean canHandle(Class className)

Checks whether this RectangleHistogramExplorer can handle objects of the given class.

Returns true if this RectangleHistogramExplorer can handle objects of the given class; false otherwise.

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true if this RectangleHistogramExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this RectangleHistogramExplorer to the given object.

Argument

Object **object** [INPUT, MANDATORY]

RectangleHistogramProduct getObject()

Returns the object.

RectangleHistogramProduct getObject()

Returns the object for this RectangleHistogramExplorer.

Return

RectangleHistogramProduct

Returns the object for this RectangleHistogramExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this RectangleHistogramExplorer.

Return

Class

Returns the expected variable type for this RectangleHistogramExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

Returns the parameter table for this RectangleHistogramExplorer.

Return

JScrollPane

Returns the parameter table for this RectangleHistogramExplorer.

2.297. RectangleHistogramPanel

Full Name:	herschel.ia.toolbox.image.gui.RectangleHistogramPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import RectangleHistogramPanel

Description

A panel for the RectangleHistogramTask.

A panel to serve as GUI for the RectangleHistogramTask.

API Summary

Constructor
`RectangleHistogramPanel()`
The construction of a new RectangleHistogramPanel.

Methods
`drawFigure()`
Draws the rectangle on the associated image.
`updateFigure()`
Updates the associated rectangle.
`trigger()`
Triggers the execution of the associated task.
`updateHistogram()`
Updates the associated histogram.

API details

Constructor

`RectangleHistogramPanel()`
The construction of a new RectangleHistogramPanel. The construction of a new RectangleHistogramPanel.

Methods

`drawFigure()`
Draws the rectangle on the associated image. Draws the rectangle on the image associated with this RectangleHistogramPanel.

`updateFigure()`
Updates the associated rectangle. Updates the rectangle associated with this RectangleHistogramPanel.

trigger()
Triggers the execution of the associated task. Triggers the execution of the task associated with this RectangleHistogramPanel.

updateHistogram()
Updates the associated histogram. Updates the histogram associated with this RectangleHistogramPanel.

2.298. RectangleHistogramProduct

Full Name:	herschel.ia.dataset.image.RectangleHistogramProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import RectangleHistogramProduct

Description

A class to deal with the results of a rectangle histogram.

API Summary

Constructor
RectangleHistogramProduct() The constructor of a new RectangleHistogramProduct.

Methods
setUpperLeftCorner(double upperLeftX, double upperLeftY) Sets the upper left corner for this RectangleHistogramProduct
setUpperLeftCorner(double upperLeftX, double upperLeftY, String upperLeftRA, String upperLefttDec) Sets the upper left corner for this RectangleHistogramProduct
setDimensions(double widthPixels, double heightPixels) Sets the dimensions for this RectangleHistogramProduct to the
setDimensions(double widthPixels, double heightPixels, double widthArcsec, double heightArcsec) Sets the dimensions for this RectangleHistogramProduct to the
Double1d **getUpperLeftCornerPixelCoordinates**() Returns the upper left corner for this RectangleHistogramProduct in
String1d **getUpperLeftCornerSkyCoordinates**() Returns the upper left corner for this RectangleHistogramProduct in
double **getWidthPixels**() Returns the width for this RectangleHistogramProduct in pixels.
double **getWidthArcsec**() Returns the width for this RectangleHistogramProduct in arcsec.
double **getHeightPixels**() Returns the height for this RectangleHistogramProduct in pixels.
double **getHeightArcsec**() Returns the height for this RectangleHistogramProduct in arcsec.

API details

Constructor

RectangleHistogramProduct()
The constructor of a new RectangleHistogramProduct.

Methods

setUpperLeftCorner(double upperLeftX, double upperLeftY)

Sets the upper left corner for this RectangleHistogramProduct

to the given pixel coordinates.

Arguments

double **upperLeftX** [INPUT, MANDATORY]

double **upperLeftY** [INPUT, MANDATORY]

setUpperLeftCorner(double upperLeftX, double upperLeftY, String upperLeftRA, String upperLefttDec)

Sets the upper left corner for this RectangleHistogramProduct

to the given pixel and sky coordinates.

Arguments

double **upperLeftX** [INPUT, MANDATORY]

double **upperLeftY** [INPUT, MANDATORY]

String **upperLeftRA** [INPUT, MANDATORY]

String **upperLefttDec** [INPUT, MANDATORY]

setDimensions(double widthPixels, double heightPixels)

Sets the dimensions for this RectangleHistogramProduct to the

given dimensions in pixels.

Arguments

double **widthPixels** [INPUT, MANDATORY]

double **heightPixels** [INPUT, MANDATORY]

setDimensions(double widthPixels, double heightPixels, double widthArcsec, double heightArcsec)

Sets the dimensions for this RectangleHistogramProduct to the

given dimensions in pixels and arcsec.

Arguments

double **widthPixels** [INPUT, MANDATORY]

double **heightPixels** [INPUT, MANDATORY]

double **widthArcsec** [INPUT, MANDATORY]

double **heightArcsec** [INPUT, MANDATORY]

Double1d getUpperLeftCornerPixelCoordinates()

Returns the upper left corner for this RectangleHistogramProduct in

pixel coordinates.

Return

Double1d

Double1d getUpperLeftCornerPixelCoordinates()

Returns the upper left corner for this RectangleHistogramProduct in pixel coordinates.

String1d getUpperLeftCornerSkyCoordinates()

Returns the upper left corner for this RectangleHistogramProduct in

sky coordinates.

Return

String1d

Returns the upper left corner for this RectangleHistogramProduct in sky coordinates.

double getWidthPixels()

Returns the width for this RectangleHistogramProduct in pixels.

Return

double

Returns the width for this RectangleHistogramProduct in pixels.

double getWidthArcsec()

Returns the width for this RectangleHistogramProduct in arcsec.

Return

double

Returns the width for this RectangleHistogramProduct in arcsec.

double getHeightPixels()

Returns the height for this RectangleHistogramProduct in pixels.

Return

double

Returns the height for this RectangleHistogramProduct in pixels.

double getHeightArcsec()

Returns the height for this RectangleHistogramProduct in arcsec.

Return

double

Returns the height for this RectangleHistogramProduct in arcsec.

2.299. RectangleHistogramTask

Full Name:	herschel.ia.toolbox.image.RectangleHistogramTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import RectangleHistogramTask

Description

A Task to make a histogram within a rectangle.

A Task to make a histogram of a region of interest, which is bounded by a rectangle.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **lowCut** [INPUT, OPTIONAL, default=Default value : NaN]
Double **highCut** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **bins** [INPUT, MANDATORY, default=Default value : new Integer(2000)]
RectangleHistogramProduct **histogram** [OUTPUT, MANDATORY, default=No default value]
Double **minX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **minY** [INPUT, OPTIONAL, default=Default value : NaN]
String **minRA** [INPUT, OPTIONAL, default=Default value : "minRA"]
String **minDec** [INPUT, OPTIONAL, default=Default value: "minDec"]
Double **widthPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **heightPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **widthArcsec** [INPUT, OPTIONAL, default=Default value : NaN]
Double **heightArcsec** [INPUT, OPTIONAL, default=Default value : NaN]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double lowCut [INPUT, OPTIONAL, default=Default value : NaN]

The lower cut level.

Double highCut [INPUT, OPTIONAL, default=Default value : NaN]

The upper cut level.

Integer bins [INPUT, MANDATORY, default=Default value : new Integer(2000)]

The number of bins.

RectangleHistogramProduct histogram [OUTPUT, MANDATORY, default=No default value]

The histogram.

Double minX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the upper left corner of the rectangle.

Double minY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the upper left corner of the rectangle.

String minRA [INPUT, OPTIONAL, default=Default value : "minRA"]

The right ascension of the upper left corner of the rectangle.

String minDec [INPUT, OPTIONAL, default=Default value: "minDec"]

The declination of the upper left corner of the rectangle.

Double widthPixels [INPUT, OPTIONAL, default=Default value : NaN]

The width of the rectangle in pixels.

Double heightPixels [INPUT, OPTIONAL, default=Default value : NaN]

The height of the rectangle in pixels.

Double widthArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The width of the rectangle in arcsec.

Double heightArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The height of the rectangle in arcsec.

2.300. RectangularSkyAperturePhotometryExplorer

Full Name:	herschel.ia.gui.image.RectangularSkyAperturePhotometryExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import RectangularSkyAperturePhotometryExplorer

Description

An explorer for RectangularSkyAperturePhotometryProducts.

An explorer for RectangularSkyAperturePhotometryProducts.

API Summary

Constructors
RectangularSkyAperturePhotometryExplorer() The construction of a new RectangularSkyAperturePhotometryExplorer.
RectangularSkyAperturePhotometryExplorer(Object object) The construction of a new RectangularSkyAperturePhotometryExplorer associated with the given object.

Methods
boolean **canHandle**(Class className) Checks whether this RectangularSkyAperturePhotometryExplorer can handle objects of the given class.
RectangularSkyAperturePhotometryProduct **getObject**() Returns the object.
Class **getVariableType**() Returns the expected variable type.
JScrollPane **getParameterTable**() Returns the parameter table.
JPanel **getPlotPanel**() Returns the plot panel.

API details

Constructors

RectangularSkyAperturePhotometryExplorer()
The construction of a new RectangularSkyAperturePhotometryExplorer. The construction of a new RectangularSkyAperturePhotometryExplorer.

RectangularSkyAperturePhotometryExplorer(Object object)
The construction of a new RectangularSkyAperturePhotometryExplorer associated with the given object.

RectangularSkyAperturePhotometryExplorer(Object object)

The construction of a new RectangularSkyAperturePhotometryExplorer associated with the given object.

Argument

Object **object** [INPUT, MANDATORY]

Methods

boolean canHandle(Class className)

Checks whether this RectangularSkyAperturePhotometryExplorer can handle objects of the given class.

Returns true if this RectangularSkyAperturePhotometryExplorer can handle objects of the given class; false otherwise.

Argument

Class **className** [INPUT, MANDATORY]

Return

boolean

Returns true if this RectangularSkyAperturePhotometryExplorer can handle objects of the given class; false otherwise.

RectangularSkyAperturePhotometryProduct getObject()

Returns the object.

Returns the object for this RectangularSkyAperturePhotometryExplorer.

Return

RectangularSkyAperturePhotometryProduct

Returns the object for this RectangularSkyAperturePhotometryExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this RectangularAperturePhotometryExplorer.

Return

Class

Returns the expected variable type for this RectangularAperturePhotometryExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

Constructs and returns the parameter table for this RectangularSkyAperturePhotometryExplorer.

Return

JScrollPane

Returns the parameter table for this RectangularSkyAperturePhotometryExplorer.

`JPanel getPlotPanel()`

Returns the plot panel.

Constructs and returns the plot panel for this RectangularSkyAperturePhotometryExplorer.

Return

JPanel

Returns the plot panel for this RectangularSkyAperturePhotometryExplorer.

2.301. RectangularSkyAperturePhotometryPanel

Full Name:	herschel.ia.toolbox.image.gui.RectangularSkyAperturePhotometryPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import RectangularSkyAperturePhotometryPanel

Description

A panel for the RectangularSkyAperturePhotometryTask.

A panel to serve as GUI for the RectangularSkyAperturePhotometryTask.

API Summary

Constructor
RectangularSkyAperturePhotometryPanel() The constructio of a new RectangularSkyAperturePhotometryPanel.

Methods
JPanel **getAperturesPanel()** Returns the apertures panel.
JComponent **getSkyApertureComponent()** Returns the panel where it is explained how to specify the rectangular sky aperture.
drawRectangle() Allows to draw a rectangle on the associated image.
int **getNbOfRectanglePoints()** Returns the number of confirmed points for the rectangle.
increaseNbOfRectanglePoints() Increases the number of confirmed rectangle points.
drawFigures() Draws the figures on the image.
moveConfirmedFigures() Allows the user to drag the figures bounding the apertures.
clearSkyAperture() Clears the rectangular sky aperture.

API details

Constructor

RectangularSkyAperturePhotometryPanel()
The constructio of a new RectangularSkyAperturePhotometryPanel. The construction of a new RectangularSkyAperturePhotometryPanel.

Methods

JPanel getAperturesPanel()

Returns the apertures panel.

Returns the panel where to specify the target radius and where it is explained how to specify the rectangular sky aperture for this RectangularSkyAperturePhotometryPane.

Return

JPanel

Returns the panel where to specify the target radius and where it is explained to specify the rectangular sky aperture for this RectangularSkyAperturePhotometryPanel.

JComponent getSkyApertureComponent()

Returns the panel where it is explained how to specify the rectangular sky aperture.

Returns the panel where it is explained how to specify the rectangular sky aperture for this RectangularSkyAperturePhotometryPanel.

Return

JComponent

Returns the panel where it is explained how to specify the rectangular sky aperture for this RectangularSkyAperturePhotometryPanel.

drawRectangle()

Allows to draw a rectangle on the associated image.

Allows to draw a rectangle on the image associated with this RectangularSkyAperturePhotometryPanel.

int getNbOfRectanglePoints()

Returns the number of confirmed points for the rectangle.

Returns the number of points that were confirmed before for the rectangle on the image for this RectangularSkyAperturePhotometryPanel.

Return

int

Returns the number of points that were confirmed before for the rectangle on the image for this RectangularSkyAperturePhotometryPanel.

increaseNbOfRectanglePoints()

Increases the number of confirmed rectangle points.

Increases the number of rectangle points that were confirmed before on the image for this RectangularSkyAperturePhotometryPanel.

drawFigures()

Draws the figures on the image.

drawFigures()
Draws the figures on the image for this RectangularSkyAperturePhotometryPanel.

moveConfirmedFigures()
Allows the user to drag the figures bounding the apertures. Allows the user to drag the figures bounding the apertures for this RectangularSkyAperturePhotometryPanel.

clearSkyAperture()
Clears the rectangular sky aperture. Clears the rectangular sky aperture for this RectangularSkyAperturePhotometryPanel.

2.302. RectangularSkyAperturePhotometryProduct

Full Name:	herschel.ia.dataset.image.RectangularSkyAperturePhotometryProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import RectangularSkyAperturePhotometryProduct

Description

A class to deal with the resuls of aperture photometry with a

rectangular sky aperture.

API Summary

Constructor
RectangularSkyAperturePhotometryProduct() The constructor of a new RectangularSkyAperturePhotometryProduct.

Methods
setUpperLeftCorner(double upperLeftX, double upperLeftY) Sets the upper left corner for this RectangularSkyAperturePhotometryProduct
setUpperLeftCorner(double upperLeftX, double upperLeftY, String upperLeftRA, String upperLeftDec) Sets the upper left corner for this RectangularSkyAperturePhotometryProduct.
setDimensions(double widthPixels, double heightPixels) Sets the dimensions for this RectangularSkyAperturePhotometryProduct to the
setDimensions(double widthPixels, double heightPixels, double widthArcsec, double heightArcsec) Sets the dimensions for this RectangularSkyAperturePhotometryProduct to the
Double1d **getUpperLeftCornerPixelCoordinates**() Returns the upper left corner for this RectangularSkyAperturePhotometryProduct in
String1d **getUpperLeftCornerSkyCoordinates**() Returns the upper left corner for this RectangularSkyAperturePhotometryProduct
double **getWidthPixels**() Returns the width for this RectangularSkyAperturePhotometryProduct
double **getWidthArcsec**() Returns the width for this RectangularSkyAperturePhotometryProduct
double **getHeightPixels**() Returns the height for this RectangularSkyAperturePhotometryProduct
getHeightArcsec() Returns the height for this RectangularSkyAperturePhotometryProduct

Miscellaneous

Aperture specific information iss stored in meta data, all other data (results of calculations) are stored in TableDatasets.

API details

Constructor

RectangularSkyAperturePhotometryProduct()

The constructor of a new RectangularSkyAperturePhotometryProduct.

Methods

setUpperLeftCorner(double upperLeftX, double upperLeftY)

Sets the upper left corner for this RectangularSkyAperturePhotometryProduct

to the given pixel coordinates.

Arguments

double **upperLeftX** [INPUT, MANDATORY]

double **upperLeftY** [INPUT, MANDATORY]

setUpperLeftCorner(double upperLeftX, double upperLeftY, String upperLeftRA, String upperLeftDec)

Sets the upper left corner for this RectangularSkyAperturePhotometryProduct.

Arguments

double **upperLeftX** [INPUT, MANDATORY]

double **upperLeftY** [INPUT, MANDATORY]

String **upperLeftRA** [INPUT, MANDATORY]

String **upperLeftDec** [INPUT, MANDATORY]

setDimensions(double widthPixels, double heightPixels)

Sets the dimensions for this RectangularSkyAperturePhotometryProduct to the

given dimensions in pixels.

Arguments

double **widthPixels** [INPUT, MANDATORY]

double **heightPixels** [INPUT, MANDATORY]

setDimensions(double widthPixels, double heightPixels, double widthArcsec, double heightArcsec)

Sets the dimensions for this RectangularSkyAperturePhotometryProduct to the

given dimensions in pixels and arcsec.

Arguments

double **widthPixels** [INPUT, MANDATORY]

double **heightPixels** [INPUT, MANDATORY]

double **widthArcsec** [INPUT, MANDATORY]

double **heightArcsec** [INPUT, MANDATORY]

Double1d getUpperLeftCornerPixelCoordinates()

Returns the upper left corner for this RectangularSkyAperturePhotometryProduct in

Double1d getUpperLeftCornerPixelCoordinates()

pixel coordinates.

Return

Double1d

Returns the upper left corner for this RectangularSkyAperturePhotometryProduct in pixel coordinates.

String1d getUpperLeftCornerSkyCoordinates()

Returns the upper left corner for this RectangularSkyAperturePhotometryProduct

in sky coordinates.

Return

String1d

Returns the upper left corner for this RectangularSkyAperturePhotometryProduct in sky coordinates.

double getWidthPixels()

Returns the width for this RectangularSkyAperturePhotometryProduct

in pixels.

Return

double

Returns the width for this RectangularSkyAperturePhotometryProduct in pixels.

double getWidthArcsec()

Returns the width for this RectangularSkyAperturePhotometryProduct

in arcsec.

Return

double

Returns the width for this RectangularSkyAperturePhotometryProduct in arcsec.

double getHeightPixels()

Returns the height for this RectangularSkyAperturePhotometryProduct

in pixels.

Return

double

Returns the height for this RectangularSkyAperturePhotometryProduct in pixels.

getHeightArcsec()

Returns the height for this RectangularSkyAperturePhotometryProduct

getHeightArcsec()
in arcsec.

2.303. RectangularSkyAperturePhotometryTask

Full Name:	herschel.ia.toolbox.image.RectangularSkyAperturePhotometryTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import RectangularSkyAperturePhotometryTask

Description

A Task for aperture photometry.

A Task for aperture photometry, using a circular target aperture and a rectangular sky aperture.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **centerX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **centerY** [INPUT, OPTIONAL, default=Default value : NaN]
String **centerRA** [INPUT, OPTIONAL, default=Default value : "centerRA"]
String **centerDEC** [INPUT, OPTIONAL, default=Default value : "centerDec"]
Double **radiusPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **radiusArcsec** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **algorithm** [INPUT, MANDATORY, default=Default value : 4]
RectangularSkyAperturePhotometryProduct **result** [OUTPUT, MANDATORY, default=No default value]
Double **minX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **minY** [INPUT, OPTIONAL, default=Default value : NaN]
String **minRA** [INPUT, OPTIONAL, default=Default value : "upperLeftRA"]
String **minDec** [INPUT, OPTIONAL, default=Default value : "upperLeftDec"]
Double **widthPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **heightPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Double **widthArcsec** [INPUT, OPTIONAL, default=Default value : NaN]
Double **heightArcsec** [INPUT, OPTIONAL, default=Default value : NaN]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double centerX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the target center.

Double centerY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the target center.

String centerRA [INPUT, OPTIONAL, default=Default value : "centerRA"]

The right ascension of the target center.

String centerDEC [INPUT, OPTIONAL, default=Default value : "centerDec"]

The declination of the target center.

Double radiusPixels [INPUT, OPTIONAL, default=Default value : NaN]

The target radius in pixels.

Double radiusArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The target radius in arcsec.

Integer algorithm [INPUT, MANDATORY, default=Default value : 4]

The sky estimation algorithm.

RectangularSkyAperturePhotometryProduct result [OUTPUT, MANDATORY, default=No default value]

The result.

Double minX [INPUT, OPTIONAL, default=Default value : NaN]

The input x-pixel-coordinate of the upper left corner of the rectangular sky aperture.

Double minY [INPUT, OPTIONAL, default=Default value : NaN]

The input y-pixel-coordinate of the upper left corner of the rectangular sky aperture.

String minRA [INPUT, OPTIONAL, default=Default value : "upperLeftRA"]

The input right ascension of the upper left corner of the rectangular sky aperture.

String minDec [INPUT, OPTIONAL, default=Default value : "upperLeftDec"]

The input declination of the upper left corner of the rectangular sky aperture.

Double widthPixels [INPUT, OPTIONAL, default=Default value : NaN]

The input width of the rectangular sky aperture in pixels.

Double heightPixels [INPUT, OPTIONAL, default=Default value : NaN]

The input height of the rectangular sky aperture in pixels.

Double widthArcsec [INPUT, OPTIONAL, default=Default value : NaN]

The input width of the rectangular sky aperture in arcsec.

Double heightArcsec [INPUT, OPTIONAL, default=Default value : NaN]
The input height of the rectangular sky aperture in arcsec.

2.304. Regrid

Full Name:	herschel.ia.numeric.toolbox.interp.Regrid
Alias:	Regrid
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.interp import Regrid

Description

The Regrid class shrinks or expands the size of an array by an

arbitrary amount. This class is similar to "Rebin" in that it can resize a one, two, or three dimensional array. "Rebin", however, requires that the new array size must be an integer multiple of the original size. Regrid will resize an array to any arbitrary size (Rebin is somewhat faster, however). Rebin averages multiple points when shrinking an array, while Regrid just resamples the array. The returned array has the same number of dimensions as the original array and is of the same data type.

Example

Example 1: Use Regrid

```
#1-d example: resize a 1d array 10 elements long to one that is 6 elements long
x = Double1d([0,1,2,3,4,5,6,7,8,9])
y = Regrid(6)(x)
print x # [0.0,1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0]
print y # [0.0,1.8,3.6,5.4,7.2,9.0]
# do the same, but this time use a different scheme
y = Regrid(6,Regrid.NEAREST_NEIGHBOR)(x)
print y # [0.0,2.0,4.0,5.0,7.0,9.0]
#resize a 2d array 2x3 elements long to  one that is 5x8 elements long
x = Double2d([[2.2, 3.1, 11.9],[109.2, 135.7, 210.8]])
y = Regrid(5,8,Regrid.LINEAR)(x)
#note the first column resamples between 2.2 and 109.2.
#i.e. going from 2 points to 5. this can be checked by -:
print y[:,0]  # [2.2,28.95,55.7,82.45,109.2]
# or concentrating on the first row, which goes
# from 2.2 to 11.9 in three steps, the out is resampled to 8 points.
print y[0:] #
[2.2,2.4571428571428573,2.7142857142857144,2.9714285714285715,4.357142857142857,6.8714285714285
```

API Summary

Constructors
Regrid(int[] d)
Regrid(int[] d, String interpMethod)
Regrid(int[] d, String interpMethod, String allowExtrapolation)
Regrid(int d1)
Regrid(int d1, String interpMethod)
Regrid(int d1, String interpMethod, String allowExtrapolation)
Regrid(int d1, int d2)
Regrid(int d1, int d2, String interpMethod)
Regrid(int d1, int d2, String interpMethod, String allowExtrapolation)

Constructors
Regrid(int d1, int d2, int d3)
Regrid(int d1, int d2, int d3, String interpMethod)
Regrid(int d1, int d2, int d3, String interpMethod, String allowExtrapolation)
Regrid(int d1, int d2, int d3, int d4)
Regrid(int d1, int d2, int d3, int d4, String interpMethod)
Regrid(int d1, int d2, int d3, int d4, String interpMethod, String allowExtrapolation)
Regrid(int d1, int d2, int d3, int d4, int d5)
Regrid(int d1, int d2, int d3, int d4, int d5, String interpMethod)
Regrid(int d1, int d2, int d3, int d4, int d5, String interpMethod, String allowExtrapolation)

Limitations

The x, INPUT, array of Int(n)d, Short(n)d, Long(n)d, Float(n)d or Double(n)d, (1<= n <=5)

Miscellaneous

Synopsis:

resample rank=d.length array to new dimensions in d.

y = Regrid(d[])(x)

resamples a one to five dimension array using default (linear) interpolation.

y = Regrid(d1,...,d5)(x)

resamples a one to five dimension array using linear interpolation.

y = Regrid(d1,...,d5,Regrid.LINEAR)(x)

resamples an array using nearest neighbor interpolation.

y = Regrid(d1,...,d5,Regrid.NEAREST_NEIGHBOR)(x)

resamples an array using cubic spline interpolation.

y = Regrid(d1,...,d5,Regrid.CUBIC_SPLINE)(x)

allows Extrapolation.

y = Regrid(d1,...,d5,Regrid.LINEAR,Regrid.EXTRAPOLATION)(x)

API details

Constructors

Regrid(int[] d)
Argument `int[] d [INPUT, MANDATORY, default=no default value]`

Regrid(int[] d)

array of Int(n)d, Short(n)d, Long(n)d, Float(n)d or Double(n)d, (1<= n <=5), MANDATORY.

Errors

`UnsupportedOperationException`

Bad dimension array! It should be 1<= d <=5.

Regrid(int[] d, String interpMethod)

Arguments

`int[] d [INPUT, MANDATORY, default=no default value]`

array of Int(n)d, Short(n)d, Long(n)d, Float(n)d or Double(n)d, (1<= n <=5), MANDATORY.

`String interpMethod [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]`

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

Errors

`UnsupportedOperationException`

Bad dimension array! It should be 1<= d <=5.

Regrid(int[] d, String interpMethod, String allowExtrapolation)

Arguments

`int[] d [INPUT, MANDATORY, default=no default value]`

array of Int(n)d, Short(n)d, Long(n)d, Float(n)d or Double(n)d, (1<= n <=5), MANDATORY.

`String interpMethod [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]`

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

`String allowExtrapolation [INPUT, NOT_MANDATORY, default=Regrid.EXTRAPOLATION]`

default is no extrapolation allowed.

Errors

`UnsupportedOperationException`

Bad dimension array! It should be 1<= d <=5.

Regrid(int d1)

Argument

`int d1 [INPUT, MANDATORY, default=no default value]`

d1 input integer

Regrid(int d1, String interpMethod)

Arguments

`int d1 [INPUT, MANDATORY]`

`String interpMethod [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]`

Regrid(int d1, String interpMethod)

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

Regrid(int d1, String interpMethod, String allowExtrapolation)

Arguments

`int` **d1** [INPUT, MANDATORY]

`String` **interpMethod** [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

`String` **allowExtrapolation** [INPUT, NOT_MANDATORY, default=Regrid.EXTRAPOLATION]

default is no extrapolation allowed.

Regrid(int d1, int d2)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

Regrid(int d1, int d2, String interpMethod)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`String` **interpMethod** [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default)

Regrid(int d1, int d2, String interpMethod, String allowExtrapolation)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`String` **interpMethod** [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

`String` **allowExtrapolation** [INPUT, NOT_MANDATORY, default=Regrid.EXTRAPOLATION]

Regrid(int d1, int d2, String interpMethod, String allowExtrapolation)

default is no extrapolation allowed.

Regrid(int d1, int d2, int d3)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`int` **d3** [INPUT, MANDATORY, default=no default value]

d3 input integer

Regrid(int d1, int d2, int d3, String interpMethod)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`int` **d3** [INPUT, MANDATORY, default=no default value]

d3 input integer

`String` **interpMethod** [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

Regrid(int d1, int d2, int d3, String interpMethod, String allowExtrapolation)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`int` **d3** [INPUT, MANDATORY, default=no default value]

d3 input integer

`String` **interpMethod** [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

`String` **allowExtrapolation** [INPUT, NOT_MANDATORY, default=Regrid.EXTRAPOLATION]

default is no extrapolation allowed.

Regrid(int d1, int d2, int d3, int d4)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

Regrid(int d1, int d2, int d3, int d4)

d1 input integer

`int` **d2** `[INPUT, MANDATORY, default=no default value]`

d2 input integer

`int` **d3** `[INPUT, MANDATORY, default=no default value]`

d3 input integer

`int` **d4** `[INPUT, MANDATORY, default=no default value]`

d4 input integer

Regrid(int d1, int d2, int d3, int d4, String interpMethod)

Arguments

`int` **d1** `[INPUT, MANDATORY, default=no default value]`

d1 input integer

`int` **d2** `[INPUT, MANDATORY, default=no default value]`

d2 input integer

`int` **d3** `[INPUT, MANDATORY, default=no default value]`

d3 input integer

`int` **d4** `[INPUT, MANDATORY, default=no default value]`

d4 input integer

`String` **interpMethod** `[INPUT, NOT_MANDATORY, default=Regrid.LINEAR]`

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

Regrid(int d1, int d2, int d3, int d4, String interpMethod, String allowExtrapolation)

Arguments

`int` **d1** `[INPUT, MANDATORY, default=no default value]`

d1 input integer

`int` **d2** `[INPUT, MANDATORY, default=no default value]`

d2 input integer

`int` **d3** `[INPUT, MANDATORY, default=no default value]`

d3 input integer

`int` **d4** `[INPUT, MANDATORY, default=no default value]`

d4 input integer

`String` **interpMethod** `[INPUT, NOT_MANDATORY, default=Regrid.LINEAR]`

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

`String` **allowExtrapolation** `[INPUT, NOT_MANDATORY, default=Regrid.EXTRAPOLATION]`

default is no extrapolation allowed.

Regrid(int d1, int d2, int d3, int d4, int d5)

Arguments

Regrid(int d1, int d2, int d3, int d4, int d5)

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`int` **d3** [INPUT, MANDATORY, default=no default value]

d3 input integer

`int` **d4** [INPUT, MANDATORY, default=no default value]

d4 input integer

`int` **d5** [INPUT, MANDATORY, default=no default value]

d5 input integer

Regrid(int d1, int d2, int d3, int d4, int d5, String interpMethod)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`int` **d3** [INPUT, MANDATORY, default=no default value]

d3 input integer

`int` **d4** [INPUT, MANDATORY, default=no default value]

d4 input integer

`int` **d5** [INPUT, MANDATORY, default=no default value]

d5 input integer

`String` **interpMethod** [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

Regrid(int d1, int d2, int d3, int d4, int d5, String interpMethod, String allowExtrapolation)

Arguments

`int` **d1** [INPUT, MANDATORY, default=no default value]

d1 input integer

`int` **d2** [INPUT, MANDATORY, default=no default value]

d2 input integer

`int` **d3** [INPUT, MANDATORY, default=no default value]

d3 input integer

`int` **d4** [INPUT, MANDATORY, default=no default value]

d4 input integer

`int` **d5** [INPUT, MANDATORY, default=no default value]

d5 input integer

`String` **interpMethod** [INPUT, NOT_MANDATORY, default=Regrid.LINEAR]

Regrid(int d1, int d2, int d3, int d4, int d5, String interpMethod, String allowExtrapolation)

allowable interpolation schemes are: CUBLIC_SPLINE, NEAREST_NEIGHBOR, and LINEAR (which is the default).

String **allowExtrapolation** [INPUT, NOT_MANDATORY, default=Regrid.EXTRAPOLATION]

default is no extrapolation allowed.

History

- 2009-10-10 - Modified: by Lijun HCSS-8078 Since I did not find the algorithm used, I checked IDL and found Congrid funtion in IDL. I believe that Regrid used the same algorithm as Congrid. Therefore I made the following changes:
- 1. Deprecated EXTRAPOLATION
- 2. Set extrapolation as a default behavior
- 3. Introduce MINUS_ONE to reflect the fact the IDL conter-parternership.
- 4. When MINUS_ONE is true, I enforced the new coordinate at newDim -1 is the same as oldDim-1. Mathematically, RegridFact = (oldDim - 1) / (newDim - 1); new_coordinate(i) = i * RegridFact when i = newDim -1, new_coordinate(newDim-1) = oldDim -1. But due to the numerically error, there may be some small detla value introduced. Therefore, I need to enforce it to oldDim -1
- 5. Replaced several false to _allowExtrapolation in calling, for example, RegridFor1dArray(d1, _interp, _allowExtrapolation);
- 6. Change the RegridConsts class to interface

2.305. REPEAT

Full Name:	herschel.ia.numeric.toolbox.array.Repeat
Alias:	REPEAT
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.array import Repeat

Description

Creates a new array which contains the specified repetitions of the original array.

Example

Example 1: Apply REPEAT on a Int1d

```
x=Int1d([0,1,2,3,4,5,6,7,8,9,10,11])
print REPEAT(x,3)     # Int2d = [[0,1,2,3,4,5,6,7,8,9,10,11],
[0,1,2,3,4,5,6,7,8,9,10,11],[0,1,2,3,4,5,6,7,8,9,10,11]]
```

API Summary

Jython Syntax

```
<y>=REPEAT(<x>,<repetitions=1>)
```

Properties

any array of any rank **x** [INPUT, MANDATORY, default=no default value]

integer **repetitions** [INPUT, MANDATORY, default=no default value]

array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of any rank x [INPUT, MANDATORY, default=no default value]

The input array must be an array of rank 1 to 4 (both included)

integer repetitions [INPUT, MANDATORY, default=no default value]

The repetitions to apply to this array. It must be greater than 0.

array y [OUTPUT, MANDATORY, default=no default value]

Returns an increased dimensional array with the specified repetitions.

2.306. ReplaceFreqRanges

Full Name:	herschel.ia.toolbox.spectrum.ReplaceFreqRanges
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import ReplaceFreqRanges

Description

Task for inserting and/or replacing ranges within the segments of a container.

Various different modes are available for how the replacement / insertion should be processed. For further details see the mode-parameter below.

Example

Example 1: from jide

```
from herschel.ia.toolbox.spectrum import ReplaceFreqRanges
replace = ReplaceFreqRanges()
replacedSlices1 = replace(ds=spectra, by=slices, mode="replace")
replacedSlices2 = replace(ds=spectra, by=slices, mode="avg")
replacedSlices3 = replace(ds=spectra, by=slices, mode="insert")
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, OPTIONAL, default=No default value.]
SpectrumContainer **by** [INPUT, OPTIONAL, default=No default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=No default value.]
String **mode** [INPUT, OPTIONAL, default=replace.]

API details

Properties

SpectrumContainer ds [INPUT, OPTIONAL, default=No default value.]

The container in which the spectra of the other input container should be inserted.

SpectrumContainer by [INPUT, OPTIONAL, default=No default value.]

The container with the slices that should be inserted into the first input container.

SpectrumContainer result [OUTPUT, OPTIONAL, default=No default value.]

The output container.

String mode [INPUT, OPTIONAL, default=replace.]

A mode specifying how the module should actually do the replacement. Three options are available:

String mode [INPUT, OPTIONAL, default=replace.]
• "replace": Resample the slices to be inserted to the frequency grid of the original container (ds) and replace the original ranges by the resampled slices. • "avg": Resample the slices to be inserted to the frequency grid of the original container (ds) and replace the original ranges by the average of the original ranges and the resampled slices. • "insert": Insert brute-force the slices by replacing the ranges of the original spectra by matching the frequency ranges - irrespective of the frequency grid.

History

- `2008-03-27 - meli`: initial.

2.307. ResampleFrequency

Full Name:	herschel.ia.toolbox.spectrum.ResampleFrequency
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import ResampleFrequency

Description

Task for resampling the flux values included in a spectrum container with respect

to a modified frequency grid. Different schemes are available - all should conserve total flux.

The standard (default) scheme uses a trapezoidal integration scheme in combination with linear interpolation. An alternative scheme consists of using an euler integration scheme in combination with nearest neighbor interpolation.

Flags and weights are processed if available:

- For the weights, the same integration/interpolation scheme is applied as is used for the flux. For the weights, we always assume that the weights are defined 'per channel'. (For the flux, we generally assume that it is given on a 'per frequency' basis - if not otherwise stated by the 'isDensity' quantity.
- The flag for an output channel is defined by combining the flags of all the input channels that are considered (for the given output channel) by an bitwise OR logic. This allows to recover all the distinct flag values that are involved in the computation of the given channel.

For output channels that are not supported by any input channels, we set for flux and weights values 'NaN' and as flag 'NotSampled' (64).

Other attributes found in the spectra are copied to the result container without any change.

Example

Example 1: from Jide:

```
resampled1 = resample(ds=spectra, density=True, resolution=1.0)
resampled1 = resample(ds=spectra, density=True, resolution=1.0, unit="MHz")
resampled1 = resample(ds=spectra, density=True, resolution=0.001, unit="GHz")
resampled2 = resample(ds=spectra, density=True, scheme="euler", resolution=1.0)
grid = [4000.0 + 2.0*Double1d.range(500), 5000.0 + 5.0*Double1d.range(200),
6000.0 + 1.0*Double1d.range(1000), 7000.0 + 2.0*Double1d.range(500)]
resampled3 = resample(ds=spectra, density=True, grid=grid)
for i in range(len(grid)):
   grid[i] = grid[i] * 0.001
resampled3 = resample(ds=spectra, density=True, grid=grid, unit="GHz")
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, MANDATORY, default=no default value.]
SpectrumContainer **result** [OUTPUT, MANDATORY, default=no default value.]
String **scheme** [INPUT, OPTIONAL, default=no default value.]
Double1d[]|Double1d **grid** [INPUT, OPTIONAL, default=no default value.]

Properties
double **resolution** [INPUT, OPTIONAL, default=no default value.]
String **unit** [INPUT, OPTIONAL, default=no default value.]
Boolean **density** [INPUT, OPTIONAL, default=no default value.]

API details

Properties

SpectrumContainer ds [INPUT, MANDATORY, default=no default value.]

The input container to be resampled.

SpectrumContainer result [OUTPUT, MANDATORY, default=no default value.]

The output container with the re-sampled spectra.

String scheme [INPUT, OPTIONAL, default=no default value.]

The scheme to be adopted for the resampling - available are "standard" (or equivalently "trapezoidal") and "simple" (or equivalently "euler").

- The "standard" scheme combines a linear interpolation with a trapezoidal integration scheme.
- The "simple" scheme combines a nearest neighbor interpolation and an Euler integration scheme.

Both scheme are constructed such that total flux is conserved.

Double1d[]|Double1d grid [INPUT, OPTIONAL, default=no default value.]

The new frequency grid the spectra should be resampled to. It is specified as a Double1d for each of the sub-segments. The grid is specified in the same units as the original frequency data. The grid may be non-equidistant.

double resolution [INPUT, OPTIONAL, default=no default value.]

In case no output frequency grid is specified, the task creates an output grid with this given resolution (2 * width) by determining, for each sub-segment, the smallest minimum frequency and the largest maximum frequency. The width is specified in the same units as the original frequency grid. In case the width is specified as a negative number the resulting grid will be in decreasing order.

String unit [INPUT, OPTIONAL, default=no default value.]

The unit the resolution or the grid is expressed in.

Boolean density [INPUT, OPTIONAL, default=no default value.]

If set to true the flux data is treated as a flux density (per frequency unit) - otherwise the flux is treated as a per channel quantity.

History

- `2008-01-29 - meli`: initial.

- `2008-03-16 - meli`: major refactoring of the toolbox.
- `2008-09-30 - meli`: trapezoidal scheme used as standard (default); some refactoring (interpolation scheme implicit in integration scheme.
- `2008-10-03 - meli`: flag, weights processing, javadoc, ...

2.308. RESHAPE

Full Name:	herschel.ia.numeric.toolbox.basic.Reshape
Alias:	RESHAPE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Reshape

Description

Creates a new array of the same type as the input array but with a different shape.

The input array can be an array of any rank, and the output array has a rank defined by the specified shape argument.

The shape argument must be an array of integers such as [3,4], and the resulting array must have the same number of elements as the input array. If the shape argument is not specified, the result will always be a 1d-array.

Example

Example 1: Apply RESHAPE on a Int1d

```
x=Int1d.range(12)
print RESHAPE(x,[2,6])   # [[0,1,2,3,4,5],[6,7,8,9,10,11]]
print RESHAPE(x,[6,2])   # [[0,1],[2,3],[4,5],[6,7],[8,9],[10,11]]
print RESHAPE(x,[2,2,3]) # [[[0,1,2],[3,4,5]],[[6,7,8],[9,10,11]]]
print RESHAPE(TRANSPOSE(RESHAPE(x,[4,3])))
# [0,3,6,9,1,4,7,10,2,5,8,11]
```

API Summary

Jython Syntax

```
<y>=RESHAPE(<x>, [<shape>])
```

Properties

any array of integral type **x** [INPUT, MANDATORY, default=no default value]
array of integers **shape** [INPUT, NOT_MANDATORY, default=1d]
boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of integral type x [INPUT, MANDATORY, default=no default value]

The input array can be an array of any rank

array of integers shape [INPUT, NOT_MANDATORY, default=1d]

The shape argument must be an array of integers such as [3,4]. If the shape argument is not specified, the result will always be a 1d-array.

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]
Returns an array with the same number of elements as the input array and with shape equal to is specified or 1d if not specified.

See also

- CONCATENATE

2.309. restore

Full Name:	herschel.ia.toolbox.util.RestoreTask
Alias:	restore
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import RestoreTask
Category:	task

Description

Restore variables from a file to a jython session

The restore task is used to restore one or more variables from a file to a jython session. The restore task is used to save one or more variable from a previously saved file into the specified namespace.

Please note that when used for restoring values using the local() option the result might be unpredictable if not executed as first command. Please note that only Serializable variable can be saved.

Examples

Example 1: restore variables (names and values) from a file

```
restore("foo.sav")
```

Example 2: restore variables (names and values) from a file into a function namespace

```
def my_function():
 restore("test.sav", space=locals())
 print locals()
```

API Summary

Jython Syntax

```
restore(<filename>[, <space>])
```

Properties

```
String filename [INPUT, MANDATORY, default=No default value]
PyStringMap space [INPUT, OPTIONAL, default=globals()]
```

Limitations

Only Serializable variable saved can be restored, when using for restoring variables using locals result might be unpredictable if not executed as first command.

Miscellaneous

No miscellaneous

API details

Properties

String filename [INPUT, MANDATORY, default=No default value]
The name of the file where the variables along with their values are stored

PyStringMap space [INPUT, OPTIONAL, default=globals()]
A jython dictionary (PyStringMap) containing the namespace to load the variables into, The choices available are: 1. "locals()" for reading variables from the local namespace (i.e. from where the function is used) 2. "globals()" for reading variables from the module where the function is used When no space is specified the top level namespace is updated.

See also

- save

History

- 2004-07-13 - NdC: first release.
- 2009-01-21 - JDS: cleanup
- 2009-09-30 - JSS: modifiers are created through getCustomModifiers (SCR HCSS-8253)

2.310. resume

Full Name:	herschel.ia.toolbox.util.ResumeTask
Alias:	resume
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import ResumeTask
Category:	task

Description

Pause the execution of jython code

The resume task is used to resume the execution of jython after a call of pause. The resume can only be performed interactively from the debbuger window and not programmatically as jython doesn't execute code just after a pause call.

Example

Example 1: resume the jython execution (only available from the debug command window)

```
resume()
```

Limitations

Resume can only be performed interactively from the debbuger window

Miscellaneous

No miscellaneous

See also

- resume

History

- `2007-10-11 - NdC`: first release.

2.311. REVERSE

Full Name:	herschel.ia.numeric.toolbox.basic.Reverse
Alias:	REVERSE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Reverse

Description

Reverses the order of the elements in an array of rank 1

Example

Example 1: Apply REVERSE on a Double1d

```
print REVERSE(Double1d.range(3)) # [2.0,1.0,0.0]
```

API Summary

Jython Syntax

```
<y>=REVERSE(<x>)
```

Properties

any array of rank 1 **x** [INPUT, MANDATORY, default=no default value]

boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of rank 1 x [INPUT, MANDATORY, default=no default value]

The input array can be an array of rank 1

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns an array with the same number of elements as the input array and with the reverse order.

2.312. RgbSimpleImage

Full Name:	herschel.ia.dataset.image.RgbSimpleImage
Type:	Java Class -
Import:	from herschel.ia.dataset.image import RgbSimpleImage
Category:	Image

Description

A Product describing three color images.

RgbSimpleImage is a Product describing three color images.

Example

Example 1: Creating a RgbSimpleImage

```
s = RgbSimpleImage()
s.setImage(myDouble2dRedImage, myDouble2dGreenImage, myDouble2dBlueImage)
```

API Summary

Constructors
RgbSimpleImage()
The standard constructor
RgbSimpleImage(String description)
Constructor with a description
RgbSimpleImage(Int2d red, Int2d green, Int2d blue)
The standard constructor
RgbSimpleImage(RgbSimpleImage copy)
Copy constructor

Methods
setRedImage(Int2d red)
Sets the red part of the image.
setGreenImage(Int2d green)
Sets the green part of the image.
setBlueImage(Int2d blue)
Sets the blue part of the image.
RgbImage **getPreview**(float res)
Returns a preview of the image
int **getHeight**()
Returns the height.
Int2d **getRedImage**()
returns the red image as a Int2d.
Int2d **getGreenImage**()

Methods
returns the green image as an Int2d.
`Int2d getBlueImage()` returns the blue image as an Int2d.
`Unit getUnit()` Returns the unit.
`int getWidth()` Returns the width
`setUnit(Unit unit)` Sets the unit.
`int[] getDimensions()` Returns the dimension.
`Wcs getWcs()` Returns the World Coordinates System.
`setWcs(Wcs wcs)` Sets the world coordinates system.

API details

Constructors

RgbSimpleImage()

The standard constructor

A constructor which creates a standard RgbSimpleImage.

Example

Typical example on how to create an RgbSimpleImage.

```
image=RgbSimpleImage()
```

RgbSimpleImage(String description)

Constructor with a description

Creates an RgbSimpleImage with a given description.

Argument

`String` **description** [INPUT, MANDATORY]

RgbSimpleImage(Int2d red, Int2d green, Int2d blue)

The standard constructor

A constructor which creates a standard RgbSimpleImage. The standard SimpleImage consists of 3 Numeric2ds for the image

Arguments

`Int2d` **red** [INPUT, MANDATORY]

`Int2d` **green** [INPUT, MANDATORY]

`Int2d` **blue** [INPUT, MANDATORY]

RgbSimpleImage(Int2d red, Int2d green, Int2d blue)

Example

Typical example on how to create an RgbSimpleImage.

```
image=RgbSimpleImage(redImage, greenImage, blueImage, description="ngc
6992", wcs=wcs)
```

RgbSimpleImage(RgbSimpleImage copy)

Copy constructor

Constructor which makes a copy from an existent RgbSimpleImage.

Argument

RgbSimpleImage **copy** [INPUT, MANDATORY]

Methods

setRedImage(Int2d red)

Sets the red part of the image.

Sets the red part of the image.

Argument

Int2d **red** [INPUT, MANDATORY]

setGreenImage(Int2d green)

Sets the green part of the image.

Sets the green part of the image.

Argument

Int2d **green** [INPUT, MANDATORY]

setBlueImage(Int2d blue)

Sets the blue part of the image.

Sets the blue part of the image.

Argument

Int2d **blue** [INPUT, MANDATORY]

RgbImage getPreview(float res)

Returns a preview of the image

Returns a new RgbSimpleImage, but with a lower resolution if res is smaller than 1. A higher resolution is returned, if res is larger than 1. The spatial regridding is based on linear interpolation which will, in general, not be suitable for scientific purposes.

Argument

float **res** [INPUT, MANDATORY]

Return

RgbImage

The preview of the image

`int getHeight()`

Returns the height.

Returns the height of this RgbSimpleImage.

Return

int

The height of this RgbSimpleImage.

`Int2d getRedImage()`

returns the red image as a Int2d.

Returns the image as an Int2d containing the data of the red image.

Return

Int2d

The red image as an Int2d

`Int2d getGreenImage()`

returns the green image as an Int2d.

Returns the image as an Int2d containing the data of the green image.

Return

Int2d

The green image as an Int2d

`Int2d getBlueImage()`

returns the blue image as an Int2d.

Returns the image as an Int2d containing the data of the blue image.

Return

Int2d

The blue image as an Int2d

`Unit getUnit()`

Returns the unit.

Returns the unit of the image. The unit of the errors of this image is the same as the unit of the image.

Return

Unit

The unit

`int getWidth()`

Returns the width

int getWidth()

Returns the width of this SimpleImage.

Return

int

The width of this SimpleImage.

setUnit(Unit unit)

Sets the unit.

Sets the unit of the image.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

int[] getDimensions()

Returns the dimension.

Returns the dimension (width, height) of this RgbSimpleImage.

Return

int[]

The dimension (width, height) of this RgbSimpleImage.

Wcs getWcs()

Returns the World Coordinates System.

Returns the World Coordinates System of the image.

Return

Wcs

The World Coordinates System of the image.

setWcs(Wcs wcs)

Sets the world coordinates system.

Sets the world coordinates system of the image.

Argument

`Wcs` **`wcs`** `[INPUT, MANDATORY]`

2.313. Rotate

Full Name:	herschel.ia.numeric.toolbox.basic.Rotate
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Rotate

Description

Rotates numeric 2d and 3d arrays.

The result is an array of the double type. The returned array is usually larger than the original because a rotation of a rectangle array creates empty corners. The corners are filled with 0 by default. (This does not happen with rotations around multiples of 90 degrees).

The rotation is always around the center of the array. That means the result contains the complete rotated array without any cuts.

Possible interpolation is nearest neighbor, bilinear und bicubic.

The interpolation quality depends on the rotation angle and on the interpolation method. It can be measured as a sum over all array indexes. An example is presented with an 200X255 Int2d array. It is constructed as follows:

```
array = Int2d();
for i in range(200):
array.append(Int1d.range(255),1)
```

The sum is 6477000

With a rotation angle of 54 deg clockwise the sums are:

Nearest neighbor: 6477268 (0.004% accurate)

Bilinear: 6447345 (0.46% accurate)

Bicubic: 6451030 (0.40% accurate)

Example

Example 1: apply Rotate to a Int2d array

```
Clockwise nearest neighbour rotation (default)
 result = Rotate(54.0)( array -)
Counterclockwise nearest neighbour rotation
 result = Rotate(-54.0)( array -)
Clockwise bicubic rotation
 result = Rotate(54.0, Rotate.BICUBIC) ( array -) or
 result = Rotate(54.0, 3) ( array -)
Counterclockwise bilinear rotation
 result = Rotate(54.0, Rotate.BILINEAR, False) ( array -)
 array = Int2d();
 for i in range(5):
     array.append(Int1d.range(5),1)
print array
[
[0,0,0,0,0],
[1,1,1,1,1],
[2,2,2,2,2],
[3,3,3,3,3],
[4,4,4,4,4]
```

Example 1: apply Rotate to a Int2d array

```
]
print Rotate(90) ( array -)
[
[4.0,3.0,2.0,1.0,0.0],
[4.0,3.0,2.0,1.0,0.0],
[4.0,3.0,2.0,1.0,0.0],
[4.0,3.0,2.0,1.0,0.0],
[4.0,3.0,2.0,1.0,0.0]
]
```

API Summary

Jython Syntax

```
<y> = <x>.apply( Rotate(angle, interpolation method, clockwise) )
or
<y> = Rotate(angle, interpolation method, clockwise)( <x> )
```

Properties

any 2- or 3d array of integral type **x** [INPUT, MANDATORY, default=no default value]
the rotation angle in degrees (360 based) **angle** [INPUT, MANDATORY, default=no default value]
the interpolation method **interpolation method** [INPUT, NOT_MANDATORY, default=Rotate.NEAREST_NEIGHBOR]
the direction of rotation **clockwise** [INPUT, NOT_MANDATORY, default=true]
DoubleNd array (same rank as the input array) **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any 2- or 3d array of integral type x [INPUT, MANDATORY, default=no default value]

the rotation angle in degrees (360 based) angle [INPUT, MANDATORY, default=no default value]

the angle can be positive or negative

the interpolation method interpolation method [INPUT, NOT_MANDATORY, default=Rotate.NEAREST_NEIGHBOR]

the possible values for the interpolation method are

Rotate.NEAREST_NEIGHBOR = 1

Rotate.BILINEAR = 2

Rotate.BICUBIC = 3

the direction of rotation clockwise [INPUT, NOT_MANDATORY, default=true]

clockwise is a boolean and has the value True for clockwise rotation and False for counterclockwise rotation.

DoubleNd array (same rank as the input array) y [OUTPUT, MANDATORY, default=no default value]

Returns a Double2d array, if the input was a 2d array. Returns a Double3d array if the input was a 3d array. 3d arrays are treated as a stack of 2d arrays. Rotation is done around the depth (3rd) dimension.

2.314. rotate

Full Name:	herschel.ia.toolbox.image.RotateTask
Alias:	rotate
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import RotateTask
Category:	task/image

Description

A Task that rotates images.

A task which rotates an Image. The Wcs is also adapted. It is possible to use 4 types of interpolation :

- INTERP_NEAREST : nearest-neighbor interpolation. Nearest-neighbor interpolation is simply pixel copying
- INTERP_BILINEAR : Bilinear interpolation requires a neighborhood extending one pixel to the right and below the central sample. If the fractional subsample position is given by (xfrac, yfrac), the resampled pixel value will be:

```
(1 -- yfrac) * [(1 -- xfrac)*s00 + xfrac*s01] + yfrac * [(1 -- xfrac)*s10 + xf\
rac*s11]
```

  A neighborhood extending one sample to the right of, and one sample below the central sample is required to perform bilinear interpolation. This implementation maintains equal subsampleBits in x and y.

- INTERP_BICUBIC : InterpolationBicubic is a subclass of Interpolation that performs interpolation using the piecewise cubic polynomial:

```
 r(x) = (a + 2)|x|^3 -- (a + 3)|x|^2  +  1 -, 0 <= -|x| < 1
r(x) = a|x|^3 -- 5a|x|^2 + 8a|x| -- 4a -, 1 <= -|x| < 2
r(x) = 0, otherwise
```

  with 'a' set to -0.5. This definition is also sometimes known as "cubic convolution", using the parameter 'a' recommended by Rifman. (Reference: Digital Image Warping, George Wolberg, 1990, pp 129-131, IEEE Computer Society Press, ISBN 0-8186-8944-7)

  A neighborhood extending one sample to the left of and above the central sample, and two samples to the right of and below the central sample is required to perform bicubic interpolation.

- INTERP_BICUBIC_2 : InterpolationBicubic2 is a subclass of Interpolation that performs interpolation using the piecewise cubic polynomial:

```
 r(x) = (a + 2)|x|^3 -- (a + 3)|x|^2  +  1 -, 0 <= -|x| < 1
r(x) = a|x|^3 -- 5a|x|^2 + 8a|x| -- 4a -, 1 <= -|x| < 2
r(x) = 0, otherwise
```

  with 'a' set to -1.0. This definition is also sometimes known as "cubic convolution", using the parameter 'a' recommended by Keys. This interpolator may produce somewhat sharper results than InterpolationBicubic, but that result is image dependent. (Reference: Digital Image Warping, George Wolberg, 1990, pp 129-131, IEEE Computer Society Press, ISBN 0-8186-8944-7)

  A neighborhood extending one sample to the left of and above the central sample, and two samples to the right of and below the central sample is required to perform bicubic interpolation.

When no interpolation is set, BiLinear interpolation (INTERP_BILINEAR) is taken as standard. INTERP_BICUBIC and INTERP_BICUBIC_2 need an extra parameter (subsample precision, in bits)

to be set. If the subsample precision is not set explicitely, the value will be 16. The errors are not calculated. At the moment, the same operation is executed on the errors. The Wcs is not always calculated exactly.

Examples

Example 1: Rotating an image over 12.2 degrees (counterclockwise for astronomical image, clockwise for other images)

```
rotate(image = im, angle = 12.2)
```

Example 2: Rotating an image over 12.2 degrees (counterclockwise for astronomical image, clockwise for other images), using Bicubic interpolation, using 32 bits

```
rotate(image = im, angle = 12.2, interpolation = Rotate.INTERP_BICUBIC,
subsampleBits = 32)
```

API Summary

Jython Syntax

```
rotate(image, 12.2, Rotate.INTERP_BICUBIC)
```

Properties

Image **image** [INPUT, MANDATORY, default=No default value]

float **angle** [INPUT, OPTIONAL, default=0.0]

int **interpolation** [INPUT, OPTIONAL, default=Rotate.INTERP_NEAREST]

int **subsampleBits** [INPUT, OPTIONAL, default=16.0]

Image **rotatedImage** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The Image to rotate.

float angle [INPUT, OPTIONAL, default=0.0]

The amount of degrees to rotate the image (counterclockwise for astronomical image, clockwise for other images).

int interpolation [INPUT, OPTIONAL, default=Rotate.INTERP_NEAREST]

The type of interpolation to use (INTERP_NEAREST, INTERP_NEAREST, INTERP_BICUBIC, INTERP_BICUBIC_2).

int subsampleBits [INPUT, OPTIONAL, default=16.0]

The number of bits to use for the interpolation (only if interpolation is INTERP_BICUBIC or INTERP_BICUBIC_2).

Image rotatedImage [OUTPUT, MANDATORY, default=No default value]

The rotated Image.

2.315. RotateTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.RotateTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import RotateTaskSignatureComponent

Description

A task dialog for the RotateTask.

A task dialog to serve as GUI for the RotateTask.

API Summary

Constructor
RotateTaskSignatureComponent() The construction of a new RotateTaskSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
getParameters() Returns a map of parameters and modifiers storing the values selected by the user.
setVariableSelection(VariableSelection selection) Setting the variable selection.
setSignature(SignatureApi sig) Setting the signature.
JComponent **getComponent()** Returns the component.

API details

Constructor

RotateTaskSignatureComponent()
The construction of a new RotateTaskSignatureComponent. The construction of a new RotateTaskSignatureComponent.

Methods

check()
Validates the current modifications. Validates the current modifications for this RotateTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this RotateTaskSignatureComponent.

getParameters()

Returns a map of parameters and modifiers storing the values selected by the user.

Returns a map of parameters and modifiers storing the values selected by the user for this RotateTaskSignatureComponent.

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this RotateTaskSignatureComponent.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

setSignature(SignatureApi sig)

Setting the signature.

Sets the given signature as the signature for this RotateTaskSignatureComponent.

Argument

`SignatureApi` **`sig`** `[INPUT, MANDATORY]`

JComponent getComponent()

Returns the component.

Returns the component for this RotateTaskSignatureComponent.

Return

JComponent

Returns the component for this RotateTaskSignatureComponent.

2.316. ROUND

Full Name:	herschel.ia.numeric.toolbox.basic.Round
Alias:	ROUND
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Round

Description

Gives a rounded result of an array.

It can perform the operation over a decimal position (second argument) or over the integer part (no second argument or equals to '0'). For rounding to the closest integer representation, the result is functionally equivalent to adding 1/2 and taking the floor of the result. The function returns a float array for float input array and double array for any other numeric array type.

Example

Example 1: Apply ROUND on a Double1d

```
x=Double1d([-0.5001, --0.5, --0.4999, 0.4999, 0.5, 0.5001, 1.1234, 2.6236])
print ROUND(x)   #[-1.0, 0.0,  0.0,  0.0, 1.0, 1.0, 1.0,   3.0]
print ROUND(x,3) #[-0.5, --0.5, --0.5, 0.5, 0.5, 0.5, 1.123, 2.624]
```

API Summary

Jython Syntax

```
<y>=ROUND(<x>[,<n>])
```

Properties

any array of any rank **x** [INPUT, MANDATORY, default=no default value]

decimal position for rounding **n** [INPUT, OPTIONAL, default=0]

float or double array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of any rank x [INPUT, MANDATORY, default=no default value]

The input array can be an array of any type (except String and Complex) of any rank.

decimal position for rounding n [INPUT, OPTIONAL, default=0]

The decimal position for rounding. By default, it rounds to the closest integer value.

float or double array y [OUTPUT, MANDATORY, default=no default value]

Returns a float array for float input array and double array for any other numeric array type.

See also

- CEIL
- FLOOR

2.317. RowByRowAverageSpectrum

Full Name:	herschel.ia.toolbox.spectrum.RowByRowAverageSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import RowByRowAverageSpectrum

Description

Task for averaging two {@link SpectrumContainer} datasets on a scan-by-scan basis.

Included here for backwards compatibility reasons.

History

- `2007-08-17 - meli`: initial.
- `2008-03-16 - meli`: major refactoring of the toolbox.

2.318. save

Full Name:	herschel.ia.toolbox.util.SaveTask
Alias:	save
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import SaveTask
Category:	task

Description

Save variables from the jython session to a file

The save task is used to save one or more variable from the jython global namespace into the specified file. Variables can be specified with a string containing a comma separated list of variable names, if no variables are specified the entire namespace is saved.

Please note that only Serializable variable can be saved.

Examples

Example 1: save all global variable names and values

```
save("foo.sav")
```

Example 2: save specific variable names and values

```
save("foo.sav","x,y,z")
```

Example 3: save specified variable names and values from the local namespace of a function

```
def my_function():
 x=100
 y=23
 save("test.sav","x,y", space=locals())
my_function()
```

API Summary

Jython Syntax

```
save(<filename>[, <variable>][, <space>])
```

Properties

```
String filename [INPUT, MANDATORY, default=No default value]
String variable [INPUT, OPTIONAL, default=""]
PyStringMap space [INPUT, OPTIONAL, default=globals()]
```

Limitations

Only Serializable variables can be saved

Miscellaneous

No miscellaneous

API details

Properties

String filename [INPUT, MANDATORY, default=No default value]

The name of the file to store the values of variables.

String variable [INPUT, OPTIONAL, default=""]

The comma-separated list of variables to save.

PyStringMap space [INPUT, OPTIONAL, default=globals()]

A jython dictionary (PyStringMap) containing the namespace of the variables, The choices available are:

1. locals() for using variables from the local namespace (i.e. from where the function is used)
2. globals() for using variables from the module where the function is used

When no space is specified the top level namespace is updated.

See also

- restore

History

- 2004-07-13 - NdC: first release.
- 2009-01-14 - JDS: cleanup
- 2009-09-30 - JSS: modifiers are created through getCustomModifiers (SCR HCSS-8253)

2.319. scale

Full Name:	herschel.ia.toolbox.image.ScaleTask
Alias:	scale
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import ScaleTask
Category:	task/image

Description

A Task to scale images.

A task to scale images. The Wcs is also adapted. It is possible to use 4 types of interpolation :

- INTERP_NEAREST : nearest-neighbor interpolation. Nearest-neighbor interpolation is simply pixel copying
- INTERP_BILINEAR : Bilinear interpolation requires a neighborhood extending one pixel to the right and below the central sample. If the fractional subsample position is given by (xfrac, yfrac), the resampled pixel value will be:

```
(1 -- yfrac) * [(1 -- xfrac)*s00 + xfrac*s01] + yfrac * [(1 -- xfrac)*s10 + xf\
rac*s11]
```

  A neighborhood extending one sample to the right of, and one sample below the central sample is required to perform bilinear interpolation. This implementation maintains equal subsampleBits in x and y.

- INTERP_BICUBIC : InterpolationBicubic is a subclass of Interpolation that performs interpolation using the piecewise cubic polynomial:

```
r(x) = (a + 2)|x|^3 -- (a + 3)|x|^2 +  1 -, 0 <= -|x| < 1
r(x) = a|x|^3 -- 5a|x|^2 + 8a|x| -- 4a -, 1 <= -|x| < 2
r(x) = 0, otherwise
```

  with 'a' set to -0.5. This definition is also sometimes known as "cubic convolution", using the parameter 'a' recommended by Rifman. (Reference: Digital Image Warping, George Wolberg, 1990, pp 129-131, IEEE Computer Society Press, ISBN 0-8186-8944-7)

  A neighborhood extending one sample to the left of and above the central sample, and two samples to the right of and below the central sample is required to perform bicubic interpolation.

- INTERP_BICUBIC_2 : InterpolationBicubic2 is a subclass of Interpolation that performs interpolation using the piecewise cubic polynomial:

```
 r(x) = (a + 2)|x|^3 -- (a + 3)|x|^2 +  1 -, 0 <= -|x| < 1
r(x) = a|x|^3 -- 5a|x|^2 + 8a|x| -- 4a -, 1 <= -|x| < 2
r(x) = 0, otherwise
```

  with 'a' set to -1.0. This definition is also sometimes known as "cubic convolution", using the parameter 'a' recommended by Keys. This interpolator may produce somewhat sharper results than InterpolationBicubic, but that result is image dependent. (Reference: Digital Image Warping, George Wolberg, 1990, pp 129-131, IEEE Computer Society Press, ISBN 0-8186-8944-7)

  A neighborhood extending one sample to the left of and above the central sample, and two samples to the right of and below the central sample is required to perform bicubic interpolation.

When no interpolation is set, BiLinear interpolation (INTERP_BILINEAR) is taken as standard. INTERP_BICUBIC and INTERP_BICUBIC_2 need an extra parameter (subsample precision, in bits)

to be set. If the subsample precision is not set explicitely, the value will be 16. The errors are not calculated. At the moment, the same operation is executed on the errors.

Examples

Example 1: Scaling an image by a factor 1.4 in x-direction, and -0.4 in y-direction (meaning flipping and scaling it by 0.4)

```
scale(image = im, x = 1.4, y = 0.4)
```

Example 2: Scaling an image by a factor 1.4 in x-direction, and 0.4 in y-direction, using Bicubic interpolation, using 32 bits

```
scale(image = im, x = 1.4, y = 0.4, interpolation = Scale.INTERP_BICUBIC,
subsampleBits = 32)
```

API Summary

Jython Syntax

```
scale(image, 1.4, 0.4, ScaleTask.INTERP_BICUBIC, 32)
```

Properties

Image **image** [INPUT, MANDATORY, default=No default value]
float **x** [INPUT, OPTIONAL, default=1.0]
float **y** [INPUT, OPTIONAL, default=1.0]
int **interpolation** [INPUT, OPTIONAL, default=Rotate.INTERP_NEAREST]
int **subsampleBits** [INPUT, OPTIONAL, default=16.0]
Image **scaledImage** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The input image that has to be scaled.

float x [INPUT, OPTIONAL, default=1.0]

The scale factor in x-direction.

float y [INPUT, OPTIONAL, default=1.0]

The scale factor in y-direction.

int interpolation [INPUT, OPTIONAL, default=Rotate.INTERP_NEAREST]

The type of interpolation to use (INTERP_NEAREST, INTERP_NEAREST, INTERP_BICUBIC, INTERP_BICUBIC_2).

int subsampleBits [INPUT, OPTIONAL, default=16.0]

The number of bits to use for the interpolation (only if interpolation is INTERP_BICUBIC or INTERP_BICUBIC_2).

Image scaledImage [OUTPUT, MANDATORY, default=No default value]
The scaled image.

2.320. ScaleTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.ScaleTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import ScaleTaskSignatureComponent

Description

The task dialog for the ScaleTask.

A task dialog to serve as GUI for the ScaleTask.

API Summary

Constructor
ScaleTaskSignatureComponent() The construction of a new ScaleTaskSignatureComponent.

Methods
check() Validates the current modifications.
clear() Clears the current modifications.
getParameters() Returns a map of parameters and modifiers storing the values selected by the user.
setVariableSelection(VariableSelection selection) Setting the variable selection.
setSignature(SignatureApi sig) Setting the signature.
JComponent **getComponent()** Returns the component.

API details

Constructor

ScaleTaskSignatureComponent()
The construction of a new ScaleTaskSignatureComponent. The construction of a new ScaleTaskSignatureComponent.

Methods

check()
Validates the current modifications. Validates the current modifications for this RotateTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this ScaleTaskSignatureComponentt.

getParameters()

Returns a map of parameters and modifiers storing the values selected by the user.

Returns a map of parameters and modifiers storing the values selected by the user for this ScaleTaskSignatureComponent.

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this ScaleTaskSignatureComponentt.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

setSignature(SignatureApi sig)

Setting the signature.

Sets the given signature as the signature for this ScaleTaskSignatureComponentt.

Argument

`SignatureApi` **`sig`** `[INPUT, MANDATORY]`

JComponent getComponent()

Returns the component.

Returns the component for this ScaleTaskSignatureComponent.

Return

JComponent

Returns the component for this ScaleTaskSignatureComponent.

2.321. SelectSpectrum

Full Name:	herschel.ia.toolbox.spectrum.SelectSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import SelectSpectrum

Description

Task for selecting individual spectra from a `SpectrumContainer` or fromw arrays of such and pack them in a new spectrum container.

Different selection schemes are available for specifying the selection:

- segments: The most simple scheme is to use 'segments' where you specify which point spectra and subsegments therein you want to select.
- selection_lookup: Specify a PyDictionary with column names as keys and a PyList of admissible values as values.
- selection: General selection model (type SelectionModel) that allows you to specify selections such as select all rows with values in a given column lying in a predefined interval.
- selection_index: Specify a PyList of indices that reference the point spectra included in the container.

The different options to specify selections can be combined. Here, an AND logic is adopted.

Example

Example 1: from jide:

```
from herschel.ia.toolbox.spectrum import SelectSpectrum
from herschel.ia.toolbox.spectrum.selections.models import RangesSelectionModel
select = SelectSpectrum()
selected = select(ds=spectra, segments=[1,3])
selected = select(ds=spectra, selection={"bbtype":[6031, 6032], -"buffer":[2]})
selected = select(ds=spectra, selection=[0,1,2,3])
selected = select(ds=spectra, selection={"LoFrequency":(4000.0,5000.0)})
selected = select(ds=spectra, selection={"Chopper":([-4.4,5.9],0.1))
from herschel.ia.toolbox.spectrum.selections.models import RangesSelectionModel
selected = select(ds=spectra, selection=RangesSelectionModel("Chopper",
[-4.4,5.9], 0.1)) # the same as above
```

API Summary

Properties
Object **ds** [INPUT, OPTIONAL, default=no default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection_lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection_index** [INPUT, OPTIONAL, default=No default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

Object ds [INPUT, OPTIONAL, default=no default value.]

Input data to be processed by the task. Several types are possible:

- SpectrumContainer
- Array of SpectrumContainer, i.e. SpectrumContainer[]
- List of SpectrumContainer, i.e. List
- Any product with implementations of `SpectrumContainer` inside.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments to restrict on. There are two options available:

- Specify a PyList of segment indices or
- pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.

Object selection [INPUT, OPTIONAL, default=None.]

Specification of what point spectra select. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra to select.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

See also

- ManyToOneSpectrumTask

History

- `2007-06-01 - meli`: initial.
- `2007-07-13 - meli`: Javadoc updated.
- `2008-03-16 - meli`: major refactoring of the toolbox.
- `2008-10-03 - meli`: segments, javadoc

2.322. SerialArchive

Full Name:	herschel.ia.io.serial.SerialArchive
Alias:	SerialArchive
Type:	Java Class -
Import:	from herschel.ia.io.serial import SerialArchive
Category:	class

Description

A class for writing and reading serialized objects.

The SerialArchive provides a transparent way to store and retrieve Products as defined within the Herschel Data Processing software.

Example

Example 1: default usage:

```
from herschel.ia.io.serial import SerialArchive
# write/read a Product in a serialized file.
s = SerialArchive()
s.save("output.ser", Product())
p = s.load("output.ser")
```

API Summary

Methods
`Product load(InputStream stream)` Loads a Product from an input stream.
`Product load(String fileName)` Loads a Product from a serialized file.
`save(String fileName, [Optionally derived] Product product)` Saves a Product to a serialized file.
`createOutputStream(String fileName)` Creates an object output stream for storing in a file.
`createOutputStream(OutputStream file)` Creates an object output stream for storing in a file.
`createOutputStream(OutputStream stream)` Creates an object output stream for storing in a file.
`createInputStream(String fileName)` Creates an object input stream for reading from a file.
`createInputStream(String file)` Creates an object input stream for reading from a file.
`createInputStream(InputStream stream)` Creates an object input stream for reading from a file.

API details

Methods

`Product load(InputStream stream)`

Loads a Product from an input stream.

Loads a Product from an input stream using a serial reader.

Argument

`InputStream` **`stream`** `[INPUT, MANDATORY, default=no default value]`

Input stream from where the Product is to be read.

Return

Product

An object of the herschel.ia.dataset.Product family.

`Product load(String fileName)`

Loads a Product from a serialized file.

Loads a Product from a serialized file using a serial reader.

Argument

`String` **`fileName`** `[INPUT, MANDATORY, default=no default value]`

Name of the serialized file.

Return

Product

An object of the herschel.ia.dataset.Product family.

`save(String fileName, [Optionally derived] Product product)`

Saves a Product to a serialized file.

Saves a Product to a serialized file with sufficient information to preserve the quantities of the data as well as the original dataset type and contents.

Arguments

`String` **`fileName`** `[INPUT, MANDATORY, default=no default value]`

Name of the serialized file

`[Optionally derived] Product` **`product`** `[INPUT, MANDATORY, default=no default value]`

An object of the herschel.ia.dataset.Product family.

`createOutputStream(String fileName)`

Creates an object output stream for storing in a file.

Creates an object output stream for storing objects in a file, by calling its writeObject method. The returned stream treats Products and Datasets as as special case, so that intermediate classes (resolvers) can manage them appropiately, even in the presence of different package names or class versions.

createOutputStream(String fileName)

Argument

`String` **fileName** [INPUT, MANDATORY]

createOutputStream(OutputStream file)

Creates an object output stream for storing in a file.

Creates an object output stream for storing objects in a file, by calling its writeObject method. The returned stream treats Products and Datasets as as special case, so that intermediate classes (resolvers) can manage them appropiately, even in the presence of different package names or class versions.

Argument

`OutputStream` **file** [INPUT, MANDATORY, default=no default value]

File in which the data is to be serialized

createOutputStream(OutputStream stream)

Creates an object output stream for storing in a file.

Creates an object output stream for storing objects in a file, by calling its writeObject method. The returned stream treats Products and Datasets as as special case, so that intermediate classes (resolvers) can manage them appropiately, even in the presence of different package names or class versions.

Argument

`OutputStream` **stream** [INPUT, MANDATORY, default=no default value]

Stream to be wrapped

createInputStream(String fileName)

Creates an object input stream for reading from a file.

Creates an object input stream for reading objects from a file, by calling its readObject method. The returned stream treats Products and Datasets as as special case, so that intermediate classes (resolvers) can manage them appropiately, even in the presence of different package names or class versions.

Argument

`String` **fileName** [INPUT, MANDATORY]

createInputStream(String file)

Creates an object input stream for reading from a file.

Creates an object input stream for reading objects from a file, by calling its readObject method. The returned stream treats Products and Datasets as as special case, so that intermediate classes (resolvers) can manage them appropiately, even in the presence of different package names or class versions.

Argument

`String` **file** [INPUT, MANDATORY, default=no default value]

Name of the serialized file

createInputStream(InputStream stream)

Creates an object input stream for reading from a file.

createInputStream(InputStream stream)

Creates an object input stream for reading objects from a file, by calling its readObject method. The returned stream treats Products and Datasets as as special case, so that intermediate classes (resolvers) can manage them appropiately, even in the presence of different package names or class versions.

Argument

`InputStream` **`stream`** `[INPUT, MANDATORY, default=no default value]`

Stream to be wrapped

See also

- FitsArchive

2.323. SerialClientPool

Full Name:	herschel.ia.pal.pool.serial.SerialClientPool
Type:	Java Class -
Import:	from herschel.ia.pal.pool.serial import SerialClientPool

Description

A ProductPool implementation used for accessing products stored on a

remote pool across the network.

In order to use this, two things need to be set up first at the remote site:

1. A ProductPool implementation should be created.
2. A SerialServer is running, that talks to the remote ProductPool and relays data back/forth to the SerialClientPool via an accessible network port.

Make a note of the URL at which the server is running (eg "myserver.esa.int"), the ID of the remote product pool, and the port number at which data is relayed.

Examples

Example 1: Creating the remote pool and SerialServer. The SerialServer relays

```
data via port 4444 server=SerialServer(4444,
SimplePool.getInstance())
```

Example 2: Create a SerialClientPool that talks to the remote pool of ID

```
"simple.default" at site of URL -"remotehost.esa.int", port 4444
storage=ProductStorage()
storage.register(SerialClientPool("myserver.esa.int", 4444,
"simple.default" -))
```

API Summary

Constructor
SerialClientPool(String hostName, String portNumber, String id)
Creates an instance of a SerialClientPool connected to a remote

API details

Constructor

SerialClientPool(String hostName, String portNumber, String id)

Creates an instance of a SerialClientPool connected to a remote

pool.

Arguments

String **hostName** [INPUT, MANDATORY, default=The URL at which the]

SerialClientPool(String hostName, String portNumber, String id)

remote server is running, eg "remotehost.esa.int"

`String` **portNumber** `[INPUT, MANDATORY, default=The port number on which]`

the remote server is running, eg 4444

`String` **id** `[INPUT, MANDATORY, default=The identifier for the remote]`

pool, eg "simple.mypool"

Return

SerialClientPool

An instance of the SerialClientPool.

2.324. SHIFT

Full Name:	herschel.ia.numeric.toolbox.basic.Shift
Alias:	SHIFT
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Shift

Description

Creates a new array out of the input array with a circular shift applied to

all elements along specified dimension.

Examples

Example 1: Apply SHIFT on a Int1d

```
x=Int1d([0,1,2,3,4,5,6,7,8,9,10,11])
print SHIFT(x,-3)     # [3,4,5,6,7,8,9,10,11,0,1,2]
```

Example 2: Apply SHIFT on a Int2d

```
x=Int2d([[0,1,2,3],[4,5,6,7],[8,9,10,11]])
print SHIFT(x,2)     # [[4,5,6,7],[8,9,10,11],[0,1,2,3]]
print SHIFT(x,2,1)   # [[2,3,0,1],[6,7,4,5],[10,11,8,9]]
```

API Summary

Jython Syntax

```
<y>=SHIFT(<x>,<shift>,<dimension=0>)
```

Properties

- any array of any rank **x** [INPUT, MANDATORY, default=no default value]
- integer **shift** [INPUT, MANDATORY, default=no default value]
- integer **dimension** [INPUT, MANDATORY, default=no default value]
- boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array of any rank x [INPUT, MANDATORY, default=no default value]

The input array can be an array of rank 1

integer shift [INPUT, MANDATORY, default=no default value]

The number of element to shift

integer dimension [INPUT, MANDATORY, default=no default value]

The dimension to apply the shift to

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns an array with the same number of elements as the input array and with the reverse order.

2.325. Short1d

Full Name:	herschel.ia.numeric.Short1d
Type:	Java Class -
Import:	from herschel.ia.numeric import Short1d

Description

A rectangular numeric short array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.326. Short2d

Full Name:	herschel.ia.numeric.Short2d
Type:	Java Class -
Import:	from herschel.ia.numeric import Short2d

Description

A rectangular numeric short array of rank 2.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.327. Short3d

Full Name:	herschel.ia.numeric.Short3d
Type:	Java Class -
Import:	from herschel.ia.numeric import Short3d

Description

A rectangular numeric short array of rank 3.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.328. Short4d

Full Name:	herschel.ia.numeric.Short4d
Type:	Java Class -
Import:	from herschel.ia.numeric import Short4d

Description

A rectangular numeric short array of rank 4.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.329. Short5d

Full Name:	herschel.ia.numeric.Short5d
Type:	Java Class -
Import:	from herschel.ia.numeric import Short5d

Description

A rectangular numeric short array of rank 5.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.330. SIGCLIP

Full Name:	herschel.ia.numeric.toolbox.basic.Sigclip
Alias:	SIGCLIP
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Sigclip

Description

Sigclip finds values in an array that are more than n*(standard deviation) larger than a comparator (the median or mean

value). The comparator can be calculated for a running box of user defined size (behavior = filter - default) or for the whole array (behavior = clip). Sigclip replaces these higher values with the comparator. In filter mode Sigclip does not include the investigated Pixel for the computation of the comparator and the sigma. The user has the choice of 8 parameters: 1. envSize: the size of the environment of surrounding pixels. If i is the coordinate of the tested pixel, the environment will be [i-envSize, i+envSize] in the 1d case. For multi-dimenional arrays the box is extended in all dimensions. The default value for envSize is 3. 2. nsigma: the number of sigmas that a value has to exceed its next smaller value before it will be replaced. The default value is also 3. 3. The returnmode: Sigclip.RETURN_ARRAY (=0) returns a copy of the input array with the replaced values. Sigclip.RETURN_BOOL (=1) returns a boolean array where the clipped locations are marked as true (the other values are false). 4. the mode: Sigclip.MEAN or Sigclip.MEDIAN determines if median or mean of the neighbouring values is used to replace a sigclipped value 5. the treatment at the array edges. This is defined with the method setEdge(int edge). The choices are: Sigclip.TRUNCATE (default: scales down the boxsize), Sigclip.FILL_EDGEVALUE (fills the empty indices of the box with the last value of the array) , Sigclip.FILL_MEAN (fills the empty indices of the box with the mean of the rest of the box array) and Sigclip.FILL_MEDIAN (fills the empty indices of the box with the median of the rest of the box array) 6. the treatment of the outliers. outliers = "positve" removes only the values that are larger than the comparator (median or mean). This is the default. Other possible values are outliers = "negative" or outliers = "both". deprecation: the default value for outliers is deprecated. Currently it is "positive", but it will be changed to "both". The deprecation is best treated in your code by explicitely specifying the value for outliers! 7. The behavior as filter (default) or clip. behavior = "filter" uses the box of size env and lets Sigclip act as a filter. behavior = "clip" calculates the comparator mean or median and the sigma for the whole array and clips all array values according to these values 8. reduce1d reduced1d = true: in 1-dimensional arrays values are removed instead of being clipped. The length of the returned array becomes shorter reduced1d = false (default): values are clipped. The returned array has the same size as the input array

Example

Example 1: apply Sigclip to an Int1d array

```
array = Int1d.range(9)
array.set(5, 20)
print array
[0,1,2,3,4,20,6,7,8]
print array.apply( Sigclip() -)
[0,1,2,3,4,5,6,7,8]
print array.apply( Sigclip(return = Sigclip.RETURN_BOOL) -)
[false,false,false,false,false,true,false,false,false]
print array.apply( Sigclip( env=4, nsigma=2.5, mode=Sigclip.MEDIAN,
edge=Sigclip.TRUNCATE, return=Sigclip.RETURN_BOOL) -)
false,false,false,false,false,true,false,false,false]
array = Int1d(20, 9)
array.set(7, 20)
array.set(17, 0)
print array
```

Example 1: apply Sigclip to an Int1d array

```
[9,9,9,9,9,9,9,20,9,9,9,9,9,9,9,9,9,0,9,9]
print array.apply( Sigclip( reduce1d = True, outliers = -"both") -)
[9,9,9,9,9,9,9,9,9,9,9,9,9,9,9,9,9,9,9,9]
```

API Summary

Properties
any 1-3d array of integral type **x** [INPUT, MANDATORY, default=no default value]
the box size that is analysed for every sample **envSize** [INPUT, NOT_MANDATORY, default=3]
the number of sigmas that a value has to exceed the next smaller value to be sigclipped **nsigma** [INPUT, NOT_MANDATORY, default=3]
determines **returnmode** [INPUT, if a numeric or a boolean array is returned, default=NOT_MANDATORY]
determines **mode** [INPUT, if median or mean is used to replace sigclipped values, default=NOT_MANDATORY]
determines **outliers** [INPUT, if only positive, default=only negtive or both outliers are removed]
determines **behavior** [INPUT, if Sigclip acts as a filter or a classical clip, default=NOT_MANDATORY]
determines **reduce1d** [INPUT, if found values are removed from the returned array, default=NOT_MANDATORY]

API details

Properties

any 1-3d array of integral type x [INPUT, MANDATORY, default=no default value]

the box size that is analysed for every sample envSize [INPUT, NOT_MANDATORY, default=3]

the number of sigmas that a value has to exceed the next smaller value to be sigclipped nsigma [INPUT, NOT_MANDATORY, default=3]

determines returnmode [INPUT, if a numeric or a boolean array is returned, default=NOT_MANDATORY]

Sigclip.RETURN_ARRAY (=0) returns a copy of the input array with the replaced values.
Sigclip.RETURN_BOOL (=1) returns a boolean array where the clipped locations are marked as true (the other values are false).

determines mode [INPUT, if median or mean is used to replace sigclipped values, default=NOT_MANDATORY]

Sigclip.MEAN (=0) uses the mean of the environment to replace sigclipped values.
Sigclip.MEDIAN (=1) uses the median of the environment to replace sigclipped values.

determines outliers [INPUT, if only positive, default=only negtive or both outliers are removed]

"positive" (default) only outliers larger than the comparator are found "negative" only outliers smaller than the comparator are found "both" all outliers are found deprecation: the default value for outliers is deprecated. Currently it is "positive", but it will be changed to "both". The deprecation is best treated in your code by explicitely specifying the value for outliers!

determines behavior [INPUT, if Sigclip acts as a filter or a classical clip, default=NOT_MANDATORY]

"filter" (default) Sigclip behaves like a filter (runs a box of size env over the input array). "clip" Sigclip works on the whole array at once.

determines reduce1d [INPUT, if found values are removed from the returned array, default=NOT_MANDATORY]

"False" (default) the size of the returned array is the same as the size of the input array "True" the sigcliped values are removed from 1d arrays.

2.331. SIGNUM

Full Name:	herschel.ia.numeric.toolbox.basic.Signum
Alias:	SIGNUM
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Signum

Description

Computes x=signum(x), where x is a number or a numeric array.

Example

Example 1: Apply SIGNUM on a Int1d

```
x=Int1d( [-1,0,2] -)
print SIGNUM(x) # [-1,0,1]
```

API Summary

Jython Syntax
<y>=SIGNUM(<x>)

Properties
any number or array **x** [INPUT, MANDATORY, default=no default value]
same type as input **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any number or array x [INPUT, MANDATORY, default=no default value]

The input can be a number or an array

same type as input y [OUTPUT, MANDATORY, default=no default value]

Returns an array (or a number if the input is not an array) where each element is the signum of the corresponding element of the input array

2.332. SimpleAsciiTableReader

Full Name:	herschel.ia.toolbox.util.SimpleAsciiTableReaderTask
Alias:	SimpleAsciiTableReader
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import SimpleAsciiTableReaderTask
Category:	task

Description

The SimpleAsciiTableReader task.

Task for reading ascii files, with minimal configuration. It provides a simple interface to AsciiTableReader but is less flexible. If it does not read your file as desired, you will have to use AsciiTableReader.

Examples

Example 1: SimpleAsciiTableReader for a table with fields separated with spaces

```
filepath = -"path_to_file"
table=SimpleAsciiTableReader(file=filepath)
```

Example 2: SimpleAsciiTableReader for a CSV file

```
filepath = -"path_to_file"
table=SimpleAsciiTableReader(file=filepath, tabletype="CSV")
```

API Summary

Jython Syntax

```
table=SimpleAsciiTableReader(<file>[, <tableType>])
```

Properties

`String file [INPUT, MANDATORY, default=null]`
`String tableType [INPUT, OPTIONAL, default="SPACES"]`
`TableDataset table [OUTPUT, MANDATORY, default=null]`

API details

Properties

`String file [INPUT, MANDATORY, default=null]`

The path of the text file to be read.

`String tableType [INPUT, OPTIONAL, default="SPACES"]`

The type of table in the input file. Valid values are "CSV" and "SPACES"

`TableDataset table [OUTPUT, MANDATORY, default=null]`

The TableDataset read from the file.

History

- `2008-11-13 - First`: prototype JDS
- `2008-11-18 - Second`: prototype JDS
- `2008-11-24 - first`: release JDS

2.333. SimpleCube

Full Name:	herschel.ia.dataset.image.SimpleCube
Type:	Java Class -
Import:	from herschel.ia.dataset.image import SimpleCube
Category:	Image

Description

A Product describing cubes.

The Simplecube is a way to store and work with Cubes in the HCSS.

Example

Example 1: Creating a SimpleCube

```
s = SimpleCube()
s.setImage(myDouble3dImage)
```

API Summary

Constructors
SimpleCube()
The standard constructor
SimpleCube(SimpleCube copy)
The copy constructor
SimpleCube(String description)
Constructor with a description

Methods
Wcs **getWcs**()
Returns the World Coordinates System.
setImage(AbstractOrdered3dData image, Unit unit, String description)
Sets the cube.
setImage(AbstractOrdered3dData image, Unit unit)
Sets the cube.
setWcs(Wcs wcs)
Sets the world coordinates system.
getIntensity(int depth, double row, double column)
Returns the intensity
double **getIntensityWorldCoordinates**(int depth, double x, double y)
Returns the intensity of the cube
setIntensity(int depth, int row, int column, Number value)
Sets the intensity of the image.
Number **getPixel**(int depth, int row, int column)

Methods
Returns 1 pixel value.
`int` **`getDepth()`** Returns the number of layers
`Cube` **`getPreview`**`(float res)` Returns a preview of the cube
`AbstractOrdered3dData` **`getError()`** Returns the error of the cube as a Numeric3d.
`AbstractOrdered3dData` **`getExposure()`** Returns the exposure of the cube as a Numeric3d.
`AbstractOrdered3dData` **`getCoverage()`** Returns the coverage of the cube as an AbstractOrdered3dData.
`Flag` **`getFlag()`** Returns the flag of the cube.
`int` **`getHeight()`** Returns the height.
`AbstractOrdered3dData` **`getImage()`** returns the cube as a Numeric3d.
`Unit` **`getUnit()`** Returns the unit.
`Unit` **`getUnit`**`(String identifier)` Returns the unit.
`int` **`getWidth()`** Returns the width
`boolean` **`hasError()`** Checks whether the cube has an error.
`boolean` **`hasExposure()`** Checks whether the cube has an exposure.
`boolean` **`hasCoverage()`** Checks whether the cube has a coverage.
`boolean` **`hasFlag()`** Checks when the cube has a flag.
`setUnit``(Unit unit)` Sets the unit.
`setUnit``(String identifier, Unit unit)` Sets the unit.
`removeError()` Removes the error.
`removeExposure()` Removes the exposure.
`removeCoverage()` Removes the coverage.

Methods
removeFlag() Removes the flag.
setImage(AbstractOrdered3dData cube) Sets the cube.
setError(AbstractOrdered3dData error) Sets the error.
setError(AbstractOrdered3dData error, String description) Sets the error.
setFlag(Flag flag, String description) Sets the flag.
setFlag(Flag flag) Sets the flag.
setExposure(AbstractOrdered3dData exposure, String description, Unit unit) Sets the exposure.
setExposure(AbstractOrdered3dData exposure, String description) Sets the exposure.
setExposure(AbstractOrdered3dData exposure) Sets the exposure.
setCoverage(AbstractOrdered3dData coverage, String description, Unit unit) Sets the coverage.
setCoverage(AbstractOrdered3dData coverage, String description) Sets the coverage.
setCoverage(AbstractOrdered3dData coverage) Sets the coverage.
int[] **getDimensions**() Returns the dimension.

API details

Constructors

SimpleCube()

The standard constructor

A constructor which creates a standard SimpleCube. The standard SimpleCube consists of a Numeric3d for the image. The SimpleCube has the depth as the first (most slowly varying) index.

Example

Typical example on how to create an SimpleCube.

```
image=SimpleCube(description="ngc 6992", image=im, flag=flag, errors=er,
unit=unit, wcs=wcs)
```

SimpleCube(SimpleCube copy)

The copy constructor

SimpleCube(SimpleCube copy)

Creates a new SimpleCube with the same contents of the given SimpleCube.

Argument

SimpleCube **copy** [INPUT, MANDATORY]

SimpleCube(String description)

Constructor with a description

Creates a SimpleCube with a given description.

Argument

String **description** [INPUT, MANDATORY]

Methods

Wcs getWcs()

Returns the World Coordinates System.

Returns the World Coordinates System of the image.

Return

Wcs

The World Coordinates System of the image.

setImage(AbstractOrdered3dData image, Unit unit, String description)

Sets the cube.

Sets the cube. You can give a description to the cube and give a unit. The given unit will automatically also be used for the errors on this cube. If the new cube has other dimensions than the original cube, the errors, the Exposure and the Flag are removed. If the new cube has the same dimensions, then the old values for the errors, exposure and flag are kept (but the unit of the errors is not).

Arguments

AbstractOrdered3dData **image** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

setImage(AbstractOrdered3dData image, Unit unit)

Sets the cube.

Sets the cube. You can give a unit. The given unit will automatically also be used for the errors on this cube. If the new cube has other dimensions than the original cube, the errors, exposure and the flag are removed. If the new cube has the same dimensions, then the old values for the errors, exposure and flag are kept (but the unit of the errors is not).

Arguments

AbstractOrdered3dData **image** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

setWcs(Wcs wcs)

Sets the world coordinates system.

Sets the world coordinates system of the cube.

Argument

Wcs **wcs** [INPUT, MANDATORY]

getIntensity(int depth, double row, double column)

Returns the intensity

Returns the intensity of the SimpleCube at a given point. If the pixel is flagged out, NaN is given back.

Arguments

int **depth** [INPUT, MANDATORY]

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

double getIntensityWorldCoordinates(int depth, double x, double y)

Returns the intensity of the cube

Returns the intensity of the vube at a given point in world coordinates. If the pixel is flagged out, NaN is given back.

Arguments

int **depth** [INPUT, MANDATORY]

double **x** [INPUT, MANDATORY]

double **y** [INPUT, MANDATORY]

Return

double

The intensity

setIntensity(int depth, int row, int column, Number value)

Sets the intensity of the image.

Sets the intensity of the image at a given point.

Arguments

int **depth** [INPUT, MANDATORY]

int **row** [INPUT, MANDATORY]

int **column** [INPUT, MANDATORY]

Number **value** [INPUT, MANDATORY]

Number getPixel(int depth, int row, int column)

Returns 1 pixel value.

Returns 1 pixel value of the image.

Arguments

Number getPixel(int depth, int row, int column)

int **depth** [INPUT, MANDATORY]

int **row** [INPUT, MANDATORY]

int **column** [INPUT, MANDATORY]

Return

Number

1 pixel value of the image.

int getDepth()

Returns the number of layers

Returns the depth of this SimpleCube. This is the first axis (slowly varying axis).

Return

int

Returns the depth of this SimpleCube.

Cube getPreview(float res)

Returns a preview of the cube

Returns a new SimpleCube, but with a lower resolution if res is smaller than 1. A higher resolution is returned, if res is larger than 1. The spatial regridding is based on linear interpolation which will, in general, not be suitable for scientific purposes.

Argument

float **res** [INPUT, MANDATORY]

Return

Cube

The preview of the cube

AbstractOrdered3dData getError()

Returns the error of the cube as a Numeric3d.

Returns the error of the cube as a Numeric3d containing the error of every pixel.

Return

AbstractOrdered3dData

The error

AbstractOrdered3dData getExposure()

Returns the exposure of the cube as a Numeric3d.

Returns the exposure of the cube as a Numeric3d containing the exposure of every pixel.

Return

AbstractOrdered3dData

The exposure

AbstractOrdered3dData getCoverage()

Returns the coverage of the cube as an AbstractOrdered3dData.

Returns the coverage of the cube as an AbstractOrdered3dData containing the coverage of every pixel.

Return

AbstractOrdered3dData

The coverage

Flag getFlag()

Returns the flag of the cube.

Returns the flag of the cube.

Return

Flag

The flag

int getHeight()

Returns the height.

Returns the height of this SimpleCube.

Return

int

Returns the height of this SimpleCube.

AbstractOrdered3dData getImage()

returns the cube as a Numeric3d.

Returns the cube as a Numeric3d containing the data of the cube.

Return

AbstractOrdered3dData

The cube as a Numeric3d

Unit getUnit()

Returns the unit.

Returns the unit of the cube. The unit of the errors of this cube is the same as the unit of the cube.

Return

Unit

The unit

Unit getUnit(String identifier)

Returns the unit.

`Unit getUnit(String identifier)`

Returns the unit of the cube, the coverage or the exposure. The unit of the errors of this cube is the same as the unit of the cube.

Argument

`String` **`identifier`** `[INPUT, MANDATORY]`

Return

Unit

The unit

`int getWidth()`

Returns the width

Returns the width of this SimpleImage.

Return

int

Returns the width of this SimpleImage.

`boolean hasError()`

Checks whether the cube has an error.

Returns true if the cube has an error.

Return

boolean

True if the error is set.

`boolean hasExposure()`

Checks whether the cube has an exposure.

Returns true if the cube has an exposure.

Return

boolean

True if the exposure is set.

`boolean hasCoverage()`

Checks whether the cube has a coverage.

Returns true if the cube has a coverage.

Return

boolean

True if the coverage is set.

`boolean hasFlag()`

Checks when the cube has a flag.

boolean hasFlag()

Returns true if the cube has a flag.

Return

boolean

True if the cube has a flag.

setUnit(Unit unit)

Sets the unit.

Sets the unit of the cube. Adapting the unit of the cube will also adapt the unit of the errors on the cube.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

setUnit(String identifier, Unit unit)

Sets the unit.

Sets the unit of the cube, coverage or exposure. Adapting the unit of the cube will also adapt the unit of the errors on the cube.

Arguments

`String` **`identifier`** `[INPUT, MANDATORY]`

`Unit` **`unit`** `[INPUT, MANDATORY]`

removeError()

Removes the error.

Removes the error, if an error exists.

removeExposure()

Removes the exposure.

Removes the exposure, if an exposure exists.

removeCoverage()

Removes the coverage.

Removes the coverage, if a coverage exists.

removeFlag()

Removes the flag.

Removes the flag, if a flag exists.

setImage(AbstractOrdered3dData cube)

Sets the cube.

setImage(AbstractOrdered3dData cube)

Sets the cube. If the new cube has other dimensions than the original cube, the errors, exposure and flag are removed. If the new cube has the same dimensions, then the old values for the errors, exposure and flag are kept.

Argument

`AbstractOrdered3dData` **`cube`** `[INPUT, MANDATORY]`

setError(AbstractOrdered3dData error)

Sets the error.

Sets the errors of the cube. The Numeric3d containing the errors should have the same dimensions as the cube. If this is not the case, the errors will not be adapted.

Argument

`AbstractOrdered3dData` **`error`** `[INPUT, MANDATORY]`

setError(AbstractOrdered3dData error, String description)

Sets the error.

Sets the errors of the cube. The Numeric3d containing the errors should have the same dimensions as the cube. If this is not the case, the errors will not be adapted. The errors are also described.

Arguments

`AbstractOrdered3dData` **`error`** `[INPUT, MANDATORY]`

`String` **`description`** `[INPUT, MANDATORY]`

setFlag(Flag flag, String description)

Sets the flag.

Sets the flag of every pixel of the cube. The Flag should have the same dimensions as the cube. If this is not the case, the Flag will not be adapted. The flag is also described.

Arguments

`Flag` **`flag`** `[INPUT, MANDATORY]`

`String` **`description`** `[INPUT, MANDATORY]`

setFlag(Flag flag)

Sets the flag.

Sets the flag of every pixel of the cube. The Flag should have the same dimensions as the cube. If this is not the case, the Flag will not be adapted.

Argument

`Flag` **`flag`** `[INPUT, MANDATORY]`

setExposure(AbstractOrdered3dData exposure, String description, Unit unit)

Sets the exposure.

Sets the exposure of every pixel of the cube. The Numeric3d containing the exposure should have the same dimensions as the cube. If this is not the case, the exposure will not be adapted.

setExposure(AbstractOrdered3dData exposure, String description, Unit unit)

Arguments

AbstractOrdered3dData **exposure** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

setExposure(AbstractOrdered3dData exposure, String description)

Sets the exposure.

Sets the exposure of every pixel of the cube. The Numeric3d containing the exposure should have the same dimensions as the cube. If this is not the case, the exposure will not be adapted.

Arguments

AbstractOrdered3dData **exposure** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

setExposure(AbstractOrdered3dData exposure)

Sets the exposure.

Sets the exposure of every pixel of the cube. The Numeric3d containing the exposure should have the same dimensions as the cube. If this is not the case, the exposure will not be adapted.

Argument

AbstractOrdered3dData **exposure** [INPUT, MANDATORY]

setCoverage(AbstractOrdered3dData coverage, String description, Unit unit)

Sets the coverage.

Sets the coverage of every pixel of the cube. The AbstractOrdered3dData containing the coverage should have the same dimensions as the cube. If this is not the case, the coverage will not be adapted.

Arguments

AbstractOrdered3dData **coverage** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

setCoverage(AbstractOrdered3dData coverage, String description)

Sets the coverage.

Sets the coverage of every pixel of the cube. The AbstractOrdered3dData containing the coverage should have the same dimensions as the cube. If this is not the case, the coverage will not be adapted.

Arguments

AbstractOrdered3dData **coverage** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

setCoverage(AbstractOrdered3dData coverage)

Sets the coverage.

setCoverage(AbstractOrdered3dData coverage)

Sets the coverage of every pixel of the cube. The AbstractOrdered3dData containing the coverage should have the same dimensions as the cube. If this is not the case, the coverage will not be adapted.

Argument

`AbstractOrdered3dData` **`coverage`** `[INPUT, MANDATORY]`

int[] getDimensions()

Returns the dimension.

Returns the dimension (depth, width, height) of this SimpleCube.

Return

int[]

Returns the dimension (depth, width, height) of this SimpleCube.

2.334. simpleFitsReader

Full Name:	herschel.ia.toolbox.util.SimpleFitsReaderTask
Alias:	simpleFitsReader
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import SimpleFitsReaderTask
Category:	task

Description

The SimpleFitsReaderTask task.

Creates a product from a FITS file.

Examples

Example 1: SimpleFitsReaderTask with just a file parameter

```
filepath = -"path_to_file"
product=simpleFitsReader(file=filepath)
```

Example 2: SimpleFitsReaderTask with an optional reader type

```
filepath = -"path_to_file"
readertype = SimpleFitsReaderTask.ReaderType.STANDARD
product=simpleFitsReader(file=filepath, reader=readertype)
```

API Summary

Jython Syntax

```
product=simpleFitsReader(<file>[, <reader>])
```

Properties

`String` **`file`** `[INPUT, MANDATORY, default=null]`

`SimpleFitsReaderTask.ReaderType` **`reader`** `[INPUT, OPTIONAL, default=SimpleFitsReaderTask.ReaderType.HCSS_THEN_STANDARD]`

`Product` **`product`** `[OUTPUT, MANDATORY, default=null]`

API details

Properties

`String file [INPUT, MANDATORY, default=null]`

The path of the FITS file to be read.

`SimpleFitsReaderTask.ReaderType reader [INPUT, OPTIONAL, default=SimpleFitsReaderTask.ReaderType.HCSS_THEN_STANDARD]`

The strategy used to parse the contents. If an unrecognized value is typed, the default value is used. HCSS has priority over STANDARD as any FITS file can be read as STANDARD but only some of them are also HCSS FITS files. Possible values:

SimpleFitsReaderTask.ReaderType reader [INPUT, OPTIONAL, default=SimpleFitsReaderTask.ReaderType.HCSS_THEN_STANDARD]
• SimpleFitsReaderTask.ReaderType.HCSS_THEN_STANDARD (default): try to read the FITS Archive as an HCSS FITS file, if it fails then try to read it as an standard FITS file. • SimpleFitsReaderTask.ReaderType.HCSS : read it as an HCSS FITS file. • SimpleFitsReaderTask.ReaderType.STANDARD : read it as an STANDARD FITS file.

Product product [OUTPUT, MANDATORY, default=null]
The Product read from the FITS file.

History

- `2008-07-09 - JCS`: first release
- `2008-08-18 - JDS`: added optional parameter reader (type) to allow transparent failover reading
- `2009-01-14 - JDS`: cleanup start (SPR HCSS-5525)
- `2009-09-30 - JSS`: modifiers are created through getCustomModifiers (SCR HCSS-8253)

2.335. simpleFitsWriter

Full Name:	herschel.ia.toolbox.util.SimpleFitsWriterTask
Alias:	simpleFitsWriter
Type:	Java Task -
Import:	from herschel.ia.toolbox.util import SimpleFitsWriterTask
Category:	task

Description

Saves a product in a FITS file

SimpleFitsWriterTask flow:

- if no filename is given, flow is finished with RuntimeException "File is required."
- if the file already exists and warn is checked: user is asked to confirm overwriting
- if the user does not confirm overwriting (or mode is not interactive), flow is finished with RuntimeException "Execution cancelled."
- Otherwise the product is saved in HCSS' FITS format in the chosen file

Examples

Example 1: Saving a product into a file

```
p = Product()
file = -"path_to_file"
simpleFitsWriter(product=p,file=file)
```

Example 2: Saving a product into a file asking before overwriting

```
p = Product()
file = -"path_to_file"
simpleFitsWriter(product=p,file=file,warn=True)
```

API Summary

Jython Syntax

```
simpleFitsWriter(<product>, <file>[, <warn>])
```

Properties

Product **product** [INPUT, MANDATORY, default=null]

String **file** [INPUT, MANDATORY, default=null]

Boolean **warn** [INPUT, OPTIONAL, default=false]

API details

Properties

Product product [INPUT, MANDATORY, default=null]

Product to be saved.

String file [INPUT, MANDATORY, default=null]
FITS filename to save the product into.

Boolean warn [INPUT, OPTIONAL, default=false]
If true, asks confirmation before overwriting.

History

- 2008-07-08 - JCS: first release
- 2008-08-19 - JDS: Using PopUpDialog, SCR 4573: asking before overwriting
- 2008-11-24 - JDS: SPR 5525: cleanup start

2.336. SimpleImage

Full Name:	herschel.ia.dataset.image.SimpleImage
Type:	Java Class -
Import:	from herschel.ia.dataset.image import SimpleImage
Category:	Image

Description

A Product describing images.

SimpleImage is a Product describing images.

Example

Example 1: Creating a SimpleImage

```
s = SimpleImage()
s.setImage(myDouble2dImage)
```

API Summary

Constructors
SimpleImage()
The standard constructor
SimpleImage(SimpleImage copy)
Copy constructor
SimpleImage(String description)
Constructor with a description

Methods
setImage(AbstractOrdered2dData image, Unit unit, String description)
Sets the image.
setWcs(Wcs wcs)
Sets the world coordinates system.
Wcs **getWcs**()
Returns the World Coordinates System.
setImage(AbstractOrdered2dData image, Unit unit)
Sets the image.
getIntensity(double row, double column)
Returns the intensity
double **getIntensityWorldCoordinates**(double x, double y)
Returns the intensity of the image
setIntensity(int row, int column, Number value)
Sets the intensity of the image.
Number **getPixel**(int row, int column)
Returns 1 pixel value.

Methods
`Image getPreview(float res)` Returns a preview of the image
`AbstractOrdered2dData getError()` Returns the error of the image as a Numeric2d.
`AbstractOrdered2dData getExposure()` Returns the exposure of the image as a Numeric2d.
`AbstractOrdered2dData getCoverage()` Returns the coverage of the image as an AbstractOrdered2dData.
`Flag getFlag()` Returns the flag of the image.
`int getHeight()` Returns the height.
`AbstractOrdered2dData getImage()` returns the image as a Numeric2d.
`Unit getUnit()` Returns the unit.
`Unit getUnit(String identifier)` Returns the unit.
`int getWidth()` Returns the width
`double getWavelength()` Returns the reference wavelength
`double getWavelength(Length unit)` Returns the reference wavelength
`boolean hasError()` Checks whether the image has an error.
`boolean hasExposure()` Checks whether the image has an exposure.
`boolean hasCoverage()` Checks whether the image has a coverage.
`boolean hasFlag()` Checks when the image has a flag.
`setUnit(Unit unit)` Sets the unit.
`setUnit(String identifier, Unit unit)` Sets the unit.
`setWavelength(double wavelength)` Sets the reference wavelength.
`setWavelength(double wavelength, Length unit)` Sets the reference wavelength.
`removeError()`

Methods
Removes the error.
removeExposure() Removes the exposure.
removeCoverage() Removes the coverage.
removeFlag() Removes the flag.
setImage(AbstractOrdered2dData image) Sets the image.
setError(AbstractOrdered2dData error) Sets the error.
setError(AbstractOrdered2dData error, String description) Sets the error.
setFlag(Flag flag, String description) Sets the flag.
setFlag(Flag flag) Sets the flag.
setExposure(AbstractOrdered2dData exposure, String description, Unit unit) Sets the exposure.
setExposure(AbstractOrdered2dData exposure, String description) Sets the exposure.
setExposure(AbstractOrdered2dData exposure) Sets the exposure.
setCoverage(AbstractOrdered2dData coverage, String description, Unit unit) Sets the coverage.
setCoverage(AbstractOrdered2dData coverage, String description) Sets the coverage.
setCoverage(AbstractOrdered2dData coverage) Sets the coverage.
double **getFrequency**() Returns the reference frequency.
double **getFrequency**(Frequency freq) Returns the reference frequency.
setFrequency(double frequency) Sets the reference frequency.
setFrequency(double frequency, Frequency unit) Sets the reference frequency.
int[] **getDimensions**() Returns the dimension.
Double2d **getImageData**()

Methods
Returns the Image data.

API details

Constructors

SimpleImage()

The standard constructor

A constructor which creates a standard SimpleImage. The standard SimpleImage consists of a Numeric2d for the image, no error and no integration time. The dimension of the standard SimpleImage is 0x0. The reference wavelength is set to 0.0 microns.

Example

Typical example on how to create an SimpleImage.

```
image=SimpleImage(description="ngc 6992", image=im, flag=flag, errors=er,
unit=unit, wavelength=wavelength, wcs=wcs)
```

SimpleImage(SimpleImage copy)

Copy constructor

Constructor which makes a copy from an existent SimpleImage.

Argument

SimpleImage **copy** [INPUT, MANDATORY]

SimpleImage(String description)

Constructor with a description

Creates a SimpleImage with a given description.

Argument

String **description** [INPUT, MANDATORY]

Methods

setImage(AbstractOrdered2dData image, Unit unit, String description)

Sets the image.

Sets the image. You can give a description to the image and give a unit. The given unit will automatically also be used for the errors on this image. If the new image has other dimensions than the original image, the errors, exposure and the flag are removed. If the new image has the same dimensions, then the old values for the errors, exposure and flag are kept (but the unit of the errors is not).

Arguments

AbstractOrdered2dData **image** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

setWcs(Wcs wcs)

Sets the world coordinates system.

Sets the world coordinates system of the image.

Argument

Wcs **wcs** [INPUT, MANDATORY]

Wcs getWcs()

Returns the World Coordinates System.

Returns the World Coordinates System of the image.

Return

Wcs

The World Coordinates System of the image.

setImage(AbstractOrdered2dData image, Unit unit)

Sets the image.

Sets the image. You can give a unit. The given unit will automatically also be used for the errors on this image. If the new image has other dimensions than the original image, the errors, the exposure and the flag are removed. If the new image has the same dimensions, then the old values for the errors, exposure and the flag are kept (but the unit of the errors is not).

Arguments

AbstractOrdered2dData **image** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

getIntensity(double row, double column)

Returns the intensity

Returns the intensity of the SimpleImage at a given point. If the pixel is flagged out, NaN is given back.

Arguments

double **row** [INPUT, MANDATORY]

double **column** [INPUT, MANDATORY]

double getIntensityWorldCoordinates(double x, double y)

Returns the intensity of the image

Returns the intensity of the image at a given point in world coordinates. If the pixel is flagged out, NaN is given back.

Arguments

double **x** [INPUT, MANDATORY]

double **y** [INPUT, MANDATORY]

Return

double

The intensity

setIntensity(int row, int column, Number value)

Sets the intensity of the image.

Sets the intensity of the image at a given point.

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

`Number` **`value`** `[INPUT, MANDATORY]`

Number getPixel(int row, int column)

Returns 1 pixel value.

Returns 1 pixel value of the image.

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

1 pixel value of the image.

Image getPreview(float res)

Returns a preview of the image

Returns a new SimpleImage, but with a lower resolution if res is smaller than 1. A higher resolution is returned, if res is larger than 1. The spatial regridding is based on linear interpolation which will, in general, not be suitable for scientific purposes.

Argument

`float` **`res`** `[INPUT, MANDATORY]`

Return

Image

The preview of the image

AbstractOrdered2dData getError()

Returns the error of the image as a Numeric2d.

Returns the error of the image as a Numeric2d containing the error of every pixel.

Return

AbstractOrdered2dData

The error

AbstractOrdered2dData getExposure()

Returns the exposure of the image as a Numeric2d.

Returns the exposure of the image as a Numeric2d containing the exposure of every pixel.

Return

`AbstractOrdered2dData getExposure()`

AbstractOrdered2dData

The exposure

`AbstractOrdered2dData getCoverage()`

Returns the coverage of the image as an AbstractOrdered2dData.

Returns the coverage of the image as an AbstractOrdered2dData containing the coverage of every pixel.

Return

AbstractOrdered2dData

The coverage

`Flag getFlag()`

Returns the flag of the image.

Returns the flag of the image.

Return

Flag

The flag

`int getHeight()`

Returns the height.

Returns the height of this SimpleImage.

Return

int

The height of this SimpleImage.

`AbstractOrdered2dData getImage()`

returns the image as a Numeric2d.

Returns the image as a Numeric2d containing the data of the image.

Return

AbstractOrdered2dData

The image as a Numeric2d

`Unit getUnit()`

Returns the unit.

Returns the unit of the image. The unit of the errors of this image is the same as the unit of the image.

Return

`Unit getUnit()`

Unit

The unit

`Unit getUnit(String identifier)`

Returns the unit.

Returns the unit of the image, the coverage or the exposure. The unit of the errors of this image is the same as the unit of the image.

Argument

`String` **`identifier`** `[INPUT, MANDATORY]`

Return

Unit

The unit

`int getWidth()`

Returns the width

Returns the width of this SimpleImage.

Return

int

The width of this SimpleImage.

`double getWavelength()`

Returns the reference wavelength

Returns the reference wavelength of the image.

Return

double

The reference wavelength

`double getWavelength(Length unit)`

Returns the reference wavelength

Returns the reference wavelength of the image.

Argument

`Length` **`unit`** `[INPUT, MANDATORY]`

Return

double

The reference wavelength

`boolean hasError()`

Checks whether the image has an error.

boolean hasError()

Returns true if the image has an error.

Return

boolean

True if the error is set.

boolean hasExposure()

Checks whether the image has an exposure.

Returns true if the image has an exposure.

Return

boolean

True if the exposure is set.

boolean hasCoverage()

Checks whether the image has a coverage.

Returns true if the image has a coverage.

Return

boolean

True if the coverage is set.

boolean hasFlag()

Checks when the image has a flag.

Returns true if the image has a flag.

Return

boolean

True if the image has a flag.

setUnit(Unit unit)

Sets the unit.

Sets the unit of the image. Adapting the unit of the image will also adapt the unit of the errors on the image.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

setUnit(String identifier, Unit unit)

Sets the unit.

Sets the unit of the image, coverage or exposure. Adapting the unit of the image will also adapt the unit of the errors on the image.

setUnit(String identifier, Unit unit)

Arguments

`String` **identifier** [INPUT, MANDATORY]

`Unit` **unit** [INPUT, MANDATORY]

setWavelength(double wavelength)

Sets the reference wavelength.

Set the reference wavelength of the image in microns.

Argument

`double` **wavelength** [INPUT, MANDATORY]

setWavelength(double wavelength, Length unit)

Sets the reference wavelength.

Set the reference wavelength of the image.

Arguments

`double` **wavelength** [INPUT, MANDATORY]

`Length` **unit** [INPUT, MANDATORY]

removeError()

Removes the error.

Removes the error, if an error exists.

removeExposure()

Removes the exposure.

Removes the exposure, if an exposure exists.

removeCoverage()

Removes the coverage.

Removes the coverage, if a coverage exists.

removeFlag()

Removes the flag.

Removes the flag, if a flag exists.

setImage(AbstractOrdered2dData image)

Sets the image.

Sets the image. If the new image has other dimensions than the original image, the errors, exposure and flag are removed. If the new image has the same dimensions, then the old values for the errors, exposure and flag are kept.

Argument

`AbstractOrdered2dData` **image** [INPUT, MANDATORY]

setError(AbstractOrdered2dData error)

Sets the error.

Sets the errors of the image. The Numeric2d containing the errors should have the same dimensions as the image. If this is not the case, the errors will not be adapted.

Argument

`AbstractOrdered2dData` **`error`** `[INPUT, MANDATORY]`

setError(AbstractOrdered2dData error, String description)

Sets the error.

Sets the errors of the image. The Numeric2d containing the errors should have the same dimensions as the image. If this is not the case, the errors will not be adapted. The errors are also described.

Arguments

`AbstractOrdered2dData` **`error`** `[INPUT, MANDATORY]`

`String` **`description`** `[INPUT, MANDATORY]`

setFlag(Flag flag, String description)

Sets the flag.

Sets the flag of every pixel of the image. The Flag should have the same dimensions as the image. If this is not the case, the Flag will not be adapted. The flag is also described.

Arguments

`Flag` **`flag`** `[INPUT, MANDATORY]`

`String` **`description`** `[INPUT, MANDATORY]`

setFlag(Flag flag)

Sets the flag.

Sets the flag of every pixel of the image. The Flag should have the same dimensions as the image. If this is not the case, the Flag will not be adapted.

Argument

`Flag` **`flag`** `[INPUT, MANDATORY]`

setExposure(AbstractOrdered2dData exposure, String description, Unit unit)

Sets the exposure.

Sets the exposure of every pixel of the image. The Numeric2d containing the exposure should have the same dimensions as the image. If this is not the case, the exposure will not be adapted.

Arguments

`AbstractOrdered2dData` **`exposure`** `[INPUT, MANDATORY]`

`String` **`description`** `[INPUT, MANDATORY]`

`Unit` **`unit`** `[INPUT, MANDATORY]`

setExposure(AbstractOrdered2dData exposure, String description)

Sets the exposure.

setExposure(AbstractOrdered2dData exposure, String description)

Sets the exposure of every pixel of the image. The Numeric2d containing the exposure should have the same dimensions as the image. If this is not the case, the exposure will not be adapted.

Arguments

AbstractOrdered2dData **exposure** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

setExposure(AbstractOrdered2dData exposure)

Sets the exposure.

Sets the exposure of every pixel of the image. The Numeric2d containing the exposure should have the same dimensions as the image. If this is not the case, the exposure will not be adapted.

Argument

AbstractOrdered2dData **exposure** [INPUT, MANDATORY]

setCoverage(AbstractOrdered2dData coverage, String description, Unit unit)

Sets the coverage.

Sets the coverage of every pixel of the image. The AbstractOrdered2dData containing the coverage should have the same dimensions as the image. If this is not the case, the coverage will not be adapted.

Arguments

AbstractOrdered2dData **coverage** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

setCoverage(AbstractOrdered2dData coverage, String description)

Sets the coverage.

Sets the coverage of every pixel of the image. The AbstractOrdered2dData containing the coverage should have the same dimensions as the image. If this is not the case, the coverage will not be adapted.

Arguments

AbstractOrdered2dData **coverage** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

setCoverage(AbstractOrdered2dData coverage)

Sets the coverage.

Sets the coverage of every pixel of the image. The AbstractOrdered2dData containing the coverage should have the same dimensions as the image. If this is not the case, the coverage will not be adapted.

Argument

AbstractOrdered2dData **coverage** [INPUT, MANDATORY]

double getFrequency()

Returns the reference frequency.

double getFrequency()

Returns the reference frequency of the image.

Return

double

The reference frequency of the image.

double getFrequency(Frequency freq)

Returns the reference frequency.

Returns the reference frequency of the image.

Argument

`Frequency` **`freq`** `[INPUT, MANDATORY]`

Return

double

The reference frequency of the image.

setFrequency(double frequency)

Sets the reference frequency.

Set the reference frequency of the image in gigahertz.

Argument

`double` **`frequency`** `[INPUT, MANDATORY]`

setFrequency(double frequency, Frequency unit)

Sets the reference frequency.

Set the reference frequency of the image.

Arguments

`double` **`frequency`** `[INPUT, MANDATORY]`

`Frequency` **`unit`** `[INPUT, MANDATORY]`

int[] getDimensions()

Returns the dimension.

Returns the dimension (width, height) of this SimpleImage.

Return

int[]

The dimension (width, height) of this SimpleImage.

Double2d getImageData()

Returns the Image data.

Returns the image data as a Double2d.

Return

Double2d getImageData()

Double2d

The image data as Double2d

2.337. SimpleStack

Full Name:	herschel.ia.slice.image.SimpleStack
Type:	Java Class -
Import:	from herschel.ia.slice.image import SimpleStack
Category:	Image

Description

A SimpleStack is a stack of Images.

The SimpleStack is a way to store and work with a stack of images in the HCSS

Example

Example 1: Typical example on how to create a SimpleStack.

```
stack = SimpleStack(description="Some images")
stack.setImage(new SimpleImage())
```

API Summary

Constructors
SimpleStack()
The standard constructor
SimpleStack(SimpleStack copy)
The copy constructor
SimpleStack(String description)
The constructor with a description

Methods
copy()
Returns a copy.
addImage(Image image)
Adds a new Image to the stack
replaceImage(int layer, Image image)
Replaces an image of the stack.
int **getDepth**()
Returns the number of layers of this stack
SimpleImage **getImage**(int layer)
Returns the chosen image from the Stack.
boolean **hasExposure**(int layer)
Checks whether the given layer has an exposure.
boolean **hasError**(int layer)
Checks whether the given layer has an error.
boolean **hasFlag**(int layer)
Checks whether the given layer has a flag.
AbstractOrdered2dData **getExposure**(int layer)

Methods
Returns the exposure of the given layer as a Numeric2d.
`AbstractOrdered2dData getError(int layer)` Returns the error of the given layer as a Numeric2d.
`Flag getFlag(int layer)` Returns the flag of the given layer.
`setExposure(int layer, AbstractOrdered2dData exposure)` Sets the exposure of a certain layer.
`setError(int layer, AbstractOrdered2dData errors)` Sets the error of a certain layer.
`setFlag(int layer, Flag flag)` Sets the flag of a certain layer.
`removeError(int layer)` Removes the error of a certain layer.
`removeExposure(int layer)` Removes the exposure of a certain layer.
`removeFlag(int layer)` Removes the flag of a certain layer.
`double getIntensity(int layer, double row, double column)` Returns the intensity.
`setIntensity(int layer, int row, int column, Number value)` Sets the intensity of the stack.
`double getIntensityWorldCoordinates(int layer, double x, double y)` Returns the intensity of the stack
`int[] getDimensions(int layer)` Return the dimensions of the layer.
`int getHeight(int layer)` Returns the height
`int getWidth(int layer)` Returns the width.
`Unit getUnit(int layer)` Returns the unit.
`setUnit(int layer, Unit unit)` Sets the unit.
`setWavelength(int layer, double wavelength)` Sets the reference wavelength.
`setWavelength(int layer, double wavelength, Length unit)` Sets the reference wavelength.
`double getWavelength(int layer)` Returns the reference wavelength
`double getWavelength(int layer, Length unit)` Returns the reference wavelength

Methods
`Wcs getWcs(int layer)` Returns the world coordinates system.
`setWcs(int layer, Wcs wcs)` Sets the world coordinates system.
`Stack getPreview(float resolution)` Returns a preview of the stack
`removeImage(int layer)` Removes a layer.

API details

Constructors

SimpleStack()

The standard constructor

A constructor which creates a standard SimpleStack.

Example

Typical example on how to create an SimpleStack.

```
image=SimpleStack(description="Some images")
```

SimpleStack(SimpleStack copy)

The copy constructor

Makes a new SimpleStack from a copy of the given Stack.

Argument

`SimpleStack` **copy** [INPUT, MANDATORY]

SimpleStack(String description)

The constructor with a description

This constructor also sets the description of the SimpleStack

Argument

`String` **description** [INPUT, MANDATORY]

Methods

copy()

Returns a copy.

Returns a copy from this SimpleStack.

addImage(Image image)

Adds a new Image to the stack

Adds a new image to the stack. The images is added as the last image.

addImage(Image image)

Argument

`Image` **`image`** `[INPUT, MANDATORY]`

replaceImage(int layer, Image image)

Replaces an image of the stack.

Replaces an image of the stack.

Arguments

`int` **`layer`** `[INPUT, MANDATORY]`

`Image` **`image`** `[INPUT, MANDATORY]`

int getDepth()

Returns the number of layers of this stack

Returns the number of layers of this stack.

Return

int

Returns the number of layers of this stack.

SimpleImage getImage(int layer)

Returns the chosen image from the Stack.

Returns the chosen layer of the Stack as a SimpleImage.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Return

SimpleImage

The chosen layer of the Stack.

boolean hasExposure(int layer)

Checks whether the given layer has an exposure.

Returns true if the layer has an exposure.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Return

boolean

True if the exposure of the given layer is set.

boolean hasError(int layer)

Checks whether the given layer has an error.

Returns true if the layer has an error.

boolean hasError(int layer)

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Return

boolean

True if the error of the given layer is set.

boolean hasFlag(int layer)

Checks whether the given layer has a flag.

Returns true if the layer has a flag.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Return

boolean

True if the flag of the given layer is set.

AbstractOrdered2dData getExposure(int layer)

Returns the exposure of the given layer as a Numeric2d.

Returns the exposure of the given layer as a Numeric2d containing the exposure of every pixel.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Return

AbstractOrdered2dData

The exposure

AbstractOrdered2dData getError(int layer)

Returns the error of the given layer as a Numeric2d.

Returns the error of the given layer as a Numeric2d containing the error of every pixel.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Return

AbstractOrdered2dData

The error

Flag getFlag(int layer)

Returns the flag of the given layer.

Returns the flag of the given layer.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Flag getFlag(int layer)

Return

Flag

The flag

setExposure(int layer, AbstractOrdered2dData exposure)

Sets the exposure of a certain layer.

Set the exposure of the given layer.

Arguments

`int` **layer** [INPUT, MANDATORY]

`AbstractOrdered2dData` **exposure** [INPUT, MANDATORY]

setError(int layer, AbstractOrdered2dData errors)

Sets the error of a certain layer.

Set the error of the given layer.

Arguments

`int` **layer** [INPUT, MANDATORY]

`AbstractOrdered2dData` **errors** [INPUT, MANDATORY]

setFlag(int layer, Flag flag)

Sets the flag of a certain layer.

Set the flag of the given layer.

Arguments

`int` **layer** [INPUT, MANDATORY]

`Flag` **flag** [INPUT, MANDATORY]

removeError(int layer)

Removes the error of a certain layer.

Removes the error of the given layer.

Argument

`int` **layer** [INPUT, MANDATORY]

removeExposure(int layer)

Removes the exposure of a certain layer.

Remove the exposure of the given layer.

Argument

`int` **layer** [INPUT, MANDATORY]

removeFlag(int layer)

Removes the flag of a certain layer.

Removes the flag of the given layer.

removeFlag(int layer)

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

double getIntensity(int layer, double row, double column)

Returns the intensity.

Returns the intensity of the stack at a given point. If the pixel is masked out, NaN is given back.

Arguments

`int` **`layer`** `[INPUT, MANDATORY]`

`double` **`row`** `[INPUT, MANDATORY]`

`double` **`column`** `[INPUT, MANDATORY]`

Return

double

The intensity

setIntensity(int layer, int row, int column, Number value)

Sets the intensity of the stack.

Sets the intensity of the stack at a given point.

Arguments

`int` **`layer`** `[INPUT, MANDATORY]`

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

`Number` **`value`** `[INPUT, MANDATORY]`

double getIntensityWorldCoordinates(int layer, double x, double y)

Returns the intensity of the stack

Returns the intensity of the stack at a given point in world coordinates. If the pixel is masked out, NaN is given back.

Arguments

`int` **`layer`** `[INPUT, MANDATORY]`

`double` **`x`** `[INPUT, MANDATORY]`

`double` **`y`** `[INPUT, MANDATORY]`

Return

double

The intensity

int[] getDimensions(int layer)

Return the dimensions of the layer.

Returns the dimension (width * height) of the given layer of this SimpleStack.

Argument

int[] getDimensions(int layer)

`int` **layer** [INPUT, MANDATORY]

Return

int[]

Returns the dimension (width * height) of the given layer this SimpleStack.

int getHeight(int layer)

Returns the height

Returns the height of the given layer of this SimpleStack.

Argument

`int` **layer** [INPUT, MANDATORY]

Return

int

The height of the given layer of this SimpleStack.

int getWidth(int layer)

Returns the width.

Returns the width of the given layer of this SimpleStack.

Argument

`int` **layer** [INPUT, MANDATORY]

Return

int

The width of the given layer of this SimpleStack.

Unit getUnit(int layer)

Returns the unit.

Returns the unit of the given layer of the stack. The unit of the errors on this layer of the stack is the same as the unit of the image.

Argument

`int` **layer** [INPUT, MANDATORY]

Return

Unit

The unit

setUnit(int layer, Unit unit)

Sets the unit.

Sets the unit of the given layer of the stack. Adapting the unit of the image will also adapt the unit of the errors on the given layer of the stack.

Arguments

setUnit(int layer, Unit unit)

int **layer** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

setWavelength(int layer, double wavelength)

Sets the reference wavelength.

Set the reference wavelength of the given layer of the stack in microns.

Arguments

int **layer** [INPUT, MANDATORY]

double **wavelength** [INPUT, MANDATORY]

setWavelength(int layer, double wavelength, Length unit)

Sets the reference wavelength.

Set the reference wavelength of the given layer of the stack.

Arguments

int **layer** [INPUT, MANDATORY]

double **wavelength** [INPUT, MANDATORY]

Length **unit** [INPUT, MANDATORY]

double getWavelength(int layer)

Returns the reference wavelength

Returns the reference wavelength of the given layer of the stack.

Argument

int **layer** [INPUT, MANDATORY]

Return

double

The reference wavelength

double getWavelength(int layer, Length unit)

Returns the reference wavelength

Returns the reference wavelength of the given layer of the stack.

Arguments

int **layer** [INPUT, MANDATORY]

Length **unit** [INPUT, MANDATORY]

Return

double

The reference wavelength

Wcs getWcs(int layer)

Returns the world coordinates system.

Wcs getWcs(int layer)

Returns the World Coordinates System of the given layer of the stack.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

Return

Wcs

The world coordinates system

setWcs(int layer, Wcs wcs)

Sets the world coordinates system.

Sets the World Coordinates System of the given layer of the stack.

Arguments

`int` **`layer`** `[INPUT, MANDATORY]`

`Wcs` **`wcs`** `[INPUT, MANDATORY]`

Stack getPreview(float resolution)

Returns a preview of the stack

Returns a preview of a stack with the same number of layers, but with a decrease in resolution in width and height.

Argument

`float` **`resolution`** `[INPUT, MANDATORY]`

Return

Stack

The preview

removeImage(int layer)

Removes a layer.

Removes a layer from the stack.

Argument

`int` **`layer`** `[INPUT, MANDATORY]`

2.338. SingularValueDecomposition

Full Name:	herschel.ia.numeric.toolbox.matrix.SingularValueDecomposition
Alias:	SingularValueDecomposition
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import SingularValueDecomposition

Example

Example 1: ##

```
##### SingularValueDecomposition #####
########################################
#
### HIPE ###
A = Double2d([[ 2.0,  1.0,  1.0],[ 4.0, --6.0,  0.0],[-2.0,  7.0,  2.0]])
svd=A.apply(SingularValueDecomposition())
leftSingularValues = svd.u
print leftSingularValues
[
[0.1938226555206747,-0.816496580927726,0.5438438301022152],
[0.47224728623497236,-0.408248290463863,-0.7812271334106601],
[0.8598925972763216,0.4082482904638631,0.3064605267937704]
]
rightSingularValues = svd.v
print rightSingularValues
[
[0.19382265552067465,-0.816496580927726,0.5438438301022155],
[0.47224728623497236,-0.40824829046386335,-0.78122713341066],
[0.8598925972763218,0.40824829046386324,0.3064605267937702]
]
singularValues = svd.singularValues
print singularValues
array([7.87298334620742, 1.0000000000000004, 0.12701665379258284], double)
diagonalMatrixOfSingularValues = svd.s
print diagonalMatrixOfSingularValues
[
[7.87298334620742,0.0,0.0],
[0.0,1.0000000000000004,0.0],
[0.0,0.0,0.12701665379258284]
]
norm2 = svd.norm2()
print norm2
7.87298334620742
cond = svd.cond()
print cond
61.98386676965949
rank = svd.rank()
print rank
3.0
```

API Summary

Jython Syntax

```
A=Double2d()
svd=B.apply(SingularValueDecomposition())
leftSingularValues = svd.u
rightSingularValues = svd.v
singularValues = svd.singularValues
```

Jython Syntax
`diagonalMatrixOfSingularValues = svd.s`
`norm2 = svd.norm2`
`cont = cvs.cond`
`rank = svd.rank`

Property
`Double2d A [INPUT, MANDATORY, default=no default value]`

API details

Property

`Double2d A [INPUT, MANDATORY, default=no default value]`
Input must be a Double2d or Float2d array.

2.339. SIN

Full Name:	herschel.ia.numeric.toolbox.basic.Sin
Alias:	SIN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Sin

Description

Computes the trigonometric sine of an number or array

Gives the sine of a number or array. The input is in radians, and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

Example

Example 1: Apply SIN on a Float1d

```
x=Float1d([0,0.5])
print  SIN(x) # [0.0,0.47942555]
```

API Summary

Jython Syntax
<y>=SIN(<x>)

Properties
any type **x** [INPUT, MANDATORY, default=no default value]
any type **y** [OUTPUT, NOT_MANDATORY, default=no default value]

API details

Properties

any type x [INPUT, MANDATORY, default=no default value]

The input is in radians, and may be of any type.

any type y [OUTPUT, NOT_MANDATORY, default=no default value]

Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

See also

- ARCSIN
- COS
- SINH
- TAN

2.340. SINH

Full Name:	herschel.ia.numeric.toolbox.basic.SinH
Alias:	SINH
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import SinH

Description

Computes the trigonometric hyperbolic sine of an number or array

Gives the hyperbolic sine of a number or array. The input is in radians, and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

API Summary

Jython Syntax
`<y>=SINH(<x>)`

Properties
`any type x [INPUT, MANDATORY, default=no default value]`
`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`

Miscellaneous

Does not work for complex values.

API details

Properties

`any type x [INPUT, MANDATORY, default=no default value]`
The input is in radians, and may be of any type.

`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`
Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

See also

- SIN
- ARCSIN

2.341. SkewGaussModel

Full Name:	herschel.ia.numeric.toolbox.fit.SkewGaussModel
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.fit import SkewGaussModel

Description

A class that defines a skew gaussian model.

A skew gaussian model is defined as f(x:p) = p0 * exp(-0.5 * ((x - p1) / p2)**2) * (1 + erf(p3 * ((x - p1) / p2) / SQRT(2))) with p0 = amplitude p1 = x-shift p2 = sigma p3 = scale, "skew"

API Summary

Constructor
SkewGaussModel()
The construction of a new SkewGaussModel.

Method
double **result**(double input, Double1d param)
Returns the result of this SkewGaussModel.

API details

Constructor

SkewGaussModel()

The construction of a new SkewGaussModel.

A new SkewGaussModel is contructed with its parameters set to [1.0, 0.0, 1.0, 0.0].

Method

double result(double input, Double1d param)

Returns the result of this SkewGaussModel.

Returns the result of this SkewGaussModel for the given input and the given parameters.

Arguments

double **input** [INPUT, MANDATORY]

Double1d **param** [INPUT, MANDATORY]

Return

double

Returns the result of this SkewGaussModel for the given input and fit parameters.

2.342. SKEWNESS

Full Name:	herschel.ia.numeric.toolbox.basic.Skewness
Alias:	SKEWNESS
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Skewness

Description

Yields the skewness of the elements in the input array.

The skewness is defined as the third moment divided by the standard deviation raised to the thrid power.

Example

Example 1: Apply SKEWNEES on a Float1d

```
x=Float1d([1,3,2,3,4])
print SKEWNESS(x) # --0.19430208
```

API Summary

Jython Syntax

```
<y>=SKEWNESS(<x>)
```

Properties

```
any scalar array x [INPUT, MANDATORY, default=no default value]
double y [OUTPUT, MANDATORY, default=no default value]
```

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array integral or floating-point arrays; the former implicitly transformed to a double array.

double y [OUTPUT, MANDATORY, default=no default value]

Returns a double

See also

- KURTOSIS
- MEAN
- MEDIAN
- STDDEV

- VARIANCE

2.343. SkyAperturePhotometryExplorer

Full Name:	herschel.ia.gui.image.SkyAperturePhotometryExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import SkyAperturePhotometryExplorer

Description

An explorer for SkyAperturePhotometryProducts.

An explorer for SkyAperturePhotometryProducts.

API Summary

Constructors
SkyAperturePhotometryExplorer() The construction of a new SkyAperturePhotometryExplorer.
SkyAperturePhotometryExplorer(Object object) The construction of a new SkyAperturePhotometryExplorer associated with the given object.

Methods
Class **getVariableType()** Returns the expected variable type.
JScrollPane **getResultsTable()** Returns the results table.

API details

Constructors

SkyAperturePhotometryExplorer()
The construction of a new SkyAperturePhotometryExplorer. The construction of a new SkyAperturePhotometryExplorer.

SkyAperturePhotometryExplorer(Object object)
The construction of a new SkyAperturePhotometryExplorer associated with the given object. The construction of a new SkyAperturePhotometryExplorer associated with the given object. **Argument** Object **object** [INPUT, MANDATORY]

Methods

Class getVariableType()
Returns the expected variable type. Returns the expected variable type for this SkyAperturePhotometryExplorer.

`Class getVariableType()`

Return

Class

Returns the expected variable type for this SkyAperturePhotometryExplorer.

`JScrollPane getResultsTable()`

Returns the results table.

Constructs and returns the results table for this SkyAperturePhotometryExplorer.

Return

JScrollPane

Returns the results table for this SkyAperturePhotometryExplorer.

2.344. SkyAperturePhotometryProduct

Full Name:	herschel.ia.dataset.image.SkyAperturePhotometryProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import SkyAperturePhotometryProduct

Description

A class to deal with the results of aperture photometry with a

circular target aperture and an annular/rectangular sky aperture.

API Summary

Constructor
SkyAperturePhotometryProduct() The constructor of a new SkyAperturePhotometryProduct.

Methods
setAlgorithm(int index) Sets the sky estimation algorithm for this SkyAperturePhotometryProduct to the
setResultsTable(Double2d resultsTable) Sets the results table for this SkyAperturePhotometryProduct to the
String **getAlgorithm**() Returns the String representation of the sky estimation algorithm for this
double **getSkyTotal**() Returns the total flux for this SkyAperturePhotometryProduct.
double **getNbOfSkyPixels**() Returns the number of pixels for the sky for this SkyAperturePhotometryProduct.
double **getSkyError**() Returns the error for the sky for this SkyAperturePhotometryProduct.
double **getTargetTotal**() Returns the total flux for the target (sky subtracted) for this
double **getNbOfTargetPixels**() Returns the number of pixels for the target (sky subtracted) for this
double **getIntensityPerTargetPixel**() Returns the intensity per pixel for the target (sky subtracted) for this
double **getTargetError**() Returns the error for the target (sky subtracted) for this

Miscellaneous

Aperture specific information is stored in meta data, all other data (results of calculations) are stored in TableDatasets.

API details

Constructor

SkyAperturePhotometryProduct()
The constructor of a new SkyAperturePhotometryProduct.

Methods

setAlgorithm(int index)
Sets the sky estimation algorithm for this SkyAperturePhotometryProduct to the algorithm with the given index. **Argument** `int` **`index`** `[INPUT, MANDATORY]`

setResultsTable(Double2d resultsTable)
Sets the results table for this SkyAperturePhotometryProduct to the given table. **Argument** `Double2d` **`resultsTable`** `[INPUT, MANDATORY]`

String getAlgorithm()
Returns the String representation of the sky estimation algorithm for this SkyAperturePhotometryProduct. **Return** **String** Returns the String representation of the sky estimation algorithm for this SkyAperturePhotometryProduct.

double getSkyTotal()
Returns the total flux for this SkyAperturePhotometryProduct. **Return** **double** Returns the total flux for this SkyAperturePhotometryProduct.

double getNbOfSkyPixels()
Returns the number of pixels for the sky for this SkyAperturePhotometryProduct. **Return** **double** Returns the number of pixels for the sky for this SkyAperturePhotometryProduct.

`double getSkyError()`

Returns the error for the sky for this SkyAperturePhotometryProduct.

Return

double

Returns the error for the sky for this SkyAperturePhotometryProduct.

`double getTargetTotal()`

Returns the total flux for the target (sky subtracted) for this

SkyAperturePhotometryProduct.

Return

double

Returns the total flux for the target (sky subtracted) for this SkyAperturePhotometryProduct.

`double getNbOfTargetPixels()`

Returns the number of pixels for the target (sky subtracted) for this

SkyAperturePhotometryProduct.

Return

double

Returns the number of pixels for the target (sky subtracted) for this SkyAperturePhotometryProduct.

`double getIntensityPerTargetPixel()`

Returns the intensity per pixel for the target (sky subtracted) for this

SkyAperturePhotometryProduct.

Return

double

Returns the intensity per pixel for the target (sky subtracted) for this SkyAperturePhotometryProduct.

`double getTargetError()`

Returns the error for the target (sky subtracted) for this

SkyAperturePhotometryProduct.

Return

double

Returns the error for the target (sky subtracted) for this SkyAperturePhotometryProduct.

2.345. SkyAperturePhotometryTask

Full Name:	herschel.ia.toolbox.image.SkyAperturePhotometryTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import SkyAperturePhotometryTask

Description

An abstract Task for aperture photometry with a sky aperture.

An abstract Task for aperture photometry, using a circular target aperture. The subclasses/subtasks are AnnularSkyAperturePhotometryTask and RectangularSkyAperturePhotometryTask, using an annular and a rectangular sky aperture respectively.

API Summary

Properties
Image **image** [INPUT, MANDATORY, default=No default value]
Double **centerX** [INPUT, OPTIONAL, default=Default value : NaN]
Double **centerY** [INPUT, OPTIONAL, default=Default value : NaN]
String **centerRA** [INPUT, OPTIONAL, default=Default value : "centerRA"]
String **centerDec** [INPUT, OPTIONAL, default=Default value : "centerDec"]
Double **radiusPixels** [INPUT, OPTIONAL, default=Default value : NaN]
Integer **radiusArcsec** [INPUT, OPTIONAL, default=Default value : 4]
String **algorithm** [INPUT, MANDATORY, default=Default value : NaN]
boolean **fractional** [INPUT, OPTIONAL, default=Default value : true]
AperturePhotometryProduct **result** [OUTPUT, MANDATORY, default=No default value]

Miscellaneous

The parameters concerning the (annular/rectangular) sky aperture are specified in the subclasses/subtasks (AnnularSkyAperturePhotometryTask and RectangularSkyAperturePhotometryTask).

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The image.

Double centerX [INPUT, OPTIONAL, default=Default value : NaN]

The x-pixel-coordinate of the target center.

Double centerY [INPUT, OPTIONAL, default=Default value : NaN]

The y-pixel-coordinate of the target center.

String centerRA [INPUT, OPTIONAL, default=Default value : "centerRA"]

The right ascension of the target center.

String centerDec [INPUT, OPTIONAL, default=Default value : "centerDec"]

The declination of the target center.

Double radiusPixels [INPUT, OPTIONAL, default=Default value : NaN]

The radius of the circular target aperture in pixels.

Integer radiusArcsec [INPUT, OPTIONAL, default=Default value : 4]

The radius of the circular target aperture in arcsec.

String algorithm [INPUT, MANDATORY, default=Default value : NaN]

The sky estimation algorithm.

boolean fractional [INPUT, OPTIONAL, default=Default value : true]

The type of pixels.

AperturePhotometryProduct result [OUTPUT, MANDATORY, default=No default value]

The result.

2.346. SlicedCube

Full Name:	herschel.ia.slice.image.SlicedCube
Type:	Java Class -
Import:	from herschel.ia.slice.image import SlicedCube
Category:	Image

Description

A SlicedCube is a large cube which is stored in slices to make the memory usage lower.

A SlicedCube is a large cube which is stored in slices to make the memory usage lower.

Example

Example 1: Typical example on how to create a SlicedCube.

```
cube = SlicedCube(description="My large cube")
cube.setImage(myData)
```

API Summary

Constructors
SlicedCube() A constructor which creates a standard SlicedCube. The cube is sliced
SlicedCube(SlicedCube copy) The copy constructor
SlicedCube(String description) The constructor with a description

Methods
copy() Returns a copy.
setSliceSize(int depth, int row, int column) Sets the size of the slices of the cube.
int[] **getSliceSize**() Returns the size of the slices of the cube.
SimpleCube **getSlice**(int sliceNumber) Returns the chosen slice.
setImage(AbstractOrdered3dData cube, Unit unit) Sets the cube.
Wcs **getWcs**() Returns the World Coordinates System.
setWcs(Wcs wcs) Sets the world coordinates system.
int[] **getDimensions**() Returns the dimensions.
setImage(AbstractOrdered3dData cube)

Methods
Sets the cube.
`int getHeight()` Returns the height.
`int getWidth()` Returns the width
`int getDepth()` Returns the depth
`Unit getUnit()` Returns the unit.
`setUnit(Unit unit)` Sets the unit.
`getIntensity(int depth, double row, double column)` Returns the intensity
`Double getIntensityWorldCoordinates(int i, double x, double y)` Returns the intensity of the cube
`Number getPixel(int depth, int row, int column)` Returns 1 pixel value.
`setIntensity(int depth, int row, int column, Number value)` Sets the intensity of the cube.
`AbstractOrdered3dData getImage(int sliceNumber)` returns the image data of the slice as a Numeric3d.
`AbstractOrdered3dData getImage()` returns the image as a Numeric2d.
`boolean hasCoverage()` Checks whether the cube has a coverage.
`boolean hasError()` Checks whether the cube has an error.
`setCoverage(AbstractOrdered3dData coverage)` Sets the coverage.
`setError(AbstractOrdered3dData error)` Sets the error.
`removeError()` Removes the error.
`removeCoverage()` Removes the coverage.
`Number getCoverage(int depth, int row, int column)` Returns the coverage of 1 pixel.
`AbstractOrdered3dData getCoverage(int sliceNumber)` returns the coverage of the slice as a Numeric3d.
`AbstractOrdered3dData getCoverage()` Returns the coverage of the cube as a Numeric3d.

Methods
`Number getError(int depth, int row, int column)` Returns the error of 1 pixel.
`AbstractOrdered3dData getError(int sliceNumber)` returns the error of the slice as a Numeric3d.
`AbstractOrdered3dData getError()` Returns the error of the cube as a Numeric3d.
`boolean hasExposure()` Checks whether the cube has an exposure.
`setExposure(AbstractOrdered3dData exposure)` Sets the exposure.
`setExposure(AbstractOrdered3dData exposure, String description)` Sets the exposure.
`removeExposure()` Removes the exposure.
`Number getExposure(int depth, int row, int column)` Returns the exposure of 1 pixel.
`AbstractOrdered3dData getExposure(int sliceNumber)` returns the exposure of the slice as a Numeric3d.
`AbstractOrdered3dData getExposure()` Returns the exposure of the cube as a Numeric3d.
`boolean hasFlag()` Checks when the image has a flag.
`setFlag(Flag flag)` Sets the flag.
`setFlag(Flag flag, String description)` Sets the flag.
`removeFlag()` Removes the flag.
`boolean getFlag(int depth, int row, int column)` Returns the flag of 1 pixel.
`Flag getFlag(int sliceNumber)` returns the flag of the slice.
`Flag getFlag()` Returns the flag of the cube.
`Cube getPreview(float res)` Returns a preview of the cube
`Double3d getImageData()` Returns the Image data.

API details

Constructors

SlicedCube()

A constructor which creates a standard SlicedCube. The cube is sliced

in pieces of 50x50x50 pixels. Every slice is kept in a ListContext as a SimpleCube. The usage of a SlicedCube should be transparent to the user. Exactly the same methods are available on a SlicedCube as on a SimpleCube.

Example

Typical example on how to create a SlicedCube.

```
cube=SlicedCube(description="ngc 6992", image=im, flag=flag, errors=er,
quantity=quant, wavelength=wavelength, wcs=wcs)
```

SlicedCube(SlicedCube copy)

The copy constructor

Makes a new SlicedCube from a copy of the given Cube.

Argument

SlicedCube **copy** [INPUT, MANDATORY]

SlicedCube(String description)

The constructor with a description

This constructor also sets the description of the SlicedCube

Argument

String **description** [INPUT, MANDATORY]

Methods

copy()

Returns a copy.

Returns a copy from this SlicedCube.

setSliceSize(int depth, int row, int column)

Sets the size of the slices of the cube.

Sets the size of the slices of the cube. The standard size is 50x50x50. At this moment, the size should be set before adding data to the SlicedImage!

Arguments

int **depth** [INPUT, MANDATORY]

int **row** [INPUT, MANDATORY]

int **column** [INPUT, MANDATORY]

int[] getSliceSize()

Returns the size of the slices of the cube.

int[] getSliceSize()

Returns the size of the slices of the cube. The standard size is 50x50x50.

Return

int[]

The size of the slices (in depth, rows and columns)

SimpleCube getSlice(int sliceNumber)

Returns the chosen slice.

Returns the chosen slice of the cube as a SimpleCube.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

SimpleCube

The chosen slice of the Cube.

setImage(AbstractOrdered3dData cube, Unit unit)

Sets the cube.

Sets the cube. You can give a unit. The given unit will automatically also be used for the errors on this cube. If the new cube has other dimensions than the original cube, the errors, exposure and flag are removed. If the new cube has the same dimensions, then the old values for the errors, exposures and flag are kept (but the unit of the errors is not). The cube data will be automatically sliced.

Arguments

`AbstractOrdered3dData` **`cube`** `[INPUT, MANDATORY]`

`Unit` **`unit`** `[INPUT, MANDATORY]`

Wcs getWcs()

Returns the World Coordinates System.

Returns the World Coordinates System of the cube.

Return

Wcs

The World Coordinates System of the cube.

setWcs(Wcs wcs)

Sets the world coordinates system.

Sets the world coordinates system of the cube.

Argument

`Wcs` **`wcs`** `[INPUT, MANDATORY]`

int[] getDimensions()

Returns the dimensions.

int[] getDimensions()

Returns the dimensions (depth, width, height) of this SlicedCube.

Return

int[]

Returns the dimensions (depth, width, height) of this SlicedCube.

setImage(AbstractOrdered3dData cube)

Sets the cube.

Sets the cube. The description is SlicedCube and the unit is Scalar.ONE. The given unit will automatically also be used for the errors on this cube. If the new cube has other dimensions than the original cube, the errors, exposure and flag are removed. If the new cube has the same dimensions, then the old values for the errors, exposures and flag are kept (but the unit of the errors is not). The cube data will be automatically sliced.

Argument

`AbstractOrdered3dData` **`cube`** `[INPUT, MANDATORY]`

int getHeight()

Returns the height.

Returns the height of this SimpleCube.

Return

int

The height of this SimpleCube.

int getWidth()

Returns the width

Returns the width of this SlicedCube.

Return

int

The width of this SlicedCube.

int getDepth()

Returns the depth

Returns the depth of this SlicedCube.

Return

int

The depth of this SlicedCube.

Unit getUnit()

Returns the unit.

`Unit getUnit()`

Returns the unit of the cube. The unit of the errors of this cube is the same as the unit of the cube.

Return

Unit

The unit

`setUnit(Unit unit)`

Sets the unit.

Sets the unit of the cube. Adapting the unit of the cube will also adapt the unit of the errors on the cube.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

`getIntensity(int depth, double row, double column)`

Returns the intensity

Returns the intensity of the SimpleCube at a given point. If the pixel is flagged out, NaN is given back.

Arguments

`int` **`depth`** `[INPUT, MANDATORY]`

`double` **`row`** `[INPUT, MANDATORY]`

`double` **`column`** `[INPUT, MANDATORY]`

`Double getIntensityWorldCoordinates(int i, double x, double y)`

Returns the intensity of the cube

Returns the intensity of the cube at a given point in world coordinates. If the pixel is flagged out, NaN is given back.

Arguments

`int` **`i`** `[INPUT, MANDATORY]`

`double` **`x`** `[INPUT, MANDATORY]`

`double` **`y`** `[INPUT, MANDATORY]`

Return

Double

The intensity

`Number getPixel(int depth, int row, int column)`

Returns 1 pixel value.

Returns 1 pixel value of the cube.

Arguments

`int` **`depth`** `[INPUT, MANDATORY]`

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Number getPixel(int depth, int row, int column)

Return

Number

1 pixel value of the cube.

setIntensity(int depth, int row, int column, Number value)

Sets the intensity of the cube.

Sets the intensity of the cube at a given point.

Arguments

int **depth** [INPUT, MANDATORY]

int **row** [INPUT, MANDATORY]

int **column** [INPUT, MANDATORY]

Number **value** [INPUT, MANDATORY]

AbstractOrdered3dData getImage(int sliceNumber)

returns the image data of the slice as a Numeric3d.

Returns the image data as a Numeric3d containing the data of the slice of the cube.

Argument

int **sliceNumber** [INPUT, MANDATORY]

Return

AbstractOrdered3dData

The image data of the slice as a Numeric3d

AbstractOrdered3dData getImage()

returns the image as a Numeric2d.

Returns the image as a Numeric2d containing the data of the image.

Return

AbstractOrdered3dData

The image as a Numeric2d

boolean hasCoverage()

Checks whether the cube has a coverage.

Returns true if the cube has a coverage.

Return

boolean

True if the coverage is set.

boolean hasError()

Checks whether the cube has an error.

boolean hasError()

Returns true if the cube has an error.

Return

boolean

True if the error is set.

setCoverage(AbstractOrdered3dData coverage)

Sets the coverage.

Sets the coverages of the cube. The Numeric3d containing the coverages should have the same dimensions as the cube. If this is not the case, the coverages will not be adapted.

Argument

`AbstractOrdered3dData` **`coverage`** `[INPUT, MANDATORY]`

setError(AbstractOrdered3dData error)

Sets the error.

Sets the errors of the cube. The Numeric3d containing the errors should have the same dimensions as the cube. If this is not the case, the errors will not be adapted.

Argument

`AbstractOrdered3dData` **`error`** `[INPUT, MANDATORY]`

removeError()

Removes the error.

Removes the error, if an error exists.

removeCoverage()

Removes the coverage.

Removes the coverage, if an error exists.

Number getCoverage(int depth, int row, int column)

Returns the coverage of 1 pixel.

Returns the coverage of 1 pixel.

Arguments

`int` **`depth`** `[INPUT, MANDATORY]`

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

The coverage of 1 pixel.

AbstractOrdered3dData getCoverage(int sliceNumber)

returns the coverage of the slice as a Numeric3d.

AbstractOrdered3dData getCoverage(int sliceNumber)

Returns the coverage as a Numeric3d.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

AbstractOrdered3dData

The coverage of the slice as a Numeric3d

AbstractOrdered3dData getCoverage()

Returns the coverage of the cube as a Numeric3d.

Returns the coverage of the cube as a Numeric3d containing the coverage of every pixel.

Return

AbstractOrdered3dData

The coverage

Number getError(int depth, int row, int column)

Returns the error of 1 pixel.

Returns the error of 1 pixel.

Arguments

`int` **`depth`** `[INPUT, MANDATORY]`

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

The error of 1 pixel.

AbstractOrdered3dData getError(int sliceNumber)

returns the error of the slice as a Numeric3d.

Returns the error as a Numeric3d.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

AbstractOrdered3dData

The error of the slice as a Numeric3d

AbstractOrdered3dData getError()

Returns the error of the cube as a Numeric3d.

Returns the error of the cube as a Numeric3d containing the error of every pixel.

AbstractOrdered3dData getError()

Return

AbstractOrdered3dData

The error

boolean hasExposure()

Checks whether the cube has an exposure.

Returns true if the cube has an exposure.

Return

boolean

True if the exposure is set.

setExposure(AbstractOrdered3dData exposure)

Sets the exposure.

Sets the exposure of every pixel of the cube. The Numeric3d containing the exposure should have the same dimensions as the cube. If this is not the case, the exposure will not be adapted.

Argument

`AbstractOrdered3dData` **`exposure`** `[INPUT, MANDATORY]`

setExposure(AbstractOrdered3dData exposure, String description)

Sets the exposure.

Sets the exposure of every pixel of the cube. The Numeric3d containing the exposure should have the same dimensions as the cube. If this is not the case, the exposure will not be adapted.

Arguments

`AbstractOrdered3dData` **`exposure`** `[INPUT, MANDATORY]`

`String` **`description`** `[INPUT, MANDATORY]`

removeExposure()

Removes the exposure.

Removes the exposure, if an exposure exists.

Number getExposure(int depth, int row, int column)

Returns the exposure of 1 pixel.

Returns the exposure of 1 pixel.

Arguments

`int` **`depth`** `[INPUT, MANDATORY]`

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

Number getExposure(int depth, int row, int column)

The exposure of 1 pixel.

AbstractOrdered3dData getExposure(int sliceNumber)

returns the exposure of the slice as a Numeric3d.

Returns the exposure as a Numeric3d.

Argument

`int` **sliceNumber** `[INPUT, MANDATORY]`

Return

AbstractOrdered3dData

The exposure of the slice as a Numeric3d

AbstractOrdered3dData getExposure()

Returns the exposure of the cube as a Numeric3d.

Returns the exposure of the cube as a Numeric3d containing the exposure of every pixel.

Return

AbstractOrdered3dData

The exposure

boolean hasFlag()

Checks when the image has a flag.

Returns true if the image has a flag.

Return

boolean

True if the image has a flag.

setFlag(Flag flag)

Sets the flag.

Sets the flag of every pixel of the cube. The Flag should have the same dimensions as the cube. If this is not the case, the Flag will not be adapted.

Argument

`Flag` **flag** `[INPUT, MANDATORY]`

setFlag(Flag flag, String description)

Sets the flag.

Sets the flag of every pixel of the cube. The Flag should have the same dimensions as the cube. If this is not the case, the Flag will not be adapted. The flag is also described.

Arguments

`Flag` **flag** `[INPUT, MANDATORY]`

setFlag(Flag flag, String description)

String **description** [INPUT, MANDATORY]

removeFlag()

Removes the flag.

Removes the flag, if a flag exists.

boolean getFlag(int depth, int row, int column)

Returns the flag of 1 pixel.

Returns the flag of 1 pixel.

Arguments

int **depth** [INPUT, MANDATORY]

int **row** [INPUT, MANDATORY]

int **column** [INPUT, MANDATORY]

Return

boolean

The flag of 1 pixel. True if flagged out.

Flag getFlag(int sliceNumber)

returns the flag of the slice.

Returns the flag.

Argument

int **sliceNumber** [INPUT, MANDATORY]

Return

Flag

The flag of the slice

Flag getFlag()

Returns the flag of the cube.

Returns the flag of the cube.

Return

Flag

The flag

Cube getPreview(float res)

Returns a preview of the cube

Returns a new SlicedImage, but with a lower resolution if res is smaller than 1. A higher resolution is returned, if res is larger than 1. The spatial regridding is based on linear interpolation which will, in general, not be suitable for scientific purposes.

Argument

Cube getPreview(float res)

float **res** [INPUT, MANDATORY]

Return

Cube

The preview of the cube

Double3d getImageData()

Returns the Image data.

Returns the cube data as a Double3d.

Return

Double3d

The cube data as Double3d

2.347. SlicedImage

Full Name:	herschel.ia.slice.image.SlicedImage
Type:	Java Class -
Import:	from herschel.ia.slice.image import SlicedImage
Category:	Image

Description

A SlicedImage is a large image which is stored in slices to make the memory usage lower.

A SlicedImage is a large image which is stored in slices to make the memory usage lower.

Example

Example 1: Typical example on how to create a SlicedImage.

```
image = SlicedImage(description="My large image")
image.setImage(myData)
```

API Summary

Constructors
SlicedImage() A constructor which creates a standard SlicedImage. The image is sliced
SlicedImage(SlicedImage copy) The copy constructor
SlicedImage(String description) The constructor with a description

Methods
copy() Returns a copy.
setSliceSize(int row, int column) Sets the size of the slices of the image.
int[] **getSliceSize**() Returns the size of the slices of the image.
SimpleImage **getSlice**(int sliceNumber) Returns the chosen slice.
setImage(AbstractOrdered2dData image, Unit unit) Sets the image.
setWavelength(double wavelength) Sets the reference wavelength.
setWavelength(double wavelength, Length unit) Sets the reference wavelength.
double **getWavelength**() Returns the reference wavelength
double **getWavelength**(Length unit)

Methods
Returns the reference wavelength
`Wcs getWcs()` Returns the World Coordinates System.
`setWcs(Wcs wcs)` Sets the world coordinates system.
`int[] getDimensions()` Returns the dimension.
`setImage(AbstractOrdered2dData image)` Sets the image.
`int getHeight()` Returns the height.
`int getWidth()` Returns the width
`Unit getUnit()` Returns the unit.
`setUnit(Unit unit)` Sets the unit.
`getIntensity(double row, double column)` Returns the intensity
`double getIntensityWorldCoordinates(double x, double y)` Returns the intensity of the image
`Number getPixel(int row, int column)` Returns 1 pixel value.
`setIntensity(int row, int column, Number value)` Sets the intensity of the image.
`AbstractOrdered2dData getImage(int sliceNumber)` returns the image data of the slice as a Numeric2d.
`AbstractOrdered2dData getImage()` returns the image as a Numeric2d.
`boolean hasCoverage()` Checks whether the image has an coverage.
`boolean hasError()` Checks whether the image has an error.
`setCoverage(AbstractOrdered2dData coverage)` Sets the coverage.
`setError(AbstractOrdered2dData error)` Sets the error.
`removeCoverage()` Removes the coverage.
`removeError()` Removes the error.

Methods
`Number getCoverage(int row, int column)` Returns the coverage of 1 pixel.
`AbstractOrdered2dData getCoverage(int sliceNumber)` returns the coverage of the slice as a Numeric2d.
`AbstractOrdered2dData getCoverage()` Returns the coverage of the image as a Numeric2d.
`Number getError(int row, int column)` Returns the error of 1 pixel.
`AbstractOrdered2dData getError(int sliceNumber)` returns the error of the slice as a Numeric2d.
`AbstractOrdered2dData getError()` Returns the error of the image as a Numeric2d.
`boolean hasExposure()` Checks whether the image has an exposure.
`setExposure(AbstractOrdered2dData exposure)` Sets the exposure.
`setExposure(AbstractOrdered2dData exposure, String description)` Sets the exposure.
`removeExposure()` Removes the exposure.
`Number getExposure(int row, int column)` Returns the exposure of 1 pixel.
`AbstractOrdered2dData getExposure(int sliceNumber)` returns the exposure of the slice as a Numeric2d.
`AbstractOrdered2dData getExposure()` Returns the exposure of the image as a Numeric2d.
`boolean hasFlag()` Checks when the image has a flag.
`setFlag(Flag flag)` Sets the flag.
`setFlag(Flag flag, String description)` Sets the flag.
`removeFlag()` Removes the flag.
`boolean getFlag(int row, int column)` Returns the flag of 1 pixel.
`Flag getFlag(int sliceNumber)` returns the flag of the slice.
`Flag getFlag()` Returns the flag of the image.
`Image getPreview(float res)`

Methods
Returns a preview of the image
`Double2d getImageData()` Returns the Image data.
`double getFrequency()` Returns the reference frequency.
`double getFrequency(Frequency freq)` Returns the reference frequency.
`setFrequency(double frequency)` Sets the reference frequency.
`setFrequency(double frequency, Frequency unit)` Sets the reference frequency.

API details

Constructors

SlicedImage()

A constructor which creates a standard SlicedImage. The image is sliced

in pieces of 500x500 pixels. Every slice is kept in a ListContext as a SimpleImage. The usage of a SlicedImage should be transparent to the user. Exactly the same methods are available on a SlicedImage as on a SimpleImage.

Example

Typical example on how to create a SlicedImage.

```
image=SlicedImage(description="ngc 6992", image=im, flag=flag, errors=er,
quantity=quant, wavelength=wavelength, wcs=wcs)
```

SlicedImage(SlicedImage copy)

The copy constructor

Makes a new SlicedImage from a copy of the given Image.

Argument

`SlicedImage` **copy** [INPUT, MANDATORY]

SlicedImage(String description)

The constructor with a description

This constructor also sets the description of the SlicedImage

Argument

`String` **description** [INPUT, MANDATORY]

Methods

copy()

Returns a copy.

copy()

Returns a copy from this SlicedImage.

setSliceSize(int row, int column)

Sets the size of the slices of the image.

Sets the size of the slices of the image. The standard size is 500 rows and 500 columns. At this moment, the size should be set before adding data to the SlicedImage!

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

int[] getSliceSize()

Returns the size of the slices of the image.

Returns the size of the slices of the image. The standard size is 500 rows and 500 columns.

Return

int[]

The size of the slices (in rows and columns)

SimpleImage getSlice(int sliceNumber)

Returns the chosen slice.

Returns the chosen slice of the image as a SimpleImage.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

SimpleImage

The chosen slice of the Image.

setImage(AbstractOrdered2dData image, Unit unit)

Sets the image.

Sets the image. You can give a unit. The given unit will automatically also be used for the errors on this image. If the new image has other dimensions than the original image, the errors, exposure and flag are removed. If the new image has the same dimensions, then the old values for the errors, exposures and flag are kept (but the unit of the errors is not). The image data will be automatically sliced.

Arguments

`AbstractOrdered2dData` **`image`** `[INPUT, MANDATORY]`

`Unit` **`unit`** `[INPUT, MANDATORY]`

setWavelength(double wavelength)

Sets the reference wavelength.

Set the reference wavelength of the image in microns.

setWavelength(double wavelength)

Argument

`double` **`wavelength`** `[INPUT, MANDATORY]`

setWavelength(double wavelength, Length unit)

Sets the reference wavelength.

Set the reference wavelength of the image.

Arguments

`double` **`wavelength`** `[INPUT, MANDATORY]`

`Length` **`unit`** `[INPUT, MANDATORY]`

double getWavelength()

Returns the reference wavelength

Returns the reference wavelength of the image.

Return

double

The reference wavelength

double getWavelength(Length unit)

Returns the reference wavelength

Returns the reference wavelength of the image.

Argument

`Length` **`unit`** `[INPUT, MANDATORY]`

Return

double

The reference wavelength

Wcs getWcs()

Returns the World Coordinates System.

Returns the World Coordinates System of the image.

Return

Wcs

The World Coordinates System of the image.

setWcs(Wcs wcs)

Sets the world coordinates system.

Sets the world coordinates system of the image.

Argument

`Wcs` **`wcs`** `[INPUT, MANDATORY]`

int[] getDimensions()

Returns the dimension.

Returns the dimension (width, height) of this SlicedImage.

Return

int[]

The dimension (width, height) of this SlicedImage.

setImage(AbstractOrdered2dData image)

Sets the image.

Sets the image. If the new image has other dimensions than the original image, the errors, exposure and flag are removed. If the new image has the same dimensions, then the old values for the errors, exposure and flag are kept.

Argument

`AbstractOrdered2dData` **`image`** `[INPUT, MANDATORY]`

int getHeight()

Returns the height.

Returns the height of this SimpleImage.

Return

int

The height of this SimpleImage.

int getWidth()

Returns the width

Returns the width of this SlicedImage.

Return

int

The width of this SlicedImage.

Unit getUnit()

Returns the unit.

Returns the unit of the image. The unit of the errors of this image is the same as the unit of the image.

Return

Unit

The unit

setUnit(Unit unit)

Sets the unit.

setUnit(Unit unit)

Sets the unit of the image. Adapting the unit of the image will also adapt the unit of the errors on the image.

Argument

`Unit` **`unit`** `[INPUT, MANDATORY]`

getIntensity(double row, double column)

Returns the intensity

Returns the intensity of the SlicedImage at a given point. If the pixel is flagged out, NaN is given back.

Arguments

`double` **`row`** `[INPUT, MANDATORY]`

`double` **`column`** `[INPUT, MANDATORY]`

double getIntensityWorldCoordinates(double x, double y)

Returns the intensity of the image

Returns the intensity of the image at a given point in world coordinates. If the pixel is flagged out, NaN is given back.

Arguments

`double` **`x`** `[INPUT, MANDATORY]`

`double` **`y`** `[INPUT, MANDATORY]`

Return

double

The intensity

Number getPixel(int row, int column)

Returns 1 pixel value.

Returns 1 pixel value of the image.

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

1 pixel value of the image.

setIntensity(int row, int column, Number value)

Sets the intensity of the image.

Sets the intensity of the image at a given point.

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

setIntensity(int row, int column, Number value)

`Number` **value** [INPUT, MANDATORY]

AbstractOrdered2dData getImage(int sliceNumber)

returns the image data of the slice as a Numeric2d.

Returns the image data as a Numeric2d containing the data of the slice of the image.

Argument

`int` **sliceNumber** [INPUT, MANDATORY]

Return

AbstractOrdered2dData

The image data of the slice as a Numeric2d

AbstractOrdered2dData getImage()

returns the image as a Numeric2d.

Returns the image as a Numeric2d containing the data of the image.

Return

AbstractOrdered2dData

The image as a Numeric2d

boolean hasCoverage()

Checks whether the image has an coverage.

Returns true if the image has an coverage.

Return

boolean

True if the coverage is set.

boolean hasError()

Checks whether the image has an error.

Returns true if the image has an error.

Return

boolean

True if the error is set.

setCoverage(AbstractOrdered2dData coverage)

Sets the coverage.

Sets the coverages of the image. The Numeric2d containing the coverages should have the same dimensions as the image. If this is not the case, the coverages will not be adapted.

Argument

`AbstractOrdered2dData` **coverage** [INPUT, MANDATORY]

setError(AbstractOrdered2dData error)

Sets the error.

Sets the errors of the image. The Numeric2d containing the errors should have the same dimensions as the image. If this is not the case, the errors will not be adapted.

Argument

`AbstractOrdered2dData` **`error`** `[INPUT, MANDATORY]`

removeCoverage()

Removes the coverage.

Removes the coverage, if an coverage exists.

removeError()

Removes the error.

Removes the error, if an error exists.

Number getCoverage(int row, int column)

Returns the coverage of 1 pixel.

Returns the coverage of 1 pixel.

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

The coverage of 1 pixel.

AbstractOrdered2dData getCoverage(int sliceNumber)

returns the coverage of the slice as a Numeric2d.

Returns the coverage as a Numeric2d.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

AbstractOrdered2dData

The coverage of the slice as a Numeric2d

AbstractOrdered2dData getCoverage()

Returns the coverage of the image as a Numeric2d.

Returns the coverage of the image as a Numeric2d containing the coverage of every pixel.

Return

AbstractOrdered2dData

AbstractOrdered2dData getCoverage()

The coverage

Number getError(int row, int column)

Returns the error of 1 pixel.

Returns the error of 1 pixel.

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

The error of 1 pixel.

AbstractOrdered2dData getError(int sliceNumber)

returns the error of the slice as a Numeric2d.

Returns the error as a Numeric2d.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

AbstractOrdered2dData

The error of the slice as a Numeric2d

AbstractOrdered2dData getError()

Returns the error of the image as a Numeric2d.

Returns the error of the image as a Numeric2d containing the error of every pixel.

Return

AbstractOrdered2dData

The error

boolean hasExposure()

Checks whether the image has an exposure.

Returns true if the image has an exposure.

Return

boolean

True if the exposure is set.

setExposure(AbstractOrdered2dData exposure)

Sets the exposure.

setExposure(AbstractOrdered2dData exposure)

Sets the exposure of every pixel of the image. The Numeric2d containing the exposure should have the same dimensions as the image. If this is not the case, the exposure will not be adapted.

Argument

`AbstractOrdered2dData` **`exposure`** `[INPUT, MANDATORY]`

setExposure(AbstractOrdered2dData exposure, String description)

Sets the exposure.

Sets the exposure of every pixel of the image. The Numeric2d containing the exposure should have the same dimensions as the image. If this is not the case, the exposure will not be adapted.

Arguments

`AbstractOrdered2dData` **`exposure`** `[INPUT, MANDATORY]`

`String` **`description`** `[INPUT, MANDATORY]`

removeExposure()

Removes the exposure.

Removes the exposure, if an exposure exists.

Number getExposure(int row, int column)

Returns the exposure of 1 pixel.

Returns the exposure of 1 pixel.

Arguments

`int` **`row`** `[INPUT, MANDATORY]`

`int` **`column`** `[INPUT, MANDATORY]`

Return

Number

The exposure of 1 pixel.

AbstractOrdered2dData getExposure(int sliceNumber)

returns the exposure of the slice as a Numeric2d.

Returns the exposure as a Numeric2d.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

AbstractOrdered2dData

The exposure of the slice as a Numeric2d

AbstractOrdered2dData getExposure()

Returns the exposure of the image as a Numeric2d.

Returns the exposure of the image as a Numeric2d containing the exposure of every pixel.

AbstractOrdered2dData getExposure()

Return

AbstractOrdered2dData

The exposure

boolean hasFlag()

Checks when the image has a flag.

Returns true if the image has a flag.

Return

boolean

True if the image has a flag.

setFlag(Flag flag)

Sets the flag.

Sets the flag of every pixel of the image. The Flag should have the same dimensions as the image. If this is not the case, the Flag will not be adapted.

Argument

`Flag` **flag** [INPUT, MANDATORY]

setFlag(Flag flag, String description)

Sets the flag.

Sets the flag of every pixel of the image. The Flag should have the same dimensions as the image. If this is not the case, the Flag will not be adapted. The flag is also described.

Arguments

`Flag` **flag** [INPUT, MANDATORY]

`String` **description** [INPUT, MANDATORY]

removeFlag()

Removes the flag.

Removes the flag, if a flag exists.

boolean getFlag(int row, int column)

Returns the flag of 1 pixel.

Returns the flag of 1 pixel.

Arguments

`int` **row** [INPUT, MANDATORY]

`int` **column** [INPUT, MANDATORY]

Return

boolean

The flag of 1 pixel. True if flagged out.

Flag getFlag(int sliceNumber)

returns the flag of the slice.

Returns the flag.

Argument

`int` **`sliceNumber`** `[INPUT, MANDATORY]`

Return

Flag

The flag of the slice

Flag getFlag()

Returns the flag of the image.

Returns the flag of the image.

Return

Flag

The flag

Image getPreview(float res)

Returns a preview of the image

Returns a new SlicedImage, but with a lower resolution if res is smaller than 1. A higher resolution is returned, if res is larger than 1. The spatial regridding is based on linear interpolation which will, in general, not be suitable for scientific purposes.

Argument

`float` **`res`** `[INPUT, MANDATORY]`

Return

Image

The preview of the image

Double2d getImageData()

Returns the Image data.

Returns the image data as a Double2d.

Return

Double2d

The image data as Double2d

double getFrequency()

Returns the reference frequency.

Returns the reference frequency of the image.

Return

double

double getFrequency()

The reference frequency of the image.

double getFrequency(Frequency freq)

Returns the reference frequency.

Returns the reference frequency of the image.

Argument

`Frequency` **`freq`** `[INPUT, MANDATORY]`

Return

double

The reference frequency of the image.

setFrequency(double frequency)

Sets the reference frequency.

Set the reference frequency of the image in gigahertz.

Argument

`double` **`frequency`** `[INPUT, MANDATORY]`

setFrequency(double frequency, Frequency unit)

Sets the reference frequency.

Set the reference frequency of the image.

Arguments

`double` **`frequency`** `[INPUT, MANDATORY]`

`Frequency` **`unit`** `[INPUT, MANDATORY]`

2.348. SmoothingTask

Full Name:	herschel.ia.toolbox.image.SmoothingTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import SmoothingTask

Description

An abstract Task for smoothing.

An abstract Task for smoothing images.

2.349. SmoothSpectrum

Full Name:	herschel.ia.toolbox.spectrum.SmoothSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import SmoothSpectrum

Description

Task for smoothing the segments included in a spectrum container according to a selected filter.

The other attributes found in the spectra are not processed but just copied to the result container.

Flags and weights can be included in the processing by setting the 'variant'-parameter accordingly.

API Summary

Properties
SpectrumContainer **ds** [INPUT, MANDATORY, default=no default value.]
SpectrumContainer **result** [OUTPUT, MANDATORY, default=no default value.]
String **filter** [INPUT, OPTIONAL, default=no default value.]
Double **width** [INPUT, MANDATORY, default=no default value.]
String **unit** [INPUT, OPTIONAL, default="pixels".]
String **variant** [INPUT, OPTIONAL, default=no default value.]
String **edge** [INPUT, OPTIONAL, default="REPEAT".]
Boolean **center** [INPUT, OPTIONAL, default=True.]
Boolean **overwrite** [INPUT, OPTIONAL, default=False.]

API details

Properties

SpectrumContainer ds [INPUT, MANDATORY, default=no default value.]

Input container with the spectra to be smoothed.

SpectrumContainer result [OUTPUT, MANDATORY, default=no default value.]

Output container with the smoothed spectra.

String filter [INPUT, OPTIONAL, default=no default value.]

Filter (convolution) to be applied. Available are: "Box" and "Gaussian".

Double width [INPUT, MANDATORY, default=no default value.]

Smoothing width parameter to configure the filter/convolution kernel. It is specified as a number of channels.

String unit [INPUT, OPTIONAL, default="pixels".]

Specify the unit the width is specified in. The default is pixels, i.e. specify the width in number of pixels. Other values should be compatible with the unit specified for the wave scale (eg width in GHz and wave scale unit given in MHz is ok but width in "cm" not).

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-weight" / "flux-flag-weight"

String edge [INPUT, OPTIONAL, default="REPEAT".]

Parameter to configure the behavior at the edges: "ZEROES", "CIRCULAR", "REPEAT", "CUT".

Boolean center [INPUT, OPTIONAL, default=True.]

Parameter to configure the behavior of the convolution: If set to true the smoothed value is assigned to the center of the smoothing interval. Otherwise, it is assigned at the left edge of the smoothing interval.

Boolean overwrite [INPUT, OPTIONAL, default=False.]

Specify whether the input data container can be reused - the values found therein are overwritten.

History

- `2008-03-19 - meli`: initial.

2.350. SORT

Full Name:	herschel.ia.numeric.toolbox.basic.Sort
Alias:	SORT
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Sort

Description

Sorts the specified array into ascending natural order.

Index sorting is available as a special case of SORT i.e. SORT.BY_INDEX which returns an index array. The SORT.IS_SORTED function tests if the given array is sorted.

Examples

Example 1: Apply SORT on a Double1d

```
x=Double1d([-1,4,2,7,2,-6,-8,3,2])
print SORT(x)              # [-8.0,-6.0,-1.0,2.0,2.0,2.0,3.0,4.0,7.0]
```

Example 2: Apply SORT.BY_INDEX

```
x=Double1d([-1,4,2,7,2,-6,-8,3,2])
print SORT.BY_INDEX(x)     # [6,5,0,2,4,8,7,1,3]
```

Example 3: Apply SORT.IS_SORTED

```
x=Double1d([-1,4,2,7,2,-6,-8,3,2])
print SORT.IS_SORTED(x)    # 0 (false)
```

API Summary

Jython Syntax

```
<y>=SORT(<x>)
```

Properties

any array **x** [INPUT, MANDATORY, default=no default value]

an array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any array x [INPUT, MANDATORY, default=no default value]

The input array can be an array of rank 1

an array y [OUTPUT, MANDATORY, default=no default value]

Returns an array with the same number of elements as the input array and sorted in the ascending natural order.

2.351. SourceExtractorDaophotTask

Full Name:	herschel.ia.toolbox.srcext.SourceExtractorDaophotTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.srcext import SourceExtractorDaophotTask
Category:	task

Description

This task extracts point sources from an HCSS SimpleImage image.

The task returns a SourceListProduct listing the sources found in the input image

The DAOPHOT algorithm is described in:

- DAOPHOT: Stetson (1987) *"DAOPHOT - A computer program for crowded-field stellar photometry"*

Note that the image must have units specified, and these must be < mJy, Jy or MJy > / < pixel, sr or beam >. Use `print myImage.getUnit()` to view the image units, and `myImage.setUnit(herschel.share.unit.Unit.parse("MJy/sr"))` to set the units of the image to MJy/sr (Jy/beam, Jy/pixel, mJy/pixel etc. also work).

Example

Example 1: Extract sources from a SimpleImage using DAOPHOT

```
# myImage is a SimpleImage
disp = Display(myImage)
#
# Extract a list of sources from the image
sourceList = sourceExtractor( \
    image = myImage,         # Image name \
    detThreshold = 10,     # Threshold in signal-to-noise ratio (or DAOPHOT H-
units) \
    fwhm = 18.6,             # FWHM of PRF (arcsec) \
    #prf = prfImage,         # SimpleImage containing PRF \
    #corner1Ra = 0.3,        # Minimum RA to consider (degrees) \
    #corner1Dec = 0.3,       # Minimum dec to consider (degrees) \
    #corner2Ra = 0.5,        # Maximum RA to consider (degrees) \
    #corner2Dec = 0.5,       # Maximum dec to consider (degrees) \
    algorithm = -"daophot",  # -"daophot" or -"sussextractor" \
    pixelRegion = 2.5,       # Source search radius in pixels \
    useSignalToNoise = True,  # If False then detThreshold is in DAOPHOT H-
units
    -)
#
# How many sources found?
print -"Found", len(sourceList), -"sources."
#
# Display each source on the image (or drag and drop the sourceList onto the
image)
disp.addPositionList(sourceList)
```

API Summary

Properties
`SimpleImage image [INPUT, MANDATORY, default=no default value]`

Properties
Double **detThreshold** [INPUT, MANDATORY, default=no default value]
Double **fwhm** [INPUT, MANDATORY, default=no default value]
SimpleImage **prf** [INPUT, OPTIONAL, default=no default value]
Double **beamArea** [INPUT, OPTIONAL, default=no default value]
Double **pixelRegion** [INPUT, MANDATORY, default=default value: 1.5]
Double **corner1Ra** [INPUT, OPTIONAL, default=default value: Ra of image pixel (0,0)]
Double **corner1Dec** [INPUT, OPTIONAL, default=default value: Dec of image pixel (0,0)]
Double **corner2Ra** [INPUT, OPTIONAL, default=default value: Ra of image pixel (width-1, height-1)]
Double **corner2Dec** [INPUT, OPTIONAL, default=default value: Dec of image pixel (width-1, height-1)]
SourceListProduct **inputSourceList** [INPUT, OPTIONAL, default=no default value]
Double **fluxPriorsLambda** [INPUT, OPTIONAL, default=default value: 1.0]
Double **fluxPriorsMin** [INPUT, OPTIONAL, default=default value: 1.0e-4]
Double **fluxPriorsMax** [INPUT, OPTIONAL, default=default value: 1.0e8]
Boolean **fitBackground** [INPUT, OPTIONAL, default=default value: False]
Double **backgroundPriorsMin** [INPUT, OPTIONAL, default=no default value]
Double **backgroundPriorsMax** [INPUT, OPTIONAL, default=no default value]
Boolean **subtractMedianBackground** [INPUT, OPTIONAL, default=default value: False]
Boolean **returnPixelCoordinates** [INPUT, OPTIONAL, default=default value: False]
Boolean **useSignalToNoise** [INPUT, Optional, default=default value: True]
SimpleImage **filteredMap** [OUTPUT, OPTIONAL, default=no default value]

Error
RuntimeException
if the image has units in per-beam but no beamArea is specified

API details

Properties

SimpleImage image [INPUT, MANDATORY, default=no default value]
Image map to search for point sources

Double detThreshold [INPUT, MANDATORY, default=no default value]

Threshold at which a local maximum is detected. The meaning of this depends on the useSignalToNoise parameter and may be set to

- Either signal-to-noise or log(evidence) for SUSSEXtractor
- Either signal-to-noise or DAOPHOT H-units for DAOPHOT extractor

Double fwhm [INPUT, MANDATORY, default=no default value]

Full-width half maximum, in arcsec, of a default Gaussian point response function (PRF).

SimpleImage prf [INPUT, OPTIONAL, default=no default value]

SimpleImage of a custom point response function (PRF). If defined, this will be used in preference to the default Gaussian. The PRF should be of odd dimension, with the peak in the centre, and is interpreted as the response of the central pixels of a 1 Jy source in a map with units of the input map.

Double beamArea [INPUT, OPTIONAL, default=no default value]

Solid angle of the beam in square arcsec. For use when the input map has units of Jy/beam. For example, for a Gaussian beam profile with a given full-width half maximum, fwhm, beamArea is given by

Math.PI * fwhm**2 / 4 / LOG(2)

For PACS and SPIRE, the values given in the Observer's Manuals for the FWHM are:

- PACS-70: 5.2
- PACS-100: 7.7
- PACS-160: 12
- SPIRE-PSW: 18
- SPIRE-PMW: 25
- SPIRE-PLW: 36

Double pixelRegion [INPUT, MANDATORY, default=default value: 1.5]

Radius around each pixel to consider when searching for local maxima. Units: pixels.

Double corner1Ra [INPUT, OPTIONAL, default=default value: Ra of image pixel (0,0)]

These "corner..." parameters locate two points on the image in world coordinates, defining opposite corners of a rectangle. Only sources within this rectangle will be returned in the output SourceListProduct. If these parameters are not used then the entire map will be searched. Otherwise, if at least one of these parameters are defined, then all four must be.

Double corner1Dec [INPUT, OPTIONAL, default=default value: Dec of image pixel (0,0)]

See description for corner1Ra.

Double corner2Ra [INPUT, OPTIONAL, default=default value: Ra of image pixel (width-1, height-1)]

See description for corner1Ra.

Double corner2Dec [INPUT, OPTIONAL, default=default value: Dec of image pixel (width-1, height-1)]

See description for corner1Ra.

SourceListProduct inputSourceList [INPUT, OPTIONAL, default=no default value]

SourceListProduct containing a list of "known" source positions, at which the fluxes will be extracted.

Double fluxPriorsLambda [INPUT, OPTIONAL, default=default value: 1.0]

Lambda value for SUSSEXtractor flux priors: 0 = tophat, 1 = Jeffreys, >1 = deboost

Double fluxPriorsMin [INPUT, OPTIONAL, default=default value: 1.0e-4]

Prior on minimum flux for SUSSEXtractor, in mJy

Double fluxPriorsMax [INPUT, OPTIONAL, default=default value: 1.0e8]

Prior on maximum flux for SUSSEXtractor, in mJy

Boolean fitBackground [INPUT, OPTIONAL, default=default value: False]

SUSSEXtractor flag to fit background as a free parameter

Double backgroundPriorsMin [INPUT, OPTIONAL, default=no default value]

Prior on minimum background level for SUSSEXtractor, in units of the input map

Double backgroundPriorsMax [INPUT, OPTIONAL, default=no default value]

Prior on maximum background level for SUSSEXtractor, in units of the input map

Boolean subtractMedianBackground [INPUT, OPTIONAL, default=default value: False]

SUSSEXtractor flag to subtract median background from image

Boolean returnPixelCoordinates [INPUT, OPTIONAL, default=default value: False]

Return x, y coordinates of sources in ra, dec columns. If image has a valid WCS, FWHM is assumed to be in arcsec; otherwise FWHM is assumed to be in pixels

Boolean useSignalToNoise [INPUT, Optional, default=default value: True]

Threshold to use. If set to False, for SUSSEXtractor the threshold will be log(evidence), while for DAOPHOT the threshold will be DAOPHOT H units. This will be returned as the 'quality' in the SourceListDataset.

SimpleImage filteredMap [OUTPUT, OPTIONAL, default=no default value]
The input map filtered by the PRF (SUSSEXtractor) or by the DAOPHOT kernel (DAOPHOT). In units of mJy (SUSSEXtractor)

Error

RuntimeException
if the image has units in per-beam but no beamArea is specified

2.352. SourceExtractorSussextractorTask

Full Name:	herschel.ia.toolbox.srcext.SourceExtractorSussextractorTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.srcext import SourceExtractorSussextractorTask
Category:	task

Description

This task extracts point sources from an HCSS SimpleImage image.

The task returns a SourceListProduct listing the sources found in the input image

The SUSSEXtractor algorithm is described in:

- SUSSEXtractor: Savage & Oliver (2007) *Bayesian Methods of Astronomical Source Extraction*

Note that the image must have units specified, and these must be < mJy, Jy or MJy > / < pixel, sr or beam >. Use `print myImage.getUnit()` to view the image units, and `myImage.setUnit(herschel.share.unit.Unit.parse("MJy/sr"))` to set the units of the image to MJy/sr (Jy/beam, Jy/pixel, mJy/pixel etc. also work).

Example

Example 1: Extract sources from a SimpleImage using SUSSEXtractor

```
# myImage is a SimpleImage
disp = Display(myImage)
#
# Extract a list of sources from the image
sourceList = sourceExtractor( \
    image = myImage,        # Image name \
    detThreshold = 10,      # Threshold in signal-to-noise ratio (or log
evidence) \
    fwhm = 18.6,            # FWHM of PRF (arcsec) \
    #prf = prfImage,        # SimpleImage containing PRF \
    #corner1Ra = 0.3,       # Minimum RA to consider (degrees) \
    #corner1Dec = 0.3,      # Minimum dec to consider (degrees) \
    #corner2Ra = 0.5,       # Maximum RA to consider (degrees) \
    #corner2Dec = 0.5,      # Maximum dec to consider (degrees) \
    algorithm = -"sussextractor",  # -"daophot" or -"sussextractor" \
    pixelRegion = 2.5,      # Source search radius in pixels \
    fluxPriorsLambda = 1.0, # Prior (0 = tophat, 1 = Jeffreys, >1 = deboost) \
    fitBackground = False,  # Perform background fit \
    subtractMedianBackground = False,  # Subtract median background before
extracting sources \
    useSignalToNoise = True,  # If False then detThreshold is in log evidence
    -)
#
# How many sources found?
print -"Found", len(sourceList), -"sources."
#
# Display each source on the image (or drag and drop the sourceList onto the
image)
disp.addPositionList(sourceList)
```

API Summary

Properties
`SimpleImage image [INPUT, MANDATORY, default=no default value]`

Properties
Double **detThreshold** [INPUT, MANDATORY, default=no default value]
Double **fwhm** [INPUT, MANDATORY, default=no default value]
SimpleImage **prf** [INPUT, OPTIONAL, default=no default value]
Double **beamArea** [INPUT, OPTIONAL, default=no default value]
Double **pixelRegion** [INPUT, MANDATORY, default=default value: 1.5]
Double **corner1Ra** [INPUT, OPTIONAL, default=default value: Ra of image pixel (0,0)]
Double **corner1Dec** [INPUT, OPTIONAL, default=default value: Dec of image pixel (0,0)]
Double **corner2Ra** [INPUT, OPTIONAL, default=default value: Ra of image pixel (width-1, height-1)]
Double **corner2Dec** [INPUT, OPTIONAL, default=default value: Dec of image pixel (width-1, height-1)]
SourceListProduct **inputSourceList** [INPUT, OPTIONAL, default=no default value]
Double **fluxPriorsLambda** [INPUT, OPTIONAL, default=default value: 1.0]
Double **fluxPriorsMin** [INPUT, OPTIONAL, default=default value: 1.0e-4]
Double **fluxPriorsMax** [INPUT, OPTIONAL, default=default value: 1.0e8]
Boolean **fitBackground** [INPUT, OPTIONAL, default=default value: False]
Double **backgroundPriorsMin** [INPUT, OPTIONAL, default=no default value]
Double **backgroundPriorsMax** [INPUT, OPTIONAL, default=no default value]
Boolean **subtractMedianBackground** [INPUT, OPTIONAL, default=default value: False]
Boolean **returnPixelCoordinates** [INPUT, OPTIONAL, default=default value: False]
Boolean **useSignalToNoise** [INPUT, Optional, default=default value: True]
SimpleImage **filteredMap** [OUTPUT, OPTIONAL, default=no default value]

Error
RuntimeException if the image has units in per-beam but no beamArea is specified

API details

Properties

SimpleImage image [INPUT, MANDATORY, default=no default value]
Image map to search for point sources

Double detThreshold [INPUT, MANDATORY, default=no default value]

Threshold at which a local maximum is detected. The meaning of this depends on the useSignalToNoise parameter and may be set to

- Either signal-to-noise or log(evidence) for SUSSEXtractor
- Either signal-to-noise or DAOPHOT H-units for DAOPHOT extractor

Double fwhm [INPUT, MANDATORY, default=no default value]

Full-width half maximum, in arcsec, of a default Gaussian point response function (PRF).

SimpleImage prf [INPUT, OPTIONAL, default=no default value]

SimpleImage of a custom point response function (PRF). If defined, this will be used in preference to the default Gaussian. The PRF should be of odd dimension, with the peak in the centre, and is interpreted as the response of the central pixels of a 1 Jy source in a map with units of the input map.

Double beamArea [INPUT, OPTIONAL, default=no default value]

Solid angle of the beam in square arcsec. For use when the input map has units of Jy/beam. For example, for a Gaussian beam profile with a given full-width half maximum, fwhm, beamArea is given by

Math.PI * fwhm**2 / 4 / LOG(2)

For PACS and SPIRE, the values given in the Observer's Manuals for the FWHM are:

- PACS-70: 5.2
- PACS-100: 7.7
- PACS-160: 12
- SPIRE-PSW: 18
- SPIRE-PMW: 25
- SPIRE-PLW: 36

Double pixelRegion [INPUT, MANDATORY, default=default value: 1.5]

Radius around each pixel to consider when searching for local maxima. Units: pixels.

Double corner1Ra [INPUT, OPTIONAL, default=default value: Ra of image pixel (0,0)]

These "corner..." parameters locate two points on the image in world coordinates, defining opposite corners of a rectangle. Only sources within this rectangle will be returned in the output SourceListProduct. If these parameters are not used then the entire map will be searched. Otherwise, if at least one of these parameters are defined, then all four must be.

Double corner1Dec [INPUT, OPTIONAL, default=default value: Dec of image pixel (0,0)]

See description for corner1Ra.

Double corner2Ra [INPUT, OPTIONAL, default=default value: Ra of image pixel (width-1, height-1)]

See description for corner1Ra.

Double corner2Dec [INPUT, OPTIONAL, default=default value: Dec of image pixel (width-1, height-1)]

See description for corner1Ra.

SourceListProduct inputSourceList [INPUT, OPTIONAL, default=no default value]

SourceListProduct containing a list of "known" source positions, at which the fluxes will be extracted.

Double fluxPriorsLambda [INPUT, OPTIONAL, default=default value: 1.0]

Lambda value for SUSSEXtractor flux priors: 0 = tophat, 1 = Jeffreys, >1 = deboost

Double fluxPriorsMin [INPUT, OPTIONAL, default=default value: 1.0e-4]

Prior on minimum flux for SUSSEXtractor, in mJy

Double fluxPriorsMax [INPUT, OPTIONAL, default=default value: 1.0e8]

Prior on maximum flux for SUSSEXtractor, in mJy

Boolean fitBackground [INPUT, OPTIONAL, default=default value: False]

SUSSEXtractor flag to fit background as a free parameter

Double backgroundPriorsMin [INPUT, OPTIONAL, default=no default value]

Prior on minimum background level for SUSSEXtractor, in units of the input map

Double backgroundPriorsMax [INPUT, OPTIONAL, default=no default value]

Prior on maximum background level for SUSSEXtractor, in units of the input map

Boolean subtractMedianBackground [INPUT, OPTIONAL, default=default value: False]

SUSSEXtractor flag to subtract median background from image

Boolean returnPixelCoordinates [INPUT, OPTIONAL, default=default value: False]

Return x, y coordinates of sources in ra, dec columns. If image has a valid WCS, FWHM is assumed to be in arcsec; otherwise FWHM is assumed to be in pixels

Boolean useSignalToNoise [INPUT, Optional, default=default value: True]

Threshold to use. If set to False, for SUSSEXtractor the threshold will be log(evidence), while for DAOPHOT the threshold will be DAOPHOT H units. This will be returned as the 'quality' in the SourceListDataset.

SimpleImage filteredMap [OUTPUT, OPTIONAL, default=no default value]
The input map filtered by the PRF (SUSSEXtractor) or by the DAOPHOT kernel (DAOPHOT). In units of mJy (SUSSEXtractor)

Error

RuntimeException
if the image has units in per-beam but no beamArea is specified

2.353. SourceExtractorTask

Full Name:	herschel.ia.toolbox.srcext.SourceExtractorTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.srcext import SourceExtractorTask
Category:	task

Description

This task extracts point sources from an HCSS SimpleImage image.

The task returns a SourceListProduct listing the sources found in the input image

The tool currently uses the SUSSEXtractor and DAOPHOT algorithms. These are described in:

- SUSSEXtractor: Savage & Oliver (2007) *Bayesian Methods of Astronomical Source Extraction*
- DAOPHOT: Stetson (1987) *"DAOPHOT - A computer program for crowded-field stellar photometry"*

Note that the image must have units specified, and these must be < mJy, Jy or MJy > / < pixel, sr or beam >. Use `print myImage.getUnit()` to view the image units, and `myImage.setUnit(herschel.share.unit.Unit.parse("MJy/sr"))` to set the units of the image to MJy/sr (Jy/beam, Jy/pixel, mJy/pixel etc. also work).

Examples

Example 1: Extract sources from a SimpleImage using SUSSEXtractor

```
# myImage is a SimpleImage
disp = Display(myImage)
#
# Extract a list of sources from the image
sourceList = sourceExtractor( \
    image = myImage,         # Image name \
    detThreshold = 10,       # Threshold in signal-to-noise ratio (or log
evidence) \
    fwhm = 18.6,             # FWHM of PRF (arcsec) \
    #prf = prfImage,         # SimpleImage containing PRF \
    #corner1Ra = 0.3,        # Minimum RA to consider (degrees) \
    #corner1Dec = 0.3,       # Minimum dec to consider (degrees) \
    #corner2Ra = 0.5,        # Maximum RA to consider (degrees) \
    #corner2Dec = 0.5,       # Maximum dec to consider (degrees) \
    algorithm = -"sussextractor",  # -"daophot" or -"sussextractor" \
    pixelRegion = 2.5,       # Source search radius in pixels \
    fluxPriorsLambda = 1.0, # Prior (0 = tophat, 1 = Jeffreys, >1 = deboost) \
    fitBackground = False,  # Perform background fit \
    subtractMedianBackground = False,  # Subtract median background before
extracting sources \
    useSignalToNoise = True,  # If False then detThreshold is in log evidence
    -)
#
# How many sources found?
print -"Found", len(sourceList), -"sources."
#
# Display each source on the image (or drag and drop the sourceList onto the
image)
disp.addPositionList(sourceList)
```

Example 2: Extract sources from a SimpleImage using DAOPHOT

```
# myImage is a SimpleImage
disp = Display(myImage)
#
```

Example 2: Extract sources from a SimpleImage using DAOPHOT

```
# Extract a list of sources from the image
sourceList = sourceExtractor( \
    image = myImage,         # Image name \
    detThreshold = 10,     # Threshold in signal-to-noise ratio (or DAOPHOT H-
units) \
    fwhm = 18.6,             # FWHM of PRF (arcsec) \
    #prf = prfImage,         # SimpleImage containing PRF \
    #corner1Ra = 0.3,        # Minimum RA to consider (degrees) \
    #corner1Dec = 0.3,       # Minimum dec to consider (degrees) \
    #corner2Ra = 0.5,        # Maximum RA to consider (degrees) \
    #corner2Dec = 0.5,       # Maximum dec to consider (degrees) \
    algorithm = -"daophot",  # -"daophot" or -"sussextractor" \
    pixelRegion = 2.5,       # Source search radius in pixels \
    useSignalToNoise = True,  # If False then detThreshold is in DAOPHOT H-
units
    -)
#
# How many sources found?
print -"Found", len(sourceList), -"sources."
#
# Display each source on the image (or drag and drop the sourceList onto the
image)
disp.addPositionList(sourceList)
```

API Summary

Properties
SimpleImage **image** [INPUT, MANDATORY, default=no default value]
Double **detThreshold** [INPUT, MANDATORY, default=no default value]
Double **fwhm** [INPUT, MANDATORY, default=no default value]
SimpleImage **prf** [INPUT, OPTIONAL, default=no default value]
Double **beamArea** [INPUT, OPTIONAL, default=no default value]
Double **pixelRegion** [INPUT, MANDATORY, default=default value: 1.5]
String **algorithm** [INPUT, OPTIONAL, default=default value: sussextractor]
Double **corner1Ra** [INPUT, OPTIONAL, default=default value: Ra of image pixel (0,0)]
Double **corner1Dec** [INPUT, OPTIONAL, default=default value: Dec of image pixel (0,0)]
Double **corner2Ra** [INPUT, OPTIONAL, default=default value: Ra of image pixel (width-1, height-1)]
Double **corner2Dec** [INPUT, OPTIONAL, default=default value: Dec of image pixel (width-1, height-1)]
SourceListProduct **inputSourceList** [INPUT, OPTIONAL, default=no default value]
Double **fluxPriorsLambda** [INPUT, OPTIONAL, default=default value: 1.0]
Double **fluxPriorsMin** [INPUT, OPTIONAL, default=default value: 1.0e-4]
Double **fluxPriorsMax** [INPUT, OPTIONAL, default=default value: 1.0e8]
Boolean **fitBackground** [INPUT, OPTIONAL, default=default value: False]

Properties
Double **backgroundPriorsMin** [INPUT, OPTIONAL, default=no default value]
Double **backgroundPriorsMax** [INPUT, OPTIONAL, default=no default value]
Boolean **subtractMedianBackground** [INPUT, OPTIONAL, default=default value: False]
Boolean **returnPixelCoordinates** [INPUT, OPTIONAL, default=default value: False]
Boolean **useSignalToNoise** [INPUT, Optional, default=default value: True]
SimpleImage **filteredMap** [OUTPUT, OPTIONAL, default=no default value]

Error
RuntimeException if the image has units in per-beam but no beamArea is specified

API details

Properties

SimpleImage image [INPUT, MANDATORY, default=no default value]

Image map to search for point sources

Double detThreshold [INPUT, MANDATORY, default=no default value]

Threshold at which a local maximum is detected. The meaning of this depends on the useSignalToNoise parameter and may be set to

- Either signal-to-noise or log(evidence) for SUSSEXtractor
- Either signal-to-noise or DAOPHOT H-units for DAOPHOT extractor

Double fwhm [INPUT, MANDATORY, default=no default value]

Full-width half maximum, in arcsec, of a default Gaussian point response function (PRF).

SimpleImage prf [INPUT, OPTIONAL, default=no default value]

SimpleImage of a custom point response function (PRF). If defined, this will be used in preference to the default Gaussian. The PRF should be of odd dimension, with the peak in the centre, and is interpreted as the response of the central pixels of a 1 Jy source in a map with units of the input map.

Double beamArea [INPUT, OPTIONAL, default=no default value]

Solid angle of the beam in square arcsec. For use when the input map has units of Jy/beam. For example, for a Gaussian beam profile with a given full-width half maximum, fwhm, beamArea is given by

Math.PI * fwhm**2 / 4 / LOG(2)

For PACS and SPIRE, the values given in the Observer's Manuals for the FWHM are:

Double beamArea [INPUT, OPTIONAL, default=no default value]

- PACS-70: 5.2
- PACS-100: 7.7
- PACS-160: 12
- SPIRE-PSW: 18
- SPIRE-PMW: 25
- SPIRE-PLW: 36

Double pixelRegion [INPUT, MANDATORY, default=default value: 1.5]

Radius around each pixel to consider when searching for local maxima. Units: pixels.

String algorithm [INPUT, OPTIONAL, default=default value: sussextractor]

Algorithm to use to extract sources. Currently SUSSEXtractor ("sussextractor") and DAOPHOT ("daophot") are implemented.

Double corner1Ra [INPUT, OPTIONAL, default=default value: Ra of image pixel (0,0)]

These "corner..." parameters locate two points on the image in world coordinates, defining opposite corners of a rectangle. Only sources within this rectangle will be returned in the output SourceListProduct. If these parameters are not used then the entire map will be searched. Otherwise, if at least one of these parameters are defined, then all four must be.

Double corner1Dec [INPUT, OPTIONAL, default=default value: Dec of image pixel (0,0)]

See description for corner1Ra.

Double corner2Ra [INPUT, OPTIONAL, default=default value: Ra of image pixel (width-1, height-1)]

See description for corner1Ra.

Double corner2Dec [INPUT, OPTIONAL, default=default value: Dec of image pixel (width-1, height-1)]

See description for corner1Ra.

SourceListProduct inputSourceList [INPUT, OPTIONAL, default=no default value]

SourceListProduct containing a list of "known" source positions, at which the fluxes will be extracted.

Double fluxPriorsLambda [INPUT, OPTIONAL, default=default value: 1.0]

Lambda value for SUSSEXtractor flux priors: 0 = tophat, 1 = Jeffreys, >1 = deboost

Double fluxPriorsMin [INPUT, OPTIONAL, default=default value: 1.0e-4]

Prior on minimum flux for SUSSEXtractor, in mJy

Double fluxPriorsMax [INPUT, OPTIONAL, default=default value: 1.0e8]

Prior on maximum flux for SUSSEXtractor, in mJy

Boolean fitBackground [INPUT, OPTIONAL, default=default value: False]

SUSSEXtractor flag to fit background as a free parameter

Double backgroundPriorsMin [INPUT, OPTIONAL, default=no default value]

Prior on minimum background level for SUSSEXtractor, in units of the input map

Double backgroundPriorsMax [INPUT, OPTIONAL, default=no default value]

Prior on maximum background level for SUSSEXtractor, in units of the input map

Boolean subtractMedianBackground [INPUT, OPTIONAL, default=default value: False]

SUSSEXtractor flag to subtract median background from image

Boolean returnPixelCoordinates [INPUT, OPTIONAL, default=default value: False]

Return x, y coordinates of sources in ra, dec columns. If image has a valid WCS, FWHM is assumed to be in arcsec; otherwise FWHM is assumed to be in pixels

Boolean useSignalToNoise [INPUT, Optional, default=default value: True]

Threshold to use. If set to False, for SUSSEXtractor the threshold will be log(evidence), while for DAOPHOT the threshold will be DAOPHOT H units. This will be returned as the 'quality' in the SourceListDataset.

SimpleImage filteredMap [OUTPUT, OPTIONAL, default=no default value]

The input map filtered by the PRF (SUSSEXtractor) or by the DAOPHOT kernel (DAOPHOT). In units of mJy (SUSSEXtractor)

Error

RuntimeException

if the image has units in per-beam but no beamArea is specified

2.354. SourceFittingExplorer

Full Name:	herschel.ia.gui.image.SourceFittingExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import SourceFittingExplorer

Description

An explorer for SourceFittingProducts.

An explorer for SourceFittingProducts.

API Summary

Constructors
SourceFittingExplorer() The construction of a new SourceFittingExplorer.
SourceFittingExplorer(Object object) The construction of a new SourceFittingExplorer associated with the given object.

Methods
String **getName()** Returns the name.
String **getDescription()** Returns the description.
boolean **canHandle(Class className)** Checks whether this SourceFittingExplorer can handle objects of the given class.
setObject(Object object) Sets the object.
SourceFittingProduct **getObject()** Returns the object.
Class **getVariableType()** Returns the expected variable type for this SoureFittingExplorer.
JComponent **getComponent()** Returns the component that is respondible for displaying the data object.
JScrollPane **getParameterTable()** Returns the parameter table.
addDataObjectListener(DataObjectListener listener) Adds the given listener.
removeDataObjectListener(DataObjectListener listener) Removes the given listener.

API details

Constructors

SourceFittingExplorer()

The construction of a new SourceFittingExplorer.

The construction of a new SourceFittingExplorer.

SourceFittingExplorer(Object object)

The construction of a new SourceFittingExplorer associated with the given object.

The construction of a new SourceFittingExplorer associated with the given object.

Argument

`Object` **object** [INPUT, MANDATORY]

Methods

String getName()

Returns the name.

Returns the name for this SourceFittingExplorer.

Return

String

Returns the name for this SourceFittingExplorer.

String getDescription()

Returns the description.

Returns the description for this SourceFittingExplorer.

Return

String

Returns the description for this SourceFittingExplorer.

boolean canHandle(Class className)

Checks whether this SourceFittingExplorer can handle objects of the given class.

Returns true if this SourceFittingExplorer can handle objects of the given class; false otherwise.

Argument

`Class` **className** [INPUT, MANDATORY]

Return

boolean

Returns true of this SourceFittingExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this SourceFittingExplorer to the given object.

Argument

`Object` **object** `[INPUT, MANDATORY]`

SourceFittingProduct getObject()

Returns the object.

Returns the object for this SourceFittingExplorer.

Return

SourceFittingProduct

Returns the object for this SourceFittingExplorer.

Class getVariableType()

Returns the expected variable type for this SoureFittingExplorer.

Returns the expected variable type for this SourceFittingExplorer.

Return

Class

Returns the expected variable type for this SourceFittingExplorer.

JComponent getComponent()

Returns the component that is respondible for displaying the data object.

Returns the component that is responsible for displaying the data object for this SourceFittingExplorer.

Return

JComponent

Returns the component that is responsible for displaying the data object for this SourceFittingExplorer.

JScrollPane getParameterTable()

Returns the parameter table.

Returns the parameter table for this SourceFittingExplorer.

Return

JScrollPane

Returns the parameter table for this SourceFittingExplorer.

addDataObjectListener(DataObjectListener listener)

Adds the given listener.

addDataObjectListener(DataObjectListener listener)

Adds the given listener to this SourceFittingExplorer to receive data object events from it.

Argument

DataObjectListener **listener** [INPUT, MANDATORY]

removeDataObjectListener(DataObjectListener listener)

Removes the given listener.

Removes the given listener for this SourceFittingExplorer, so that it no longer receives data object events by this explorer.

Argument

DataObjectListener **listener** [INPUT, MANDATORY]

2.355. SourceFittingPanel

Full Name:	herschel.ia.toolbox.image.gui.SourceFittingPanel
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import SourceFittingPanel

Description

A panel for the SourceFittingTask.

A panel to serve as GUI for the SourceFittingTask.

API Summary

Constructor
SourceFittingPanel() The constructor of a new SourceFittingPanel.

Methods
JPanel **getImagePanel()** Returns a display of the image.
JPanel **getButtonPanel()** Returns the button panel.
setSiteEventHandler(SiteEventHandler handler) Sets the site event handler.
setTask(TaskApi task) Associates the task.
setVariableSelection(VariableSelection selection) Sets the variable selection.
Display **getDisplay()** Returns the display of the image.
Image **getImage()** Returns the associated image.
TaskApi **getTask()** Returns the associated task.
Map **getMap()** Returns the associated map.
SiteEventHandler **getHandler()** Returns the associated site event handler
updateFigure() Updates the rectangle.
setPoint(MouseEvent me) Stores the location of the given mouse event in pixel coordinates.
setPoint(Double point)

Methods
Stores the given location in pixel coordinates.

API details

Constructor

`SourceFittingPanel()`
The constructor of a new SourceFittingPanel. The constructor of a new SourceFittingPanel.

Methods

`JPanel getImagePanel()`
Returns a display of the image. Returns a panel that displays the image for this SourceFittingPanel. **Return** **JPanel** Returns a panel that displays the image for this SourceFittingPanel.

`JPanel getButtonPanel()`
Returns the button panel. Returns the button panel for this SourceFittingPanel. **Return** **JPanel** Returns the button panel for this SourceFittingPanel.

`setSiteEventHandler(SiteEventHandler handler)`
Sets the site event handler. Sets the site event handler for this SourceFittingPanel to the given site event handler. **Argument** `SiteEventHandler` **`handler`** `[INPUT, MANDATORY]`

`setTask(TaskApi task)`
Associates the task. Associates the given task with this SourceFittingPanel. **Argument** `TaskApi` **`task`** `[INPUT, MANDATORY]`

`setVariableSelection(VariableSelection selection)`
Sets the variable selection.

setVariableSelection(VariableSelection selection)

Sets the variable selection for this SourceFittingPanel to the given variable selection.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

Display getDisplay()

Returns the display of the image.

Returns the display for this SourceFittingPanel.

Return

Display

Returns the display for this SourceFittingPanel.

Image getImage()

Returns the associated image.

Returns the image associated with this SourceFittingPanel.

Return

Image

Returns the image associated with this SourceFittingPanel.

TaskApi getTask()

Returns the associated task.

Returns the task associated with this SourceFittingPanel

Return

TaskApi

Returns the task associated with this SourceFittingPanel.

Map getMap()

Returns the associated map.

Returns the map associated with this SourceFittingPanel.

Return

Map

Returns the map associated with this SourceFittingPanel.

SiteEventHandler getHandler()

Returns the associated site event handler

Returns the site event handler associated with this SourceFittingPanel.

Return

SiteEventHandler

SiteEventHandler getHandler()

Returns the site event handler associated with this SourceFittingPanel.

updateFigure()

Updates the rectangle.

Updates the rectangle associated with this SourceFittingPanel.

setPoint(MouseEvent me)

Stores the location of the given mouse event in pixel coordinates.

Sets the position of the given mouse event at the appropriate place (i.e. at the index that corresponds with the number of times there was clicked before) in the list of clicked points for this SourceFittingPanel in pixel coordinates.

Argument

MouseEvent **me** [INPUT, MANDATORY]

setPoint(Double point)

Stores the given location in pixel coordinates.

Sets the given screen coordinates at the appropriate place (i.e. at the index that corresponds with the number of times there was clicked before) in the list of clicked points for this SourceFittingPanel in pixel coordinates.

Argument

Double **point** [INPUT, MANDATORY]

2.356. SourceFittingProduct

Full Name:	herschel.ia.dataset.image.SourceFittingProduct
Type:	Java Class -
Import:	from herschel.ia.dataset.image import SourceFittingProduct

Description

A class to handle the result of the SourceFittingTask.

A class to handle the result of the SourceFittingTask.

API Summary

Constructors
SourceFittingProduct() The construction of a new SourceFittingProduct.
SourceFittingProduct(double peak, double centerX, double centerY, double sigmaPixels, double background, Wcs wcs, Unit unit) Construction of a new SourceFittingProduct.
SourceFittingProduct(double peak, double centerX, double centerY, double sigmaXPixels, double sigmaYPixels, double rotationAngle, double background, Wcs wcs, Unit unit) Construction of a new SourceFittingProduct.

Methods
double **getPeak**() Returns the peak intensity for this SourceFittingProduct.
double **getCenterX**() Returns the x-pixel-coordinate for the center for this SourceFittingProduct.
double **getCenterY**() Returns the y-pixel-coordinate for the center for this SourceFittingProduct.
double **getCenterRA**() Returns the right ascension for the center for this SourceFittingProduct.
double **getCenterDec**() Returns the declination for the center for this SourceFittingProduct.
double **getSigmaPixels**() Returns the width for this SourceFittingProduct in pixels.
double **getSigmaXPixels**() Returns the width in the x-direction for this SourceFittingProduct in pixels.
double **getSigmaYPixels**() Returns the width in the y-direction for this SourceFittingProduct in pixels.
double **getSigmaArcsec**() Returns the width for this SourceFittingProduct in arcsec.
double **getSigmaXArcsec**()

Methods
Returns the width in the x-direction for this SourceFittingProduct in arcsec.
`double` **`getSigmaYArcsec()`** Returns the width in the y-direction for this SourceFittingProduct in arcsec.
`double` **`getRotationAngle()`** Returns the rotation angle for this SourceFittingProduct in arcsec.
`double` **`getBackground()`** Returns the background intensity for this SourceFittingProduct.
`String` **`getUnit()`** Returns the unit of the image for which the fit was made.
`setUnit``(Unit unit)` Sets the unit for this SourceFittingProduct.

API details

Constructors

`SourceFittingProduct()`

The construction of a new SourceFittingProduct.

The construction of a new SourceFittingProduct.

`SourceFittingProduct(double peak, double centerX, double centerY, double sigmaPixels, double background, Wcs wcs, Unit unit)`

Construction of a new SourceFittingProduct.

Construction of a new SourceFittingProduct with the given peak intensity, pixel coordinates of the center, width and background.

Arguments

`double` **`peak`** `[INPUT, MANDATORY]`

`double` **`centerX`** `[INPUT, MANDATORY]`

`double` **`centerY`** `[INPUT, MANDATORY]`

`double` **`sigmaPixels`** `[INPUT, MANDATORY]`

`double` **`background`** `[INPUT, MANDATORY]`

`Wcs` **`wcs`** `[INPUT, MANDATORY]`

`Unit` **`unit`** `[INPUT, MANDATORY]`

`SourceFittingProduct(double peak, double centerX, double centerY, double sigmaXPixels, double sigmaYPixels, double rotationAngle, double background, Wcs wcs, Unit unit)`

Construction of a new SourceFittingProduct.

Construction of a new SourceFittingProduct with the given peak intensity, pixel coordinates of the center, width and background.

Arguments

`double` **`peak`** `[INPUT, MANDATORY]`

`double` **`centerX`** `[INPUT, MANDATORY]`

SourceFittingProduct(double peak, double centerX, double centerY, double sigmaXPixels, double sigmaYPixels, double rotationAngle, double background, Wcs wcs, Unit unit)

double **centerY** [INPUT, MANDATORY]

double **sigmaXPixels** [INPUT, MANDATORY]

double **sigmaYPixels** [INPUT, MANDATORY]

double **rotationAngle** [INPUT, MANDATORY]

double **background** [INPUT, MANDATORY]

Wcs **wcs** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

Methods

double getPeak()

Returns the peak intensity for this SourceFittingProduct.

Returns the value for the peak parameter.

Return

double

Returns the peak intensity for this SourceFittingProduct.

double getCenterX()

Returns the x-pixel-coordinate for the center for this SourceFittingProduct.

Returns the value for the centerX parameter.

Return

double

Returns the x-pixel-coordinate for the center for this SourceFittingProduct.

double getCenterY()

Returns the y-pixel-coordinate for the center for this SourceFittingProduct.

Returns the value of the centerY parameter.

Return

double

Returns the y-pixel-coordinate for the center for this SourceFittingProduct.

double getCenterRA()

Returns the right ascension for the center for this SourceFittingProduct.

Returns the value of the centerRA parameter.

Return

double

Returns the right ascension for the center for this SourceFittingProduct.

`double getCenterDec()`

Returns the declination for the center for this SourceFittingProduct.

Returns the value of the centerDec parameter.

Return

double

Returns the declination for the center for this SourceFittingProduct.

`double getSigmaPixels()`

Returns the width for this SourceFittingProduct in pixels.

Returns the value of the sigmaPixels parameter.

Return

double

Returns the width for this SourceFittingProduct in pixels.

`double getSigmaXPixels()`

Returns the width in the x-direction for this SourceFittingProduct in pixels.

Returns the value of the sigmaXPixels parameter.

Return

double

Returns the width in the x-direction for this SourceFittingProduct in pixels.

`double getSigmaYPixels()`

Returns the width in the y-direction for this SourceFittingProduct in pixels.

Returns the value of the sigmaYPixels parameter.

Return

double

Returns the width in the y-direction for this SourceFittingProduct in pixels.

`double getSigmaArcsec()`

Returns the width for this SourceFittingProduct in arcsec.

Returns the value of the sigmaArcsec parameter.

Return

double

Returns the width for this SourceFittingProduct in arcsec.

`double getSigmaXArcsec()`

Returns the width in the x-direction for this SourceFittingProduct in arcsec.

`double getSigmaXArcsec()`

Returns the value of the sigmaXArcsec parameter.

Return

double

Returns the width in the x-direction for this SourceFittingProduct in arcsec.

`double getSigmaYArcsec()`

Returns the width in the y-direction for this SourceFittingProduct in arcsec.

Returns the value of the sigmaYArcsec parameter.

Return

double

Returns the width in the y-direction for this SourceFittingProduct in arcsec.

`double getRotationAngle()`

Returns the rotation angle for this SourceFittingProduct in arcsec.

Returns the value for the rotationAngle parameter.

Return

double

Returns the rotation angle for this SourceFittingProduct in arcsec.

`double getBackground()`

Returns the background intensity for this SourceFittingProduct.

Returns the value of the background parameter.

Return

double

Returns the background intensity for this SourceFittingProduct.

`String getUnit()`

Returns the unit of the image for which the fit was made.

Returns the unit of the image for which the fit was made for this SourceFittingProduct.

Return

String

Returns the unit of the image for which the fit was made for this SourceFittingProduct.

`setUnit(Unit unit)`

Sets the unit for this SourceFittingProduct.

Sets the unit for this SourceFittingProduct.

setUnit(Unit unit)

Argument

Unit **unit** [INPUT, MANDATORY]

2.357. SourceFittingTask

Full Name:	herschel.ia.toolbox.image.SourceFittingTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import SourceFittingTask

Description

A Task to fit a two-dimensional gaussian to a source in a specified region on an image.

A Task to fit a two-dimensional gaussian combined with a constant to a source in a specified region on an image. The user can assume a circular source or an elongated source.

API Summary

Properties
`Image image [INPUT, MANDATORY, default=No default value]`
`Double minX [INPUT, MANDATORY, default=Default value : Double.NaN]`
`Double minY [INPUT, MANDATORY, default=Default value : Double.NaN]`
`Double width [INPUT, MANDATORY, default=Default value : 0.0]`
`Double height [INPUT, MANDATORY, default=Default value : 0.0]`
`Boolean elongated [INPUT, OPTIONAL, default=Default value : true]`
`SourceFittingProduct parameters [OUTPUT, MANDATORY, default=No default value]`

Miscellaneous

For circular sources : * model : Gauss2DModel + PolySurfaceModel(degree = 0) * initial parameters : -- the maximum value in the cropped region yields an inital value for the center of the gaussian and its peak value -- the background is estimated via the Daophot algorithm (as for aperture photometry) on the whole rectangle * fitter : LevenbergMarquardtFitter For elongated sources : * model : Gauss2DRotModel + PolySurfaceModel(degree = 0) * initial paramters : -- the fit that would be done if the source was circular yields an initial value for the center and the peak value of the gaussian and for the background -- the sigma's and the rotation angle of the gaussian are estimated via profile plotting : for all straight lines through the estimated center with an angle between 0 and 180 degrees w.r.t. the x-axis (in steps of 15 degrees), a gaussian combined with a constant function is fitted (deriving the initial parameters from the circular 2D-fit) and the largest sigma is taken to be the initial value for the width of the gaussian in the x-direction and the correponding angle as initial value for the rotation angle of the gaussian; the sigma in the y-direction is estimated via the fit of the line perpendicular to the previous one * fitter : LevenBergMarquardtFitter

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The input image.

`Double minX [INPUT, MANDATORY, default=Default value : Double.NaN]`

The x-pixel-coordinate of the lower left corner of the rectangle.

Double minY [INPUT, MANDATORY, default=Default value : Double.NaN]

The y-pixel-coordinate of the lower left corner of the rectangle.

Double width [INPUT, MANDATORY, default=Default value : 0.0]

The width of the rectangle in pixels.

Double height [INPUT, MANDATORY, default=Default value : 0.0]

The height of the rectangle in pixels.

Boolean elongated [INPUT, OPTIONAL, default=Default value : true]

Indicated whether the source is elongated (or circular).

SourceFittingProduct parameters [OUTPUT, MANDATORY, default=No default value]

The fitting parameters.

2.358. SpectralProjectionAlgorithm

Full Name:	herschel.ia.toolbox.spectrum.projection.SpectralProjectionAlgorithm
Type:	Java Class -
Import:	from herschel.ia.toolbox.spectrum.projection import SpectralProjectionAlgorithm

History

- `2009-11-22 - DS`: [HCSS SCR-8470] Added methods to propagate units and metadata. Changed Column parameters to Double1d.

2.359. Spectrum1d

Full Name:	herschel.ia.dataset.spectrum.Spectrum1d
Type:	Java Class -
Import:	from herschel.ia.dataset.spectrum import Spectrum1d
Category:	Datasets

Description

Spectrum1d is an extension of AbstractSpectrumDataset which in turn

is an extension of (Strict)TableDataset. It is a 1-dimensional incarnation of a SpectrumDataset.

Spectrum1d implements an iterator over spectral segmants when these are defined.

Within a Spectrum1d there are provisions for 4 (predefined) columns.

1. flux, a Double1d array. This flux column is more or less obligatory, otherwise there can't be much talk of a spectrum.

2. weight. A Double1d array of the same dimensionality as flux.

   weight = 0, means that the corresponding samples are irrelevant.

   weight = 1 / stdev^2, if such a value is available for the fluxes.

3. flag, an Int1d array of the same size as flux. The definition of flags is of course problem dependent. It is suggested to store the meaning of the flags in MetaData.

4. segment, an Int1d array of the same size as flux. The values within this array indicate to which segment the corresponding flux/weight/flag/wave belong. If this column is not present it is assumed the Spectrum1d contains only one {@link SpectralSegment spectral segment}.

The other part that a spectrum needs is a frequency or wavelength scale. See {@link herschel.ia.dataset.spectrum.AbstractSpectrumDataset}

Example

Example 1: In Jide:

```
#flux is a Double1d
#segment is a Int1d of the same length containing [1,1,...1,2,2,...2,3,3...]
s1 = Spectrum1d()
s1.setFlux( flux -)
s1.setSegment( segment -)
it = s1.iterator()
seg = s1.getSpectralSegment()
while it.hasNext() -:
  print F.p( seg.getFlux() -)        # gets the 1's, the 2's etc.
  seg = it.next()
```

Limitations

Spectrum1d still **is** a TableDataset and can be addressed as such. If you do so, the special methods of Spectrum1d (and its predecessors, AbstractSpectrumDataset and StrictTableDataset) are **not** guarandeed to work.

History

- 06-03-2006 DK.

2.360. Spectrum2d

Full Name:	herschel.ia.dataset.spectrum.Spectrum2d
Type:	Java Class -
Import:	from herschel.ia.dataset.spectrum import Spectrum2d
Category:	Datasets

Description

Spectrum2d is an extension of AbstractSpectrumDataset which in turn

is an extension of (Strict)TableDataset. It is a 2-dimensional incarnation of a SpectrumDataset.

Within a Spectrum2d there are provisions for 3 (predefined) columns.

1. flux, a Double2d array, where the first axis runs over the spectral dimension and the second axis runs over e.g. time. In the following this time index is called sequential index or sequindex.

   There is no requirement that either axis projects monotonically or equidistantly on the frequency/sequindex scale. It is not even necessary that they are independent, ie. frequency can change over sequindex. This flux column is more or less obligatory, otherwise there can't be much talk of a spectrum.

2. weight. An Double2d array of the same dimensionality as flux.

   weight = 0, means that the corresponding samples are irrelevant.

   weight = 1 / stdev^2, if such a value is available for the fluxes.

3. flag, an Int1d array of the same size as flux. The definition of flags is of course problem dependent. It is suggested to store the meaning of the flags in MetaData.

The other part that a spectrum needs is a frequency or wavelength scale. See {@link herschel.ia.dataset.spectrum.AbstractSpectrumDataset}

As a further extension of the Spectrum2d we introduce the concept of "subbands". Subbands are vertical splits in the flux (and weight, flag etc.) columns, equivalent to (functionality of) the segment column in {@link Spectrum1d}. The flux etc. columns are replaced with flux_1, flux_2, ... columns, depending on how many subbands were defined. The definition of the subbands is stored in small array MetaData subbandstart and subbandlength. {@link herschel.ia.dataset.spectrum.StrictTableDataset#setMeta(String name, Double1d data)} Operations of split and join are exact inverses of each other as long as the metadata of subbandstart and subbandlength is kept consistent and provided that the subband ranges cover the complete width of flux. Otherwise what is lost will stay so.

The {@link SpectralSegment SpectralSegment} interface is fully implemented on Spectrum2d, whether it has subbands or not. When there are no subbands, each time a next segment is requested, the next row is returned. When subbands are present, first a row from the next subband at the same sequential index is returned. When there are no more subbands, the row at the next sequindex in the first subband is returned. This behaviour can be overruled by {@link #setColumnFirst(boolean cf)}.

Example

Example 1: In Jide:

```
flux = Double2d()
for i in range(5) -: flux.appendRow( Double1d( range(1000 -) -) + i -)
```

Example 1: In Jide:

```
flag = Int2d( 5, 1000 -)
s2 = Spectrum2d( flux, None, flag -)
F = DataFormatter()
print F.p( s2.getFlux( -), 6 -)
s2.setMeta( -"subbandstart", Int1d( [0,100,500] -) -)
s2.setMeta( -"subbandlength", Int1d( [100,200,400] -) -)
s2.splitInSegments( ["flux","flag"] -);
print F.p( s2.getFlux( 2 -) -)
print s2.getSegmentCount()            # 15 = 5 * 3
it = s2.iterator()
seg = s2.getSpectralSegment()
while it.hasNext() -:
  seg = it.next()
  print F.p( seg.getFlux() -)
```

Limitations

Spectrum2d still **is** a TableDataset and can be addressed as such. If you do so, the special methods of Spectrum2d (and its predecessors, AbstractSpectrumDataset and StrictTableDataset) are **not** guarandeed to work.

History

- 07-03-2006 DK.

2.361. SpectrumPlotting

Full Name:	herschel.ia.gui.cube.SpectrumPlotting
Type:	Java Class -
Import:	from herschel.ia.gui.cube import SpectrumPlotting

Description

SpectrumPlotting

A class to deal with CubeSpectrumAnalysis, the real creactomputation of the spectrum is mades in the task ExtractSpectrum()

API Summary

Constructor
SpectrumPlotting(boolean useAsComponent, CubeSpectrumAnalysisToolbox toolbox) Constructor for SpectrumPlotting. When the new SpectrumPlotting is

Methods
setClicked(Double center) Sets the center of the rectancle, associated with this
PlotXY **getPlot**() Returns the PlotXY, shown in this SpectrumPlotting.
ImageFigure **getRect**() Returns the straight line (ImageFigure), of which we wish to plot
Double **getClicked**() Returns the clicked position in PixelCoordinates.
int **getClicks**() Returns the number of valid clicks (i.e. in the image) you made.
void **resetClicks**() reste the number of valid clicks
String **getSkyCoordinates**() Returns the String version of the sky coordinates
String **getPixelCoordinates**() Returns the String version of the PixelCoordinates center of
setPlot() initiate the PlotXY, shown in this SpectrumPlotting.
boolean **checkPointclicked**() Returns a Flag
ArrayList **getImageFigures**() Returns all ImageFigures used for this SpectrumPlotting (the
Double1d **getSpectrum**() Returns a Double1d at this date containing the spectrum values

Methods
Spectrum1d **getSpectrum1d**() Returns a Spectrum1d containing the currently extracted spectrum
void **saveFits**() Returns all ImageFigures used for this SpectrumPlotting (the
void **saveScript**() Returns all ImageFigures used for this SpectrumPlotting (the

API details

Constructor

SpectrumPlotting(boolean useAsComponent, CubeSpectrumAnalysisToolbox toolbox)

Constructor for SpectrumPlotting. When the new SpectrumPlotting is

component-based, a window for plotting the intensity is opened; otherwise nothing will be shown.

Arguments

boolean **useAsComponent** [INPUT, MANDATORY]

CubeSpectrumAnalysisToolbox **toolbox** [INPUT, MANDATORY]

Methods

setClicked(Double center)

Sets the center of the rectancle, associated with this

SpectrumPlotting to the given point (in UserCoordinates).

Argument

Double **center** [INPUT, MANDATORY]

PlotXY getPlot()

Returns the PlotXY, shown in this SpectrumPlotting.

Return

PlotXY

The PlotXY, shown in this SpectrumPlotting.

ImageFigure getRect()

Returns the straight line (ImageFigure), of which we wish to plot

the intensity in this SpectrumPlotting.

Return

ImageFigure

The straight line (ImageFigure), of which we wish to plot the intensity in this SpectrumPlotting.

Double getClicked()

Returns the clicked position in PixelCoordinates.

Double getClicked()

Return

Double

Returns the clicked position in PixelCoordinates.

int getClicks()

Returns the number of valid clicks (i.e. in the image) you made.

Return

int

Returns the number of valid clicks (i.e. in the image) you made.

void resetClicks()

reste the number of valid clicks

Return

void

reset the number of valid clicks

String getSkyCoordinates()

Returns the String version of the sky coordinates

(WorldCoordinates) of the point Clicked.

Return

String

Returns the String version of the sky coordinates (WorldCoordinates) of the point Clicked.

String getPixelCoordinates()

Returns the String version of the PixelCoordinates center of

the rectanlgle which is also the point analysed.

Return

String

Returns the String version of the PixelCoordinates.

setPlot()

initiate the PlotXY, shown in this SpectrumPlotting.

boolean checkPointclicked()

Returns a Flag

Return

boolean

returns a Boolean Flag which allow the extraction of the spectrum at the given position.

ArrayList getImageFigures()

Returns all ImageFigures used for this SpectrumPlotting (the

rectangle on the image).

Return

ArrayList

Returns all ImageFigures used for this SpectrumPlotting (the rectangle on the image).

Double1d getSpectrum()

Returns a Double1d at this date containing the spectrum values

Return

Double1d

Returns a Double1d at this date containing the spectrum values

Spectrum1d getSpectrum1d()

Returns a Spectrum1d containing the currently extracted spectrum

Return

Spectrum1d

Returns a Spectrum1d containing the currently extracted spectrum

void saveFits()

Returns all ImageFigures used for this SpectrumPlotting (the

rectangle on the image).

Return

void

Returns all ImageFigures used for this SpectrumPlotting (the rectangle on the image).

void saveScript()

Returns all ImageFigures used for this SpectrumPlotting (the

rectangle on the image).

Return

void

Returns all ImageFigures used for this SpectrumPlotting (the rectangle on the image).

2.362. SpectrumStatistics

Full Name:	herschel.ia.toolbox.spectrum.SpectrumStatistics
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import SpectrumStatistics

Description

Task to compute statistical characteristics for the spectrum data included in one or several containers.

Mean, RMS and median are always reported - percentiles can be given on demand. Two modes are available: Compute the statistics over a set of PointSpectra on a channel by channel basis or compute the statistics for a range within a single point spectrum.

Example

Example 1: from Jide:

```
from herschel.ia.toolbox.spectrum import SpectrumStatistics
# ds: some spectrum container
statistics = SpectrumStatistics()
stats = statistics(ds=ds, mode="all") # stats is a product
stats = statistics(ds=ds, mode="perChannel") # stats is a product but
without -"summary" TableDataset
stats = statistics(ds=ds, mode="acrossChannels") # stats is a TableDataset
stats = statistics(ds=ds, mode = -"all", percentiles=[0.2,0.8], ranges =
Range(500,1500))
stats = statistics(ds=ds, mode = -"acrossChannels", percentiles=[0.2,0.8],
ranges = (4200,4500))
stats = statistics(ds=ds, mode = -"acrossChannels", percentiles=[0.2,0.8],
ranges = [(4200,4500),(7300,7600)])
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, MANDATORY, default=no default value.]
String **mode** [INPUT, OPTIONAL, default=default value 'all'.]
Object **stats** [OUTPUT, OPTIONAL, default=no default value.]
Object **ranges** [INPUT, OPTIONAL, default=no default value.]
double[] **percentiles** [INPUT, OPTIONAL, default=no default value.]
Boolean **ignoreNaNs** [INPUT, OPTIONAL, default=False.]

API details

Properties

SpectrumContainer ds [INPUT, MANDATORY, default=no default value.]

The input container(s) to be considered.

String mode [INPUT, OPTIONAL, default=default value 'all'.]

Contains the output with the statistics when the task is used in the normal mode. Possible values are 'acrossChannel', 'perChannel', 'all'. 'acrossChannel'-mode: Here, the statistics are computed

String mode [INPUT, OPTIONAL, default=default value 'all'.]

separately for each spectrum and each segments. If a range has been set, this range is taken accordingly. 'perChannel'-mode: Here, the statistics are computed for all the spectra included in the container on a per channel basis. 'all': Both, the per channel and the across channel statistics are computed.

Object stats [OUTPUT, OPTIONAL, default=no default value.]

If the task is used in the per channel mode, a product is created which contains for each statistical characteristics and each sub-segment one Spectrum1d. In case 'mode' is set to 'all', the product also contains the across channel statistics as a "summary". In case the task is used in the across channel mode, the statistics are written in a TableDataset (each point spectrum included in the input spectrum container corresponds a line in the table).

Object ranges [INPUT, OPTIONAL, default=no default value.]

Specify the ranges that should be considered within the spectra when computing the 'across channels'-statistics. You have various alternatives to do that:

- Specify a 'Range'-object: Then this range object is considered for all the sub-segments as the range of pixel numbers to select.
- Specify an array of 'Range'-objects: Here, each Range object in the array is associated with the Range of pixel number to select for each sub-segments. The number of ranges specified in the array must correspond to the number of segments.
-
-

double[] percentiles [INPUT, OPTIONAL, default=no default value.]

Specify what percentiles should be given in the output (a list of probabilities).

Boolean ignoreNaNs [INPUT, OPTIONAL, default=False.]

Flag to specify that NaN's found in the flux data should be ignored when computing the statistics.

History

- `2008-06-05 - meli`: initial.
- `2008-06-14 - meli`: more methods to specify ranges.
- `2008-06-05 - meli`: ignoreNaNs added.

2.363. SpectrumTask

Full Name:	herschel.ia.toolbox.spectrum.SpectrumTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import SpectrumTask

Description

Abstract base class for tasks processing {@link SpectrumContainer} data structures.

2.364. SpireFlags

Full Name:	herschel.ia.obs.quality.SpireFlags
Type:	Java Class -
Import:	from herschel.ia.obs.quality import SpireFlags

History

- 03 Jun 09: Renamed several "get" methods to address SPR 6995.
- 16 Jul 09: Added more quality control flags (see SPR-7431).

2.365. SQRT

Full Name:	herschel.ia.numeric.toolbox.basic.Sqrt
Alias:	SQRT
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Sqrt

Description

Computes x=#x, where x is a number or a numeric array.

Example

Example 1: Apply SQRT on a Int1d

```
x=Int1d( [0,4,9] -)
print SQRT(x) # [0,2.,3.]
```

API Summary

Jython Syntax
<y>=SQRT(<x>)

Properties
any number or array **x** [INPUT, MANDATORY, default=no default value]
boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any number or array x [INPUT, MANDATORY, default=no default value]

The input can be a number or an array

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns an array (or a number if the input is not an array) where each element is the the # of the corresponding element of the input array

2.366. SQUARE

Full Name:	herschel.ia.numeric.toolbox.basic.Square
Alias:	SQUARE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Square

Description

Computes $x=x^2$, where x is a number or a numeric array.

Example

Example 1: Apply SQUARE on a Int1d

```
x=Int1d( [-1,0,2] -)
print SQUARE(x) # [1,0,4]
```

API Summary

Jython Syntax
<y>=SQUARE(<x>)

Properties
any number or array **x** [INPUT, MANDATORY, default=no default value]
boolean array or a boolean **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any number or array x [INPUT, MANDATORY, default=no default value]

The input can be a number or an array

boolean array or a boolean y [OUTPUT, MANDATORY, default=no default value]

Returns an array (or a number if the input is not an array) where each element is the the square of the corresponding element of the input array

2.367. Sso

Full Name:	herschel.ia.toolbox.pointing.Sso
Type:	Java Class -
Import:	from herschel.ia.toolbox.pointing import Sso
Category:	toolbox

Description

To obtain an Horizons object you need an Ephemeris object and a directory with SSO files

Example

Example 1: Untitled

```
TODO
```

History

- Tools for SSO centered coordinate systems
- The origin of a object-centered reference frame is defined as the instantaneous ephemeris of the solar system object
- To reposition SKY(X,Y) as (OCX,OCY)
- For Attitude

2.368. STDDEV

Full Name:	herschel.ia.numeric.toolbox.basic.StdDev
Alias:	STDDEV
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import StdDev

Description

Yields the standard deviation of the elements in the input array.

The standard deviation is equivalent to SQRT(VARIANCE(x)).

Example

Example 1: Apply STDDEV on a Float1d

```
x=Float1d([1,3,2,3,4])
print STDDEV(x) # 1.3
```

API Summary

Jython Syntax
<y>=STDDEV(<x>)

Properties
any scalar array x [INPUT, MANDATORY, default=no default value]
double y [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array integral or floating-point arrays; the former implicitly transformed to a double array.

double y [OUTPUT, MANDATORY, default=no default value]

Returns a double

See also

- MEAN
- MEDIAN
- VARIANCE

2.369. StitchSpectrum

Full Name:	herschel.ia.toolbox.spectrum.StitchSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import StitchSpectrum

Description

Task for stitching the spectra (segments) included in a SpectrumContainer.

The stitching is performed on a per point spectrum (scan) basis. The result is again a point spectrum that still may consist of several segments - in case gaps are found between consecutive segments. The way how the stitching is done is defined by the parameter 'variant' (see below). Once the stitching is done, the resulting point spectra are included in a new spectrum container. Here, in general, resampling is needed so that all the resulting point spectra have the same shape (which is a requirement so that the point spectra can be included in a common container (dataset)). In case no or a zero stepsize (which is the channel width for the resampled spectra) is specified, resampling is avoided if all the stitched point spectra happen to have all the same shape.

Example

Example 1: from Jide:

```
# all defaults -- cut at crossover points and concatenate
stitched11 = stitch(ds=spectra)
# cut at crossover points and concatenate
stitched12 = stitch(ds=spectra, variant="crossoverPoints")
# cut at crossover points and concatenate, consider crossover points only by
10 percent off the border to of the overlapping region
stitched13 = stitch(ds=spectra, variant="crossoverPoints", edgeTolerance=0.1)
# cut at crossover points and concatenate, resample the resulting spectra to
1MHz channel width
stitched14 = stitch(ds=spectra, variant="crossoverPoints", edgeTolerance=0.1,
stepsize=1.0, unit="MHz")
# cut at mid points of the overlapping regions and concatenate
stitched21 = stitch(ds=spectra, variant="midPoints")
# cut at mid points of the overlapping regions and concatenate, resample to
1.0 channel width (in units of the underlying frequency scale)
stitched22 = stitch(ds=spectra, variant="midPoints", stepsize=1.0)
# cut at predefined split points and concatenate
stitched31 = stitch(ds=spectra, variant="splitPoints", splitPoints = [5000.0,
6000.0, 7000.0])
# cut at predefined split points and concatenate, resample to 1.0 channel
width (in units of the underlying frequency scale)
stitched32 = stitch(ds=spectra, variant="splitPoints", splitPoints = [5000.0,
6000.0, 7000.0], stepsize=1.0)
# cut at predefined split points and concatenate, resample to 0.001 GHz
channel width
stitched33 = stitch(ds=spectra, variant="splitPoints", splitPoints = [5.0,
6.0, 7.0], stepsize=0.001, unit="GHz")
# average the parts of the spectra that are overlapping, resample to a 1.0
channel width (in units of the underlying frequency scale)
stitched4 = stitch(ds=spectra, variant="average", stepsize=1.0)
# average the parts of the spectra that are overlapping, resample to a 1.0
MHz channel width, do not consider flags and weights
# when computing teh average (but propagate them)
stitched41 = stitch(ds=spectra, variant="average", stepsize=1.0, unit="MHz",
avg_variant="flux")
# average the parts of the spectra that are overlapping, avoid resampling as
far as possible
stitched42 = stitch(ds=spectra, variant="average", avg_variant="flux")
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, MANDATORY, default=no default value.]
SpectrumContainer **result** [OUTPUT, MANDATORY, default=no default value.]
String **variant** [INPUT, OPTIONAL, default="crossoverPoints".]
double **edgeTolerance** [INPUT, OPTIONAL, default=0.01.]
Object **splitPoints** [INPUT, OPTIONAL, default=no default value]
double **stepsize** [INPUT, OPTIONAL, default=no default value.]
String **unit** [INPUT, OPTIONAL, default=no default value.]
String **avg variant** [INPUT, OPTIONAL, default=no default value.]

API details

Properties

SpectrumContainer ds [INPUT, MANDATORY, default=no default value.]

The input container with the spectra to be stitched.

SpectrumContainer result [OUTPUT, MANDATORY, default=no default value.]

The output container with the stitched spectra.

String variant [INPUT, OPTIONAL, default="crossoverPoints".]

The parameter that specifies the way how the stitching should be done. Possible values:

- "crossoverPoints": In overlapping ranges of the spectra a crossover point is taken to split the spectra. In case no crossover point is found a point is taken where the spectra come closest. In case many crossover points are found the one closest to the midpoint of the overlapping range is taken. The range where the crossover points are searched for is reduced by setting a non-zero edge tolerance (see parameter `edgeTolerance` below). This option only works if at most two segments 'participate' in the same overlapping range.
- "midPoint": In the overlapping ranges of the spectra the mid point is taken to split the spectra. Similar to the above, this option only works if at most two segments 'participate' in the same overlapping range.
- "splitPoints": In the overlapping ranges of the spectra previously specified points are taken to split the spectra (parameter `splitPoints`). the mid point is taken. Similar to the above, this option only works if at most two segments 'participate' in the same overlapping range.
- "average": In the overlapping ranges the average of the involved spectra is taken. This option allows to stitch spectra in which more than two spectra contribute to the same overlapping part.

double edgeTolerance [INPUT, OPTIONAL, default=0.01.]

Reduce the range (an overlapping range in the spectra) in which cross over points are searched. With `length` denoting the length of the original overlapping range `[n,m]` (in number of

double edgeTolerance [INPUT, OPTIONAL, default=0.01.]

pixels) the reduced range is defined by `[n+p*length, m-p*length]` where `p` is the edge tolerance.

Object splitPoints [INPUT, OPTIONAL, default=no default value]

Specify the list of split points explicitly. This parameter is used only in combination with the option `variant="splitPoints"`. The split points are specified as a Python list. Note that the number of split points shoudl correspond to the number of overlapping ranges (per point spectrum).

double stepsize [INPUT, OPTIONAL, default=no default value.]

Specify the stepsize used to define a linear frequency the spectra are resampled to. The resampling is important in the following situations:

- When including the stitched point spectra in a common container. In case a `stepsize>0` is specified, a frequency grid is constructed with the given step size. The upper and lower bounds are determined from the minimum and maximum frequencies found in all the stitched point spectra (for a give segment index). In case a `stepsize=0` is specified, the frequency grid found in the first (stitched) point spectrum is taken as the output grid.
- When using `variant="average"` the spectra contributing to common ovrlapping frequency ranges are resampled to a common frequency grid.

When searching for crossover points, one of the spectra also needs to be resampled to a common frequency scale - here, the frequency scale of the other spectrum is used, though so that the `stepsize` parameter is not needed here.

String unit [INPUT, OPTIONAL, default=no default value.]

The unit the stepsize and/or split points are expressed in. In case no unit is specified the stepsize and/or the split points are assumed to be in the same units as the underlying frequency grid.

String avg_variant [INPUT, OPTIONAL, default=no default value.]

The variant of the average to be used: whether to include flags and weights in the processing.

History

- `2009-11-21 - meli`: initial.

2.370. String1d

Full Name:	herschel.ia.numeric.String1d
Type:	Java Class -
Import:	from herschel.ia.numeric import String1d

Description

A rectangular numeric String array of rank 1.

Numeric arrays are part of the Numeric library. An explanation on how to use them, you can find in chapter **Numeric -> Arrays**. (Yes, it should be a link)

2.371. SubtractSpectrum

Full Name:	herschel.ia.toolbox.spectrum.SubtractSpectrum
Type:	Java Task -
Import:	from herschel.ia.toolbox.spectrum import SubtractSpectrum

Description

Task for subtracting a scalar from the flux data included in a spectrum container or for subtracting two spectrum containers from each other on a spectrum-by-spectrum basis.

For the scalar mode, 'ds' and 'param' need to specified - for the pair-wise mode, 'ds1' and 'ds2' need to be set. In the pairwise mode, the task iterates through the two containers and computes the pair-operation. In case the size of the two containers is different, the iteration stops at the minimum size. Hence, the remaining spectra in the larger container are ignored. In case one of the datasets only contains a single spectrum, the task always refers to this single spectrum while iterating over all the spectra in the other dataset.

Different selection schemes are available for selecting the point spectra or the segments to be processed. The most simple scheme is to specify lists of point spectrum indices (`selection=[1,3,4,2]`). In this case, the operation (scalar- or pair-operation) is just taken over the point spectra with corresponding indices. Instead of specifying a list of indices (which requires the knowledge of these) other recipes to specify a selection are available. Typical recipes test attribute values to match certain values or to be included in a given interval. These recipes we refer to as selection models. The different options to specify selections can be combined. Here, an AND logic is adopted.

Similarly, you can specify what segments to consider. In the most simple case, you can just specify the indices of segments to be considered (for the scalar operation `segments=[1,3,4]` and for the pair operation `segments1=[1,3,4], segments1=[3,6,5]`). In more advanced situations you can use a `SegmentSelection` object. Note that the pairs of segments to be processed need to be consistent - otherwise the processing will fail.

You can specify whether the orginal datasets should be overwritten with the 'overwrite' flag. By default no data is overwritten. In the pair-wise mode, it is not always possible to overwrite the data - in particular if non-trivial segment selections are specified.

For the pair-wise mode, there are further options that can be selected by the 'variant' (e.g. whether to use flags and weights).

Example

Example 1: from Jide:

```
from herschel.ia.toolbox.spectrum import SubtractSpectrum
subtract = SubtractSpectrum()
subtractConstant = subtract(ds=spectra, param=2.1)
subtractedFactor = subtract(ds=spectra, selection={"bbtype":[6031]}, param=2.1)
subtractedFactor = subtract(ds=spectra, selection=[0,1,2,3], param=2.1)
subtractedFactor = subtract(ds=spectra, selection={"Chopper":
([-4.4,5.9],0.2), -"bbtype":[6031]}, param=2.1)
subtractedFactor = subtract(ds=spectra, selection={"LoFrequency":
(4000.0,5000.0)}, param=2.1)
subtractedPairWise = subtract(ds1=spectra1, ds2=spectra2)
subtractedPairWise = subtract(ds1=spectra1, ds2=spectra2, selection={"bbtype":
[6031]})
subtractedPairWise = subtract(ds1=spectra1, ds2=spectra2, selection=[0,1,2,3])
subtractedPairWise = subtract(ds1=spectra1, ds2=spectra2, selection={"Chopper":
([-4.4,5.9],0.2), -"bbtype":[6031]})
```

Example 1: from Jide:

```
subtractedPairWise = subtract(ds1=spectra1, ds2=spectra2,
selection={"LoFrequency":(4000.0,5000.0)})
```

API Summary

Properties
SpectrumContainer **ds** [INPUT, OPTIONAL, default=no default value.]
Double **param** [INPUT, OPTIONAL, default=no default value.]
Object **selection** [INPUT, OPTIONAL, default=None.]
PyDictionary|Map> **selection_lookup** [INPUT, OPTIONAL, default=no default value.]
PyList **selection_index** [INPUT, OPTIONAL, default=No default value.]
Boolean **overwrite** [INPUT, OPTIONAL, default=False.]
SpectrumContainer **ds1** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **ds2** [INPUT, OPTIONAL, default=no default value.]
Object **segments** [INPUT, OPTIONAL, default=no default value.]
Object **segments1** [INPUT, OPTIONAL, default=no default value.]
Object **segments2** [INPUT, OPTIONAL, default=no default value.]
String **variant** [INPUT, OPTIONAL, default=no default value.]
SpectrumContainer **result** [OUTPUT, OPTIONAL, default=no default value]

API details

Properties

SpectrumContainer ds [INPUT, OPTIONAL, default=no default value.]

Input container to be processed by the task in case the task is used as a scalar operation.

Double param [INPUT, OPTIONAL, default=no default value.]

The scalar parameter to be considered when the task is used as scalar operation.

Object selection [INPUT, OPTIONAL, default=None.]

Specify what point spectra the operation should be applied to. Different ways to specify these selections are possible:

- Specify a list of indices (in jython) of the point spectra for which the add should be applied.
- Use a dictionary (in jython) to specify a selection model (lookup for attributes, filter attributes to be included in ranges or intervals).
- Pass a string representation of a jython list or a jython dictionary. The string will be parsed and the prcessing delegated to the two cases above.
- Pass any java instance that implements the SelectionModel interface (for the advanced user).

PyDictionary|Map> selection_lookup [INPUT, OPTIONAL, default=no default value.]

Specify a PyDictionary with keys given by the attribute name to look up and a list of admissible values. Behind the scenes, a DiscreteValueSelectionModel is instantiated.

PyList selection_index [INPUT, OPTIONAL, default=No default value.]

Specify a PyList with the indices of the point spectra to be considered.

Boolean overwrite [INPUT, OPTIONAL, default=False.]

Specify whether the input data container can be reused - the values found therein is overwritten.

SpectrumContainer ds1 [INPUT, OPTIONAL, default=no default value.]

First input container for pair-wise operations.

SpectrumContainer ds2 [INPUT, OPTIONAL, default=no default value.]

Second input container for pair-wise operations.

Object segments [INPUT, OPTIONAL, default=no default value.]

Specify what segments the operation should be applied to. There are two options available:

- Either pass an instance of a SegmentSelection which gives the information on what segments for each point spectrum included in the container.
- Specify a PyList of segment indices.

Object segments1 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds1'.

Object segments2 [INPUT, OPTIONAL, default=no default value.]

Specify the segment selection to be associated with 'ds2'.

String variant [INPUT, OPTIONAL, default=no default value.]

Specify the variant of processing mode you would like to run (including flags / weights / ...). HCSS defaults include: "flux" / "flux-wave" / "flux-wave-weight" / "flux-flag-wave" / "flux-weight-flag-wave"

SpectrumContainer result [OUTPUT, OPTIONAL, default=no default value]

Result object containing the results of the operation applied.

See also

- SpectrumTask

History

- `2007-08-17 - meli`: initial.

- `2008-03-16 - meli`: major refactoring of the toolbox.
- `2008-10-03 - meli`: segments, javadoc

2.372. SUM

Full Name:	herschel.ia.numeric.toolbox.basic.Sum
Alias:	SUM
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Sum

Description

Yields the sum of all elements in the input array.

Returns a scalar of the same type as the type of the input array.

Example

Example 1: Apply SUM on a Int2d

```
x=Int2d( [ [1,2], [-1,3] -])
print SUM(x)    # 5
print SUM(x, 0) # [0,5]
print SUM(x, 1) # [3,2]
```

API Summary

Jython Syntax

```
<y>=SUM(<x>, [,<dim>])
```

Properties

any scalar array **x** [INPUT, MANDATORY, default=no default value]

integer **dim** [INPUT, MANDATORY, default=no default value]

float or double array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array can be any scalar array.

integer dim [INPUT, MANDATORY, default=no default value]

The dimension to compute the calculation along

float or double array y [OUTPUT, MANDATORY, default=no default value]

Returns a scalar of the same type as the type of the input array.

See also

- PRODUCT

2.373. TablePlotter

Full Name:	herschel.ia.gui.explorer.table.TablePlotter
Type:	Java Class -
Import:	from herschel.ia.gui.explorer.table import TablePlotter

Description

TablePlotter is a GUI tool to view and analyze TableDataset. It can be invoked in JIDE and HIPE by right clicking

on a TableDataset. It can also be invoked by a Jython command line in JIDE or Hipe through jython script. By default, the second column is plotted as y data and first column as x data unless x and y index are specified. All the default can be changed vs a group of buttons and selectors.

Example

Example 1: Invoke TablePlotter from command line

```
TablePlotter is a pluggable component which can be plugged in any GUI
containers.
Example:  This example shows how to use TablePlotter in command line
<pre>
from herschel.ia.io.fits import FitsArchive
from herschel.ia.dataset import TableDataset
from herschel.ia.dataset import Product
from herschel.ia.gui.explorer.table import TablePlotter
from herschel.ia.gui.explorer.table import OverPlotter
from herschel.ia.gui.explorer.table import *
from herschel.share.component import *
################################################
# Load your data
################################################
fits=FitsArchive();
path="/home/zhang/Development/data/"
filename = -"loadCurve.fits"
try:
     fits.reader = FitsArchive.HCSS_READER
     p = fits.load(path+filename)
 except java.io.IOException:
    fits.reader = FitsArchive.STANDARD_READER
     p = fits.load(path+filename)
 ################################################
 # Load TablePlotter with a TableDataset only
 ################################################
 tbs =p.default
 tpl=TablePlotter(tbs)
 wm=WindowManager.getDefault()
 #Load TablePlotter
 wm.addWindow('test', tpl.component, 1)
 #get extracted table
 extractedTable = tpl.activeLayerStruct.extractedTableDataset
 #get flags
 flags = tpl.activeLayerStruct.flags
 print flags.size
 print flags.dimensions
 ################################################
 # Load a TablePlotter with a 2d flags
 ################################################
 tpl1=TablePlotter(tbs, flags)
 wm=WindowManager.getDefault()
 print tbs.rowCount
 #Load TablePlotter
```

Example 1: Invoke TablePlotter from command line

```
wm.addWindow('test 2d fkags', tpl1.component, 1)
################################################
# Load TablePlotter with a 1d flag
################################################
flag=flags.get(Range(0, tbs.rowCount), 1)
tpl2=TablePlotter(tbs, flag)
wm=WindowManager.getDefault()
print tbs.rowCount
#Load TablePlotter
wm.addWindow('test 1d flags', tpl2.component, 1)
flags1d = tpl2.activeLayerStruct.flags
print flags1d.size
</pre>
```

API Summary

Constructors
TablePlotter() A default constructor
TablePlotter(TableDataset tds) A constructor
TablePlotter(TableDataset tds, Bool2d flags) A constructor
TablePlotter(TableDataset tds, integer xIndex, integer yIndex) A constructor
TablePlotter(TableDataset tds, Bool1d flags, integer xIndex, int yIndex) A constructor
TablePlotter(TablePlotter tds, Bool1d flags) This constructor will initiate an instance of TablePlotter with pre selected and de-selected columns.

Methods
JComponent **getComponent**() Inherit from explorer
String **getDescription**()
String **getName**()
setObject(Object data)
LayerStruct **getActiveLayerStruct**() This is a command line API. It is a getter to get the active LayerStruct object.

Limitations

The TableDataset has to be one dimensional numeric array such as Double1d, Float1d, Long1d, Short1d and Complex1d.

Miscellaneous

All the examples here are given in Jython script

API details

Constructors

TablePlotter()

A default constructor

This is a default constructor which will be called in DatasetInspector It initializes the DataObjectLinsterSupport for data extraction.

TablePlotter(TableDataset tds)

A constructor

This constroctor will initialize and create an instance of TablePlotter for the input dataset.

Argument

`TableDataset` **`tds`** `[INPUT, MANDATORY, default=no default value]`

A TableDataset to be plotted. It contains one or more columns.

Example

Create a TablePlotter instance with a tds dataset

```
from hersechl.ia.gui.explorer.table import TablePlotter  #import
TablePlotter
tpl=TablePlotter(tds)  #tds is a dataset defined somewhere
else
```

TablePlotter(TableDataset tds, Bool2d flags)

A constructor

This constructor will initiate an instance of TablePlotter with two inputs, a TableDataset and its flags. The flags tell which data points are selected and de-selected. TablePlotter will display two layer plots and one of which is for selected data (blue color) and the other is for de-selected data (red color).

Arguments

`TableDataset` **`tds`** `[INPUT, MANDATORY, default=no default value]`

A TableDataset to be plotted and viewed. It contains one or more columns.

`Bool2d` **`flags`** `[INPUT, MANDATORY, default=no default value]`

A flags to indicate which data points are selected and de-selected.

Example

create a TablePlotter instance with a tds dataset and flags

```
<pre>
 from hersechl.ia.gui.explorer.table import TablePlotter #import
TablePlotter
 tpl=TablePlotter(tds, flags) #tds and flags are defined somewhere else
</pre>
```

TablePlotter(TableDataset tds, integer xIndex, integer yIndex)

A constructor

This constructor will initiate an instance of an TablePlotter with three input, a table, the xIndex and the yIndex.

TablePlotter(TableDataset tds, integer xIndex, integer yIndex)

Arguments

`TableDataset` **`tds`** `[INPUT, MANDATORY, default=no default value]`

A TableDataset to be plotted and viewed. It contains one or more columns.

`integer` **`xIndex`** `[INPUT, MANDATORY, default=no default value]`

The xIndex is an integer which indicates the x column data

`integer` **`yIndex`** `[INPUT, MANDATORY, default=no default value]`

The yIndex is an integer which indicates the y column data

Example

create an instance of TablePlotter where column 3 is x and column 10 is y

```
from hersechl.ia.gui.explorer.table import TablePlotter #import the
TablePlotter
#plot the 10th column vs the first column from tds table
tablePlotter = TablePlotter (tds, 0, 10)  #tds is a dataset defined
somwhere else
```

TablePlotter(TableDataset tds, Bool1d flags, integer xIndex, int yIndex)

A constructor

This constructor will initiate an instance of TablePlotter with specified x and y data.

Arguments

`TableDataset` **`tds`** `[INPUT, MANDATORY, default=no default value]`

A TableDataset to plot and view. The tds contains one or more columns.

`Bool1d` **`flags`** `[INPUT, MANDATORY, default=no default value]`

The flags specify which rows are de-selected and selected for all columns

`integer` **`xIndex`** `[INPUT, MANDATORY, default=no default value]`

The xIndex specifies the x axis data

`int` **`yIndex`** `[INPUT, MANDATORY, default=no default value]`

The yIndex speicies the y axis data

Example

create an TablePlotter object with tds, flags and x and y column indices

```
from hersechl.ia.gui.explorer.table import TablePlotter  #import the
TablePlotter
#Plot the fourth column vs the second column
tpl = TablePlotter(tds, flags, 1, 3) #tds, flags are defined somewhere
else
```

TablePlotter(TablePlotter tds, Bool1d flags)

This constructor will initiate an instance of TablePlotter with pre selected and de-selected columns.

The Bool1d flag indicate which rows are selected and which rows are de-selected.

Arguments

`TablePlotter` **`tds`** `[INPUT, MANDATORY, default=no default value]`

The tds is the TableDataset to be plotted. It contains one or more columns.

`Bool1d` **`flags`** `[INPUT, MANDATORY, default=no default value]`

TablePlotter(TablePlotter tds, Bool1d flags)

The flags speicifies which rows are de-selected and which rows are selected

Methods

JComponent getComponent()

Inherit from explorer

This method will return a TablePlotter as a component so that users can plug it in his/her own applications.

Return

JComponent

- return the TablePlotter as a component

Examples

Use TablePlotter as a plug-in

```
<pre>
from herschel.share.component import *
from javax.swing import *
from java.awt import *
from herschel.ia.io.fits import FitsArchive
from herschel.ia.dataset import TableDataset
from herschel.ia.dataset import Product
from herschel.ia.dataset.gui import *
from herschel.ia.gui.explorer.table import TablePlotter
fits=FitsArchive();
#Change to your data path
path="/home/zhang/Development/data/"
filename = -"loadCurve.fits"
#load the table
try:
  fits.reader = FitsArchive.HCSS_READER
  p = fits.load(path+filename)
except java.io.IOException:
  fits.reader = FitsArchive.STANDARD_READER
   p = fits.load(path+filename)
#create a TableDataset
table =p.default
#create a container to hold the controls/components
pane=JPanel()
#set the layout, there are many different kinds users can choose according
to his/her need
pane.setLayout(BoxLayout(pane, BoxLayout.Y_AXIS))
#add control one, a lael
title = JLabel("Display TablePlotter")
pane.add(title)
#Add TablePlotter to the pane
tablePlotter=TablePlotter(table)
pane.add(tablePlotter.component)
pane.setPreferredSize(Dimension(tablePlotter.component.width,
tablePlotter.component.height))
#add to your application
frame =JFrame("TablePlotter as Plug-in demo");
frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE)
frame.getContentPane().add(pane, BorderLayout.CENTER)
frame.pack
frame.visible=1
</pre>
```

- example 2

```
from herschel.ia.gui.explorer.table import
from herschel.share.component import
```

JComponent getComponent()

```
wm=WindowManager.getDefault()
tpl = TablePlotter(tds)
wm.addWindow('My Application', tpl.component, 1)
```

String getDescription()

Return

String

- the description of this class

String getName()

Return

String

- the nam of the application

setObject(Object data)

Argument

`Object` **`data`** `[INPUT, MANDATORY, default=no default value]`

If data is a TableDataset, it will be processed and plotted. If data is not a TableDataset, nothing will be displayed.

Example

Pass the dataset to TablePlotter instance

```
<pre>
tpl = TablePlotter()
tpl.object = tds #tds defined somewhere else
</pre>
```

LayerStruct getActiveLayerStruct()

This is a command line API. It is a getter to get the active LayerStruct object.

Through the active LayerStruct object, extracted table and flags can be retreived.

Return

LayerStruct

- return the current active LayerStruct

Example

Get the extracted dataset and flags

```
tpl = TablePlotter(tds) #tds defined somewhere else
extracteDataset = tpl.activeLayerStruct.extractedTableDataset
flags = tpl.activeLayerStruct.flgs
```

History

- `2006-10-06 - first`: version of TablePlotter
- `2007-12-21 - Major`: GUI changes

2.374. TAN

Full Name:	herschel.ia.numeric.toolbox.basic.Tan
Alias:	TAN
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Tan

Description

Computes the trigonometric tangent of an number or array

Gives the tangent of a number or array. The input is in radians, and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

Example

Example 1: Apply TAN on a Float1d

```
x=Float1d([0,0.5])
print  TAN(x) # [0.0,0.5463025]
```

API Summary

Jython Syntax
<y>=TAN(<x>)

Properties
any type **x** [INPUT, MANDATORY, default=no default value]
any type **y** [OUTPUT, NOT_MANDATORY, default=no default value]

API details

Properties

any type x [INPUT, MANDATORY, default=no default value]

The input is in radians, and may be of any type.

any type y [OUTPUT, NOT_MANDATORY, default=no default value]

Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

See also

- ARCTAN
- COS
- SINH
- TANH

2.375. TANH

Full Name:	herschel.ia.numeric.toolbox.basic.TanH
Alias:	TANH
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import TanH

Description

Computes the trigonometric hyperbolic tangent of an number or array

Gives the hyperbolic tangent of a number or array. The input is in radians, and may be of any type. Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

API Summary

Jython Syntax
`<y>=TANH(<x>)`

Properties
`any type x [INPUT, MANDATORY, default=no default value]`
`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`

Miscellaneous

Does not work for complex values.

API details

Properties

`any type x [INPUT, MANDATORY, default=no default value]`
The input is in radians, and may be of any type.

`any type y [OUTPUT, NOT_MANDATORY, default=no default value]`
Returns a float array for float input array, complex array for input complex array, and double array for any other numeric array type.

See also

- TAN
- ARCTAN

2.376. TaskWrapper

Full Name:	herschel.ia.dataflow.TaskWrapper
Type:	Java Class -
Import:	from herschel.ia.dataflow import TaskWrapper

Description

Wraps a task into a process.

TaskWrapper is a special process which allows reuse of a Task instance within stream type environment. It automatically creates an connector for each parameter of the Task instance (as passed as an arg for the constructor of this class).

In default mode (= state mode) it will enable the user to build up an input array (if present) for each Task parameter. In practice it means it creates (a) an input connector which deals with instances of the array's component type and (b) a control connector allowing the user to select the number (default = 1) of instances to gather in an ArrayList before these can be passed to the tasks input parameter as an array.

I.e. for the input parameters of the type [] this class allows you to maintain a state: in case fifo = true (default) the array(list) as maintained by this object is using the fifo concept for the case the array size = "number as set by the related control". Otherwise (i.e fifo=false) the array will be emptied after the number (as set by the control) is reached. Everytime the array is filled it is passed to the task's parameter, the task's "perform()" method is called and the tasks output(s) are passed to the related output(s) of this TaskWrapper object.

Example

Example 1: how to use a TaskWrapper with AverageTask

```
<pre>
from herschel.ia.dataflow import *
from mytasks import AverageTask
tw = TaskWrapper("avg", AverageTask(), True, True, True)
df = DataFlow("mydf")
df.addProcess(tw)
# The rest is obvious...
</pre>
```

Limitations

no limitation

See also

- reference

History

- 26-5-2005 JCG: change javadoc format for help support.

2.377. ThreadDynamicProcessImpl

Full Name:	herschel.ia.dataflow.ThreadDynamicProcessImpl
Type:	Java Class -
Import:	from herschel.ia.dataflow import ThreadDynamicProcessImpl

Description

Provides the thread-based model for implementing processes.

Class to be extended. It provides thread-based model. The only method that in general should be overrriden is run method. The most interested methods are start, stop and run. The run method has always to be overriden, since it is where the execution of the process is done. As this class is handling a Thread, run method has to follow some rules. The typical run method should be like:

```
public void run() {
while( isRunning() -) {
try {
input = _input.getData();
output =doJob(input);
_output.dataReady(output);
} catch( InterruptedException ex -) {
break;
} catch( Exception ex2 -) {
handlingException(ex2);
}
}
```

The way a thread is stopped is simply letting it to return from the run method. isRunning() will stop the thread, but sometimes in the run method is stucked, waiting in a blocked method (as _input.getData() in the example above). So, the stop method not only makes that isRunning() will return false, but it will try to interrupt the thread just in case. That means that it is important to let run() method to be finished in case an InterruptedException is catched. If not, probably the thread will be eating all the CPU in an infinite loop. For a simpler thread-based super class, see herschel.ia.dataflow.template.ThreadDynamicProcessImplTemplate

IMPORTANT NOTE: This class provides two methods start/stop. These two methods are managing an internal thread. That means that when `start` is called, it will launch a thread, that may be stopped with `stop`. So, if you are using your own thread, redefine `start/stop` methods but do not call `super.start()/super.stop()` because two threads will be launched (unless this is really what you want to do).

Example

Example 1: how to implement a ThreadDynamicProcessImpl

```
<pre>
import  herschel.ia.dataflow.*;
public class ProcessFFT extends ThreadDynamicProcessImpl {
   private final ProcessInput _input;
   private final ProcessOutpu _output;
  public ProcessFFT(String name) {
      super(name);
      _input = createInput("input", Product.class);
      _output = createOutput("output", Product.class);
 -}
 public void run() {
      while( isRunning() -) {
          try {
             Product product = (Product)_input.nextData();
```

Example 1: how to implement a ThreadDynamicProcessImpl

```
              -// a doStuff method should be defined and would do the
processing.
              Product new_product = doStuff(product);
              _output.dataReady( new_product -);
           -} catch ( InterruptedException ex -) {
               System.out.println("Interrupted exception thrown:" + ex+ -".
Exiting thread");
               break;
           -}
       -} -// while
  -}
}
</pre>
```

Limitations

no limitation

See also

- reference

History

- 26-5-2005 jcg: change javadoc format for help support.

2.378. tiledImage

Full Name:	herschel.ia.toolbox.image.TiledImageTask
Alias:	tiledImage
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import TiledImageTask
Category:	task/image

Description

A Task to convert an image to a TiledImage.

A Task to convert an image to a TiledImage, taking the flag into account. TiledImageTask is a task which returns the TiledImage of an Image.

Examples

Example 1: Return the TiledImage, taking into account the flag.

```
tiledImage(image = im, flag = True)
```

Example 2: Return the TiledImage, not taking into account the flag.

```
tiledImage(image = im, method=CutLevels.MEDIAN_FILTER)
```

API Summary

Jython Syntax

```
TiledImage(image, True)
```

Properties

`Image image [INPUT, MANDATORY, default=No default value]`
`boolean flag [INPUT, MANDATORY, default=true]`
`TiledImage result [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The image to use for returning the TiledImage.

`boolean flag [INPUT, MANDATORY, default=true]`

True if the flag should be taken into account.

`TiledImage result [OUTPUT, MANDATORY, default=No default value]`

The final TiledImage.

2.379. Transform2dTask

Full Name:	herschel.ia.toolbox.image.Transform2dTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import Transform2dTask

Description

An abstract Task for two dimensional transforms.

An abstract Task that calculates the Fourier Transform and the power spectrum.

API Summary

Properties
Numeric2dData **image** [INPUT, MANDATORY, default=No default value]
Complex2d **transform** [OUTPUT, MANDATORY, default=No default value]
Double2d **spectrum** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Numeric2dData image [INPUT, MANDATORY, default=No default value]

The input image.

Complex2d transform [OUTPUT, MANDATORY, default=No default value]

The transform.

Double2d spectrum [OUTPUT, MANDATORY, default=No default value]

The spectrum.

2.380. translate

Full Name:	herschel.ia.toolbox.image.TranslateTask
Alias:	translate
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import TranslateTask
Category:	task/image

Description

The Translate task for Images.

Translate is a task which translates an Image. The Wcs is also adapted. The image is translated over the given parameters (if ra = 1h00m00s, the image will be moved 1h00m00s to the right. At the left, 0.0's will be added which will be masked out.)

Examples

Example 1: translating an image using image coordinates

```
translate(image = im, x = 5, y = 7)
```

Example 2: translating an image using sky coordinates

```
translate(image = im, ra = 0.03, dec = 0.03)
```

API Summary

Jython Syntax

```
translate()
translate(image, ra, dec)
translate(image, x, y)
```

Properties

`Image image [INPUT, MANDATORY, default=No default value]`
`double x [INPUT, OPTIONAL, default=0.0]`
`double y [INPUT, OPTIONAL, default=0.0]`
`Angle ra [INPUT, OPTIONAL, default=Angle(0.0, ANGLE.DEGREES)]`
`Angle dec [INPUT, OPTIONAL, default=Angle(0.0, ANGLE.DEGREES)]`
`Image translatedImage [OUTPUT, MANDATORY, default=No default value]`

API details

Properties

`Image image [INPUT, MANDATORY, default=No default value]`

The Image to translate

double x [INPUT, OPTIONAL, default=0.0]

The number of pixels to translate in x-direction

double y [INPUT, OPTIONAL, default=0.0]

The number of pixels to translate in y-direction

Angle ra [INPUT, OPTIONAL, default=Angle(0.0, ANGLE.DEGREES)]

The amount of degrees to move in right ascension

Angle dec [INPUT, OPTIONAL, default=Angle(0.0, ANGLE.DEGREES)]

The amount of degrees to move in declination

Image translatedImage [OUTPUT, MANDATORY, default=No default value]

Result of the translation of the Image

2.381. TranslateTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.TranslateTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import TranslateTaskSignatureComponent

Description

The task dialog for the TranslateTask.

A task dialog to serve as GUI for the TranslateTask.

API Summary

Constructor
`TranslateTaskSignatureComponent()` The construction of a new TranslateTaskSignatureComponent.

Methods
`check()` Validates the current modifications.
`clear()` Clears the current modifications.
`getParameters()` Returns a map of parameters and modifiers storing the values selected by the user.
`setVariableSelection(VariableSelection selection)` Setting the variable selection.
`setSignature(SignatureApi sig)` Setting the signature.
`JComponent getComponent()` Returns the component.

API details

Constructor

`TranslateTaskSignatureComponent()`
The construction of a new TranslateTaskSignatureComponent. The construction of a new TranslateTaskSignatureComponent.

Methods

`check()`
Validates the current modifications. Validates the current modifications for this TranslateTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this TranslateTaskSignatureComponentt.

getParameters()

Returns a map of parameters and modifiers storing the values selected by the user.

Returns a map of parameters and modifiers storing the values selected by the user for this TranslateTaskSignatureComponent.

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this TranslateTaskSignatureComponentt.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

setSignature(SignatureApi sig)

Setting the signature.

Sets the given signature as the signature for this TranslateTaskSignatureComponentt.

Argument

`SignatureApi` **`sig`** `[INPUT, MANDATORY]`

JComponent getComponent()

Returns the component.

Returns the component for this TranslateTaskSignatureComponent.

Return

JComponent

Returns the component for this TranslateTaskSignatureComponent.

2.382. TRANSPOSE

Full Name:	herschel.ia.numeric.toolbox.matrix.MatrixTranspose
Alias:	TRANSPOSE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.matrix import MatrixTranspose

Description

Transposes a matrix.

Example

Example 1: Transposing a 2D array

```
x=Int2d([ [1,2],[3,4],[5,6] -])
print TRANSPOSE(x) # [ [1,3,5],[2,4,6] -]
```

API Summary

Jython Syntax
<y>=TRANSPOSE(<x>)

Property
Array2dData **x** [INPUT, MANDATORY, default=no default value]

Miscellaneous

TRANSPOSE is an alias for MatrixTranspose.FUNCTION

API details

Property

Array2dData x [INPUT, MANDATORY, default=no default value]

Input must be a 2d array as defined by the numeric library.

2.383. transpose

Full Name:	herschel.ia.toolbox.image.TransposeTask
Alias:	transpose
Type:	Java Task -
Import:	from herschel.ia.toolbox.image import TransposeTask
Category:	task/image

Description

The Transpose task for Images.

TransposeTask is a task which transposes an Image. The Wcs is also adapted. The following types of are possible :

- FLIP_VERTICAL : The image is flipped upside-down
- FLIP_HORIZONTAL : The image is flipped left-right
- FLIP_DIAGONAL : The image is mirrored around the diagonal
- FLIP_ANTIDIAGONAL : The image is mirrored around the antidiagonal
- ROTATE_90 : The image is rotated 90 degrees
- ROTATE_180 : The image is rotated 180 degrees
- ROTATE_270 : The mirror is rotated 270 degrees

Examples

Example 1: Flipping an image horizontal

```
transpose(image = im, type = TransposeTask.FLIP_HORIZONTAL)
```

Example 2: Flipping an image antidiagonal

```
transpose(im, TransposeTask.FLIP_ANTIDIAGONAL)
```

API Summary

Jython Syntax

```
transpose()
transpose(image, TransposeTask.FLIP_VERTICAL)
```

Properties

Image **image** [INPUT, MANDATORY, default=No default value]
TransposeType **type** [INPUT, MANDATORY, default=Transpose.FLIP_VERTICAL]
Image **transposedImage** [OUTPUT, MANDATORY, default=No default value]

API details

Properties

Image image [INPUT, MANDATORY, default=No default value]

The Image to transpose

TransposeType type [INPUT, MANDATORY, default=Transpose.FLIP_VERTICAL]

The type of transposition to apply (FLIP_VERTICAL, FLIP_HORIZONTAL, FLIP_DIAGONAL, FLIP_ANTIDIAGONAL, ROTATE_90, ROTATE_180 or ROTATE_270)

Image transposedImage [OUTPUT, MANDATORY, default=No default value]

Result of the transposition of the Image

2.384. TransposeTaskSignatureComponent

Full Name:	herschel.ia.toolbox.image.gui.TransposeTaskSignatureComponent
Type:	Java Class -
Import:	from herschel.ia.toolbox.image.gui import TransposeTaskSignatureComponent

Description

The task dialog for the TransposeTask.

A task dialog to serve as GUI for the TransposeTask.

API Summary

Constructor
`TransposeTaskSignatureComponent()` The construction of a new TransposeTaskSignatureComponent.

Methods
`check()` Validates the current modifications.
`clear()` Clears the current modifications.
`getParameters()` Returns a map of parameters and modifiers storing the values selected by the user.
`setVariableSelection(VariableSelection selection)` Setting the variable selection.
`setSignature(SignatureApi sig)` Setting the signature.
`JComponent` **`getComponent()`** Returns the component.

API details

Constructor

`TransposeTaskSignatureComponent()`
The construction of a new TransposeTaskSignatureComponent. The construction of a new TransposeTaskSignatureComponent.

Methods

`check()`
Validates the current modifications. Validates the current modifications for this TransposeTaskSignatureComponent.

clear()

Clears the current modifications.

Clears the current modifications for this TransposeTaskSignatureComponentt.

getParameters()

Returns a map of parameters and modifiers storing the values selected by the user.

Returns a map of parameters and modifiers storing the values selected by the user for this TransposeTaskSignatureComponent.

setVariableSelection(VariableSelection selection)

Setting the variable selection.

Sets the given selection as the variable selection for this TransposeTaskSignatureComponentt.

Argument

`VariableSelection` **`selection`** `[INPUT, MANDATORY]`

setSignature(SignatureApi sig)

Setting the signature.

Sets the given signature as the signature for this TransposeTaskSignatureComponentt.

Argument

`SignatureApi` **`sig`** `[INPUT, MANDATORY]`

JComponent getComponent()

Returns the component.

Returns the component for this TransposeTaskSignatureComponent.

Return

JComponent

Returns the component for this TransposeTaskSignatureComponent.

2.385. UNIQ_SORTED

Full Name:	herschel.ia.numeric.toolbox.basic.UniqSorted
Alias:	UNIQ_SORTED
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import UniqSorted

Description

Returns the unique elements of an array.

An index uniq is available as a special case of UNIQ_SORTED i.e. UNIQ_SORTED.BY_INDEX which returns an index array into the original array. UNIQ_SORTED.COUNT_UNIQ_VALUES returns the number of unique values in an array; although it works also with unsorted arrays, passing an already sorted array is much more efficient.

Examples

Example 1: Apply UNIQ_SORTED on a Double1d

```
x=Double1d([-1,4,2,7,2,-6,-8,3,2])
print UNIQ_SORTED(SORT(x))              # [-8.0,-6.0,-1.0,2.0,3.0,4.0,7.0]
```

Example 2: Apply UNIQ_SORTED.BY_INDEX

```
x=SORT(Double1d([-1,4,2,7,2,-6,-8,3,2]))
print UNIQ_SORTED.BY_INDEX(x)     # [0,1,2,3,6,7,8]
```

Example 3: Apply UNIQ_SORTED.COUNT_UNIQ_VALUES

```
x=Double1d([4, 5, 7, 4, 8, 8, 3, 1, 5])
print UNIQ_SORTED.COUNT_UNIQ_VALUES(SORT(x))  # 6
```

API Summary

Jython Syntax

```
<y>=UNIQ_SORTED(<x>)
```

Properties

any sorted array **x** [INPUT, MANDATORY, default=no default value]

an array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any sorted array x [INPUT, MANDATORY, default=no default value]

The input array can only be an array of rank 1

an array y [OUTPUT, MANDATORY, default=no default value]

Returns an array containing only the unique elements from the input array.

2.386. UNIQ

Full Name:	herschel.ia.numeric.toolbox.basic.Uniq
Alias:	UNIQ
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Uniq

Description

Returns the unique elements of an array.

An index uniq is available as a special case of UNIQ i.e. UNIQ.BY_INDEX which returns an index array into the original array. UNIQ.COUNT_UNIQ_VALUES returns the number of unique values in an array; although it works also with unsorted arrays, passing an already sorted array is much more efficient. The UNIQ.IS_UNIQ function, which tests if the given array indeed contains unique elements, is deprecated. It is strongly recomended that you sort the array and use UNIQ_SORTED due to performance issues.

Examples

Example 1: Apply UNIQ on a Double1d

```
x=Double1d([-1,4,2,7,2,-6,-8,3,2])
print UNIQ(x)                    # [-8.0,-6.0,-1.0,2.0,3.0,4.0,7.0]
print UNIQ(SORT(x))              # [-8.0,-6.0,-1.0,2.0,3.0,4.0,7.0]
```

Example 2: Apply UNIQ.BY_INDEX

```
x=Double1d([-1,4,2,7,2,-6,-8,3,2])
print UNIQ.BY_INDEX(x)         # [0,1,2,3,5,6,7]
print UNIQ.BY_INDEX(SORT(x))   # [0,1,2,3,6,7,8]  SORT(x) =
[-8.0,-6.0,-1.0,2.0,2.0,2.0,3.0,4.0,7.0]
```

Example 3: Apply UNIQ.COUNT_UNIQ_VALUES

```
x=Double1d([4, 5, 7, 4, 8, 8, 3, 1, 5])
print UNIQ.COUNT_UNIQ_VALUES(x)  # 6
```

Example 4: Apply UNIQ.IS_UNIQ

```
x=Double1d([-1,4,7,-2,-6,-8,3,2])
print UNIQ.IS_UNIQ(x)        # 0 (false) -- Note that this function is
deprecated
print UNIQ.IS_UNIQ(SORT(x))  # 1 (true) -- Note that this function is
deprecated
```

API Summary

Jython Syntax

```
<y>=UNIQ(<x>)
```

Properties

any sorted/unsorted array **x** [INPUT, MANDATORY, default=no default value]

Properties
an array **y** [OUTPUT, MANDATORY, default=no default value]

API details

Properties

any sorted/unsorted array x [INPUT, MANDATORY, default=no default value]

The input array can only be an array of rank 1

an array y [OUTPUT, MANDATORY, default=no default value]

Returns an array containing only the unique elements from the input array.

2.387. VARIANCE

Full Name:	herschel.ia.numeric.toolbox.basic.Variance
Alias:	VARIANCE
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import Variance

Description

Yields the variance value of the elements in the input array.

The standard deviation is equivalent to SQRT(VARIANCE(x)).

Example

Example 1: Apply VARIANCE on a Float1d

```
x=Float1d([1,3,2,3,4])
print VARIANCE(x) # 1.3
```

API Summary

Jython Syntax

```
<y>=VARIANCE(<x>)
```

Properties

```
any scalar array x [INPUT, MANDATORY, default=no default value]
double y [OUTPUT, MANDATORY, default=no default value]
```

API details

Properties

any scalar array x [INPUT, MANDATORY, default=no default value]

The input array integral or floating-point arrays; the former implicitly transformed to a double array.

double y [OUTPUT, MANDATORY, default=no default value]

Returns a double

See also

- MEAN
- MEDIAN
- STDDEV

2.388. VelocityPosMapComputeTask

Full Name:	herschel.ia.toolbox.cube.VelocityPosMapComputeTask
Type:	Java Task -
Import:	from herschel.ia.toolbox.cube import VelocityPosMapComputeTask

Description

VelocityPosMapComputeTask The task to compute Velocity position map from a Simplecube

API Summary

Properties
simpleCube **simplecube** [INPUT, MANDATORY, default=no default value]
axis **unknown** [INPUT, Boolean, default=MANDATORY]
coordSlitArray **unknown** [INPUT, Double2d, default=no default value]
widthSlit **unknown** [INPUT, Integer, default=no default value]
referenceLayer **unknown** [INPUT, Integer, default=no default value]
totalWeight **unknown** [INPUT, no default value, default=no default value]
velocityMap **unknown** [OUTPUT, Double3d, default=no default value]
velocityMapAxis **unknown** [OUTPUT, Double2d, default=no default value]
velocityMapAxisProd **unknown** [OUTPUT, SimpleImage, default=no default value]
cubeVelocityMap **unknown** [OUTPUT, SimpleCube, default=no default value]

API details

Properties

simpleCube simplecube [INPUT, MANDATORY, default=no default value]

The spectralCube as a SimpleCube containing the spectral and velocities information

axis unknown [INPUT, Boolean, default=MANDATORY]

Define the type of map to generate axis coordSlitArray widthSlit referenceLayer totalWeight

coordSlitArray unknown [INPUT, Double2d, default=no default value]

new version array of pixel to be read : manage the width of the slit the order of the information is index, X, Y , weight

widthSlit unknown [INPUT, Integer, default=no default value]

width of the slit

referenceLayer unknown [INPUT, Integer, default=no default value]

The layer considered as reference for the computation of the velocities

totalWeight unknown [INPUT, no default value, default=no default value]

The inside total weight of the array of pixel to be read

velocityMap unknown [OUTPUT, Double3d, default=no default value]

The 2D map of velocity

velocityMapAxis unknown [OUTPUT, Double2d, default=no default value]

The map of velocity along the axis to come soon:

velocityMapAxisProd unknown [OUTPUT, SimpleImage, default=no default value]

The map of velocity along the axis, stored in a SimpleCube

cubeVelocityMap unknown [OUTPUT, SimpleCube, default=no default value]

a cube containing the map of velocity at maximmum of emission, the dispersion map, an error value ...

2.389. VelocityPosMapPlotting

Full Name:	herschel.ia.gui.cube.VelocityPosMapPlotting
Type:	Java Class -
Import:	from herschel.ia.gui.cube import VelocityPosMapPlotting

Description

PositionVelocityDiagramPlotting.

A class to deal with PositionVelocityDiagramComputeTask.

API Summary

Constructors
`VelocityPosMapPlotting(type toolbox)`
`VelocityPosMapPlotting(boolean useAsComponent, CubeSpectrumAnalysisToolbox toolbox)` Constructor for VelocityPosMapPlotting.

Methods
`setBegin(Double begin)` Sets the begin of the straight line, associated with this
`setEnd(Double end)` Sets the end of the straight line, associated with this
`ImageFigure getLine()` Returns the straight line (ImageFigure), along which we wish to
`Double getBegin()` Returns the begin of the drawn line in PixelCoordinates.
`Double getEnd()` Returns the end of the drawn line in PixelCoordinates.
`Double1d IntensityVelocityPosMapPlotting()` Returns the intensity of the pixels along the straight line,
`Point2D[] getPlotPoints()` Returns the intensity of the pixels along the straight line,
`void getCoordPoints()` Returns the intensity of the pixels along the straight line,
`String getSkyCoordinates()` Returns the String version of the sky coordinates

API details

Constructors

`VelocityPosMapPlotting(type toolbox)`
Argument

VelocityPosMapPlotting(type toolbox)

`type` **toolbox** `[INPUT, MANDATORY, default=no default value]`

The CubeSpectrumAnalysisToolbox, for which you want to extract a velocity position map

VelocityPosMapPlotting(boolean useAsComponent, CubeSpectrumAnalysisToolbox toolbox)

Constructor for VelocityPosMapPlotting.

When the new VelocityPosMapPlotting is component-based, a window for plotting the histogram is opened; otherwise nothing will be shown. jparameter useAsComponent Indication whether the new VelocityPosMapPlotting should be component-based.

Arguments

`boolean` **useAsComponent** `[INPUT, MANDATORY]`

`CubeSpectrumAnalysisToolbox` **toolbox** `[INPUT, MANDATORY]`

Methods

setBegin(Double begin)

Sets the begin of the straight line, associated with this

Velocity position map to the given point (in UserCoordinates).

Argument

`Double` **begin** `[INPUT, MANDATORY]`

setEnd(Double end)

Sets the end of the straight line, associated with this

Velocity position map to the given point (in UserCoordinates).

Argument

`Double` **end** `[INPUT, MANDATORY]`

ImageFigure getLine()

Returns the straight line (ImageFigure), along which we wish to

create the diagram velocity position based on the Bresenham's Line-Drawing Algorithm

Return

ImageFigure

The straight line (ImageFigure), along which we wish to create the diagram velocity position based on the Bresenham's Line-Drawing Algorithm

Double getBegin()

Returns the begin of the drawn line in PixelCoordinates.

Return

Double

Returns the begin of the drawn line in PixelCoordinates.

Double getEnd()

Returns the end of the drawn line in PixelCoordinates.

Return

Double

Returns the end of the drawn line in PixelCoordinates.

Double1d IntensityVelocityPosMapPlotting()

Returns the intensity of the pixels along the straight line,

associated with the given Velocity position map.

Return

Double1d

Returns the intensity of the pixels along the drawn straight line, associated with the given Velocity position map.

Point2D[] getPlotPoints()

Returns the intensity of the pixels along the straight line,

associated with the given Velocity position map.

Return

Point2D[]

Returns the intensity of the pixels along the drawn straight line, associated with the given Velocity position map.

void getCoordPoints()

Returns the intensity of the pixels along the straight line,

associated with the given Velocity position map.

Return

void

Returns the intensity of the pixels along the drawn straight line, associated with the given Velocity position map.

String getSkyCoordinates()

Returns the String version of the sky coordinates

(WorldCoordinates) of the begin and end of the drawn straight line.

Return

String

Returns the String version of the sky coordinates (WorldCoordinates) of the begin and end of the drawn straight line.

2.390. WcsExplorer

Full Name:	herschel.ia.gui.image.WcsExplorer
Type:	Java Class -
Import:	from herschel.ia.gui.image import WcsExplorer

Description

An explorer to view a Wcs.

An explorer to view a Wcs.

API Summary

Constructors
`WcsExplorer()` The construction of a new WcsExplorer.
`WcsExplorer(Object object)` The construction of a new WcsExplorer associated with the given object.

Methods
`String` **`getName()`** Returns the name.
`String` **`getDescription()`** Returns the description.
`boolean` **`canHandle(Class className)`** Checks whether this WcsExplorer can handle objects of the given class.
`setObject(Object object)` Sets the object.
`Wcs` **`getObject()`** Returns the object.
`Class` **`getVariableType()`** Returns the expected variable type.
`JComponent` **`getComponent()`** Returns the component that is responsible for displaying the data object.
`boolean` **`makeEditorContent()`** Creates the editor content for this Explorer.
`addDataObjectListener(DataObjectListener arg0)` Adds the given listener.
`removeDataObjectListener(DataObjectListener arg0)` Removes the given listener.

API details

Constructors

WcsExplorer()

The construction of a new WcsExplorer.

The construction of a new WcsExplorer.

WcsExplorer(Object object)

The construction of a new WcsExplorer associated with the given object.

The construction of a new WcsExplorer associated with the given object.

Argument

`Object` **object** `[INPUT, MANDATORY]`

Methods

String getName()

Returns the name.

Returns the name for this WcsExplorer.

Return

String

Returns the name for this WcsExplorer.

String getDescription()

Returns the description.

Returns the description for this WcsExplorer.

Return

String

Returns the description for this WcsExplorer.

boolean canHandle(Class className)

Checks whether this WcsExplorer can handle objects of the given class.

Returns true if this WcsExplorer can handle objects of the given class; false otherwise.

Argument

`Class` **className** `[INPUT, MANDATORY]`

Return

boolean

Returns true of this WcsExplorer can handle objects of the given class; false otherwise.

setObject(Object object)

Sets the object.

Sets the object for this WcsExplorer to the given object.

Argument

`Object` **object** [INPUT, MANDATORY]

Wcs getObject()

Returns the object.

Returns the object for this WcsExplorer.

Return

Wcs

Returns the object for this WcsExplorer.

Class getVariableType()

Returns the expected variable type.

Returns the expected variable type for this WcsExplorer.

Return

Class

Returns the expected variable type for this WcsExplorer.

JComponent getComponent()

Returns the component that is responsible for displaying the data object.

Returns the component that is responsible for displaying the data object for this WcsExplorer.

Return

JComponent

Returns the component that is responsible for displaying the data object for this WcsExplorer.

boolean makeEditorContent()

Creates the editor content for this Explorer.

Returns true if the editor content for this WcsExplorer could be made; false otherwise.

Return

boolean

Returns true if the editor content for this WcsExplorer could be made; false otherwise.

addDataObjectListener(DataObjectListener arg0)

Adds the given listener.

Adds the given listener to this WcsExplorer to receive data object events from it.

Argument

addDataObjectListener(DataObjectListener arg0)

DataObjectListener **arg0** [INPUT, MANDATORY]

removeDataObjectListener(DataObjectListener arg0)

Removes the given listener.

Removes the given listener for this WcsExplorer, so that it no longer receives data object events by this explorer.

Argument

DataObjectListener **arg0** [INPUT, MANDATORY]

2.391. Wcs

Full Name:	herschel.ia.dataset.image.wcs.Wcs
Type:	Java Class -
Import:	from herschel.ia.dataset.image.wcs import Wcs
Category:	Image

Description

A class to create a Wcs.

This class creates a Wcs. The Wcs describes the World coordinate system, which is used to convert between image coordinates and world coordinates.

Example

Example 1: A basic example on how to create a Wcs

```
wcs = Wcs(crval1=30.0, crval2=-89.50, crpix1=109, crpix2=109)
```

API Summary

Constructors
Wcs() The default constructor.
Wcs(int naxis) Constructor for 2 or 3 dimensional Wcs.
Wcs(Wcs orig) The copy constructor.

Methods
Wcs **copy**() Returns a copy of the Wcs object.
setParameter(String paramname, Object param, String description) Adds a new parameter to the Wcs.
isCompleteWcs() Checks whether the Wcs is complete.
Object **getParameter**(String paramname) Returns a parameter from the Wcs.
Object[] **getParameters**() Returns all parameters.
removeParameter(String paramname) Removes a parameter.
setNAxis(int naxis) Sets the number of axes.
int **getNAxis**() Returns the number of axes.

Methods
setImageIndex(Double1d index, Unit unit) Sets the image index for a non-equidistant 3rd dimension.
boolean **hasImageIndex**() Checks the image index
TableDataset **getImageIndex**() Returns the image index.
boolean **isEquidistantInZ**() Checks whether the Wcs is equidistant in the 3rd dimension.
setCrval1(double crval1) Sets crval1.
double **getCrval1**() Returns crval1
setCrval2(double crval2) Sets crval2.
double **getCrval2**() Returns crval2
setCrval3(double crval3) Sets crval3.
double **getCrval3**() Returns crval3
setCrpix1(double crpix1) Sets crpix1.
double **getCrpix1**() Returns crpix1
setCrpix2(double crpix2) Sets crpix2.
double **getCrpix2**() Returns crpix2
setCrpix3(double crpix3) Sets crpix3.
double **getCrpix3**() Returns crpix3
setCdelt1(double cdelt1) Sets cdelt1.
double **getCdelt1**() Returns cdelt1
setCdelt2(double cdelt2) Sets cdelt2.
double **getCdelt2**() Returns cdelt2
setCdelt3(double cdelt3)

Methods
Sets cdelt3.
`double getCdelt3()` Returns cdelt3
`boolean checkCtypeValidity(String ctype)` Checks the validity of the ctype parameter.
`setCtype1(String ctype1)` Sets ctype1.
`String getCtype1()` Returns ctype1
`setCtype2(String ctype2)` Sets ctype2.
`String getCtype2()` Returns ctype2
`setCtype3(String ctype3)` Sets ctype3.
`String getCtype3()` Returns ctype3
`setCunit1(String cunit1)` Sets cunit1.
`String getCunit1()` Returns cunit1
`setCunit2(String cunit2)` Sets cunit2.
`String getCunit2()` Returns cunit2
`boolean hasParameter(String parameter)` Checks the availability of a parameter.
`setCunit3(String cunit3)` Sets cunit3.
`String getCunit3()` Returns cunit3
`setEpoch(double epoch)` Sets the epoch.
`double getEpoch()` Returns the epoch
`setEquinox(double equinox)` Sets the equinox.
`double getEquinox()` Returns the equinox
`setRadesys(String Radesys)` Sets the reference frame.

Methods
`String` **`getRadesys`**`()` Returns the reference frame
`setCd1_1``(double cd1_1)` Sets the cd1_1 element.
`setCd1_2``(double cd1_2)` Sets the cd1_2 element.
`setCd1_3``(double cd1_3)` Sets the cd1_3 element.
`setCd2_1``(double cd2_1)` Sets the cd2_1 element.
`setCd2_2``(double cd2_2)` Sets the cd2_2 element.
`setCd2_3``(double cd2_3)` Sets the cd2_3 element.
`setCd3_1``(double cd3_1)` Sets the cd3_1 element.
`setCd3_2``(double cd3_2)` Sets the cd3_2 element.
`setCd3_3``(double cd3_3)` Sets the cd3_3 element.
`double` **`getCd1_1`**`()` Returns cd1_1
`double` **`getCd1_2`**`()` Returns cd1_2
`double` **`getCd2_1`**`()` Returns cd2_1
`double` **`getCd2_2`**`()` Returns cd2_2
`double` **`getCd1_3`**`()` Returns cd1_3
`double` **`getCd2_3`**`()` Returns cd2_3
`double` **`getCd3_1`**`()` Returns cd3_1
`double` **`getCd3_2`**`()` Returns cd3_2
`double` **`getCd3_3`**`()` Returns cd3_3
`setPc1_1``(double pc1_1)` Sets the pc1_1 element.
`double` **`getPc1_1`**`()`

Methods
Returns pc1_1
setPc1_2(double pc1_2) Sets the pc1_2 element.
double **getPc1_2**() Returns pc1_2
setPc1_3(double pc1_3) Sets the pc1_3 element.
double **getPc1_3**() Returns pc1_3
setPc2_1(double pc2_1) Sets the pc2_1 element.
double **getPc2_1**() Returns pc2_1
setPc2_2(double pc2_2) Sets the pc2_2 element.
double **getPc2_2**() Returns pc2_2
setPc2_3(double pc2_3) Sets the pc2_3 element.
double **getPc2_3**() Returns pc2_3
setPc3_1(double pc3_1) Sets the pc3_1 element.
double **getPc3_1**() Returns pc3_1
setPc3_2(double pc3_2) Sets the pc3_2 element.
double **getPc3_2**() Returns pc3_2
setPc3_3(double pc3_3) Sets the pc3_3 element.
double **getPc3_3**() Returns pc3_3
setProjection(String projection) Sets the projection.
String **getProjection**() Returns the projection.
MetaData **getMeta**() Return the Wcs as metadata.
String **toString**() Returns a string representation of the Wcs.

Methods
`double[] getWorldCoordinates(double row, double column)` Returns the world coordinates of the given image coordinates.
`double getZCoordinate(int depth)` Returns the world coordinates of the given layer.
`double[] getPixelCoordinates(double c1, double c2)` Returns the pixel coordinates.
`setCrota2(double crota2)` Sets crota2
`double getCrota2()` Returns crota2.
`boolean isValid()` Checks the possibility to convert from pixel to world coordinates.
`setWavelength(double wavelength)` Sets the wavelength in the Wcs.
`getWavelength()` Returns the wavelength which is stored in the Wcs

API details

Constructors

`Wcs()`

The default constructor.

A constructor which creates a standard Wcs object. The standard Wcs sets naxis = 2 (NAXIS = 2)

Example

Typical example on how to create a Wcs.

```
wcs = Wcs(crval1=30.0, crval2=-89.50, crpix1=109,
crpix2=109)
```

`Wcs(int naxis)`

Constructor for 2 or 3 dimensional Wcs.

A constructor which creates a Wcs object with the chosen number of axes. The standard Wcs has only parameter naxis set

Argument

`int` **`naxis`** `[INPUT, MANDATORY]`

Example

Typical example on how to create a Wcs.

```
wcs = Wcs(3)
wcs.setCrval1(30.0)
```

`Wcs(Wcs orig)`

The copy constructor.

Wcs(Wcs orig)

Constructor for Wcs A constructor which creates a copy of an existing Wcs object.

Argument

Wcs **orig** [INPUT, MANDATORY]

Methods

Wcs copy()

Returns a copy of the Wcs object.

Returns a copy of the Wcs object.

Return

Wcs

A copy of the Wcs.

setParameter(String paramname, Object param, String description)

Adds a new parameter to the Wcs.

Adds a new parameter to the Wcs.

Arguments

String **paramname** [INPUT, MANDATORY]

Object **param** [INPUT, MANDATORY]

String **description** [INPUT, MANDATORY]

isCompleteWcs()

Checks whether the Wcs is complete.

Returns true if the Wcs has enough information to convert to and from World Coordinates.

Object getParameter(String paramname)

Returns a parameter from the Wcs.

Returns the requested parameter of the Wcs.

Argument

String **paramname** [INPUT, MANDATORY]

Return

Object

The requested parameter.

Object[] getParameters()

Returns all parameters.

Returns the list of all Wcs parameters.

Return

Object[]

Object[] getParameters()

The list of all Wcs parameters.

removeParameter(String paramname)

Removes a parameter.

Removes the requested parameter of the Wcs.

Argument

String **paramname** [INPUT, MANDATORY]

setNAxis(int naxis)

Sets the number of axes.

Sets the number of axes of the Wcs.

Argument

int **naxis** [INPUT, MANDATORY]

int getNAxis()

Returns the number of axes.

Returns the number of axes of the Wcs.

Return

int

The number of axes.

setImageIndex(Double1d index, Unit unit)

Sets the image index for a non-equidistant 3rd dimension.

Sets the image index for a non-equidistant 3rd dimension.

Arguments

Double1d **index** [INPUT, MANDATORY]

Unit **unit** [INPUT, MANDATORY]

boolean hasImageIndex()

Checks the image index

Returns true if there is an image index.

Return

boolean

True if there is an image index.

TableDataset getImageIndex()

Returns the image index.

Returns the image index for a non-equidistant 3rd dimension.

`TableDataset getImageIndex()`

Return

TableDataset

The image index for a non-equidistant 3rd dimension.

`boolean isEquidistantInZ()`

Checks whether the Wcs is equidistant in the 3rd dimension.

isEquidistantInZ returns true when the 3rd axis is equidistant. In this case, the crval3, crpix3 and cdelt3 keywords are used. If the 3rd axis is not equidistant, the ImageIndex is used.

Return

boolean

True if the Wcs is equidistant.

`setCrval1(double crval1)`

Sets crval1.

Sets the first coordinate of the center.

Argument

`double` **`crval1`** `[INPUT, MANDATORY]`

`double getCrval1()`

Returns crval1

Returns the first coordinate of the reference pixel.

Return

double

The first coordinate of the reference pixel.

`setCrval2(double crval2)`

Sets crval2.

Sets the second coordinate of the center.

Argument

`double` **`crval2`** `[INPUT, MANDATORY]`

`double getCrval2()`

Returns crval2

Returns the second coordinate of the reference pixel.

Return

double

The second coordinate of the reference pixel.

setCrval3(double crval3)

Sets crval3.

Sets the third coordinate of the center.

Argument

`double` **`crval3`** `[INPUT, MANDATORY]`

double getCrval3()

Returns crval3

Returns the third coordinate of the reference pixel.

Return

double

The third coordinate of the reference pixel.

setCrpix1(double crpix1)

Sets crpix1.

Sets the reference pixel position of axis 1. WARNING: CRPIX1 should be given in x,y coordinates. The standard specifies that the image starts at pixel (1,1) and not at pixel (0,0). So to set the first pixel, you should use 1 as value for crpix1.

Argument

`double` **`crpix1`** `[INPUT, MANDATORY]`

double getCrpix1()

Returns crpix1

Returns the reference pixel position of axis 1.

Return

double

The reference pixel position of axis 1.

setCrpix2(double crpix2)

Sets crpix2.

Sets the reference pixel position of axis 2. WARNING: CRPIX2 should be given in x,y coordinates. The standard specifies that the image starts at pixel (1,1) and not at pixel (0,0). So to set the first pixel, you should use 1 as value for crpix2.

Argument

`double` **`crpix2`** `[INPUT, MANDATORY]`

double getCrpix2()

Returns crpix2

Returns the reference pixel position of axis 2.

Return

double getCrpix2()

double

The reference pixel position of axis 2.

setCrpix3(double crpix3)

Sets crpix3.

Sets the reference pixel position of axis 3.

Argument

`double` **`crpix3`** `[INPUT, MANDATORY]`

double getCrpix3()

Returns crpix3

Returns the reference pixel position of axis 3.

Return

double

The reference pixel position of axis 3.

setCdelt1(double cdelt1)

Sets cdelt1.

Sets the pixel scale of axis 1.

Argument

`double` **`cdelt1`** `[INPUT, MANDATORY]`

double getCdelt1()

Returns cdelt1

Returns the pixel scale of axis 1.

Return

double

The pixel scale of axis 1.

setCdelt2(double cdelt2)

Sets cdelt2.

Sets the pixel scale of axis 2.

Argument

`double` **`cdelt2`** `[INPUT, MANDATORY]`

double getCdelt2()

Returns cdelt2

Returns the pixel scale of axis 2.

double getCdelt2()

Return

double

The pixel scale of axis 2.

setCdelt3(double cdelt3)

Sets cdelt3.

Sets the pixel scale of axis 3.

Argument

`double` **cdelt3** `[INPUT, MANDATORY]`

double getCdelt3()

Returns cdelt3

Returns the pixel scale of axis 3.

Return

double

The pixel scale of axis 3.

boolean checkCtypeValidity(String ctype)

Checks the validity of the ctype parameter.

Checks the validity of the ctype parameter.

Argument

`String` **ctype** `[INPUT, MANDATORY]`

Return

boolean

true if the ctype parameter is valid.

setCtype1(String ctype1)

Sets ctype1.

Sets the projection type of axis 1.

Argument

`String` **ctype1** `[INPUT, MANDATORY]`

String getCtype1()

Returns ctype1

Returns the projection type of axis 1.

Return

String

The projection type of axis 1.

setCtype2(String ctype2)

Sets ctype2.

Sets the projection type of axis 2.

Argument

`String` **ctype2** [INPUT, MANDATORY]

String getCtype2()

Returns ctype2

Returns the projection type of axis 2.

Return

String

The projection type of axis 2.

setCtype3(String ctype3)

Sets ctype3.

Sets the projection type of axis 3.

Argument

`String` **ctype3** [INPUT, MANDATORY]

String getCtype3()

Returns ctype3

Returns the projection type of axis 3.

Return

String

The projection type of axis 3.

setCunit1(String cunit1)

Sets cunit1.

Sets the unit of axis 1.

Argument

`String` **cunit1** [INPUT, MANDATORY]

String getCunit1()

Returns cunit1

Returns the unit of axis 1.

Return

String

The unit of axis 1.

setCunit2(String cunit2)

Sets cunit2.

Sets the unit of axis 2.

Argument

`String` **cunit2** [INPUT, MANDATORY]

String getCunit2()

Returns cunit2

Returns the unit of axis 2.

Return

String

The unit of axis 2.

boolean hasParameter(String parameter)

Checks the availability of a parameter.

Checks whether the parameter is available.

Argument

`String` **parameter** [INPUT, MANDATORY]

Return

boolean

True if the parameter is available.

setCunit3(String cunit3)

Sets cunit3.

Sets the unit of axis 3.

Argument

`String` **cunit3** [INPUT, MANDATORY]

String getCunit3()

Returns cunit3

Returns the unit of axis 3.

Return

String

The unit of axis 3.

setEpoch(double epoch)

Sets the epoch.

Sets the epoch.

setEpoch(double epoch)

Argument

`double` **epoch** `[INPUT, MANDATORY]`

double getEpoch()

Returns the epoch

Returns the epoch.

Return

double

The epoch.

setEquinox(double equinox)

Sets the equinox.

Sets the equinox.

Argument

`double` **equinox** `[INPUT, MANDATORY]`

double getEquinox()

Returns the equinox

Returns the equinox.

Return

double

The equinox.

setRadesys(String Radesys)

Sets the reference frame.

Sets the reference frame.

Argument

`String` **Radesys** `[INPUT, MANDATORY]`

String getRadesys()

Returns the reference frame

Returns the reference frame.

Return

String

The reference frame.

setCd1_1(double cd1_1)

Sets the cd1_1 element.

setCd1_1(double cd1_1)

Sets element (1, 1) of the corrected CD matrix CDi_j..

Argument

`double` **`cd1_1`** `[INPUT, MANDATORY]`

setCd1_2(double cd1_2)

Sets the cd1_2 element.

Sets element (1, 2) of the corrected CD matrix CDi_j..

Argument

`double` **`cd1_2`** `[INPUT, MANDATORY]`

setCd1_3(double cd1_3)

Sets the cd1_3 element.

Sets element (1, 3) of the corrected CD matrix CDi_j..

Argument

`double` **`cd1_3`** `[INPUT, MANDATORY]`

setCd2_1(double cd2_1)

Sets the cd2_1 element.

Sets element (2, 1) of the corrected CD matrix CDi_j..

Argument

`double` **`cd2_1`** `[INPUT, MANDATORY]`

setCd2_2(double cd2_2)

Sets the cd2_2 element.

Sets element (2, 2) of the corrected CD matrix CDi_j..

Argument

`double` **`cd2_2`** `[INPUT, MANDATORY]`

setCd2_3(double cd2_3)

Sets the cd2_3 element.

Sets element (2, 3) of the corrected CD matrix CDi_j..

Argument

`double` **`cd2_3`** `[INPUT, MANDATORY]`

setCd3_1(double cd3_1)

Sets the cd3_1 element.

Sets element (3, 1) of the corrected CD matrix CDi_j..

Argument

`double` **`cd3_1`** `[INPUT, MANDATORY]`

setCd3_2(double cd3_2)

Sets the cd3_2 element.

Sets element (3, 2) of the corrected CD matrix CDi_j..

Argument

`double` **`cd3_2`** `[INPUT, MANDATORY]`

setCd3_3(double cd3_3)

Sets the cd3_3 element.

Sets element (3, 3) of the corrected CD matrix CDi_j..

Argument

`double` **`cd3_3`** `[INPUT, MANDATORY]`

double getCd1_1()

Returns cd1_1

Returns element (1,1) of the corrected CD matrix CDi_j.

Return

double

Element (1,1) of the corrected CD matrix CDi_j.

double getCd1_2()

Returns cd1_2

Returns element (1,2) of the corrected CD matrix CDi_j.

Return

double

Element (1,2) of the corrected CD matrix CDi_j.

double getCd2_1()

Returns cd2_1

Returns element (2,1) of the corrected CD matrix CDi_j.

Return

double

Element (2,1) of the corrected CD matrix CDi_j.

double getCd2_2()

Returns cd2_2

Returns element (2,2) of the corrected CD matrix CDi_j.

Return

double

double getCd2_2()

Element (2,2) of the corrected CD matrix CDi_j.

double getCd1_3()

Returns cd1_3

Returns element (1,3) of the corrected CD matrix CDi_j.

Return

double

Element (1,3) of the corrected CD matrix CDi_j.

double getCd2_3()

Returns cd2_3

Returns element (2,3) of the corrected CD matrix CDi_j.

Return

double

Element (2,3) of the corrected CD matrix CDi_j.

double getCd3_1()

Returns cd3_1

Returns element (3,1) of the corrected CD matrix CDi_j.

Return

double

Element (3,1) of the corrected CD matrix CDi_j.

double getCd3_2()

Returns cd3_2

Returns element (3,2) of the corrected CD matrix CDi_j.

Return

double

Element (3,2) of the corrected CD matrix CDi_j.

double getCd3_3()

Returns cd3_3

Returns element (3,3) of the corrected CD matrix CDi_j.

Return

double

Element (3,3) of the corrected CD matrix CDi_j.

setPc1_1(double pc1_1)

Sets the pc1_1 element.

Sets element (1, 1) of the linear transformation matrix PCi_j..

Argument

`double` **`pc1_1`** `[INPUT, MANDATORY]`

double getPc1_1()

Returns pc1_1

Returns element (1,1) of the linear transformation matrix PCi_j.

Return

double

Element (1,1) of the linear transformation matrix PCi_j.

setPc1_2(double pc1_2)

Sets the pc1_2 element.

Sets element (1, 2) of the linear transformation matrix PCi_j..

Argument

`double` **`pc1_2`** `[INPUT, MANDATORY]`

double getPc1_2()

Returns pc1_2

Returns element (1,2) of the linear transformation matrix PCi_j.

Return

double

Element (1,2) of the linear transformation matrix PCi_j.

setPc1_3(double pc1_3)

Sets the pc1_3 element.

Sets element (1, 3) of the linear transformation matrix PCi_j..

Argument

`double` **`pc1_3`** `[INPUT, MANDATORY]`

double getPc1_3()

Returns pc1_3

Returns element (1,3) of the linear transformation matrix PCi_j.

Return

double

Element (1,3) of the linear transformation matrix PCi_j.

setPc2_1(double pc2_1)

Sets the pc2_1 element.

Sets element (2, 1) of the linear transformation matrix PCi_j..

Argument

`double` **`pc2_1`** `[INPUT, MANDATORY]`

double getPc2_1()

Returns pc2_1

Returns element (2,1) of the linear transformation matrix PCi_j.

Return

double

Element (2,1) of the linear transformation matrix PCi_j.

setPc2_2(double pc2_2)

Sets the pc2_2 element.

Sets element (2, 2) of the linear transformation matrix PCi_j..

Argument

`double` **`pc2_2`** `[INPUT, MANDATORY]`

double getPc2_2()

Returns pc2_2

Returns element (2,2) of the linear transformation matrix PCi_j.

Return

double

Element (2,2) of the linear transformation matrix PCi_j.

setPc2_3(double pc2_3)

Sets the pc2_3 element.

Sets element (2, 3) of the linear transformation matrix PCi_j..

Argument

`double` **`pc2_3`** `[INPUT, MANDATORY]`

double getPc2_3()

Returns pc2_3

Returns element (2,3) of the linear transformation matrix PCi_j.

Return

double

Element (2,3) of the linear transformation matrix PCi_j.

setPc3_1(double pc3_1)

Sets the pc3_1 element.

Sets element (3, 1) of the linear transformation matrix PCi_j..

Argument

`double` **`pc3_1`** `[INPUT, MANDATORY]`

double getPc3_1()

Returns pc3_1

Returns element (3,1) of the linear transformation matrix PCi_j.

Return

double

Element (3,1) of the linear transformation matrix PCi_j.

setPc3_2(double pc3_2)

Sets the pc3_2 element.

Sets element (3, 2) of the linear transformation matrix PCi_j..

Argument

`double` **`pc3_2`** `[INPUT, MANDATORY]`

double getPc3_2()

Returns pc3_2

Returns element (3,2) of the linear transformation matrix PCi_j.

Return

double

Element (3,2) of the linear transformation matrix PCi_j.

setPc3_3(double pc3_3)

Sets the pc3_3 element.

Sets element (3, 3) of the linear transformation matrix PCi_j..

Argument

`double` **`pc3_3`** `[INPUT, MANDATORY]`

double getPc3_3()

Returns pc3_3

Returns element (3,3) of the linear transformation matrix PCi_j.

Return

double

Element (3,3) of the linear transformation matrix PCi_j.

setProjection(String projection)

Sets the projection.

Sets the projection type.

Argument

`String` **projection** [INPUT, MANDATORY]

String getProjection()

Returns the projection.

Returns the projection type.

Return

String

The projection type.

MetaData getMeta()

Return the Wcs as metadata.

Returns the Wcs as metadata.

Return

MetaData

The Wcs as metadata.

String toString()

Returns a string representation of the Wcs.

Returns a string representation of the values of the Wcs object. The format of this string is undefined and subject to change.

Return

String

a string representation of the values of the Wcs object.

double[] getWorldCoordinates(double row, double column)

Returns the world coordinates of the given image coordinates.

Returns the world coordinates when the image coordinates are given.

Arguments

`double` **row** [INPUT, MANDATORY]

`double` **column** [INPUT, MANDATORY]

Return

double[]

The corresponding world coordinates as a 2 dimensional array. When the ctype1 and ctype2 keywords of the wcs are defined as "RA---TAN" and "DEC--TAN", the first coordinates describes the right ascension and the second the declination.

double getZCoordinate(int depth)

Returns the world coordinates of the given layer.

Returns the world coordinates of the given layer.

Argument

`int` **`depth`** `[INPUT, MANDATORY]`

Return

double

The corresponding world coordinates of the Z axis.

double[] getPixelCoordinates(double c1, double c2)

Returns the pixel coordinates.

Returns the pixelCoordinates of the given SkyCoordinates. The pixel- coordinates are the row and the column of the image!

Arguments

`double` **`c1`** `[INPUT, MANDATORY]`

`double` **`c2`** `[INPUT, MANDATORY]`

Return

double[]

A 2-dimensional array of doubles describing the pixel coordinates of the given world coordinates.

setCrota2(double crota2)

Sets crota2

Sets the rotation angle in degrees.

Argument

`double` **`crota2`** `[INPUT, MANDATORY]`

double getCrota2()

Returns crota2.

Returns the rotation angle in degrees.

Return

double

The rotation angle in degrees.

boolean isValid()

Checks the possibility to convert from pixel to world coordinates.

Checks if the conversion from pixel to world coordinates is possible and returns true if this is the case.

Return

boolean

boolean isValid()

true is the conversion from pixel to world coordinates is possible.

setWavelength(double wavelength)

Sets the wavelength in the Wcs.

Sets the wavelength in the Wcs (in micrometers). The WAVELNTH and the WAVEUNIT parameter are set.

Argument

`double` **`wavelength`** `[INPUT, MANDATORY]`

getWavelength()

Returns the wavelength which is stored in the Wcs

Returns the wavenlength in micrometer.

2.392. WeightedMean

Full Name:	herschel.ia.numeric.toolbox.basic.WeightedMean
Type:	Java Class -
Import:	from herschel.ia.numeric.toolbox.basic import WeightedMean

Description

This class calculates the quadratically weighted mean and the uncertainty of it, based on

the assumption that the distribution of the errors is Gaussian, of an array of numbers and its corresponding uncertainties in the same units.

Formula:

```
Let -"x" be a vector of n numbers for input and -"dx" be a vector of -"n" numbers
that represent the uncertainties of -"x" in the same units.
Let -"x[i]" be the i'st element of a vector -"x".
Let sum() be the sum over all indices i from 1 to n.
The weighted mean wmean is then:
wmean = sum( x[i]/(dx[i]^2) -) -/ sum( 1/(dx[i]^2))
Standard deviation of the distribution (old name ewmean):
errorDistr = sqrt( sum( (x[i]-wmean)^2/(dx[i]^2) -) -/ sum( 1/(dx[i]^2) -) -)
Standard deviation of the mean:
errorMean = sqrt( (1/sum(1/dx[i]^2)) * (1/(N-1)) * sum((x[i]-wmean)^2/(dx[i\
]^2)) -)
Standard deviation of the mean for trusted errors:
errorMeanTrusted = sqrt(1/sum(1/dx[i]^2))
```

NaN numbers: if ignoreNaN is set to 'true', a NaN value, either in values or uncertainties, is not used in the procedure. If ignoreNaN if set to 'false' (default value) and a NaN is found, a NaN value is returned. NOTE: NaN values can be used for double, float and complex arrays only.

Example

Example 1: Untitled

```
values = Double1d([1,3,5])
errors = Double1d([0.1,0.2,0.3])
wmean = WeightedMean(values,errors)
print wmean.mean()
print wmean.errorDistr()
print wmean.errorMean()
print wmean.errorMeanTrusted()
values = Complex1d([1+1j,3+1j,5+1j])
errors = Complex1d([0.1+1j,0.2+1j,0.3+1j])
wmean = WeightedMean(values,errors)
print wmean.mean()
print wmean.errorDistr()
print wmean.errorMean()
print wmean.errorMeanTrusted()
</pre>
```

API Summary

Jython Syntax

```
wm = WeightedMean(<values>,<errors>,<ignoreNaN>)
wm.mean()
```

Jython Syntax
`wm.errorDistr()`
`wm.errorMean()`
`wm.errorMeanTrusted()`

Properties
`number array values [INPUT, MANDATORY, default=no default value]`
`number array errors [INPUT, MANDATORY, default=no default value]`
`boolean ignoreNaN [INPUT, OPTIONAL, default=false]`

API details

Properties

`number array values [INPUT, MANDATORY, default=no default value]`

The input numbers array can be integer, long, float, double and complex one dimensional array.

`number array errors [INPUT, MANDATORY, default=no default value]`

The input uncertainties array can be integer, long, float, double and complex one dimensional array.

`boolean ignoreNaN [INPUT, OPTIONAL, default=false]`

If 'true' a NaN value will be ignored. By default is 'false'.

See also

- WeightedMean